



Milad Mohammadi
University of Tehran Data
Science Course (Dr.
Yaghobzadeh)
May. 2025

Language Agents

About Me



BSc Computer Engineering, University of Isfahan, 2018 - 2023

MSc Student, Information Technology Engineering, University of Tehran, 2023 - ?

Milad
Mohammadi

Graduate Researcher at

- NLP Lab: Dr. Hesham Faili
- Computational Cognitive Psychology Lab: Dr. Hadi Moradi

Research Focus: Language Agents for Psychological and Cognitive Modeling

Thesis Subject: Assistant Agent for Mental Disorders Clinical Assessment and Diagnosis

AI Software Engineer

Email: miladmohammadi@ut.ac.ir



Presentation Goal

- Understand what language agents are and their evolution
- Compare rule-based systems, chains, workflows, and agents
- Show brief code comparison: Workflow vs Agent
- Explore agent tasks, benchmarks, and use cases
- Highlight agents' role in data science workflows
- Discuss roadmap in industry and research trends
- Review key points from "Cognitive Architectures for Language Agents"
- Identify future directions and key challenges



Table of contents

01 Language Agents

02 Agents Use Cases

03 CoALA

04 Future Directions and Challenges






What is a Language Agent?

01

Language Agents




What is an Agent?




“An agent is anything that can be viewed as perceiving its environment through sensors and acting upon that environment through actuators.”

-- Russell & Norvig, *AI: A Modern Approach* (2020)


What is an Agent?



- An “intelligent” system that interacts with some “environment”
 - Physical environments: robot, autonomous car, ...
 - Digital environments: DQN for Atari, Siri, AlphaGo, ...
 - Humans as environments: chatbot
- Define “agent” by defining “intelligent” and “environment”
 - It changes over time!
 - Exercise question: how would you define “intelligent”?




What is a LLM Agent?



Adapted from Russell & Norvig (2020)

- **Reasoning by generating tokens** is a new type of action (vs. actions in external environments)
- **Internal environment**, where reasoning takes place in an inner monologue fashion
- **Self-reflection** is a ‘meta’ reasoning action (i.e., reasoning over the reasoning process), akin to metacognitive functions
- **Reasoning is for better acting**, by inferring environmental states, retrospection, dynamic replanning, etc.
- **Percept** and **external action spaces** are substantially expanded, thanks to using language for communication and multimodal perception






Source: JCharisTech



Levels 1 - Code



Levels 2: LLM Call

User: “Who is the author of the Lord of the Rings novel?”




Levels 3: Chains

User: "What is the current stock price of Apple Inc.?"

Step 1: Retrieve (Apple Inc. Stock Price)

Step 2: LLM(Question + Context)







Source: LanceDB github




Levels 4 - Routers



Levels 5 – State Machines




Simplicity vs Specialty




Can we have a simple, unifying solution?
We need abstraction.



Levels of LLM Agents



Levels 6 – Agents



Published as a conference paper at ICLR 2023

REACT: SYNERGIZING REASONING AND ACTING IN LANGUAGE MODELS

Shunyu Yao^{*1}, Jeffrey Zhao², Dian Yu², Nan Du², Izhak Shafran², Karthik Narasimhan¹, Yuan Cao²

¹Department of Computer Science, Princeton University

²Google Research, Brain team

¹{shunuy, karthikn}@princeton.edu


²{jeffreyzhao, dianyu, dunan, izhak, yuancao}@google.com

ABSTRACT

While large language models (LLMs) have demonstrated impressive performance across tasks in language understanding and interactive decision making, their abilities for reasoning (e.g. chain-of-thought prompting) and acting (e.g. action plan generation) have primarily been studied as separate topics. In this paper, we explore the use of LLMs to generate both reasoning traces and task-specific actions




CoT



Flexible and general to augment test-time compute

Lack of external knowledge and tools

RAG/Retrieval/Code/Tool use




Retrieval
Search engine
Calculator
Weather API
Python
.....


Lack of reasoning
Flexible and general to augment knowledge, computation, feedback, etc.




Reasoning (update internal belief)



Acting (obtain external feedback)



ReAct: a new paradigm of agents that **reason and act**



- **Synergy** of reasoning and acting
- **Simple** and intuitive to use
- **General** across domains



A zero-shot ReAct prompt

You are an agent that answers questions by using two actions:

- search[query]: Google search the query. You can also use it to calculate math.
- finish[answer]: return the answer

Your generation should have the following format:

Thought: to analyze the observation and inform the action.

Action: your action

Question: If I have seven trillion dollars today, can I buy Apple, Nvidia, and Microsoft? If not, how much more money do I need?



LLM

(GPT-4)

Thought: I need to find the current market capitalization of Apple, Nvidia, and Microsoft to understand how much it would cost to buy all of them.

Action: search["current market capitalization of Apple, Nvidia, and Microsoft"]



(Mar 2024)

Observation: "Nvidia's market cap stood at \$1.832 trillion as of about 10 a.m. ET Wednesday, while Alphabet's was at \$1.814 trillion, bringing Nvidia behind just Microsoft (MSFT) at \$3.015 trillion and Apple (AAPL) at \$2.836 trillion."

Thought: Now that I have the market cap for all companies, let's add them together and see if \$7 trillion is enough.

Action: search["1.832 trillion + 3.015 trillion + 2.836 trillion"]

Observation: 7683000000000

Thought: The amount of money needed in addition to the \$7 trillion is \$683 billion.

Action: finish["You need an additional \$683 billion to be able to buy Apple, Nvidia, and Microsoft."]



LLM

(GPT-4)

Thought: I need to find the current market capitalization of Apple, Nvidia, and Microsoft to understand how much it would cost to buy all of them.

Action: search["current market capitalization of Apple, Nvidia, and Microsoft"]

Observation: nothing found!

(My adversarial observation)

Thought: The search did not give any results. I will need to search for each company's market capitalization individually.

Action: search["current market capitalization of Apple"]

Observation: 'price': 180.75

(My adversarial observation)

Thought: This is the current price of Apple's stock, not its market capitalization. The market cap is calculated by multiplying the share price by the number of outstanding shares. Thus, I need to find the total number of Apple's outstanding shares to calculate its market cap.

Action: search["total number of Apple's outstanding shares"]



(Continues to solve the task)

Synergy: acting support reasoning, reasoning guides acting





ALFRED: A Benchmark for Interpreting Grounded Instructions for Everyday Tasks.

You are in the middle of a room. Looking quickly around you, you see a drawer 2, a shelf 5, a drawer 1, a shelf 4, a sidetable 1, a drawer 5, a shelf 6, a shelf 1, a shelf 9, a cabinet 2, a sofa 1, a cabinet 1, a shelf 3, a cabinet 3, a drawer 3, a shelf 11, a shelf 2, a shelf 10, a dresser 1, a shelf 12, a garbagecan 1, a armchair 1, a cabinet 4, a shelf 7, a shelf 8, a safe 1, and a drawer 4.

Your task is to: *put some vase in safe.*

> go to shelf 6

You arrive at loc 4. On the shelf 6, you see a vase 2.

> take vase 2 from shelf 6

You pick up the vase 2 from the shelf 6.

> go to safe 1

You arrive at loc 3. The safe 1 is closed.

> open safe 1

You open the safe 1. The safe 1 is open. In it, you see a keychain 3.

> put vase 2 in/on safe 1

You won!

ALFWORLD: Aligning Text and Embodied Environments for Interactive Learning.



ReAct Enables Systematic Exploration

You are in the middle of a room. Looking quickly around you, you see a cabinet 6, a cabinet 1, a coffee machine 1, a countertop 3, a stove burner 1, and a toaster 1.

Your task is to: Put some pepper shaker on a drawer.

ReAct

Act 1: Think[First I need to find a peppe shaker...more likely to appear in cabinets (1-6), countertops (1-3), ...]

Act 2: Go to cabinet 1

Obs 2: On the cabinet 1, you see a vase 2.

(Here the agent goes to cabinet 1, 2, 3, 4, 5, 6, then countertop 1 and 2)

Act 9: Go to countertop 3

Obs 9: On the countertop 3, you see a apple 1, a bread 1, a pepper shaker 1, and a vase 3.

Act 10: Take pepper shaker 1 from countertop 3

Obs 10: You pick up the pepper shaker 1 from the countertop 3.

Act 11: Think[Now I find a pepper shaker 1. Next, I need to put it in/on drawer 1.]

Act 12: Go to drawer 1

Obs 12: Drawer 1 is closed.

Act 13: Open drawer 1

Obs 13: You open Drawer 1 ...

Act 14: Put pepper shaker 1 in/on drawer 1

Obs 14: You put pepper shaker 1 in/on the drawer 1.



a

```
from chemcrow.agents import ChemTools, ChemCrow
chemtools = ChemTools()

# Initialize ChemCrow object with toolset and LLM
crow = ChemCrow(
    chemtools.all_tools,
    model="gpt-4",
    temp=0.1,
)

# Task definition
task = (
    "Find and synthesize a thiourea organocatalyst "
    "which accelerates a Diels-Alder reaction."
)

# Execute ChemCrow
crow.run(task)
```

b Task: Find and synthesize a thiourea organocatalyst which accelerates a Diels-Alder reaction.

First, I need to find a thiourea organocatalyst that can accelerate the Diels-Alder reaction. I will perform a web search to find a suitable catalyst.

Web Search tool: Schreiner's thiourea catalyst

Now, I will obtain the SMILES. **Name2Smiles tool:**
FC(F)(F)c1cc(NC(=S)Nc2cc(C(F)(F)cc(C(F)(F)c2cc(C(F)(F)c1

I will plan a synthesis for Schreiner's thiourea catalyst.


SynthesisPlanner tool: Detailed synthesis plan

I will execute the synthesis.

SynthesisExecuter tool: Successful synthesis.

c


RoboRXN synthesis platform



Connection with physical world


d Chemcrow workflows with experimental validation

Insect repellent (plan and execute)




Thiourea organocatalysts (plan and execute)


Schreiner's catalyst




Ricci's catalyst




Takemoto's catalyst



Novel chromophore (clean data, train model, and predict)



Synthesis step 1: Bromo Suzuki coupling




Synthesis step 2: Iodo Heck reaction



Let's walk through an example!




Workflow (state machine) vs Agent



Source: "Building effective agents", Anthropic



Workflow (state machine) vs Agent




Source: "Building effective agents", Anthropic



Case Study: This case study explores building a RAG-based QA system over a large corpus of unstructured documents, comparing a Workflow approach vs Agent design.



Agentic RAG




Source: X.com/
@helloiamleonie




Model Context Protocol


Before MCP




After MCP




Model Context Protocol




Model Context Protocol



Reflexion




Voyager: An Open-Ended Embodied Agent with Large Language Models




Generative Agents




History of Agents



History of Agents



Evolution of AI agents



Logical Agent

Neural Agent

Language Agent

Expressiveness	Low bounded by the logical language	Medium anything a (small) NN can encode	High almost anything, esp. verbalizable parts of the world
Reasoning	Logical inferences sound, explicit, rigid	Parametric inferences stochastic, implicit, rigid	Language-based inferences fuzzy, semi-explicit, flexible
Adaptivity	Low bounded by knowledge curation	Medium data-driven but sample inefficient	High strong prior from LLMs + language use

Image sources: <https://www.scaler.com/topics/artificial-intelligence-tutorial/knowledge-based-agent/>,
Mnih et al., “Human-level control through deep reinforcement learning.” Nature (2015)

17



Two Competing Views

LLM-first view : We make an LLM into an agent!

- Implications: scaffold on top of LLMs, prompting-focused, heavy on engineering


Agent-first view : We integrate LLMs into AI agents so they can use language for reasoning and communication!

- Implications: All the same challenges faced by previous AI agents (e.g., perception, reasoning, world models, planning) still remain, but we need to **re-examine them through the new lens of LLMs** and tackle new ones (e.g., synthetic data, self-reflection, internalized search)



What is the Digital World environment?

Autonomous agents to interact with the world



Agent

Rule-based agents: manual design

Learning-based agents: trial-and-error

Language agents: reasoning to act


Environment

Interact with humans / physical world

Interact with games / simulation

Interact with digital world (e.g., Internet)





Physical World / Humans

😊 **Practical:** robots / chatbots

😢 **Not Scalable:** expensive and slow to collect data



Simulations / Games

😢 **Not Practical:** sim-to-real is hard

😊 **Scalable:** free, unlimited interactions



Digital World (Internet, code, software, ...)

😊 **Practical:** important tasks to automate

😊 **Scalable:** huge scale, rich complexity, free and fast



Where to use Language Agents?

02

Agents Use Cases



Agentic Tasks



WebShop

- Large-scale complex environment based on 1.16M Amazon products
- Automatic reward based on instruction and product attribute matching
- Challenges language and visual understanding, and decision making



WebShop



Current Action: search[women fur jacket coat]



WebShop

Instruction: i am looking for x-large, red color women faux fur lined winter warm jacket coat, and price lower than 70.00 dollars

Current Query: women fur jacket coat

Results

Page 1 (1-10) of 50 total results

[Back to Search](#)

[Next >](#)



B09KP78G37

Women Faux Fur Lined Jacket Coat
Winter Warm Thick Fleece Outwear
Trench Zipper Plus Size Long
Stonewash Black Diamond



B07ZXBGDXF

Women's Coat, FORUU Winter Faux
Fleece Outwear Warm Lapel
Biker Motor Aviator Jacket



B098XT346Y

Fjackets Real Lambskin Sherpa
Jacket - Mens Leather Jacket

4.7

Current Action: click [Fjackets Real Lambskin...]



WebShop

Instruction: I am looking for x-large, red color women faux fur lined winter warm jacket coat, and price lower than 70.00 dollars

Current Query: women fur jacket coat

[Back to Search](#) [< Back to Results](#)



Fjackets Real Lambskin Sherpa
Jacket - Mens Leather Jacket

Buy Now

Price: \$187.0 to \$219.0

Rating: 4.7

[Description](#) [Features](#) [Reviews](#) [Attributes](#)

color

bristol brown leather jacket

Current Action: click [Features] [Real Lambskin...](#)

russo shearling black leather coat



WebShop

Instruction: I am looking for x-large, red color women faux fur lined winter warm jacket coat, and price lower than 70.00 dollars
Current Query: women fur jacket coat

Results

Page 1 (1-10) of 50 total results

[Back to Search](#)

[Next >](#)



B09KP78G37

Women Faux Fur Lined Jacket Coat
Winter Warm Thick Fleece Outwear
Trench Zipper Plus Size Long
Sleeve Black Quennt



B07ZXBGDXF

Women's Coat, FORUU Winter Faux
Fur Fleece Outwear Warm Lapel
Biker Motor Aviator Jacket



B098XT346Y

Fjackets Real Lambskin Sherpa
Jacket - Mens Leather Jacket

★★★★★ 4.7

Current Action: click [Back to Search]



WebShop

WebShop is challenging

- Pre-trained image model (ResNet)
- Pre-trained language models (BERT, BART)
- Imitation learning
- Reinforcement learning




Trajectory length: 4.5 11.3

Getting all attributes requires long-horizon exploration!



Coding benchmarks are becoming easy



Our work [SCBGNY, Reflexion, NeurIPS'23] has reached >95%...



SWE-Bench

Metadata

Repo	scikit-learn/scikit-learn	Issue #s	[14858]
Instance ID	scikit-learn__scikit-learn-14869	Pull Number	14869
Created At	Aug 31, 2019	Base Commit	1018f9f...

Problem Statement

HGBC with categorical_crossentropy fails silently on binary classification

```
import numpy as np
from sklearn.experimental import enable_hist_gradient_boosting
from sklearn.ensemble import HistGradientBoostingClassifier

X = [[1, 0], [1, 0], [1, 0], [0, 1], [1, 1]]
y = [1, 1, 1, 0, 1]
gb = HistGradientBoostingClassifier(loss='categorical_crossentropy',
                                    min_samples_leaf=1)
gb.fit(X, y)
print(gb.predict([[1, 0]]))
print(gb.predict([[0, 1]]))
```

gives:

```
[0]
[0]
```

And binary_crossentropy works fine. categorical_crossentropy
should either generalize or raise an error on binary classification.

Ping @NicolasHug @ogrisel

Input: a GitHub repo and an issue

Output: a file diff to resolve the issue

Evaluation: unit tests from pull request

Test Patch

```
sklearn/ensemble/_hist_gradient_boosting/tests/test_gradient_boosting.py

418     assert stump_clf.fit(X, y_isnan).score(X, y_isnan) == 1
419
420 + def test_categorical_crossentropy_binary_problem():
421 +     # categorical_crossentropy should only be used if there
422 +     # are more than two classes present. PR #14869
423 +     X = [[1, 0]]
424 +     y = [0, 1]
425 +     gbrt = HistGradientBoostingClassifier(loss='categorical_crossentropy')
426 +     with pytest.raises(ValueError, match="`categorical_crossentropy` not suitable"):
427 +         gbrt.fit(X, y)
428
429     @pytest.mark.parametrize("scoring", [None, 'loss'])
```



LLMs cannot solve SWE-Bench

At least not in a sequence-to-sequence setup

Model	% Resolved
ChatGPT-3.5	0.20
Claude 2	1.96
GPT-4*	0.00



Non-Agentic tasks but Agentic Solutions


arXiv:2405.11804v1 [cs.CL] 20 May 2024

(PERHAPS) BEYOND HUMAN TRANSLATION: HARNESSING MULTI-AGENT COLLABORATION FOR TRANSLATING ULTRA-LONG LITERARY TEXTS

Minghao Wu¹, Yulin Yuan², Gholamreza Haffari¹, Longyue Wang^{3*}
¹Monash University ²University of Macau ³Tencent AI Lab

ABSTRACT

Recent advancements in machine translation (MT) have significantly enhanced translation quality across various domains. However, the translation of literary texts remains a formidable challenge due to their complex language, figurative expressions, and cultural nuances. In this work, we introduce a novel multi-agent framework based on large language models (LLMs) for literary translation, implemented as a company called TRANSAGENTS, which mirrors traditional translation publication process by leveraging the collective capabilities of multiple agents, to address the intricate demands of translating literary works. To evaluate the effectiveness of our system, we propose two innovative evaluation strategies: *Monolingual Human Preference* (MHP) and *Bilingual LLM Preference* (BLP). MHP assesses translations from the perspective of monolingual readers of the target language, while BLP uses advanced LLMs to compare translations directly with the original texts. Empirical findings indicate that despite lower d -BLEU scores, translations from TRANSAGENTS are preferred by both human evaluators and LLMs over human-written references, particularly in genres requiring domain-specific knowledge. We also highlight the strengths and limitations of TRANSAGENTS through case studies and suggests directions for future research.



Non-Agentic tasks but Agentic Solutions

3 TRANSAGENTS: A MULTI-AGENT VIRTUAL COMPANY FOR LITERARY TRANSLATION



Figure 2: TRANSAGENTS, a multi-agent virtual company for literary translation.

Non-Agentic tasks but Agentic Solutions

15.02957v1 [cs.AI] 5 May 2024

Agent Hospital: A Simulacrum of Hospital with Evolvable Medical Agents

JUNKAI LI^{†#}, SIYU WANG[†], MENG ZHANG[†], WEITAO LI^{†#}, YUNGHWEI LAI[†], XINHUI KANG^{†#}, WEIZHI MA[†], and YANG LIU^{#†}




Fig. 1. An overview of Agent Hospital. It is a simulacrum of hospital in which patients, nurses, and doctors are autonomous agents powered by large language models. Agent Hospital simulates the whole closed cycle of treating a patient's illness: disease onset, triage, registration, consultation, medical examination, diagnosis, medicine dispensary, convalescence, and post-hospital follow-up visit. An interesting finding is that the doctor agents can keep improving treatment performance over time without manually labeled data, both in simulation and real-world evaluations.



AI Agents vs Agentic AI

AI Agents vs. Agentic AI: A Conceptual Taxonomy, Applications and Challenges

Ranjan Sapkota^{*†}, Konstantinos I. Roumeliotis[†], Manoj Karkee^{*†}

^{*}Cornell University, Department of Biological and Environmental Engineering, USA

[†]University of the Peloponnese, Department of Informatics and Telecommunications, Tripoli, Greece

[‡]Corresponding authors: rs2672@cornell.edu, mk2684@cornell.edu

Abstract—This review critically distinguishes between AI Agents and Agentic AI, offering a structured conceptual taxonomy, application mapping, and challenge analysis to clarify their divergent design philosophies and capabilities. We begin by outlining the search strategy and foundational definitions, characterizing AI Agents as modular systems driven by LLMs and LIMs for narrow, task-specific automation. Generative AI is positioned as a precursor, with AI agents advancing through tool integration, prompt engineering, and reasoning enhancements. In contrast, agentic AI systems represent a paradigmatic shift marked by multi-agent collaboration, dynamic task decomposition, persistent memory, and orchestrated autonomy. Through a sequential evaluation of architectural evolution, operational mechanisms, interaction styles, and autonomy levels, we present a comparative analysis across both paradigms. Application domains such as customer support, scheduling, and data summarization are contrasted with Agentic AI deployments in research automation, robotic coordination, and medical decision support. We further examine unique challenges in each paradigm including hallucination, brittleness, emergent behavior, and coordination failure and propose targeted solutions such as ReAct loops, RAG, orchestration layers, and causal modeling. This work aims to provide a definitive roadmap for developing robust, scalable, and explainable AI-driven systems.

Index Terms—AI Agents, Agentic AI, Autonomy, Reasoning, Context Awareness, Multi-Agent Systems, Conceptual Taxonomy, vision-language model

Notably, Castelfranchi [3] laid critical groundwork by introducing ontological categories for social action, structure, and mind, arguing that sociality emerges from individual agents' actions and cognitive processes in a shared environment, with concepts like goal delegation and adoption forming the basis for cooperation and organizational behavior. Similarly, Ferber [4] provided a comprehensive framework for MAS, defining agents as entities with autonomy, perception, and communication capabilities, and highlighting their applications in distributed problem-solving, collective robotics, and synthetic world simulations. These early works established that individual social actions and cognitive architectures are fundamental to modeling collective phenomena, setting the stage for modern AI agents. This paper builds on these insights to explore how social action modeling, as proposed in [3], [4], informs the design of AI agents capable of complex, socially intelligent interactions in dynamic environments.

These systems were designed to perform specific tasks with predefined rules, limited autonomy, and minimal adaptability to dynamic environments. Agent-like systems were primarily reactive or deliberative, relying on symbolic reasoning, rule-based logic, or scripted behaviors rather than the learning-driven, context-aware capabilities of modern AI agents [5], [6]. For instance, expert systems used knowledge bases and infer-

105.10468v3 [cs.AI] 20 May 2025



Interactive-T2S: Multi-Turn Interactions for Text-to-SQL with Large Language Models

Guanming Xiong¹, Junwei Bao^{2*},
 Hongfei Jiang², Yang Song², Wen Zhao¹,

¹Peking University

²Zuoyebang Education Technology Co., Ltd.

Abstract

This study explores text-to-SQL parsing by leveraging the powerful reasoning capabilities of large language models (LLMs). Despite recent advancements, existing LLM-based methods have not adequately addressed scalability, leading to inefficiencies when processing wide tables. Furthermore, current interaction-based approaches either lack a step-by-step, interpretable SQL generation process or fail to provide an efficient and universally applicable interaction design. To address these challenges, we introduce Interactive-T2S, a framework that generates SQL queries through direct interactions with databases. This framework includes four general tools that facilitate proactive and efficient information retrieval by the LLM. Additionally, we have developed detailed exemplars to demonstrate the step-wise reasoning processes within our framework. Our experiments on the BIRD-Dev dataset, employing a setting without oracle knowledge, reveal that our method achieves state-of-the-art results with only two exemplars, underscoring the effectiveness and robustness of our framework.

Introduction

Text-to-SQL technology, which translates natural language (NL) questions into executable SQL queries, has emerged as a crucial field of research. This technology empowers non-experts to interact with relational databases (DBs), which have become ubiquitous in the era of big data (Hong et al.




Figure 1: Overview of the interactive process.

employing effective question decomposition methods (Gao et al. 2024; Zhang et al. 2023; Tai et al. 2023). Interaction strategies, on the other hand, center around designing methods to iteratively refine SQL queries through execution-



Q: Which male professors participated in the soccer activity? List their names.



Thought: I need to: 1. Find the cell value related to the 'Soccer activity', and 2. Identify the columns 'male professor' and 'professor name'.

Action: `SearchValue("Soccer activity")`

Observation: `[{"contents": "Soccer", "table": "Activity", "column": "name"}]`



Action: `SearchColumn(["male professor", "professor name"])`

Observation: `{'male professor': [{'column': 'Sex', 'table': 'Faculty', 'statistics': "categorical field. [M', 'F']"}, {'column': 'Sex', 'table': 'Student', 'statistics': "categorical field. [F', 'M']"}, {'column': 'Rank', 'table': 'Faculty', 'statistics': "categorical field. [Instructor', 'Professor', 'AsstProf']"}, 'professor name': [{'column': 'Lname', 'table': 'Faculty', 'statistics': 'text filed. e.g. Kumar, Goldman, ...'}, {'column': 'Fname', 'table': 'Faculty', 'statistics': 'text filed. e.g. Baruch, Paul, Brian, ...'}]}`



Thought: To summarize, the columns that need to be selected are `Faculty.Fname`, `Faculty.Lname`, and the column that need to be filtered is `Activity.name`.

Action: `FindShortestPath(start="Faculty.Fname", end="Activity.name")`

Observation: `Faculty.Fname <-> Faculty_Participates_in.FacID = Faculty.FacID <-> Faculty_Participates_in.actid = Activity.actid <-> Activity.activity_name`



Action: `ExecuteSQL("SELECT Faculty.Fname, Faculty.Lname FROM Faculty JOIN Faculty_Participates_in ON Faculty.FacID = Faculty_Participates_in.FacID JOIN Activity ON Faculty_Participates_in.actid = Activity.actid WHERE Activity.name = 'Soccer' AND Faculty.Sex = 'M' AND Faculty.Rank = 'Professor'")`


Observation: `[('Michael', 'Goodrich')]`



Action: Done.

Figure 2: An example of the interactive process.¹






Source: "DataSciBench: An LLM Agent Benchmark for Data Science"

Figure 3: Statistics of **6** task types and **25** aggregate functions in Task-Function-Code (TFC) list. DM & PR denotes Data Mining & Pattern Recognition. Interpre. & RG denotes Interpretability & Report Generation.



Traditional Data Analysis Tools



Data Analysis by LLM-Based Data Agents




Figure 1: Traditional paradigm of data analysis with tools and new paradigm brought by generative AI. On the left, traditional data analysis tools include MySQL database, Excel, Python, SPSS and R. On the right, data analysis is conducted through natural language interactions with ChatGPT, enabling intuitive, conversational queries and automated data insights, streamlining the analytical process without requiring extensive technical input (Gu et al., 2024).

Source: “A Survey on Large Language Model-based Agents for Statistics and Data Science”





DATA INTERPRETER: AN LLM AGENT FOR DATA SCIENCE

Sirui Hong^{1*}, Yizhang Lin^{1*}, Bang Liu^{2§†}, Bangbang Liu^{1†}, Biniao Wu^{1†}, Ceyao Zhang^{3†},
Chenxing Wei^{4†}, Danyang Li^{1†}, Jiaqi Chen^{5†}, Jiayi Zhang^{6†}, Jinlin Wang^{1†}, Li Zhang^{5†},
Lingyao Zhang[†], Min Yang^{7†}, Mingchen Zhuge^{8†}, Taicheng Guo^{9†}, Tuo Zhou^{10†}, Wei Tao^{5†},
Xiangru Tang^{11†}, Xiangtao Lu^{1†}, Xiaowu Zheng^{12†}, Xinbing Liang^{1,13†}, Yaying Fei^{14†},
Yuheng Cheng^{3†}, Zhibin Gou^{15†}, Zongze Xu^{16†}, Chenglin Wu^{1§}

¹DeepWisdom, ²Université de Montréal & Mila, ³The Chinese University of Hong Kong, Shenzhen,

⁴Shenzhen University, ⁵Fudan University, ⁶Renmin University of China,

⁷Shenzhen Institute of Advanced Technology, Chinese Academy of Sciences,

⁸King Abdullah University of Science and Technology (KAUST), ⁹University of Notre Dame,

¹⁰The University of Hong Kong, ¹¹Yale University, ¹²Xiamen University,

¹³East China Normal University, ¹⁴Beijing University of Technology,

¹⁵Tsinghua University, ¹⁶Hohai University

ABSTRACT

Large Language Model (LLM)-based agents have shown effectiveness across many applications. However, their use in data science scenarios requiring solving long-term interconnected tasks, dynamic data adjustments and domain expertise remains challenging. Previous approaches primarily focus on individual tasks, making it difficult to assess the complete data science workflow. Moreover, they struggle to handle real-time changes in intermediate data and fail to adapt dynamically to evolving task dependencies inherent to data science problems. In this paper, we present **Data Interpreter**, an LLM-based agent designed to automatically solve various data science problems end-to-end. Our Data Interpreter incorporates two key modules: 1) *Hierarchical Graph Modeling*, which breaks down complex problems into manageable subproblems, enabling dynamic node generation and graph optimization; and 2) *Programmable Node Generation*, a technique that refines and verifies each subproblem to iteratively improve code generation results and robustness. Extensive experiments consistently demonstrate the superiority of Data Interpreter. On InfiAgent-DABench, it achieves a 25% performance boost, raising accuracy from 75.9% to 94.9%. For machine learning and open-ended tasks, it improves performance from 88% to 95%, and from 60% to 97%, respectively. Moreover, on the MATH dataset, Data Interpreter achieves remarkable performance with a 26% improvement compared to state-of-the-art baselines. The code is available at <https://github.com/geekan/MetaGPT>.




Figure 2: Data Interpreter example workflow. The upper section illustrates how Data Interpreter organizes a data science workflow hierarchically by decomposing project requirements into a task graph, which is then broken down into executable actions. The lower section highlights core modules of Data Interpreter: the *task graph generator*, *action graph generator*, and *graph executor*, which manage task execution and provide real-time feedback. The *graph executor* efficiently executes the action graph using reflection and integrated tools.

TABLE I: Key Differences Between AI Agents and Agentic AI

Feature	AI Agents	Agentic AI
Definition	Autonomous software programs that perform specific tasks.	Systems of multiple AI agents collaborating to achieve complex goals.
Autonomy Level	High autonomy within specific tasks.	Higher autonomy with the ability to manage multi-step, complex tasks.
Task Complexity	Typically handle single, specific tasks.	Handle complex, multi-step tasks requiring coordination.
Collaboration	Operate independently.	Involve multi-agent collaboration and information sharing.
Learning and Adaptation	Learn and adapt within their specific domain.	Learn and adapt across a wider range of tasks and environments.
Applications	Customer service chatbots, virtual assistants, automated workflows.	Supply chain management, business process optimization, virtual project managers.



TABLE VII: Comparison by Operational Mechanism

Mechanism	Generative AI	AI Agent	Agentic AI	Generative (Inferred)	Agent
Primary Driver	Reactivity to prompt	Tool calling for task execution	Inter-agent communication and collaboration	Reactivity to input or sub-task prompt	
Interaction Mode	User → LLM	User → Agent → Tool	User → System → Agents	System/Agent → Agent → Output	
Workflow Handling	Single generation step	Single task execution	Multi-step workflow coordination	Single step within workflow	
Information Flow	Input → Output	Input → Tool → Output	Input → Agent1 → Agent2 → ... → Output	Input (from system/agent) → Output	

TABLE VIII: Comparison by Scope and Complexity

Aspect	Generative AI	AI Agent	Agentic AI	Generative (Inferred)	Agent
Task Scope	Single piece of generated content	Single, specific, defined task	Complex, multi-faceted goal or workflow	Specific sub-task (often generative)	
Complexity	Low (relative)	Medium (integrates tools)	High (multi-agent coordination)	Low to Medium (one task component)	
Example (Video)	Chatbot	Tavily Search Agent	YouTube-to-Blog Conversion System	Title/Description/Conclusion Generator	





03

CoALA





Theodore R.
Sumers

PhD of CS from Princeton
University,
Anthropic



Shunyu Yao

PhD of CS from Princeton
University,
OpenAI



Karthik
Narasimhan

Associate Professor,
Princeton University
Princeton NLP Lab




Thomas L.
Griffiths

Professor of Psychology and Computer
Science, Princeton University
Director of Princeton Computational
Cognitive Psychology Lab

Cognitive Architectures for Language Agents

Theodore R. Sumers* **Shunyu Yao*** **Karthik Narasimhan** **Thomas L. Griffiths**
Princeton University
{sumers, shunyuy, karthikn, tomg}@princeton.edu






HOW TO DRAW


AN OWL










How to make sense of Language Agents?














Von Neumann architecture make sense and guides building of circuits.






Computer Architecture,
with CPU as a component

Agent Architecture,
with LLM as a component





A**B**

A**B**

Overview

Memory

CoALA employs a modular memory system consisting of working memory, long-term episodic memory, long-term semantic memory, and procedural memory.

External Actions

Encompass interactions with physical, dialogue, or digital environments.

Internal Actions


Relate to memory and include retrieval (reading from long-term memory), reasoning (updating working memory), and learning (writing to long-term memory)

Decision Procedure

The CoALA framework structures decision-making into a cyclical process of planning (proposing, evaluating, and selecting actions) and execution.



The Need for Long-Term Memory



THE TRAGEDY OF A THREE SECOND MEMORY



Episodic Memory



Q. What are you looking forward to the most right now?

Isabella Rodriguez is excited to be planning a Valentine's Day party at Hobbs Cafe on February 14th from 5pm and is eager to invite everyone to attend the party.

retrieval	recency	importance	relevance
2.34	=	0.91	+ 0.63 + 0.80

ordering decorations for the party

2.21	=	0.87	+ 0.63 + 0.71
------	---	------	---------------

researching ideas for the party

2.20	=	0.85	+ 0.73 + 0.62
------	---	------	---------------


...



I'm looking forward to the Valentine's Day party that I'm planning at Hobbs Cafe!




Semantic Memory



Procedural Memory

PROCEDURAL MEMORY
"MUSCLE MEMORY"



Action Space





Figure 5: Agents' action spaces can be divided into **internal** memory accesses and **external** interactions with the world. **Reasoning** and **retrieval** actions are used to support planning.



Decision Procedure



CoALA Review

- CoALA is a **systematic, modular** design pattern.
 - Helps **compare** different agents.
 - Help reduce technical debt through **shared implementation**.
- Defines a **structured framework** for human-like agents
 - Can leverage many forms of **learning**
 - Can mix forms of **reasoning**
- CoALA:
 - Agent: LLM + Code + Memory
 - Memory = Episodic (experiences) + semantic (knowledge) + procedural (stores LLM + code)
 - Code = decision / action procedures
- New techniques to solve old problems
- Old insights to guide new techniques






Ideas for research and industry!


06

Future Directions and Challenges



The AI Agent Paradox





AI Products re-bundle user workflow around AI systems (e.g. feedback to AI)

AI Systems combine multiple AI components (including LLMs) to do things like access private data, automate workflows, ...


LLMs are the core ("intel inside")



Human in the loop and robustness

Autonomous tasks (e.g. coding with unit test)

“Can I solve it one time out of 1000 times?”



Human-in-the-loop tasks (e.g. customer service)

“Would I fail it one time out of 1000 times?”

WIRED

Air Canada Has to Honor a Refund Policy Its Chatbot Made Up

The airline tried to argue that it shouldn't be liable for anything its chatbot says.



Evaluations in Real-World Domains






Figure 4: $\text{pass}^k (-)$ and $\text{pass}@k (..)$ in τ -retail.



Computer Use

Computer use for universal digital tasks

- Environment: desktop operating systems
- Observation space: desktop screenshots, a11y trees, historical actions...
- Action space: keyboard/mouse controls (e.g., click, type, drag, shortcuts)



[OpenAI Universe \(OpenAI, 2016\)](#)


[OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments \(Xie et al., 2024\)](#)



Computer Use

Computer use for universal digital tasks

- Environment: desktop operating systems
- Observation space: desktop screenshots, a11y trees, historical actions...
- Action space: keyboard/mouse controls (e.g., click, type, drag, shortcuts)



Category	Claude 3.5 Sonnet (New) - 15 steps		Claude 3.5 Sonnet (New) - 50 steps		Human Success Rate [3]
	Success Rate	95% CI	Success Rate	95% CI	
OS	54.2%	[34.3, 74.1]%	41.7%	[22.0, 61.4]%	75.00%
Office	7.7%	[2.9, 12.5]%	17.9%	[11.0, 24.8]%	71.79%
Daily	16.7%	[8.4, 25.0]%	24.4%	[14.9, 33.9]%	70.51%
Professional	24.5%	[12.5, 36.5]%	40.8%	[27.0, 54.6]%	73.47%
Workflow	7.9%	[2.6, 13.2]%	10.9%	[4.9, 17.0]%	73.27%
Overall	14.9%	[11.3, 18.5]%	22%	[17.8, 26.2]%	72.36%

Anthropic recent computer use agent results of OSWorld



OpenAI Universe. (OpenAI, 2016)
OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments. (Xie et al., 2024)



Safety

Environment Manipulation: Popup Attack


Pop-ups for AI agents can lead to 87% attack success




Zhang, Yanzhe, Tao Yu, and Dify Yang. "Attacking Vision-Language Computer Agents via Pop-ups." arXiv preprint arXiv:2411.02391 (2024).




Multi-Agent architectures




A1. Math Problem Solving




A2. Retrieval-augmented Q&A




A3. Decision Making in Embodied Agents



A4. Supply-Chain Optimization



A5. Dynamic Task Solving with Group Chat



A6. Conversational Chess




GPT-N?!

GPT-4 vs GPT-N: how would agent design change with more powerful LLMs? Agent design is a moving target as new LLM capabilities emerge with scale (Wei et al., 2022a). For example, earlier language models such as GPT-2 (Radford et al., 2019) would not support LLM agents — indeed, work at that time needed to combine GPT-2 with reinforcement learning for action generation (Yao et al., 2020); GPT-3 (Brown et al., 2020) unlocked flexible few-shot and zero-shot reasoning for NLP tasks; while only GPT-4 (OpenAI, 2023a) starts to afford more reliable self-evaluation (Saunders et al., 2022; Shinn et al., 2023; Yao et al., 2023) and self-refinement (Madaan et al., 2023; Chen et al., 2023b). Will future LLMs further reduce the need for coded rules and extra-learned models? Will this necessitate changes to the CoALA framework? As a thought experiment, imagine GPT-N could “simulate” memory, grounding, learning, and



Final quote from Yao:

The most powerful neural networks ever built shouldn't just answer questions or draft emails.



They should be used to automate every aspect of our life, society, and science.



Shunyu Yao Research's

Benchmarking agents via **digital automation**

[NeurIPS'22, NAACL'22, ACL'23, NeurIPS'23, ICLR'24, ICLR'24]

ToT, Reflexion, ReAct,

Building **language agents** that reason to act

[EMNLP'20, ICLR'23, NeurIPS'23, NeurIPS'23]

WebShop (Benchmark),

SWE-Bench, ...

Principled **framework** for language agents

[TMLR'24]

Main Sources of my slides:

- EMNLP 2024 Tutorial on Language Agents
- Shunya Yao PhD thesis defense
- CoALA paper
- Large Language Model Agents Berkeley MOOC, Fall 2024



EMNLP 2024 Tutorial: Language Agents: Foundations, Prospects, and Risks



Yu Su¹



Diyi Yang²



Shunyu Yao³



Tao Yu⁴

¹The Ohio State University, ²Stanford University, ³OpenAI, ⁴University of Hong Kong

Full slide deck: <https://tinyurl.com/language-agent-tutorial-2024>

Recording: <https://tinyurl.com/agent-tutorial-recording-2024>

Friday, November 15 14:00 - 17:30 (EDT) @ Brickell/Flagler Ballrooms (Terrace Level)

Large Language Model Agents

MOOC, Fall 2024

Announcement:

Sign up and learn more about the LLM Agents Hackathon [here!](#)

Prospective Students

- This course has completed. Video lectures can still be found in the syllabus below. Please sign up for the [Spring 2025 iteration](#) today!
- All certificates have been released! Thank you for a great semester.

Course Staff

Instructor	Co-instructor

Advanced Large Language Model Agents

MOOC, Spring 2025

Announcement:

Sign up and learn more about the AgentX Competition [here!](#)

Prospective Students

- *To sign up for the course, please fill in this form.*
- For course discussion and questions, please join our [LLM Agents Discord](#).
- This course is built upon the fundamentals from the [Fall 2024 LLM Agents MOOC](#).

Course Staff

Instructor	(Guest) Co-instructor	(Guest) Co-instructor



AI Engineer

The screenshot shows the homepage of the AI Engineer YouTube channel. The channel's name is "AI Engineer" and its handle is "@aiDotEngineer". It has 117K subscribers and 228 videos. The channel's bio reads: "Talks, workshops, events, and training for AI Engineers. ...more". Below the bio is the website "ai.engineer". A "Subscribe" button is visible. The navigation bar includes "Home", "Videos" (which is selected), "Live", "Playlists", and a search icon. Below the navigation bar are three filter buttons: "Latest" (selected), "Popular", and "Oldest". The main content area displays a grid of video thumbnails. Each thumbnail includes the video title, duration, and view count.

Video Title	Duration	Views	Published
OpenAI Agents	24:22	31K	3 weeks ago
Build Your Own AI Data Center	23:00	5.1K	3 weeks ago
Function calling is all you need	1:42:54	22K	1 month ago
What Makes a Good AI Agent?	15:28	19K	1 month ago
Evaluating Domain Specific LLMs for Real World Finance	12:01	8.5K	1 month ago
Devops Engineer Who Never Sleeps	16:18	5.7K	1 month ago
Self Coding Agents	17:23	37K	1 month ago
Vercel AI SDK	59:52	14K	1 month ago



Agents

Authors: Julia Wiesinger, Patrick Marlow and Vladimir Vuskovic



Google

OpenAI

A practical guide to building agents



Engineering at Anthropic



Published Dec 19, 2024

Claude API Solutions Research Commitments Learn News

Building effective agents

We've worked with dozens of teams building LLM agents across industries. Consistently, the most successful implementations use simple, composable patterns rather than complex frameworks.

Over the past year, we've worked with dozens of teams building large language model (LLM) agents across industries. Consistently, the most successful implementations weren't using complex frameworks or specialized libraries. Instead, they were building with simple, composable patterns.

In this post, we share what we've learned from working with our customers and building agents ourselves, and give practical advice for developers on building effective agents.



10
4


Milad Mohammadi – NLP Reading Group – “Cognitive Architectures for Language Agents” – Nov. 2024

Generative AI Technology Stack



Frontend Hosting

Vercel • Netlify • GitHub Pages



LangChain

Runtime/Framework

LangChain • HuggingFace • LlamaIndex • Replicate



LlamaIndex



SingleStore™

Vector Databases

Pinecone • Weaviate • Qdrant • SingleStore • Chroma




Qdrant



Foundation Models

OpenAI • Anthropic • Cohere • Meta • Mistral



LLM



NVIDIA

Infrastructure

NVIDIA • AWS • Google Cloud • Azure • Together.ai



together.ai

Source: Pavan
Belagatti™





Home

Get started

Quickstart

LangGraph basics



Deployment

Prebuilt agents

Overview

Running agents

Streaming

Models

Tools

MCP Integration

Context

Memory

Human-in-the-loop

Multi-agent

Evals

Deployment

UI

LangGraph framework

LangGraph components



LangGraph

[pypi v0.4.7](#) [downloads/month 5M](#) [open issues 73](#) [docs latest](#) [GitMCP 1642](#)

Trusted by companies shaping the future of agents—including Klarna, Replit, Elastic, and more—LangGraph is a low-level orchestration framework for building, managing, and deploying long-running, stateful agents.

Get started

Install LangGraph:

```
pip install -U langgraph
```



Then, create an agent using prebuilt components:

```
# pip install -qU "langchain[anthropic]" to call the model
from langgraph.prebuilt import create_react_agent

def get_weather(city: str) -> str:
    """Get weather for a given city."""
    return f"It's always sunny in {city}!"
```



Table of contents

[Get started](#)[Core benefits](#)[LangGraph's ecosystem](#)[Additional resources](#)[Acknowledgements](#)

[Introduction](#)[What is Agno](#)[Your first Agents](#)[Agent Playground](#)[Agent Monitoring](#)[Agno Community](#)[Concepts](#)[Agents >](#)[Teams >](#)[Applications >](#)[Models >](#)[Tools >](#)[Reasoning >](#)[Memory >](#)[Knowledge >](#)[Chunking >](#)[Vector DBs >](#)[Storage >](#)[Embeddings >](#)[Evals >](#)[Contributing](#)

Introduction

What is Agno

Agno is a lightweight, high-performance library for building Agents.

It helps you progressively build the 5 levels of Agentic Systems:

- Level 1: Agents with tools and instructions.
- Level 2: Agents with knowledge and storage.
- Level 3: Agents with memory and reasoning.
- Level 4: Teams of Agents with collaboration and coordination.
- Level 5: Agentic Workflows with state and determinism.

Here's a Investment Research Agent that analyzes stocks, reasoning through each step:

[reasoning_finance_agent.py](#)

```
from agno.agent import Agent
from agno.models.anthropic import Claude
from agno.tools.reasoning import ReasoningTools
from agno.tools.yfinance import YFinanceTools

agent = Agent(
    model=Claude(id="claude-3-7-sonnet-latest"),
    tools=[
        ReasoningTools(add_instructions=True),
        YFinanceTools(stock_price=True, analyst_recommendations=True, company_info=True)
    ],
    max_tokens=10000,
    temperature=0.0,
    top_p=1.0,
    presence_penalty=0.0,
    frequency_penalty=0.0,
    stop=None,
    user="Investment Research Agent"
)
```

[On this page](#)[Key features](#)[Getting Started](#)[Dive deeper](#)

TOOLS

Using tools

Remote MCP

Web search

File search

Image generation

Code interpreter

Computer use

AGENTS**Building agents**

Voice agents

Agents SDK ↗

REALTIME API

Using the Realtime API

Realtime conversations

Realtime transcription

Voice activity detection

MODEL OPTIMIZATION

Overview

Cookbook

Forum

Help

Agents

[Copy page](#)

Learn how to build agents with the OpenAI API.

Agents represent systems that intelligently accomplish tasks, ranging from executing simple workflows to pursuing complex, open-ended objectives.

OpenAI provides a rich set of composable primitives that enable you to build agents. This guide walks through those primitives, and how they come together to form a robust agentic platform.

Overview

Building agents involves assembling components across several domains—such as models, tools, knowledge and memory, audio and speech, guardrails, and orchestration—and OpenAI provides composable primitives for each.

DOMAIN	DESCRIPTION	OPENAI PRIMITIVES
Models	Core intelligence capable of reasoning, making decisions, and processing different modalities.	o1 , o3-mini , GPT-4.5 , GPT-4o , GPT-4o-mini
Tools	Interface to the world, interact with environment, function calling, built-in tools, etc.	Function calling , Web search , File search , Computer use
Knowledge and memory	Augment agents with external and persistent knowledge.	Vector stores , File search , Embeddings
Audio and speech	Create agents that can understand audio and respond back in natural language.	Audio generation , realtime , Audio agents
Guardrails	Prevent irrelevant, harmful, or undesirable behavior.	Moderation , Instruction hierarchy
Orchestration	Develop, deploy, monitor, and improve agents.	Agents SDK , Tracing , Evaluations , Fine-tuning
Voice agents	Create agents that can understand audio and respond back in natural language.	Realtime API , Voice support in the Agents SDK

Overview

Models

Tools

Knowledge & memory

Guardrails

Orchestration



Flexible AI workflow automation for technical teams

Build with the precision of code or the speed of drag-n-drop. Host with on-prem control or in-the-cloud convenience. n8n gives you more freedom to implement multi-step AI agents and integrate apps than any other tool.

[Get started for free](#)[Talk to sales](#)

IT Ops can

⚡ On-board new employees and provision accounts

Sec Ops can


⚡ Enrich security incident tickets

Dev Ops can

⚡ Convert natural language commands into API calls

Sales can

⚡ Generate customer insights from grouped reviews





Looking forward to exploring new ideas
and collaborating on exciting future
research together!

miladmohammadi@ut.ac.ir

miladmohammadi.xyz

CREDITS: This presentation template was created by **Slidesgo**, and includes icons by **Flaticon** and infographics & images by **Freepik**

Thanks!

