



# Sorting in linear time

Data Structures & Algorithms

# Counting Sort

**Counting sort** assumes that each of the  $n$  input elements is an integer in the range 0 to  $k$ , for some integer  $k$ .

COUNTING-SORT( $A, B, k$ )

```
1  let  $C[0..k]$  be a new array
2  for  $i = 0$  to  $k$ 
3       $C[i] = 0$ 
4  for  $j = 1$  to  $A.length$ 
5       $C[A[j]] = C[A[j]] + 1$ 
6  //  $C[i]$  now contains the number of elements equal to  $i$ .
7  for  $i = 1$  to  $k$ 
8       $C[i] = C[i] + C[i - 1]$ 
9  //  $C[i]$  now contains the number of elements less than or equal to  $i$ .
10 for  $j = A.length$  downto 1
11      $B[C[A[j]]] = A[j]$ 
12      $C[A[j]] = C[A[j]] - 1$ 
```

# Counting Sort

	1	2	3	4	5	6	7	8
A	2	5	3	0	2	3	0	3
	0	1	2	3	4	5		
C	2	0	2	3	0	1		

(a)

	0	1	2	3	4	5
C	2	2	4	7	7	8

(b)

	1	2	3	4	5	6	7	8
B							3	
	0	1	2	3	4	5		
C	2	2	4	6	7	8		

(c)

	1	2	3	4	5	6	7	8
B		0					3	
	0	1	2	3	4	5		
C	1	2	4	6	7	8		

(d)

	1	2	3	4	5	6	7	8
B		0				3	3	
	0	1	2	3	4	5		
C	1	2	4	5	7	8		

(e)

	1	2	3	4	5	6	7	8
B	0	0	2	2	3	3	3	5


(f)



# Stability

- numbers with the same value appear in the output array in the same order as they do in the input array.
- Normally, the property of stability is important only when satellite data are carried around with the element being sorted.
- Counting sort is stable.

# Radix Sort





## Radix sort


RADIX-SORT( $A, d$ )

```
1  for  $i = 1$  to  $d$ 
2      use a stable sort to sort array  $A$  on digit  $i$ 
```

Given  $n$   $d$ -digit numbers in which each digit can take on up to  $k$  possible values, RADIX-SORT correctly sorts these numbers in  $\Theta(d(n + k))$  time if the stable sort it uses takes  $\Theta(n + k)$  time.

# Bucket sort

- Bucket sort assumes that the input is drawn from a uniform distribution and has an average-case running time of  $O(n)$



## Bucket sort

BUCKET-SORT( $A$ )

```
1  let  $B[0 \dots n - 1]$  be a new array
2   $n = A.length$ 
3  for  $i = 0$  to  $n - 1$ 
4      make  $B[i]$  an empty list
5  for  $i = 1$  to  $n$ 
6      insert  $A[i]$  into list  $B[\lfloor nA[i] \rfloor]$ 
7  for  $i = 0$  to  $n - 1$ 
8      sort list  $B[i]$  with insertion sort
9  concatenate the lists  $B[0], B[1], \dots, B[n - 1]$  together in order
```





## Bucket sort

$$T(n) = \Theta(n) + \sum_{i=0}^{n-1} O(n_i^2)$$

$$\begin{aligned} E[T(n)] &= E \left[ \Theta(n) + \sum_{i=0}^{n-1} O(n_i^2) \right] \\ &= \Theta(n) + \sum_{i=0}^{n-1} E[O(n_i^2)] \\ &= \Theta(n) + \sum_{i=0}^{n-1} O(E[n_i^2]) \end{aligned}$$

## Bucket sort

$X_{ij} = I\{A[j] \text{ falls in bucket } i\}$

for  $i = 0, 1, \dots, n-1$  and  $j = 1, 2, \dots, n$ . Thus,

$$n_i = \sum_{j=1}^n X_{ij}.$$

$$\begin{aligned} E[n_i^2] &= E\left[\left(\sum_{j=1}^n X_{ij}\right)^2\right] \\ &= E\left[\sum_{j=1}^n \sum_{k=1}^n X_{ij} X_{ik}\right] \\ &= E\left[\sum_{j=1}^n X_{ij}^2 + \sum_{1 \leq j \leq n} \sum_{\substack{1 \leq k \leq n \\ k \neq j}} X_{ij} X_{ik}\right] \\ &= \sum_{j=1}^n E[X_{ij}^2] + \sum_{1 \leq j \leq n} \sum_{\substack{1 \leq k \leq n \\ k \neq j}} E[X_{ij} X_{ik}] \end{aligned}$$

$$\begin{aligned} E[X_{ij}^2] &= 1^2 \cdot \frac{1}{n} + 0^2 \cdot \left(1 - \frac{1}{n}\right) \\ &= \frac{1}{n}. \end{aligned}$$

$$\begin{aligned} E[X_{ij} X_{ik}] &= E[X_{ij}] E[X_{ik}] \\ &= \frac{1}{n} \cdot \frac{1}{n} \\ &= \frac{1}{n^2}. \end{aligned}$$

$$\begin{aligned} E[n_i^2] &= \sum_{j=1}^n \frac{1}{n} + \sum_{1 \leq j \leq n} \sum_{\substack{1 \leq k \leq n \\ k \neq j}} \frac{1}{n^2} \\ &= n \cdot \frac{1}{n} + n(n-1) \cdot \frac{1}{n^2} \\ &= 1 + \frac{n-1}{n} \\ &= 2 - \frac{1}{n}, \end{aligned}$$