



Sorting

Data Structures & Algorithms



Definition

Input: A sequence of n numbers $\langle a_1, a_2, \dots, a_n \rangle$.

Output: A permutation (reordering) $\langle a'_1, a'_2, \dots, a'_n \rangle$ of the input sequence such that $a'_1 \leq a'_2 \leq \dots \leq a'_n$.



Sorting Types

- a sorting algorithm sorts **in place** if only a constant number of elements of the input array are ever stored outside the array.
- **comparison sorts** determine the sorted order of an input array by comparing elements.

Complexity


Algorithm	Worst-case running time	Average-case/expected running time
Insertion sort	$\Theta(n^2)$	$\Theta(n^2)$
Merge sort	$\Theta(n \lg n)$	$\Theta(n \lg n)$
Heapsort	$O(n \lg n)$	—
Quicksort	$\Theta(n^2)$	$\Theta(n \lg n)$ (expected)
Counting sort	$\Theta(k + n)$	$\Theta(k + n)$
Radix sort	$\Theta(d(n + k))$	$\Theta(d(n + k))$
Bucket sort	$\Theta(n^2)$	$\Theta(n)$ (average-case)

Insertion Sort

INSERTION-SORT(A)

```

1  for  $j = 2$  to  $A.length$ 
2       $key = A[j]$ 
3      // Insert  $A[j]$  into the sorted sequence  $A[1 \dots j - 1]$ .
4       $i = j - 1$ 
5      while  $i > 0$  and  $A[i] > key$ 
6           $A[i + 1] = A[i]$ 
7           $i = i - 1$ 
8       $A[i + 1] = key$ 
    
```



Merge Sort

MERGE-SORT(A, p, r)

```
1  if  $p < r$ 
2       $q = \lfloor (p + r) / 2 \rfloor$ 
3      MERGE-SORT( $A, p, q$ )
4      MERGE-SORT( $A, q + 1, r$ )
5      MERGE( $A, p, q, r$ )
```

MERGE(A, p, q, r)

```
1   $n_1 = q - p + 1$ 
2   $n_2 = r - q$ 
3  let  $L[1..n_1 + 1]$  and  $R[1..n_2 + 1]$  be new arrays
4  for  $i = 1$  to  $n_1$ 
5       $L[i] = A[p + i - 1]$ 
6  for  $j = 1$  to  $n_2$ 
7       $R[j] = A[q + j]$ 
8   $L[n_1 + 1] = \infty$ 
9   $R[n_2 + 1] = \infty$ 
10  $i = 1$ 
11  $j = 1$ 
12 for  $k = p$  to  $r$ 
13     if  $L[i] \leq R[j]$ 
14          $A[k] = L[i]$ 
15          $i = i + 1$ 
16     else  $A[k] = R[j]$ 
17          $j = j + 1$ 
```



Bubble sort

BUBBLESORT(A)

```
1  for  $i = 1$  to  $A.length - 1$ 
2      for  $j = A.length$  downto  $i + 1$ 
3          if  $A[j] < A[j - 1]$ 
4              exchange  $A[j]$  with  $A[j - 1]$ 
```

Selection Sort

ALGORITHM *SelectionSort*($A[0..n - 1]$)

//Sorts a given array by selection sort

//Input: An array $A[0..n - 1]$ of orderable elements

//Output: Array $A[0..n - 1]$ sorted in nondecreasing order

for $i \leftarrow 0$ **to** $n - 2$ **do**

$min \leftarrow i$

for $j \leftarrow i + 1$ **to** $n - 1$ **do**

if $A[j] < A[min]$ $min \leftarrow j$

 swap $A[i]$ and $A[min]$



Heap Sort

HEAPSORT(A)

```
1  BUILD-MAX-HEAP( $A$ )
2  for  $i = A.length$  downto 2
3      exchange  $A[1]$  with  $A[i]$ 
4       $A.heap-size = A.heap-size - 1$ 
5      MAX-HEAPIFY( $A, 1$ )
```

Quick Sort

QUICKSORT(A, p, r)

```

1  if  $p < r$ 
2       $q = \text{PARTITION}(A, p, r)$ 
3      QUICKSORT( $A, p, q - 1$ )
4      QUICKSORT( $A, q + 1, r$ )



```

PARTITION(A, p, r)


```

1   $x = A[r]$ 
2   $i = p - 1$ 
3  for  $j = p$  to  $r - 1$ 
4      if  $A[j] \leq x$ 
5           $i = i + 1$ 
6          exchange  $A[i]$  with  $A[j]$ 
7  exchange  $A[i + 1]$  with  $A[r]$ 
8  return  $i + 1$ 

```



Two case in partition





Performance of quicksort

- Worst-case

$$\begin{aligned}T(n) &= T(n-1) + T(0) + \Theta(n) \\ &= T(n-1) + \Theta(n) .\end{aligned}$$

- Best-case

$$T(n) = 2T(n/2) + \Theta(n)$$



Random version of partition

RANDOMIZED-PARTITION(A, p, r)

- 1 $i = \text{RANDOM}(p, r)$
- 2 exchange $A[r]$ with $A[i]$
- 3 **return** PARTITION(A, p, r)

Average case

- each pair of elements is compared at most once:
 - Elements are compared only to the pivot element and, after a particular call of PARTITION finishes, the pivot element used in that call is never again compared to any other elements.

$$X_{ij} = I\{z_i \text{ is compared to } z_j\}$$

$$X = \sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij}$$

$$E[X] = E\left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{ij}\right]$$

$$= \sum_{i=1}^{n-1} \sum_{j=i+1}^n E[X_{ij}]$$

$$= \sum_{i=1}^{n-1} \sum_{j=i+1}^n \Pr\{z_i \text{ is compared to } z_j\}$$

Average case

$$\begin{aligned}\Pr\{z_i \text{ is compared to } z_j\} &= \Pr\{z_i \text{ or } z_j \text{ is first pivot chosen from } Z_{ij}\} \\ &= \Pr\{z_i \text{ is first pivot chosen from } Z_{ij}\} \\ &\quad + \Pr\{z_j \text{ is first pivot chosen from } Z_{ij}\} \\ &= \frac{1}{j-i+1} + \frac{1}{j-i+1} \\ &= \frac{2}{j-i+1}.\end{aligned}$$

$$E[X] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1}$$

Average case

$$\begin{aligned} E[X] &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n \frac{2}{j-i+1} \\ &= \sum_{i=1}^{n-1} \sum_{k=1}^{n-i} \frac{2}{k+1} \\ &< \sum_{i=1}^{n-1} \sum_{k=1}^n \frac{2}{k} \\ &= \sum_{i=1}^{n-1} O(\lg n) \\ &= O(n \lg n) . \end{aligned}$$