

## 1. Includes

Includes works more like components from Laravel like <x-component>

Example, from child component snippets like **navigation.php**,

```
<nav class="navbar navbar-inverse navbar-fixed-top" role="navigation">
  <div class="container">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle" data-toggle="collapse"
        data-target="#bs-example-navbar-collapse-1">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Start Bootstrap</a>
    </div>
    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">
        <li>
          <a href="#">About</a>
        </li>
        <li>
          <a href="#">Services</a>
        </li>
        <li>
          <a href="#">Admin</a>
        </li>
      </ul>
    </div>
    <!-- /.navbar-collapse -->
  </div>
  <!-- /.container -->
</nav>
```

Now from where it is included, like **index.php**,

```
<?php include("includes/header.php"); ?>
```

Example code snippet,

```
<?php include("includes/header.php"); ?>

<div class="row">

  <!-- Blog Entries Column -->
  <div class="col-md-8">

  </div>

  <!-- Blog Sidebar Widgets Column -->
  <div class="col-md-4">

    <?php include("includes/sidebar.php"); ?>
```

```
</div>  
<!-- /.row -->  
  
<?php include("includes/footer.php"); ?>
```