




UNIVERSITY OF
WATERLOO



Ecological and Resilient
Autonomous robots
Laboratory



Value Iteration for Learning Concurrently Executable Robotic Control Tasks

Sheikh A. Tahmid and Gennaro Notomista

24th International Conference on Autonomous Agents and Multiagent Systems

Department of Electrical and Computer Engineering, University of Waterloo, Canada

Motivation



Modern robots are required to do complex tasks and possibly multiple at the same time.

- Let's use RL to learn several control tasks for a robotic system to execute.
 - RL lets us generalize to possibly complex control tasks.
- Let's combine and execute each of these tasks together.
 - Preferably in a way that lets us swap out tasks and/or reorder priorities.
- How do we know that tasks will not interfere with each other?

Assumptions

- Assume that our robotic system is control-affine:

$$\dot{x} = f(x) + g(x)u, \quad x \in \mathbb{R}^n, \quad u \in \mathbb{R}^p$$

- Assume that each RL task we learn is encoded with a “cost-to-go”/value function of the form:

$$J_i(x) \approx \min_{u(\cdot)} \int_t^\infty e^{-\beta\tau} \left(q_i(x(\tau)) + \|u(\tau)\|^2 \right) d\tau \quad q_i \text{ is P.S.D}$$

Key Related Works

Related Work - Combining Learned Tasks Using a Min-Norm Controller

- Treat learned value functions as Control Lyapunov Functions
- Make progress on each task using constrained optimization problem

$$\begin{aligned} \min_{u \in \mathcal{U}, \delta \in \mathbb{R}^N} \quad & \|u\|^2 + \kappa \|\delta\|^2 \\ \text{s.t.} \quad & L_f J_1(x) + L_g J_1(x)u \leq -\sigma_1(x) + \delta_1 \\ & \vdots \\ & L_f J_N(x) + L_g J_N(x)u \leq -\sigma_N(x) + \delta_N \\ & K\delta \geq 0 \end{aligned}$$

Note that: $L_f J_i(x) = \frac{\partial J_i}{\partial x} f(x)$, $L_g J_i(x) = \frac{\partial J_i}{\partial x} g(x)$.

Related Work - Value Iteration for Continuous Action Spaces

Assume continuous, control-affine dynamics and cost function as mentioned previously.

$$\dot{x} = f(x) + g(x)u, \quad x \in \mathbb{R}^n, \quad u \in \mathbb{R}^p$$

$$J_i(x) \approx \min_{u(\cdot)} \int_t^\infty (q_i(x(\tau)) + \|u(\tau)\|^2) d\tau$$

Use expression from solved HJB equation as “optimal input” at each iteration.

$$u^* = -\frac{1}{2}(L_g J_i(x))^\top = -\frac{1}{2}g(x)^\top \left(\frac{\partial J_i}{\partial x} \right)^\top$$

[2] M. Lutter, S. Mannor, J. Peters, D. Fox, and A. Garg, “Value Iteration in Continuous Actions, States and Time,” in Proceedings of the 38th International Conference on Machine Learning, Jul. 2021, vol. 139, pp. 7224–7234.

Related Work - Independence and Orthogonality for Robotic Control Tasks

- Work in [3] defines notions of independence and orthogonality between Jacobian-based tasks to analyze how multi-joint robot arms can achieve multiple tasks at the same time.
- Work in [4] define these notions for Extended Set-Based Tasks.

[3] Gianluca Antonelli. 2009. Stability Analysis for Prioritized Closed-Loop Inverse Kinematic Algorithms for Redundant Robotic Systems. *IEEE Transactions on Robotics* 25, 5 (2009), 985–994

[4] Gennaro Notomista, Mario Selvaggio, María Santos, Siddharth Mayya, Francesca Pagano, Vincenzo Lippiello, and Cristian Secchi. 2023. Beyond Jacobian-based tasks: Extended set-based tasks for multi-task execution and prioritization. (2023).

How do we know that tasks are compatible with each other?


$$\begin{aligned} \min_{u \in \mathcal{U}, \delta \in \mathbb{R}^N} \quad & \|u\|^2 \\ \text{s.t.} \quad & L_f J_1(x) + L_g J_1(x) u \leq -\sigma_1(x) \\ & \vdots \\ & L_f J_N(x) + L_g J_N(x) u \leq -\sigma_N(x) \end{aligned}$$

We do not.

Sometimes they are compatible

$J_1 \rightarrow$ Learn to avoid circular region


$J_2 \rightarrow$ Learn to go to some point



Sometimes they are compatible

$J_1 \rightarrow$ Learn to avoid circular region


$J_2 \rightarrow$ Learn to go to some point



Sometimes they are compatible

$J_1 \rightarrow$ Learn to avoid circular region


$J_2 \rightarrow$ Learn to go to some point



Sometimes they are compatible

$J_1 \rightarrow$ Learn to avoid circular region


$J_2 \rightarrow$ Learn to go to some point



Sometimes they are compatible

$J_1 \rightarrow$ Learn to avoid circular region


$J_2 \rightarrow$ Learn to go to some point



Sometimes they are compatible

$J_1 \rightarrow$ Learn to form a triangle

$J_2 \rightarrow$ Learn to send one robot to a point




Sometimes they are NOT compatible

$J_1 \rightarrow$ Learn to avoid square-shaped region

$J_2 \rightarrow$ Learn to go to a point



Sometimes they are NOT compatible



- The above are heat maps of the two value functions.
- Combining them results in the trajectory on the right.

Definitions of Independence and Orthogonality

$$\begin{aligned} \min_{u \in \mathcal{U}, \delta \in \mathbb{R}^N} \quad & \|u\|^2 \\ \text{s.t.} \quad & L_f J_1(x) + L_g J_1(x) u \leq -\sigma_1(x) \\ & \vdots \\ & L_f J_N(x) + L_g J_N(x) u \leq -\sigma_N(x) \end{aligned}$$

J_1, \dots, J_N are *independent* at $x \in \mathcal{X} \Leftrightarrow L_g J_1(x)^\top, \dots, L_g J_N(x)^\top$ are linearly independent

J_1, \dots, J_N are *orthogonal* at $x \in \mathcal{X} \Leftrightarrow \langle L_g J_i(x)^\top, L_g J_j(x)^\top \rangle = 0 \quad \forall i, j \in \{1, \dots, N\}$

Introducing “Interference” Input Cost

$$J_{N+1} \approx \min_{u(\cdot)} \int_t^\infty e^{-\beta\tau} \left(q_{N+1}(x) + \|u\|^2 + \sum_{i=1}^N (L_g J_i(x) u)^2 \lambda_i \right) d\tau$$

In Proposition 2, we show that by picking large enough values of λ_i and successfully fitting the cost functional, we can make the new task, J_{N+1} , independent to previously trained tasks J_1, \dots, J_N .

Variant of Value Iteration in Continuous Action Space

Can extend previous work in [2] to approximate this new cost functional.

$$J_{N+1} \approx \min_{u(\cdot)} \int_t^\infty e^{-\beta\tau} \left(q_{N+1}(x) + \|u\|^2 + \sum_{i=1}^N (L_g J_i(x) u)^2 \lambda_i \right) d\tau$$

At each iteration, use the following input to estimate the next iteration of the value function.

$$u^* = -\frac{1}{2} R(x)^{-1} (L_g J_{N+1}(x))^\top$$
$$R(x) = I + \sum_{i=1}^N (L_g J_i(x))^\top L_g J_i(x)$$

[2] M. Lutter, S. Mannor, J. Peters, D. Fox, and A. Garg, “Value Iteration in Continuous Actions, States and Time,” in Proceedings of the 38th International Conference on Machine Learning, Jul. 2021, vol. 139, pp. 7224–7234.

Proposition 3:


Assume that J_1, \dots, J_N are independent at $x \in \mathcal{X}$.

If we train a new cost-to-go function, J_{N+1} to be independent to J_1, \dots, J_N ,
 J_{N+1} is orthogonal to each of J_1, \dots, J_N at $x \in \mathcal{X}$.

\Leftrightarrow




the optimal input is $-\frac{1}{2}L_g J_{N+1}(x)^\top$.

Now they ARE compatible.



- The above are heat maps of the two value functions.
- Combining them results in the trajectory on the right.

We tried our idea on other scenarios.



Summary of Contributions

- Defined notions of independence and orthogonality for learned value functions
- Introduced “interference” for encouraging newly trained value functions to be independent to previous ones
- Introduced variant of value iteration for continuous input/action space that can fit cost functionals with this new “interference” cost
- Tested our idea in a few different scenarios involving controlling a team of mobile robots