

# Class 13: RNA-Seq analysis mini-project

Tahmid Ahmed

## Section 1. Differential Expression Analysis

```
library(DESeq2)
```

Loading required package: S4Vectors

Loading required package: stats4

Loading required package: BiocGenerics

Attaching package: 'BiocGenerics'

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

anyDuplicated, aperm, append, as.data.frame, basename, cbind,  
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,  
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,  
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,  
Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,  
table, tapply, union, unique, unsplit, which.max, which.min

Attaching package: 'S4Vectors'

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgPerRowSet, colCollapse,  
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,  
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,  
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,  
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,  
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,  
colWeightedMeans, colWeightedMedians, colWeightedSds,  
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgPerColSet,  
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,  
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,  
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,  
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,  
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,  
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,  
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with  
'browseVignettes()'. To cite Bioconductor, see  
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

Load our data files

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"
```

```
# Import metadata and take a peak
colData = read.csv(metaFile, row.names=1)
head(colData)
```

```
              condition
SRR493366 control_sirna
SRR493367 control_sirna
SRR493368 control_sirna
SRR493369      hoxa1_kd
SRR493370      hoxa1_kd
SRR493371      hoxa1_kd
```

```
# Import countdata
countData = read.csv(countFile, row.names=1)
head(countData)
```

	length	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370
ENSG00000186092	918	0	0	0	0	0
ENSG00000279928	718	0	0	0	0	0
ENSG00000279457	1982	23	28	29	29	28
ENSG00000278566	939	0	0	0	0	0
ENSG00000273547	939	0	0	0	0	0
ENSG00000187634	3214	124	123	205	207	212

	SRR493371
ENSG00000186092	0
ENSG00000279928	0
ENSG00000279457	46
ENSG00000278566	0
ENSG00000273547	0
ENSG00000187634	258

Q. Complete the code below to remove the troublesome first column from countData

```
# Note we need to remove the odd first $length col
countData <- as.matrix(countData[,-1])
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

```
# Filter count data where you have 0 read count across all samples.
countData = countData[rowSums(countData, na.rm = TRUE, ) > 0, ]
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000279457	23	28	29	29	28	46
ENSG00000187634	124	123	205	207	212	258
ENSG00000188976	1637	1831	2383	1226	1326	1504
ENSG00000187961	120	153	180	236	255	357

ENSG00000187583	24	48	65	44	48	64
ENSG00000187642	4	9	16	14	16	16

```
dds = DESeqDataSetFromMatrix(countData=countData,
                              colData=colData,
                              design=~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds = DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
dds
```

```
class: DESeqDataSet
dim: 15975 6
metadata(1): version
assays(4): counts mu H cooks
rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
               ENSG00000271254
rowData names(22): baseMean baseVar ... deviance maxCooks
colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
colData names(2): condition sizeFactor
```


Q. Call the `summary()` function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff.

```
res = results(dds, contrast=c("condition", "hoxa1_kd", "control_sirna"))
summary(res)
```

```
out of 15975 with nonzero total read count
adjusted p-value < 0.1
LFC > 0 (up)      : 4349, 27%
LFC < 0 (down)    : 4396, 28%
outliers [1]      : 0, 0%
low counts [2]    : 1237, 7.7%
(mean count < 0)
[1] see 'cooksCutoff' argument of ?results
[2] see 'independentFiltering' argument of ?results
```

Volcano Plot

```
plot( res$log2FoldChange, -log(res$padj) )
```



Q. Improve this plot by completing the below code, which adds color and axis labels

```


# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2
inds <- (res$padj < 0.01 ) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col=mycols, xlab="Log2(FoldChange)", ylab="-Log("

```



Q. Use the `mapIDs()` function multiple times to add SYMBOL, ENTREZID and GENENAME annotation to our results by completing the code below.

```

library("AnnotationDbi")
library("org.Hs.eg.db")

```

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
res$symbol = mapIds(org.Hs.eg.db,  
  keys=row.names(res),  
  keytype="ENSEMBL",  
  column="ENTREZID",  
  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez = mapIds(org.Hs.eg.db,  
  keys=row.names(res),  
  keytype="ENSEMBL",  
  column="ENTREZID",  
  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$name = mapIds(org.Hs.eg.db,  
  keys=row.names(res),  
  keytype="ENSEMBL",  
  column="ENTREZID",  
  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```



log2 fold change (MLE): condition hoxa1\_kd vs control\_sirna  
Wald test p-value: condition hoxa1 kd vs control sirna  
DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630158	1.43990e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01
ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51282e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467163	8.346304	7.04321e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez	name	
	<numeric>	<character>	<character>	<character>	
ENSG00000279457	6.86555e-01	NA	NA	NA	
ENSG00000187634	5.15718e-03	148398	148398	148398	
ENSG00000188976	1.76549e-35	26155	26155	26155	
ENSG00000187961	1.13413e-07	339451	339451	339451	
ENSG00000187583	9.19031e-01	84069	84069	84069	
ENSG00000187642	4.03379e-01	84808	84808	84808	
ENSG00000188290	1.30538e-24	57801	57801	57801	
ENSG00000187608	2.37452e-02	9636	9636	9636	
ENSG00000188157	4.21963e-16	375790	375790	375790	
ENSG00000237330	NA	401934	401934	401934	

Q. Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.

```
res = res[order(res$pvalue),]
write.csv(res, file="deseq_results.csv")
```

## Section 2. Pathway Analysis

```
library(pathview)
```

#####  
Pathview is an open source software package distributed under GNU General Public License version 3 (GPLv3). Details of GPLv3 is available at <http://www.gnu.org/licenses/gpl-3.0.html>. Particullary, users are required to

formally cite the original Pathview paper (not just mention it) in publications or products. For details, do `citation("pathview")` within R.

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

#####

```
library(gage)
```

```
library(gageData)
```

```
data(kegg.sets.hs)
```

```
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
```

```
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways
```

```
head(kegg.sets.hs, 3)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"  
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"  
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"  
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"  
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"  
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"  
[49] "8824" "8833" "9" "978"
```

```
$`hsa00230 Purine metabolism`
```

```
[1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"  
[9] "108" "10846" "109" "111" "11128" "11164" "112" "113"  
[17] "114" "115" "122481" "122622" "124583" "132" "158" "159"  
[25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"  
[33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
```

```

[41] "271"      "27115"    "272"      "2766"     "2977"     "2982"     "2983"     "2984"
[49] "2986"     "2987"     "29922"    "3000"     "30833"    "30834"    "318"      "3251"
[57] "353"      "3614"     "3615"     "3704"     "377841"   "471"      "4830"     "4831"
[65] "4832"     "4833"     "4860"     "4881"     "4882"     "4907"     "50484"    "50940"
[73] "51082"    "51251"    "51292"    "5136"     "5137"     "5138"     "5139"     "5140"
[81] "5141"     "5142"     "5143"     "5144"     "5145"     "5146"     "5147"     "5148"
[89] "5149"     "5150"     "5151"     "5152"     "5153"     "5158"     "5167"     "5169"
[97] "51728"    "5198"     "5236"     "5313"     "5315"     "53343"    "54107"    "5422"
[105] "5424"     "5425"     "5426"     "5427"     "5430"     "5431"     "5432"     "5433"
[113] "5434"     "5435"     "5436"     "5437"     "5438"     "5439"     "5440"     "5441"
[121] "5471"     "548644"   "55276"    "5557"     "5558"     "55703"    "55811"    "55821"
[129] "5631"     "5634"     "56655"    "56953"    "56985"    "57804"    "58497"    "6240"
[137] "6241"     "64425"    "646625"   "654364"   "661"      "7498"     "8382"     "84172"
[145] "84265"    "84284"    "84618"    "8622"     "8654"     "87178"    "8833"     "9060"
[153] "9061"     "93034"    "953"      "9533"     "954"      "955"      "956"      "957"
[161] "9583"     "9615"

```

```

foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)

```

```

      1266      54855      1465      51232      2034      2317
-2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792

```

```

# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)

```

```

attributes(keggres)

```

```

$names
[1] "greater" "less"    "stats"

```

```

# Look at the first few down (less) pathways
head(keggres$less)

```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05

hsa03013	RNA transport	1.375901e-03	-3.028500	1.375901e-03
hsa03440	Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114	Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010	Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03
		q.val	set.size	exp1
hsa04110	Cell cycle	0.001448312	121	8.995727e-06
hsa03030	DNA replication	0.007586381	36	9.424076e-05
hsa03013	RNA transport	0.073840037	144	1.375901e-03
hsa03440	Homologous recombination	0.121861535	28	3.066756e-03
hsa04114	Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010	Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04110.pathview.png

```
# A different PDF based output of the same data
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04110.pathview.pdf

```
## Focus on top 5 upregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$greater)[1:5]

# Extract the 8 character long IDs part of each string
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
[1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04640.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04630.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa00140.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04142.pathview.png

Info: some node width is different from others, and hence adjusted!

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04330.pathview.png

Q. Can you do the same procedure as above to plot the pathview figures for the top 5 down-regulated pathways?

```
## Focus on top 5 downregulated pathways here
keggrespathways.less <- rownames(keggres$less)[1:5]

# Extract the 8 character long IDs part of each string
keggresids.less = substr(keggrespathways.less, start=1, stop=8)
keggresids.less
```

```
[1] "hsa04110" "hsa03030" "hsa03013" "hsa03440" "hsa04114"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids.less, species="hsa")
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class_13
```

```
Info: Writing image file hsa04110.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class_13
```

```
Info: Writing image file hsa03030.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class_13
```

```
Info: Writing image file hsa03013.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```


```
Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class_13
```

```
Info: Writing image file hsa03440.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```


Info: Working in directory /Users/tahmid/Desktop/BIMM 143 Fall 2022/Class\_13

Info: Writing image file hsa04114.pathview.png




# DNA REPLICATION


## Replication complex (Bacteria)



## Replication complex (Archaea)




## Replication complex (Eukaryotes)





# NUCLEOCYTOPLASMIC TRANSPORT



## Nuclear Pore complex (NPC)

Cytoplasmic fibrils										Nup358 complex				
ALADIN	hCG1	Gle1	DDX19	Rae1	Nup98	Nup214	Nup88			RanBP2	RanGAP	UBC9	SUMO	
Cytoplasmic ring / Nucleoplasmic ring (Symmetrical nups)														
Nup160	Nup85	Sec13	Nup107	Nup133		Nup96		Seh1	Nup43	Nup37	ELYS			
						Nup145								
Central channel					Spoke complex									
Nup62	Nup84	Nup54			Nup205	Nup188	Nup155	Nup93	Nup53					
									Nup59					
Luminal ring														
NDC1	gp210	pm121	pm152	pm34	pm33									
Nuclear basket														
Tpr	Nup20	Nup153	Smp2											
	Nup2	Nup1			Nup60									

## Nuclear transport complex

Importin					Adaptor proteins				
IPOA	IPOB				SPN1				
Exportin									
XPO	Ran	eEF1A			PHAX	CBC			
					NMD3				

## Exon-junction complex (EJC)


EJC inner core				
Y14	MAGOH	MLN51	EIF4A3	
EJC outer shell				
ACINI	SAP18	RNPS1	Pinin	RefAly


## Transiently interacting factors

Upl1	Upl2	Upl3		
Tap	p15	UAP56	SRm160	PYM

## Transcription-export (TREX) complex

THO subcomplex				
THOC1	THOC2	THOC5	THOC6	THOC7
				TEX1





```
data(go.sets.hs)
data(go.subs.hs)
```

```
# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]
```

```
gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)
```

```
lapply(gobpres, head)
```

```
$greater
```

	p.geomean	stat.mean	p.val
G0:0007156 homophilic cell adhesion	8.519724e-05	3.824205	8.519724e-05
G0:0002009 morphogenesis of an epithelium	1.396681e-04	3.653886	1.396681e-04
G0:0048729 tissue morphogenesis	1.432451e-04	3.643242	1.432451e-04
G0:0007610 behavior	2.195494e-04	3.530241	2.195494e-04

G0:0060562	epithelial tube morphogenesis	5.932837e-04	3.261376	5.932837e-04
G0:0035295	tube development	5.953254e-04	3.253665	5.953254e-04
		q.val	set.size	exp1
G0:0007156	homophilic cell adhesion	0.1951953	113	8.519724e-05
G0:0002009	morphogenesis of an epithelium	0.1951953	339	1.396681e-04
G0:0048729	tissue morphogenesis	0.1951953	424	1.432451e-04
G0:0007610	behavior	0.2243795	427	2.195494e-04
G0:0060562	epithelial tube morphogenesis	0.3711390	257	5.932837e-04
G0:0035295	tube development	0.3711390	391	5.953254e-04

\$less

		p.geomean	stat.mean	p.val
G0:0048285	organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280	nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067	mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059	chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236	mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10
		q.val	set.size	exp1
G0:0048285	organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280	nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067	mitosis	5.841698e-12	352	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059	chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236	mitotic prometaphase	1.178402e-07	84	1.729553e-10

\$stats

	stat.mean	exp1
G0:0007156	homophilic cell adhesion	3.824205
G0:0002009	morphogenesis of an epithelium	3.653886
G0:0048729	tissue morphogenesis	3.643242
G0:0007610	behavior	3.530241
G0:0060562	epithelial tube morphogenesis	3.261376
G0:0035295	tube development	3.253665

#### Section 4. Reactome Analysis

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quo
```

Q: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?

Signaling by Rho GTPases, Miro GTPases and RHOBTB3 has the most significant “Entities p-value” of 1.39E-5. No the pathways listed do not match my previous KEGG results. The differences could be caused by our KEGG using Log2 and LogAdj changes whereas reactome could have different methods.

```
sessionInfo()
```

```
R version 4.2.2 (2022-10-31)
```

```
Platform: x86_64-apple-darwin17.0 (64-bit)
```

```
Running under: macOS Big Sur ... 10.16
```

```
Matrix products: default
```

```
BLAS: /Library/Frameworks/R.framework/Versions/4.2/Resources/lib/libRblas.0.dylib
```

```
LAPACK: /Library/Frameworks/R.framework/Versions/4.2/Resources/lib/libRlapack.dylib
```

```
locale:
```

```
[1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
```

```
attached base packages:
```

```
[1] stats4      stats      graphics  grDevices  utils      datasets  methods
```

```
[8] base
```

```
other attached packages:
```

```
[1] gageData_2.36.0          gage_2.48.0
```

```
[3] pathview_1.38.0          org.Hs.eg.db_3.16.0
```

```
[5] AnnotationDbi_1.60.0     DESeq2_1.38.0
```

```
[7] SummarizedExperiment_1.28.0 Biobase_2.58.0
```

```
[9] MatrixGenerics_1.10.0    matrixStats_0.62.0
```

```
[11] GenomicRanges_1.50.1     GenomeInfoDb_1.34.2
```

```
[13] IRanges_2.32.0           S4Vectors_0.36.0
```

```
[15] BiocGenerics_0.44.0
```

```
loaded via a namespace (and not attached):
```

```
[1] httr_1.4.4               bit64_4.0.5              jsonlite_1.8.3
```

```
[4] splines_4.2.2            blob_1.2.3               GenomeInfoDbData_1.2.9
```

```
[7] yaml_2.3.6               pillar_1.8.1             RSQLite_2.2.18
```

[10] lattice_0.20-45	glue_1.6.2	digest_0.6.30
[13] RColorBrewer_1.1-3	XVector_0.38.0	colorspace_2.0-3
[16] htmltools_0.5.3	Matrix_1.5-1	XML_3.99-0.12
[19] pkgconfig_2.0.3	genefilter_1.80.0	zlibbioc_1.44.0
[22] GO.db_3.16.0	xtable_1.8-4	scales_1.2.1
[25] BiocParallel_1.32.0	tibble_3.1.8	annotate_1.76.0
[28] KEGGREST_1.38.0	generics_0.1.3	ggplot2_3.4.0
[31] cachem_1.0.6	cli_3.4.1	survival_3.4-0
[34] magrittr_2.0.3	crayon_1.5.2	KEGGgraph_1.58.0
[37] memoise_2.0.1	evaluate_0.18	fansi_1.0.3
[40] graph_1.76.0	tools_4.2.2	lifecycle_1.0.3
[43] stringr_1.4.1	munsell_0.5.0	locfit_1.5-9.6
[46] DelayedArray_0.24.0	Biostrings_2.66.0	compiler_4.2.2
[49] rlang_1.0.6	grid_4.2.2	RCurl_1.98-1.9
[52] bitops_1.0-7	rmarkdown_2.17	gtable_0.3.1
[55] codetools_0.2-18	DBI_1.1.3	R6_2.5.1
[58] knitr_1.40	dplyr_1.0.10	fastmap_1.1.0
[61] bit_4.0.4	utf8_1.2.2	Rgraphviz_2.42.0
[64] stringi_1.7.8	parallel_4.2.2	Rcpp_1.0.9
[67] vctrs_0.5.0	geneplotter_1.76.0	png_0.1-7
[70] tidyselect_1.2.0	xfun_0.34	