

# Bottom-Up Parsing

---

- ❖ Attempts to traverse a parse tree bottom up (**post-order traversal**)
- ❖ Reduces a sequence of tokens to the start symbol
- ❖ At each reduction step, the RHS of a production is replaced with LHS
- ❖ A reduction step corresponds to the **reverse of a rightmost derivation**
- ❖ Example: given the following grammar

$$\begin{aligned} E &\rightarrow E + T \mid T \\ T &\rightarrow T * F \mid F \\ F &\rightarrow ( E ) \mid \mathbf{id} \end{aligned}$$

A rightmost derivation for  $\mathbf{id} + \mathbf{id} * \mathbf{id}$  is shown below:

$$\begin{aligned} E &\Rightarrow_{\text{rm}} E + T \Rightarrow_{\text{rm}} E + T * F \Rightarrow_{\text{rm}} E + T * \mathbf{id} \\ &\Rightarrow_{\text{rm}} E + F * \mathbf{id} \Rightarrow_{\text{rm}} E + \mathbf{id} * \mathbf{id} \Rightarrow_{\text{rm}} T + \mathbf{id} * \mathbf{id} \\ &\Rightarrow_{\text{rm}} F + \mathbf{id} * \mathbf{id} \Rightarrow_{\text{rm}} \mathbf{id} + \mathbf{id} * \mathbf{id} \end{aligned}$$

# Handles

---

- ❖ If  $S \Rightarrow_{\text{rm}}^+ \alpha$  then  $\alpha$  is called a **right sentential form**
- ❖ A **handle** of a right sentential form is:
  - \* A substring  $\beta$  that matches the RHS of a production  $A \rightarrow \beta$
  - \* The reduction of  $\beta$  to  $A$  is a step along the reverse of a rightmost derivation
- ❖ If  $S \Rightarrow_{\text{rm}}^+ \gamma A w \Rightarrow_{\text{rm}} \gamma \beta w$ , where  $w$  is a sequence of tokens then
  - \* The substring  $\beta$  of  $\gamma \beta w$  and the production  $A \rightarrow \beta$  make the handle
- ❖ Consider the reduction of **id + id \* id** to the start symbol  $E$

<i>Sentential Form</i>	<i>Production</i>	<i>Sentential Form</i>	<i>Production</i>
<b>id</b> + id * id	$F \rightarrow \text{id}$	$E + T * \text{id}$	$F \rightarrow \text{id}$
<u>F</u> + id * id	$T \rightarrow F$	$E + \underline{T * F}$	$T \rightarrow T * F$
<u>T</u> + id * id	$E \rightarrow T$	<u>E + T</u>	$E \rightarrow E + T$
$E + \text{id} * \text{id}$	$F \rightarrow \text{id}$	$E$	
$E + \underline{F} * \text{id}$	$T \rightarrow F$		

# Stack Implementation of a Bottom-Up Parser

---

- ❖ A bottom-up parser uses an explicit stack in its implementation
- ❖ The main actions are **shift** and **reduce**
  - ★ A bottom-up parser is also known as as **shift-reduce** parser
- ❖ Four operations are defined: **shift**, **reduce**, **accept**, and **error**
  - ★ **Shift**: parser shifts the next token on the parser stack
  - ★ **Reduce**: parser reduces the RHS of a production to its LHS
    - ✧ The handle always appears on top of the stack
  - ★ **Accept**: parser announces a successful completion of parsing
  - ★ **Error**: parser discovers that a syntax error has occurred
- ❖ The parser operates by:
  - ★ Shifting tokens onto the stack
  - ★ When a handle  $\beta$  is on top of stack, parser reduces  $\beta$  to LHS of production
  - ★ Parsing continues until an error is detected or input is reduced to start symbol

# Example on Bottom-Up Parsing

❖ Consider the parsing of the input string **id + id \* id**

Stack	Input	Action	
\$	id + id * id \$	shift	
\$ <u>id</u>	+ id * id \$	reduce $F \rightarrow \text{id}$	$E \rightarrow E + T \mid T$
\$ <u>F</u>	+ id * id \$	reduce $T \rightarrow F$	$T \rightarrow T * F \mid F$
\$ <u>T</u>	+ id * id \$	reduce $E \rightarrow T$	$F \rightarrow (E) \mid \text{id}$
\$E	+ id * id \$	shift	
\$E +	id * id \$	shift	
\$E + <u>id</u>	* id \$	reduce $F \rightarrow \text{id}$	
\$E + <u>F</u>	* id \$	reduce $T \rightarrow F$	
\$E + T	* id \$	shift	
\$E + T *	id \$	shift	
\$E + T * <u>id</u>	\$	reduce $F \rightarrow \text{id}$	
\$E + <u>T * F</u>	\$	reduce $T \rightarrow T * F$	
\$ <u>E + T</u>	\$	reduce $E \rightarrow E + T$	
\$E	\$	accept	

We use \$ to mark the bottom of the stack as well as the end of input

# LR Parsing

---

- ❖ To have an operational shift-reduce parser, we must determine:
  - ★ Whether a handle appears on top of the stack
  - ★ The reducing production to be used
  - ★ The choice of actions to be made at each parsing step
- ❖ LR parsing provides a solution to the above problems
  - ★ Is a general and efficient method of shift-reduce parsing
  - ★ Is used in a number of automatic parser generators
- ❖ The LR( $k$ ) parsing technique was introduced by Knuth in 1965
  - ★ L is for Left-to-right scanning of input
  - ★ R corresponds to a Rightmost derivation done in reverse
  - ★  $k$  is the number of lookahead symbols used to make parsing decisions

# LR Parsing – cont'd

---

- ❖ LR parsing is attractive for a number of reasons ...
  - ★ Is the most general deterministic parsing method known
  - ★ Can recognize virtually all programming language constructs
  - ★ Can be implemented very efficiently
  - ★ The class of LR grammars is a proper superset of the LL grammars
  - ★ Can detect a syntax error as soon as an erroneous token is encountered
  - ★ A LR parser can be generated by a parser generating tool
- ❖ Four LR parsing techniques will be considered
  - ★ LR(0) : LR parsing with no lookahead token to make parsing decisions
  - ★ SLR(1) : Simple LR, with one token of lookahead
  - ★ LR(1) : Canonical LR, with one token of lookahead
  - ★ LALR(1) : Lookahead LR, with one token of lookahead
- ❖ LALR(1) is the preferable technique used by parser generators

# LR Parsers

- ❖ An LR parser consists of ...

- ★ Driver program

- ✧ Same driver is used for all LR parsers

- ★ Parsing stack


- ✧ Contains state information, where  $s_i$  is *state  $i$*

- ✧ States are obtained from grammar analysis

- ★ Parsing table, which has two parts

- ✧ Action section: specifies the parser actions

- ✧ Goto section: specifies the successor states



- ❖ The parser driver receives tokens from the scanner one at a time

- ❖ Parser uses top state and current token to lookup parsing table

- ❖ Different LR analysis techniques produce different tables

# LR Parsing Table Example

❖ Consider the following grammar  $G_1 \dots$

1:  $E \rightarrow E + T$

3:  $T \rightarrow \mathbf{ID}$

2:  $E \rightarrow T$

4:  $T \rightarrow ( E )$

❖ The following parsing table is obtained after grammar analysis

State	Action					Goto	
	+	ID	(	)	\$	$E$	$T$
0		S1	S2			G4	G3
1	R3			R3	R3		
2		S1	S2			G6	G3
3	R2			R2	R2		
4	S5				A		
5		S1	S2				G7
6	S5			S8			
7	R1			R1	R1		
8	R4			R4	R4		

Entries are labeled with ...

**$Sn$** : Shift token and goto state  $n$   
(call scanner for next token)

**$Rn$** : Reduce using production  $n$

**$Gn$** : Goto state  $n$  (after reduce)

**A**: Accept parse

(terminate successfully)

*blank* : Syntax error



# LR Parsing Example

Stack	Symbols	Input	Action
0	\$	id + ( id + id ) \$	S1
0 <u>1</u>	\$ <u>id</u>	+ ( id + id ) \$	R3, G3
0 <u>3</u>	\$ <u>T</u>	+ ( id + id ) \$	R2, G4
0 4	\$ E	+ ( id + id ) \$	S5
0 4 5	\$ E +	( id + id ) \$	S2
0 4 5 2	\$ E + (	id + id ) \$	S1
0 4 5 2 <u>1</u>	\$ E + ( <u>id</u>	+ id ) \$	R3, G3
0 4 5 2 <u>3</u>	\$ E + ( <u>T</u>	+ id ) \$	R2, G6
0 4 5 2 6	\$ E + ( E	+ id ) \$	S5
0 4 5 2 6 5	\$ E + ( E +	id ) \$	S1
0 4 5 2 6 5 <u>1</u>	\$ E + ( E + <u>id</u>	) \$	R3, G7
0 4 5 2 <u>6 5 7</u>	\$ E + ( <u>E + T</u>	) \$	R1, G6
0 4 5 2 6	\$ E + ( E	) \$	S8
0 4 5 <u>2 6 8</u>	\$ E + ( <u>E</u>	\$	R4, G7
0 <u>4 5 7</u>	\$ <u>E + T</u>	\$	R1, G4
0 4	\$ E	\$	A

1:  $E \rightarrow E + T$   
 2:  $E \rightarrow T$   
 3:  $T \rightarrow \text{id}$   
 4:  $T \rightarrow ( E )$

Grammar symbols do not appear on the parsing stack  
 They are shown here for clarity

# LR Parser Driver

---

- ❖ Let  $s$  be the parser stack top state and  $t$  be the current input token
- ❖ If  $action[s, t] = \text{shift } n$  then
  - ★ Push state  $n$  on the stack
  - ★ Call scanner to obtain next token
- ❖ If  $action[s, t] = \text{reduce } A \rightarrow X_1 X_2 \dots X_m$  then
  - ★ Pop the top  $m$  states off the stack
  - ★ Let  $s'$  be the state now on top of the stack
  - ★ Push  $goto[s', A]$  on the stack (using the goto section of the parsing table)
- ❖ If  $action[s, t] = \text{accept}$  then return
- ❖ If  $action[s, t] = \text{error}$  then call error handling routine
- ❖ All LR parsers behave the same way
  - ★ The difference depends on how the parsing table is computed from a CFG

# LR(0) Parser Generation – Items and States

---

- ❖ LR(0) grammars can be parsed looking only at the stack
- ❖ Making shift/reduce decisions without any lookahead token
- ❖ Based on the idea of an **item** or a **configuration**
- ❖ **An LR(0) item consists of a production and a dot**

$$A \rightarrow X_1 \dots X_i \bullet X_{i+1} \dots X_n$$

- ❖ The dot symbol  $\bullet$  may appear anywhere on the right-hand side
  - ★ Marks how much of a production has already been seen
  - ★  $X_1 \dots X_i$  appear on top of the stack
  - ★  $X_{i+1} \dots X_n$  are still expected to appear
- ❖ An LR(0) **state** is a set of LR(0) items
  - ★ It is the **set of all items that apply** at a given point in parse

# LR(0) Parser Generation – Initial State

---

❖ Consider the following grammar  $GI$ :

$$1: E \rightarrow E + T$$

$$3: T \rightarrow \mathbf{ID}$$

$$2: E \rightarrow T$$

$$4: T \rightarrow ( E )$$

❖ For LR parsing, grammars are **augmented** with a . . .

★ New start symbol  $S$ , and a

★ New start production  $0: S \rightarrow E \$$

❖ The input should be reduced to  $E$  followed by  $\$$

★ We indicate this by the item:  $S \rightarrow \bullet E \$$

❖ The initial state (numbered 0) will have the item:  $S \rightarrow \bullet E \$$

❖ An LR parser will start in state 0

❖ State 0 is initially pushed on top of parser stack

# Identifying the Initial State

---


- ❖ Since the dot appears before  $E$ , an  $E$  is expected
  - ★ There are two productions of  $E$ :  $E \rightarrow E + T$  and  $E \rightarrow T$
  - ★ Either  $E+T$  or  $T$  is expected
  - ★ The items:  $E \rightarrow \bullet E + T$  and  $E \rightarrow \bullet T$  are added to the initial state
- ❖ Since  $T$  can be expected and there are two productions for  $T$ 
  - ★ Either **ID** or  $( E )$  can be expected
  - ★ The items:  $T \rightarrow \bullet \mathbf{ID}$  and  $T \rightarrow \bullet ( E )$  are added to the initial state
- ❖ The initial state (0) is identified by the following set of items

$S$	$\rightarrow$	$\bullet E \$$
$E$	$\rightarrow$	$\bullet E + T$
$E$	$\rightarrow$	$\bullet T$
$T$	$\rightarrow$	$\bullet \mathbf{ID}$
$T$	$\rightarrow$	$\bullet ( E )$

①


# Shift Actions

- ❖ In state 0, we can shift either an **ID** or a left parenthesis
  - ★ If we shift an **ID**, we shift the dot past the **ID**
  - ★ We obtain a new item  $T \rightarrow \mathbf{ID} \bullet$  and a new state (state 1)
  - ★ If we shift a left parenthesis, we obtain  $T \rightarrow ( \bullet E )$
  - ★ Since the dot appears before  $E$ , an  $E$  is expected
  - ★ We add the items  $E \rightarrow \bullet E + T$  and  $E \rightarrow \bullet T$
  - ★ Since the dot appears before  $T$ , we add  $T \rightarrow \bullet \mathbf{ID}$  and  $T \rightarrow \bullet ( E )$
  - ★ The new set of items forms a new state (state 2)
- ❖ In State 2, we can also shift an **ID** or a left parenthesis as shown




# Reduce and Goto Actions

- ❖ In state 1, the dot appears at the end of item  $T \rightarrow \mathbf{ID} \bullet$ 
  - ★ This means that **ID** appears on top of stack and can be reduced to  $T$
  - ★ When  $\bullet$  appears at end of an item, the parser can perform a reduce action
- ❖ If **ID** is reduced to  $T$ , what is the next state of the parser?
  - ★ **ID** is popped from the stack; Previous state appears on top of stack
  - ★  $T$  is pushed on the stack
  - ★ A new item  $E \rightarrow T \bullet$  and a new state (state 3) are obtained
  - ★ If top of stack is state 0 and we push a  $T$ , we go to state 3
  - ★ Similarly, if top of stack is state 2 and we push a  $T$ , we go also to state 3



# DFA of LR(0) States

- ❖ We complete the state diagram to obtain the DFA of LR(0) states
- ❖ In state 4, if next token is \$, the parser **accepts** (successful parse)





# LR(0) Parsing Table

---

- ❖ The LR(0) parsing table is obtained from the LR(0) state diagram
- ❖ The rows of the parsing table correspond to the LR(0) states
- ❖ The columns correspond to tokens and non-terminals
- ❖ For each state transition  $i \rightarrow j$  caused by a token  $x \dots$ 
  - ★ Put **Shift**  $j$  at position  $[i, x]$  of the table
- ❖ For each transition  $i \rightarrow j$  caused by a nonterminal  $A \dots$ 
  - ★ Put **Goto**  $j$  at position  $[i, A]$  of the table
- ❖ For each state containing an item  $A \rightarrow \alpha \bullet$  of rule  $n \dots$ 
  - ★ Put **Reduce**  $n$  at position  $[i, y]$  for every token  $y$
- ❖ For each transition  $i \rightarrow \text{Accept} \dots$ 
  - ★ Put **Accept** at position  $[i, \$]$  of the table

# LR(0) Parsing Table – cont'd

- ❖ The LR(0) table of grammar  $G1$  is shown below
  - ★ For a shift, the token to be shifted determines the next state
  - ★ For a reduce, the state on top of stack specifies the production to be used

State	Action					Goto	
	+	ID	(	)	\$	$E$	$T$
0		S1	S2			G4	G3
1	R3	R3	R3	R3	R3		
2		S1	S2			G6	G3
3	R2	R2	R2	R2	R2		
4	S5				A		
5		S1	S2				G7
6	S5			S8			
7	R1	R1	R1	R1	R1		
8	R4	R4	R4	R4	R4		

Entries are labeled with ...

**$Sn$** : Shift token and goto state  $n$   
(call scanner for next token)

**$Rn$** : Reduce using production  $n$

**$Gn$** : Goto state  $n$  (after reduce)

**A**: Accept parse  
(terminate successfully)

*blank* : Syntax error

# LR(0) Closure and Goto Functions

- ❖ To construct the LR(0) DFA, we need  $closure(I)$  and  $goto(I, X)$ 
  - ★  $I$  is a set of items and  $X$  is a grammar symbol
- ❖  $Closure(I)$  returns the complete set of items for an LR(0) state
  - ★ New items are added to a state when dot appears before a non-terminal
- ❖  $Goto(I, X)$  determines next state for a given state  $I$  and symbol  $X$ 
  - ★ The dot is moved past  $X$  and the  $closure$  of new set of items is obtained

**function**  $closure(I)$

$J := I$

**forall** item  $A \rightarrow \alpha \bullet B \gamma$  in  $J$  **do**

**forall** production  $B \rightarrow \beta$  **do**

**if**  $B \rightarrow \bullet \beta \notin J$  **then**

$J := J \cup \{B \rightarrow \bullet \beta\}$

**return**  $J$

**end function**  $closure$

**function**  $goto(I, X)$

$J := \emptyset$

**forall** item  $A \rightarrow \alpha \bullet X \gamma$  in  $I$  **do**

$J := J \cup \{A \rightarrow \alpha X \bullet \gamma\}$

**return**  $closure(J)$

**end function**  $goto$

# Constructing the DFA of LR(0) States

---

- ❖ The following algorithm builds an LR(0) DFA for a grammar  $G$ 
  - ★ The algorithm determines the set of LR(0) states and the set of transitions
  - ★ The algorithm ends when no additional states or transitions can be added

```
function LR0_DFA( $G$ )  
     $States := \{closure(\{S' \rightarrow \bullet S \$\})\}$     -- Set of all LR(0) states  
     $Edges := \emptyset$                                 -- Set of all transitions  
    forall state  $I$  in  $States$  do  
        forall item  $A \rightarrow \alpha \bullet X \gamma$  in  $I$  do  
             $J := goto(I, X)$   
            if  $J \notin States$  then  $States := States \cup \{J\}$   
             $Edges := Edges \cup \{ I \xrightarrow{X} J \}$   
    return  $States, Edges$   
end function LR0_DFA
```


# Limitations of the LR(0) Parsing Method

- ❖ Consider grammar  $G_2$  for matched parentheses

0:  $S' \rightarrow S \$$       1:  $S \rightarrow ( S ) S$       2:  $S \rightarrow \varepsilon$


- ❖ The LR(0) DFA of grammar  $G_2$  is shown below

- ❖ In states: 0, 2, and 4, parser can shift ( and reduce  $\varepsilon$  to  $S$



# Conflicts

- ❖ In state 0 parser encounters a conflict ...
  - ★ It can shift state 2 on stack when next token is (
  - ★ It can reduce production 2:  $S \rightarrow \varepsilon$
  - ★ This is called a **shift-reduce** conflict
  - ★ This conflict also appears in states 2 and 4



- ❖ Two kinds of conflicts may arise

- ★ **Shift-reduce** and **reduce-reduce**

## ➤ **Shift-reduce** conflict

Parser can shift and can reduce

## ➤ **Reduce-reduce** conflict

Two (or more) productions can be reduced

State	Action			Goto
	(	)	\$	S
0	S2,R2	R2	R2	G1
1			A	
2	S2,R2	R2	R2	G3
3		S4		
4	S2,R2	R2	R2	G5
5	R1	R1	R1	

# LR(0) Grammars

---

- ❖ The shift-reduce conflict in state 0 indicates that  $G_2$  is not LR(0)
- ❖ A grammar is LR(0) if and only if each state is either ...
  - ★ A **shift state**, containing only shift items
  - ★ A **reduce state**, containing only a single reduce item
- ❖ If a state contains  $A \rightarrow \alpha \bullet x \gamma$  then it cannot contain  $B \rightarrow \beta \bullet$ 
  - ★ Otherwise, parser can shift  $x$  and reduce  $B \rightarrow \beta \bullet$  (**shift-reduce conflict**)
- ❖ If a state contains  $A \rightarrow \alpha \bullet$  then it cannot contain  $B \rightarrow \beta \bullet$ 
  - ★ Otherwise, parser can reduce  $A \rightarrow \alpha \bullet$  and  $B \rightarrow \beta \bullet$  (**reduce-reduce conflict**)
- ❖ LR(0) lacks the power to parse programming language grammars
  - ★ Because they do not use the lookahead token in making parsing decisions

# SLR(1) Parsing

---

- ❖ SLR(1), or simple LR(1), improves LR(0) by ...
  - ★ Making use of the lookahead token to eliminate conflicts
- ❖ SLR(1) works as follows ...
  - ★ It uses the same DFA obtained by the LR(0) parsing method
  - ★ It puts reduce actions only where indicated by the FOLLOW set
- ❖ To reduce  $\alpha$  to  $A$  in  $A \rightarrow \alpha \bullet$  we must ensure that ...
  - ★ Next token may follow  $A$  (belongs to  $\text{FOLLOW}(A)$ )
- ❖ We should not reduce  $A \rightarrow \alpha \bullet$  when next token  $\notin \text{FOLLOW}(A)$
- ❖ In grammar  $G_2$  ...
  - ★ 0:  $S' \rightarrow S \$$                       1:  $S \rightarrow ( S ) S$                       2:  $S \rightarrow \varepsilon$
  - ★  $\text{FOLLOW}(S) = \{ \$, ) \}$
  - ★ Productions 1 and 2 are reduced when next token is  $\$$  or  $)$  only



# SLR(1) Parsing Table

---

- ❖ The SLR(1) parsing table of grammar  $G_2$  is shown below
- ❖ The shift-reduce conflicts are now eliminated
  - ★ The R2 action is removed from  $[0, ( ]$ ,  $[2, ( ]$ , and  $[4, ( ]$
  - ★ Because  $($  does not follow  $S$
  - ★ S2 remains under  $[0, ( ]$ ,  $[2, ( ]$ , and  $[4, ( ]$
  - ★ R1 action is also removed from  $[5, ( ]$
- ❖ Grammar  $G_2$  is SLR(1)
  - ★ No conflicts in parsing table
  - ★ R1 and R2 for  $)$  and  $\$$  **only**
  - ★ **Follow set indicates when to reduce**

State	Action			Goto
	$($	$)$	$\$$	$S$
0	S2	R2	R2	G1
1			A	
2	S2	R2	R2	G3
3		S4		
4	S2	R2	R2	G5
5		R1	R1	

# SLR(1) Grammars


---

- ❖ SLR(1) parsing increases the power of LR(0) significantly
  - ★ Lookahead token is used to make parsing decisions
  - ★ Reduce action is applied more selectively according to FOLLOW set
- ❖ A grammar is SLR(1) if two conditions are met in every state ...
  - ★ If  $A \rightarrow \alpha \bullet x \gamma$  and  $B \rightarrow \beta \bullet$  then token  $x \notin \text{FOLLOW}(B)$
  - ★ If  $A \rightarrow \alpha \bullet$  and  $B \rightarrow \beta \bullet$  then  $\text{FOLLOW}(A) \cap \text{FOLLOW}(B) = \emptyset$
- ❖ Violation of first condition results in **shift-reduce conflict**
  - ★  $A \rightarrow \alpha \bullet x \gamma$  and  $B \rightarrow \beta \bullet$  and  $x \in \text{FOLLOW}(B)$  then ...
  - ★ Parser can shift  $x$  and reduce  $B \rightarrow \beta$
- ❖ Violation of second condition results in **reduce-reduce conflict**
  - ★  $A \rightarrow \alpha \bullet$  and  $B \rightarrow \beta \bullet$  and  $x \in \text{FOLLOW}(A) \cap \text{FOLLOW}(B)$
  - ★ Parser can reduce  $A \rightarrow \alpha$  and  $B \rightarrow \beta$
- ❖ SLR(1) grammars are a superset of LR(0) grammars

# Limits of the SLR(1) Parsing Method

---

- ❖ Consider the following grammar  $G3$  ...  
0:  $S' \rightarrow S \$$    1:  $S \rightarrow \text{id}$    2:  $S \rightarrow V := E$    3:  $V \rightarrow \text{id}$    4:  $E \rightarrow V$    5:  $E \rightarrow \text{n}$
- ❖ The initial state consists of 4 items as shown below
  - ★ When **id** is shifted in state 0, we obtain 2 items:  $S \rightarrow \text{id} \bullet$  and  $V \rightarrow \text{id} \bullet$
- ❖  $\text{FOLLOW}(S) = \{\$ \}$  and  $\text{FOLLOW}(V) = \{:=, \$ \}$
- ❖ **Reduce-reduce conflict** in state 1 when lookahead token is  $\$$ 
  - ★ Therefore, grammar  $G3$  is **not** SLR(1)
  - ★ The reduce-reduce conflict is caused by the weakness of SLR(1) method
  - ★  $V \rightarrow \text{id}$  should be reduced only when lookahead token is  $:=$  (but not  $\$$ )



# General LR(1) Parsing – Items and States

---

- ❖ Even more powerful than SLR(1) is the LR(1) parsing method
- ❖ LR(1) generalizes LR(0) by including a lookahead token in items
- ❖ An LR(1) item consists of ...
  - ★ **Grammar production rule**
  - ★ **Right-hand position represented by the dot**, and
  - ★ **Lookahead token**
$$A \rightarrow X_1 \dots X_i \bullet X_{i+1} \dots X_n, l \quad \text{where } l \text{ is a } \mathbf{lookahead\ token}$$
- ❖ The  $\bullet$  represents how much of the right-hand side has been seen
  - ★  $X_1 \dots X_i$  appear on top of the stack
  - ★  $X_{i+1} \dots X_n$  are expected to appear
- ❖ The lookahead token  $l$  is expected **after**  $X_1 \dots X_n$  appear on stack
- ❖ **An LR(1) state is a set of LR(1) items**

# LR(1) Parser Generation – Initial State

---

❖ Consider again grammar  $G_3$  ...

0:  $S' \rightarrow S \$$    1:  $S \rightarrow \mathbf{id}$    2:  $S \rightarrow V := E$    3:  $V \rightarrow \mathbf{id}$    4:  $E \rightarrow V$    5:  $E \rightarrow \mathbf{n}$

❖ The initial state contains the LR(1) item:  $S' \rightarrow \bullet S, \$$

★  $S' \rightarrow \bullet S, \$$  means that  $S$  is expected and to be followed by  $\$$

❖ The closure of  $(S' \rightarrow \bullet S, \$)$  produces the initial state items

★ Since the dot appears before  $S$ , an  $S$  is expected

★ There are two productions of  $S$ :  $S \rightarrow \mathbf{id}$  and  $S \rightarrow V := E$

★ The LR(1) items  $(S \rightarrow \bullet \mathbf{id}, \$)$  and  $(S \rightarrow \bullet V := E, \$)$  are obtained

✧ The lookahead token is  $\$$  (end-of-file token)

★ Since the  $\bullet$  appears before  $V$  in  $(S \rightarrow \bullet V := E, \$)$ , a  $V$  is expected

★ The LR(1) item  $(V \rightarrow \bullet \mathbf{id}, :=)$  is obtained


✧ The lookahead token is  $:=$  because it appears after  $V$  in  $(S \rightarrow \bullet V := E, \$)$

# Shift Action

- ❖ The initial state (state 0) consists of 4 items
- ❖ In state 0, we can shift an **id**
  - ★ The token **id** can be shifted in two items
  - ★ When shifting **id**, we shift the dot past the **id**
  - ★ We obtain ( $S \rightarrow \mathbf{id} \bullet, \$$ ) and ( $V \rightarrow \mathbf{id} \bullet, :=$ )
  - ★ The two LR(1) items form a new state (state 1)
  - ★ The two items are **reduce items**
  - ★ No additional item can be added to state 1


$S' \rightarrow$	$\bullet S, \$$
$S \rightarrow$	$\bullet \mathbf{id}, \$$
$S \rightarrow$	$\bullet V := E, \$$
$V \rightarrow$	$\bullet \mathbf{id}, :=$

(0)




# Reduce and Goto Actions

- ❖ In state 1,  $\bullet$  appears at end of (  $S \rightarrow \mathbf{id} \bullet, \$$  ) and (  $V \rightarrow \mathbf{id} \bullet, :=$  )
  - ★ This means that **id** appears on top of stack and can be reduced
  - ★ Two productions can be reduced:  $S \rightarrow \mathbf{id}$  and  $V \rightarrow \mathbf{id}$
- ❖ The lookahead token eliminates the conflict of the reduce items
  - ★ If lookahead token is  $\$$  then **id** is reduced to  $S$
  - ★ If lookahead token is  $:=$  then **id** is reduced to  $V$
- ❖ When in state 0 after a reduce action ...
  - ★ If  $S$  is pushed, we obtain item (  $S' \rightarrow S \bullet, \$$  ) and go to state 2
  - ★ If  $V$  is pushed, we obtain item (  $S \rightarrow V \bullet := E, \$$  ) and go to state 3



# LR(1) State Diagram

- ❖ The LR(1) state diagram of grammar  $G3$  is shown below
- ❖ Grammar  $G3$ , which was not SLR(1), is now LR(1)
- ❖ The reduce-reduce conflict that existed in state 1 is now removed
- ❖ The lookahead token in LR(1) items eliminated the conflict





# LR(1) Closure and Goto Functions

- ❖ To construct the LR(1) DFA, we need *closure* and *goto* functions
- ❖ *Closure(I)* returns the complete set of LR(1) items for a state
  - ★ For items  $(A \rightarrow \alpha \bullet B \gamma, l) \in I$ , add  $(B \rightarrow \bullet \beta, x)$  for all  $x \in \text{FIRST}(\gamma l)$
  - ★  $x \in \text{FIRST}(\gamma l)$  is what follows  $B$  in  $(A \rightarrow \alpha \bullet B \gamma, l)$
- ❖ *Goto(I, X)* determines next state for a given state  $I$  and symbol  $X$

```
function closure( $I$ )  
   $J := I$   
  forall item  $(A \rightarrow \alpha \bullet B \gamma, l)$  in  $J$  do  
    forall production  $B \rightarrow \beta$  do  
      forall  $x \in \text{FIRST}(\gamma l)$  do  
        if  $(B \rightarrow \bullet \beta, x) \notin J$  then  
           $J := J \cup \{(B \rightarrow \bullet \beta, x)\}$   
  return  $J$   
end function closure
```

```
function goto( $I, X$ )  
   $J := \emptyset$   
  forall item  $(A \rightarrow \alpha \bullet X \gamma, l)$  in  $I$  do  
     $J := J \cup \{(A \rightarrow \alpha X \bullet \gamma, l)\}$   
  return closure( $J$ )  
end function goto
```

# LR(1) Grammars

---


- ❖ A grammar is LR(1) if the following two conditions are met ...
  - ★ If a state contains  $(A \rightarrow \alpha \bullet x \gamma, a)$  and  $(B \rightarrow \beta \bullet, b)$  then  $b \neq x$
  - ★ If a state contains  $(A \rightarrow \alpha \bullet, a)$  and  $(B \rightarrow \beta \bullet, b)$  then  $a \neq b$
- ❖ Violation of first condition results in a **shift-reduce conflict**
- ❖ If a state contains  $(A \rightarrow \alpha \bullet x \gamma, a)$  and  $(B \rightarrow \beta \bullet, x)$  then ...
  - ★ It can shift  $x$  and can reduce  $B \rightarrow \beta$  when lookahead token is  $x$
- ❖ Violation of second condition results in **reduce-reduce conflict**
- ❖ If a state contains  $(A \rightarrow \alpha \bullet, a)$  and  $(B \rightarrow \beta \bullet, a)$  then ...
  - ★ It can reduce  $A \rightarrow \alpha$  and  $B \rightarrow \beta$  when lookahead token is  $a$
- ❖ LR(1) grammars are a superset of SLR(1) grammars

## Drawback of LR(1)

---

- ❖ LR(1) can generate very large parsing tables
- ❖ For a typical programming language grammar ...
  - ★ The number of states is around several hundred for LR(0) and SLR(1)
  - ★ The number of states can be several thousand for LR(1)
- ❖ This is why parser generators do not adopt the general LR(1)
- ❖ Consider again grammar G2 for matched parentheses
$$0: S' \rightarrow S \$ \quad 1: S \rightarrow ( S ) S \quad 2: S \rightarrow \varepsilon$$
- ❖ The LR(1) DFA has 10 states, while the LR(0) DFA has 6

# LR(1) DFA of Grammar G2



# LALR(1) : Look-Ahead LR(1)

---

- ❖ Preferred parsing technique in many parser generators
- ❖ Close in power to LR(1), but with less number of states
- ❖ Increased number of states in LR(1) is because
  - ★ Different lookahead tokens are associated with same LR(0) items
- ❖ Number of states in LALR(1) = states in LR(0)
- ❖ LALR(1) is based on the observation that
  - ★ Some LR(1) states have same LR(0) items
  - ★ Differ only in lookahead tokens
- ❖ LALR(1) can be obtained from LR(1) by
  - ★ Merging LR(1) states that have same LR(0) items
  - ★ Obtaining the union of the LR(1) lookahead tokens

# LALR(1) DFA of Grammar G2

