

If a student turns on their microphone or camera or uses the public chat feature, this constitutes consent for the student's video image or sound audio to be uploaded with the office hour or tutorial on university approved platforms such as D2L. If the student wishes to ensure that their questions/faces/voices are not recorded in the video, they should instead use private chat to ask questions.

# Convolutional Neural Networks

## A Gentle Introduction

Roberto Souza  
Assistant Professor  
Electrical and Software Engineering  
Schulich School of Engineering

January 2022


# Outline

- Learning Goals
- Convolutional Neural Networks (CNNs)
  - Basic Operations
  - Properties
  - Computing number of parameters
- Summary

# Learning Goals

- Understand how CNNs work and when to apply them
- Compute the number of parameters of your model


# Data – Euclidean Domains




- Images, audio, text among others all have regular structures in a Euclidean space
  - Convolutions are well-defined operations that can be computed efficiently in these structures

# Convolutional Neural Networks

- Convolutional layers learn features
- Connected layers perform classification
- Fewer trainable parameters than fully connected networks




# Fully Connected Neural Network – Global Property



- The fully connected layer can lead to an explosion in the number of parameters
- Imagine your input is a 256 x 256 image and your layer has 10 outputs, how many parameters would the model have?
  - $256 \times 256 \times 10 + 10 = 655,370$

# Convolutional Neural Network – Weight Sharing



- Convolutional neural networks share weights across inputs (*i.e.*, connection **sparsity**)
- Convolutions leverage local correlations (*i.e.*, **locality**)
- Imagine your input is a 256 x 256 image, your convolution size is 3 and your layer has 10 filters, how many parameters would the model have?
  - $3 \times 10 + 10 = 40$



# Convolution (single-channel input)


1x1	1x0	1x1	0	0
0x0	1x1	1x0	1	0
0x1	0x0	1x1	1	1
0	0	1	1	0
0	1	1	0	0

4		


The bias term is added after the convolution

# Convolution (padding)

- Image can be padded prior to convolution to preserve its dimensions




# N-channel Images/Signals



- Results of convolutions are stacked resulting in n-channel images/signals


# Convolution – multi-channel input



- The convolutions encompass the channels of the input
- A  $W1 \times W2$  convolution is actually a  $W1 \times W2 \times n_{\text{channels}}$  convolution


# Max-Pooling

- Non-linear operation
- Reduce dimensionality and computational cost
- After a max-pooling, the number of filters in the subsequent layer is increased




# Flatten

- The flatten operation is applied before the fully connected layer




# CNN Hierarchy of Concepts





# VGG-16 Architecture





# Summary

- CNNs share weights and have sparse connections
- They depend on local correlations to operate
- The basic operations are convolutions and max-pooling layers
- Implicit hierarchy of concepts

# Thank you!



UNIVERSITY OF  
CALGARY

