

1. Introduction

exp-resume is a small Typst package for writing an ATS-friendly resume. It configures a clean one-page layout, a name and contact row, and a set of components for the common resume sections. Personal documents should be kept outside the repository and import either the published package or the local clone.

2. Installation

Publish the package to the Typst package repository, then create a new document from the template:

```
typst init @preview/#pkg:#version
```

During development a sibling document can import the implementation from a local clone:

```
#import "exp-resume-template/src/lib.typ": *
```

3. Quick Start

The document starts with `#show: resume.with(...)`, which applies the global rules and renders the name and contact row. The rest of the document is the body:

```
#import "@preview/#pkg:#version": *
```

```
#show: resume.with(
  author: "John Doe",
  email: "john.doe@example.com",
  accent-color: "#26428b",
)
```

== Experience

```
#work(
  title: "Software Engineer",
  company: "Example Corporation",
  location: "Example City, EX",
  dates: dates-helper(start-date: "Jun 2024", end-date: "Present"),
)
- Replace this placeholder with an accomplishment.
```

== Skills

```
#skills(
  category: "Languages",
  items: "Python, Go, TypeScript, SQL, Bash",
)
```

Lines that start with `==` are formatted into small-caps section headings with a rule underneath.

4. Resume Configuration

The `resume` function accepts the following parameters:

Parameter	Description
author	Your name, shown as a level-one heading
location	City and country or region, shown in the contact row
email	Email address, linked with <code>mailto:</code>

email-text	Optional display text for the email link
github	GitHub handle, linked with <code>https://</code>
github-text	Optional display text for the GitHub link
linkedin	LinkedIn handle, linked with <code>https://</code>
linkedin-text	Optional display text for the LinkedIn link
phone	Phone number, linked with <code>tel:</code>
personal-site	Personal site, linked with <code>https://</code>
personal-site-text	Optional display text for the personal site link
accent-color	Color for headings and links, defaults to black
font	Body font, defaults to “New Computer Modern”
paper	Page paper, defaults to “us-letter”
font-size	Body font size, defaults to 10pt
author-font-size	Name size, defaults to 20pt
lang	Document language, defaults to “en”
pronouns	Optional pronouns, shown in the contact row
author-position	Alignment of the name, defaults to left
personal-info-position	Alignment of the contact row, defaults to left
section-content-inset	Body indent under section titles, defaults to 2pt
spacing	Optional spacing overrides; see Spacing below

Parameters that are optional can be omitted or set to `""`. The template contains commented example values.

5. Spacing

`default-spacing` is exported from the package and used when `spacing` is omitted. It is a soft recommendation: examples leave it unset. Pass a partial dictionary to override keys:

```
#import "@preview/#pkg:#version": *

#show: resume.with(
  author: "John Doe",
  spacing: (gap: 0.85em, row: 0.65em),
)
```

Or merge with the exported defaults:

```
#show: resume.with(
  author: "John Doe",
  spacing: default-spacing + (leading: 0.5em),
)
```

Key	Role
leading	Paragraph leading (line rhythm inside a paragraph)
gap	Paragraph spacing and space above entry headers
row	Certificate/skill row spacing, and space under an entry title before its first bullet

after-header	Space under the contact row
after-section-title	Space between the section title and its rule
after-section-rule	Space between the section rule and body
rule-stroke	Stroke for section rules and link underlines
link-offset	Underline offset under links
row-delta	Optical size nudge between the two rows of <code>generic-two-by-two</code>

6. Section Components

Each component is placed directly below a `== Section` heading. Bold and italic emphasis inside the argument strings is preserved.

6.1. Summary

`summary` renders a justified paragraph below a heading:

`== Summary`

```
#summary[Backend engineer experienced in scaling distributed services.]
```

6.2. Education

```
#edu(
  institution: "Example University",
  location: "Example City, EX",
  dates: dates-helper(start-date: "Aug 2020", end-date: "May 2024"),
  degree: "Bachelor of Science, Computer Science",
)
```

Set `consistent: true` to move the dates to the top-right and the location to the bottom-right, matching the other components.

6.3. Work Experience

```
#work(
  title: "Software Engineer",
  company: "Example Corporation",
  location: "Example City, EX",
  dates: dates-helper(start-date: "Jun 2024", end-date: "Present"),
)
- Built reliable services and shipped measurable improvements.
```

6.4. Projects

```
#project(
  name: "Example Project",
  technologies: "Python, FastAPI, Redis",
  links: (
    (url: "github.com/johndoe/example-project", text: "Github"),
    (url: "example.com", text: "Live"),
  ),
)
```

Pass multiple links as `(url, text)` dictionaries. They are joined with `•` and shown on the right.

6.5. Certificates

One row per call. Consecutive rows share the `row` spacing token.

```
#certificates(
  name: "Example Certification",
  issuer: "Example Institute",
  url: "example.com/cert",
  url-text: "Certificate",
  date: "Jun 2024",
)
```

6.6. Skills

One row per call, same spacing path as certificates:

```
#skills(
  category: "Languages",
  items: "Python, Go, TypeScript, SQL, Bash",
)
```

6.7. Extracurricular Activities

```
#extracurriculars(
  activity: "Example Open Source Group",
  dates: dates-helper(start-date: "Jan 2022", end-date: "Present"),
)
```

7. Generic Helpers

These helpers provide layout without section-specific formatting and can be used to build custom entries.

7.1. dates-helper

Formats a start and end date with an em dash. Pass only an end date to omit the dash:

```
#dates-helper(start-date: "Jun 2024", end-date: "Present")
```

7.2. linked-text

Renders value as a hyperlink when a link-prefix is given, optionally using text as the visible label:

```
#linked-text("example.com", link-prefix: "https://")
```

7.3. generic-one-by-two

Places left and right on one line, with right pushed to the right edge. By default uses gap above and row below. Pass spacing: <length> to set both sides explicitly.

```
#generic-one-by-two(left: "Title", right: "Date")
```

7.4. generic-two-by-two

Places two pairs on two lines, with each right-hand cell pushed to the right edge. Same default above/below behavior as generic-one-by-two. The top row is slightly larger than the bottom row by row-delta.

```
#generic-two-by-two(
  top-left: "Title",
  top-right: "Date",
  bottom-left: "Company",
  bottom-right: "Location",
)
```