UNIVERSITAS SCIENTIARUM SZEGEDIENSIS
UNIVERSITY OF SZEGED
Department of Software Engineering

Beyond Code Coverage – an Approach for Test Suite Assessment and Improvement

Dávid Tengeri*, *Árpád Beszédes**, *Tamás Gergely**, *László Vidács*❖, *Dávid Havas** and *Tibor Gyimóthy**

**Department of Software Engineering, University of Szeged, Hungary*
❖MTA-SZTE Research Group on Artificial Intelligence, University of Szeged, Hungary

Industrial Motivation



Industrial Motivation

WebKit

- Open source web browser engine
- ~ 2.2 million lines of code (mostly C++)
- More than 27 000 test cases




Industrial Motivation



Motivation and Goals

- "Quality" of a (regression) test suite:
  - What is the likelihood of defect detection?
  - How efficient, modular, etc. it is?
- How can the quality be improved?
- Quality assessment of source code – problem solved (?)
- Quality assessment of ***test suites***?



Test suite Assessment and Improvement Method (TAIME)

Determine functional units



Assessment of WebKit

Test \ Code	WebKit	canvas	css	dom	editing	html5lib	http	js	svg	tables
WebKit	.53	.56	.61	.59	.67	.67	.65	.47	.50	.72
canvas	.16	.46	.26	.24	.07	.19	.00	.30	.03	.45
css	.24	.13	.51	.33	.25	.36	.00	.32	.11	.62
dom	.33	.17	.38	.52	.34	.51	.12	.35	.08	.57
editing	.23	.02	.31	.38	.66	.35	.01	.31	.06	.59
html5lib	.29	.12	.37	.43	.46	.52	.13	.34	.20	.63
http	.33	.23	.41	.42	.25	.41	.65	.39	.14	.57
js	.33	.16	.37	.47	.51	.44	.15	.44	.11	.63
svg	.26	.01	.38	.35	.17	.21	.01	.31	.50	.56
tables	.18	.00	.29	.30	.16	.31	.00	.26	.02	.62

Function level coverage of groups in WebKit

The TAIME approach



The TAIME approach



Use cases

Assessment

- Detect any issues that require further investigation
- Helps find the initial goal in the improvement phases

One-shot refactoring

- Delete, reorganize, rewrite, create test cases
- To improve test suite quality

Change-oriented test suite evolution

- Create new test cases or possibly remove test cases
- To preserve or improve test suite quality

White-box test design

- Monitor and maintain test suite quality during design
- Use specific measurements as white-box criteria

Improvement of SoDA

- Software Development Analysis Framework
  - http://soda.sed.hu
  - Platform independent
  - Plugin based
  - TAIME support (with GUI)
- SoDA Repository
  - Benchmark programs (SIR, WebKit, GCC)
  - Set of measurement results

Improvement of SoDA

- White-box test design

Func. unit	Tests (before)	Tests (after)	Procedures	Statements
cluster	1	10	36	263
data	86	89	213	1588
fl-technique	2	4	16	175
io	13	16	56	429
metric	3	18	60	549
prioritization	2	6	21	159
reader	4	13	35	431
reduction	0	8	33	414
other	1	1	145	331
SoDA	112	165	615	4339

Improvement of SoDA



Improvement of the *cluster* unit



Improvement of the *cluster* unit

Improving the coverage of other units



Improvement of the *cluster* unit



UNIVERSITAS SCIENTIARUM SZEGEDIENSIS
UNIVERSITY OF SZEGED
Department of Software Engineering

TAIME

- One-shot refactoring
- White-box test design
- Change-oriented test suite evolution
- Assessment

http://soda.sed.hu