

Chapter 2 - Algorithm performance basics

When creating a computer program, usually a very important part is to know how fast the program is going to run. But "how fast" is a relative term. The same program is not going to run with the same runtime in a 10-year-old computer than in a top-notch game computer with all the best components that can be available at the moment. Or than in one of the 500 fastest supercomputers of the world. The programmer can't know beforehand in absolute terms the time required to run their program, but given that usually there are different forms to solve a problem, they can at least know that some of the solutions are faster than others. In other words, some algorithms are faster than others. And something similar can be said about the memory or space that a program is going to need based on its algorithm.

So, deciding what algorithm needs to be used to solve some complex problem is a very important part of programming. Programmers want their programs to be fast and to use as few resources, like memory, as possible. And they will try to use the algorithm that best suites to these goals.

However sometimes one of the goals is at a expense of other/s. It is possible that, for the program to be the fastest possible, a lot of memory has to be used. At least a lot more than other viable solutions. But this a decision that is up to the programmer to make. The programmer must find the sweet spot between speed and memory consumption. There is no general rule. The best solution depends on the circumstances and goals of the project, and even it can happen that two

programmers have different project goals and therefore they choose different solutions and algorithms to solve a similar problem.

But in any case, they all have to know how to measure these important criterias like speed and memory consumption to make an informed decision. They also have to know how to attack the problems to get some solution and ponder if that solution is viable. Notice that there are problems that don't have good computational solutions in terms of speed or memory consumption (at least known solutions), so there is not always going to be a wonderful algorithm to solve the day...

When solving a problem, we treat it like a black box that has some kind of interface. The interface defines what the black should do and what it should produce in return. We feed it some inputs or values through some of the functions the interface defines, and the function return us some output values, whatever they are. The interface definition doesn't take any stake on how the output is produced, it just defines what the output should be. So, the "how" is the algorithm that is used. The algorithm can be changed but the black box should be able to be used in the exact same way. What we, as programmers, want to do is to measure the performance of these algorithms to choose the one that best suits our goals.

Arrays

Let's see an example... One particular problem that programmers face very often is how to store some data. Depend on the data to store and how to access it, there are different data structures a programmer can use. But for the sake of the argument, let's say we want to store some list type of data. We want to be able to insert new data, to search for the data based on a value and to delete some of the data based on a position on the list.

A very basic structure to store information that fulfills these requirements is an **array**. An array is a sequential list of adjacent locations of the same size on memory. The advantage of that is that given a position index in the array and the size of every position, it's very easy, and therefore **very fast**, to calculate the location of that position in relation of the array's start. The array element we want to use can be easily located with:
$array_start_position_in_memory + (element_size_in_bytes * position_index)$
Computers can calculate this **very** quickly.

There are actually two types of arrays: **static arrays** and **dynamic arrays**.

Static arrays have fixed size. That means that once the array is created with a defined length, that length can't be modified. Array's content can be modified, but we can **not** add more positions or delete some positions from the array. Strictly speaking the length of the array can't be modified, but

there is a circumvent to that, that is to create a new array and copy the content of the array to the new one.

On the other hand, we have **dynamic arrays**. This type of arrays reserves some space at the end of the array to be able to expand the array if necessary. So, if we need to store `n` different values in an array (`n` is only a variable and can be any positive integer, it's just a way of generalization), the array is going to be created with `n` plus some arbitrary space that will be used if necessary.

This data structure stores two different size variables for the array. One is the **logical size** of the array, i.e., the size of the array to the user, and the other the **physical size** of the array, i.e. the size of the array in memory. How much extra space has to be reserved depends on the implementation, but typical sizes go from one third to half of the logical size (but other values are also possible). This is called the **growth factor**. For example, a growth factor of 2, indicate that when creating or expanding the array, the extra space will be the same amount than the official size of the array. If we create an array of 5 elements, another 5 will be added for future expansion. The logical size of the array is 5, but the physical size of the array is ten (a factor of 2).

We see, that the array can grow in size up to the maximum physical size at a minimum cost. When more positions are needed, then, same as with static arrays, a new array with the same rules as before has to be created and the current content is copied to it. That gives the array room to grow again.

When deleting items from the array we also want at some point to reduce the size of the array, so as not to waste memory. Therefore, in this case a new smaller array has to be created and the content of the old array has to be copied to it.

To find out if a dynamic array is better data structure than a fixed array, let's analyze them. But to analyze them, let's watch for the typical actions we need to perform on them:

- Array creation
- Insert an element at the end
- Remove an element from the end
- Insert an element at any point of the array
- Remove an element from any point of the array
- Read a position's value based on its index position
- Search the array based on a value (in which position is a value at?)

Analyzing performance (The big O notation)

Computer scientists use different notations to define what type of algorithm or process we are dealing with. One of them is the Big O notation. This represents the upper bound on the growth of the algorithm's run time or space requirements. In other words, a mathematical function that shows how much time or space use is going to be needed **at worst** given different input sizes.

So, for example, let's analyze the creation of a static array. The data structure should reserve a memory space and initialize some internal values or variables like the array's length. This process should take more or less the same time independently of the size of the array we are creating. In different computers it's going to take a different time to run, depending on the characteristics of the computer, but in general we can say that creation time is more or less a constant, in the sense that it shouldn't vary depending on size of the array (maybe some small difference, but not significant).

As we see the creation time doesn't vary with the array size and we can represent it with a constant, for example c. The function that corresponds with this behavior is $f(n) = c$ and it's big O notation would be $O(1)$, as constants can be discarded in big O notation.

A simple list of big O notations for algorithms would be:

- constant: $O(1)$
- logarithmic: $O(\log n)$
- linear: $O(n)$
- n log-star n: $O(n \cdot \log n)$
- quadratic: $O(n^2)$
- polynomial: $O(n^c)$ for $c > 2$
- exponential: $O(c^n)$ for $c > 1$
- factorial: $O(n!)$
- $O(n^n)$

There can be many more big O notations, but these are probably the more common ones. The important thing is how any one of them behaves in relation to the others. The list is in growth order. A logarithmic function is going to grow slower than the linear one when the input size (n) increases. The linear function grows slower than the "n log-star n" one. Each big O notation of that list grows slower than the next one.

In this case less is better, so the fastest algorithm is one with $O(1)$ and the slowest one is an algorithm with $O(n^n)$. When we have different algorithms to solve a problem, we can compare them by their big O notations.

One thing to note is that big O notation is just a way to represent something. For programming, it could be the **time complexity** (how much time a program is going to need when the input sizes grows?) or it could be **space complexity** (how much space a program is going to need when the input size grows?).

Notice also, that for low values of n (small input sizes), the order of the list can be different. This explains, why sometimes, depending on the input size, the faster algorithm can be different. Programming languages select different sorting methods depending on the size of the structure to be sorted.



Image from Wikipedia. License: CC BY-SA 4.0

But how is the big O notation of an algorithm calculated? Let's show it with an example:

```
def find_pair(array):                          # line 1
    n = len(array)                             # line 2
    for i in range(n):                         # line 3
        for j in range(n):                     # line 4
            if i != j and array[i] == array[j] # line 5
                return (i,j)                   # line 6
    return None                                # line 7
```

The function in the example tries to find a pair of positions of an array with the same value. If it finds them, it returns a tuple with the positions. If it doesn't it returns `None`. To try to find the pair it uses two loops and each one of them (lines 3 and 4) traverses the array from start to end. That's $n \cdot n$ iterations (being n the size of the array). Inside the loops the algorithm makes some checks. But we can safely asumme that those checks use some constant c time (whatever the actual time is).

The worst case is the one where a pair is not found and loops have to run until the end, i.e., something like $n \cdot n$ iterations in total and c time for each iteration. That's $c \cdot n^2$. Lines 2 and 7 also make some operation, but they use just some constant time (they don't depend on the input size). Let's join them and use d for their run time.

The total run time for the worst case would then be $c \cdot n^2 + d$. That means that the function for the run time is $f(n) = c \cdot n^2 + d$. To calculate the big O notation, we take the **leading** polynomial factor. That would be n^2. So this algorithm is $O(n^2)$ (quadratic). It could be worse, but still, if we can think of some other algorithm with better O notation (like $O(n)$ or $O(n \cdot \log n)$) it should perform better.

Once the function $f(n)$ that represents the run time of the algorithm based on the input size is calculated, it is usually quite easy to get the big O notation $O(n)$, but sometimes a little bit of calculus is involved.

Static array big O notations

So, for the list of actions that we mentioned before, we are going to get the following results:

- **Array creation**: $O(1)$. As mentioned, this is basically a constant.
- **Insert an element at the end**: $O(n)$. A new array must be created and the whole content of the array (hence the n) should be copied to it before the insertion.
- **Remove an element from the end**: $O(n)$. Same case as before. A whole copy is necessary.
- **Insert an element at any point of the array**: $O(n)$. Same case as before. A whole copy is necessary.

- **Remove an element from any point of the array**: $O(n)$. Same case as before. A whole copy is necessary.
- **Read a position's value based on its index position**: $O(1)$. Read a given positions value is trivial.
- **Search the array based on a value (in which position is a value at?)**: $O(n)$. Worst case is to traverse the whole array.

Dynamic array big O notations

Ok. Is it better with a dynamic array?

- **Array creation**: $O(1)$. This is basically constant.
- **Insert an element at the end**: This a little bit tricky. As some space is reserved for expansion beforehand, sometimes is going to be just $O(1)$, but when that space is exhausted, a whole copy would be necessary: $O(n)$. Overall we say it's $O(1)$ in **amortized cost**. That means that usually is going to have a time complexity of $O(1)$ (in this case), but from time to time (depends on the algorithm in question) is going to have a higher cost, for example $O(n)$
- **Remove an element from the end**: $O(1)$ amortized. Same case as before.
- **Insert an element at any point of the array**: $O(n)$. Even if no array copy was necessary, n elements should be move in the worst case to make room for a new element.
- **Remove an element from any point of the array**: $O(n)$. Same case as before.
- **Read a position's value based on its index position**: $O(1)$. Read a given position's value is trivial.
- **Search the array based on a value (in which position is a value at?)**: $O(n)$. Worst case is to traverse the whole array.

Comparing static and dynamic arrays

Given the big O notations above, a **dynamic array should be faster than a static array**. Some actions are going to run with the same or similar run time, but there is at least two actions (insert and remove elements at the end) where the dynamic array is going to be faster: $O(1)$ for dynamic vs $O(n)$ for static arrays. But this gain is at the expense of a more space consumption of the array.

Some implementations of the dynamic array also use some extra space at the beginning of the array. This way insertions and deletions **at the start** of the array are also "cheaper".

Array example in Python

In Python **strings are implemented with static arrays**. One characteristic of arrays is that every position has the same size. For example if every position has a size of 2 bytes and there are 10

positions, that means that such array has a size of 20 bytes and that every position can be addressed with the formula `2 * position_index` from the start of the array (`position_index` being in zero-based indexing, i.e. that the very first position of the array is the position number 0).

However, this doesn't fit too well with how text is encoded (and stored) in modern times. In modern software Unicode is used to store or handle text and usually UTF-8 is used as the encoding method for Unicode. But UTF-8 uses a variable character length. That is, some characters use more bytes than others. For example, the character `a` needs one byte to be represented as where the character `ñ` needs two bytes. This can be checked encoding these characters with 'UTF-8':

```
len('a'.encode('UTF-8'))    # Gives 1 byte

len('ñ'.encode('UTF-8'))    # Gives 2 bytes
```

And other characters need even more bytes:

```
len('€'.encode('UTF-8'))   # Gives 3 bytes

len('😀'.encode('UTF-8'))   # Gives 4 bytes
```

Python could have decided to use some other encoding like UTF-16 (2 bytes) or UTF-32 (4 bytes) to store strings, but that also means that strings would use more memory even if many times, at least in English, text can be encoded using just UTF-8 or any other encoding that uses 1 byte per character.

So, to store strings Python developers came up with the following system:

- If a character belongs to Latin-1 character set, then *preferably* **Latin-1** encoding is used (**1 byte**).
- If the character does not belong to Latin-1 but belongs to UCS-2 character set, then *preferably* **UCS-2** encoding is used (UCS-2 is quite similar to UTF-16 but fixed size and it uses **2 bytes** per character).
- If the character doesn't belong to Latin-1 or UCS-2 character sets, then **UCS-4** encoding is used (UCS-4 is quite similar to UTF-32 but fixed size and it uses **4 bytes** per character).

With this arragement, at least in most cases, some space can be saved.

The character size in a Python string can be checked with the help of the string's internal `__sizeof__()` method:

```
'aa'.__sizeof__() - 'a'.__sizeof__()    # Gives 1 byte or memory position. 'a' is encoded
preferably in Latin-1

'ññ'.__sizeof__() - 'ñ'.__sizeof__()    # Also gives 1 byte or memory position. 'ñ' is
encoded preferably in Latin-1. Notice that this character uses 2 bytes in UTF-8.

'€€'.__sizeof__() - '€'.__sizeof__()    # Gives 2 bytes or memory positions. '€' is encoded
preferably in UCS-2/UTF-16. Notice that this character uses 3 bytes in UTF-8.

'😀😀'.__sizeof__() - '😀'.__sizeof__() # Gives 4 bytes or memory positions. '😀' is
encoded in UCS-4/UTF-32.
```

Note

The size of the elements in the string have to be calculated this way and not by a single `__sizeof__()` because the "string" data structure itself uses some space for internal purposes.

But in an array all elements must have the same size for it to be trivial to find a particular element based on its index. That is why the word "preferably" was used in the previous paragraph. Not always a character is encoded with the preferred method. What Python does is to use the **largest encoding** found in any element of a string **as the encoding for all elements** of such string.

This way all elements have always the same size, but the drawback is that just one character can make the whole string to use a longer encoding even if the rest of characters could have been represented in a shorter encoding like Latin-1. We can see this behavior in action the same way as before:

```
'😀a'.__sizeof__() - '😀'.__sizeof__() # Gives 4. Meaning that in this string the 'a'
character is using 4 bytes (UCS-4/UTF-32)
```

The `a` character now uses 4 bytes in this string, when in the previous example it was using only 1 byte. That is because some other character in the string, in this case an emoji, is causing that all other characters in the string are also going to be encoded in UCS-4/UTF-32.



In any case, Python hides all this complexity from us and we have a consistent and simple syntaxis and functions where one character means one position:

```
len('a')    # Gives 1
len('€')    # Gives 1
len('😀')   # Gives 1
```

> **Note**
>
> You can read more about how Python stores strings in this article.

Conclusion

So as we have seen, arrays are very fast at indexing, that is, to find the value of certain known position (it's $O(1)$), but they are not so fast for some other actions like insertion, deletion or searching, as we have also seen.

Arrays are simple to understand and to implement, and the suit very well when we need to store fixed size data and we don't need to make many modifications to the list. But on the other hand, they don't fit well (or at all) when we need to store data of different size or when we need to modify the list frequently.

We will see in the next chapters other data structures that can fit better in those cases where the arrays perform badly.

Chapter's 2 exercises

Please complete the exercises you will find in chapter 2 of the Moodle environment.