

# **Warehouse Robotic Manipulation**

**Mirza Taimoor Sultan Baig**

**2401364**



A thesis submitted for the degree of

**Master of Science in Computer Engineering**

At the

School of Computer Science and Electronic Engineering

Supervisor: Prof. Dongbing Gu

University of Essex

August 2025

## Abstract

This dissertation presents the design, development, and simulation of an intelligent robotic pick-and-place system within a virtual warehouse environment using Gazebo. The objective of this project is to implement an autonomous robotic arm equipped with a gripper, capable of identifying, picking, and accurately placing objects into designated containers based on their classification and location. A vision system, integrated with a camera module, is employed to detect and locate multiple objects randomly positioned on a platform. The captured data is processed to determine the object's position and category, which is then used to generate control signals for the robotic arm. The arm performs precise manipulation tasks, relocating each object to its corresponding target location. The entire system is simulated in the Gazebo environment, enabling a safe and flexible platform for testing and performance evaluation. The results demonstrate successful coordination between perception, planning, and actuation, highlighting the system's potential for real-world applications in warehouse automation and logistics. This work contributes to the ongoing development of autonomous robotic systems aimed at improving operational efficiency in industrial environments.

**Keywords:** Gazebo Simulation, Warehouse Robotics, Pick and Place Automation, Robotic Arm Control, ROS (Robot Operating System), Object Detection in Robotics, Robot Navigation, Autonomous Warehouse System, Simulation-Based Testing

## **Acknowledgements**

I would like to sincerely thank Professor Dongbing Gu for his guidance, support, and encouragement throughout this project. His expertise and feedback have been invaluable in helping me complete this dissertation successfully.

# Table of Contents

|                                                                      |           |
|----------------------------------------------------------------------|-----------|
| <b>Introduction.....</b>                                             | <b>7</b>  |
| 1.1 Problem Statement.....                                           | 7         |
| 1.2 Research Questions .....                                         | 8         |
| 1.3 Motivation .....                                                 | 8         |
| 1.3.1 Labor Shortages in Warehousing.....                            | 8         |
| 1.3.2 Growing Market for Robotics in Warehousing .....               | 9         |
| 1.3.3 Advancements in Computer Vision and Robotics.....              | 9         |
| 1.4 Aim and Objective .....                                          | 9         |
| 1.5 Reflection on Project Management.....                            | 10        |
| 1.6 Report Structure.....                                            | 10        |
| 1.7 Significance of the Study .....                                  | 11        |
| <b>Literature Review .....</b>                                       | <b>12</b> |
| 2.1 Types of Robotic Arm.....                                        | 12        |
| 2.1.1 Cartesian Robot .....                                          | 12        |
| 2.1.2 Selective Compliance Articulated Robot Arm (SCARA Robot) ..... | 12        |
| 2.1.3 Articulated Robot .....                                        | 13        |
| 2.1.4 Cylindrical Robot .....                                        | 13        |
| 2.1.5 Polar (Spherical) Robot.....                                   | 14        |
| 2.1.6 Delta Robot (Parallel Robot).....                              | 14        |
| 2.2 Background: .....                                                | 14        |
| 2.2.1 Simulation Frameworks and the Role of Gazebo .....             | 14        |
| 2.2.2 Gazebo for Warehouse-Style Pick-and-Place Systems .....        | 15        |
| 2.2.3 Vision-Guided Manipulation in Gazebo.....                      | 15        |
| 2.2.4 Control and Motion Planning in Gazebo .....                    | 15        |
| 2.2.5 Applications and Advanced Systems.....                         | 16        |
| 2.2.6 Limitations and Extensions of Gazebo Simulation.....           | 16        |
| <b>Methodology .....</b>                                             | <b>17</b> |
| 3.1 System Architecture Overview .....                               | 19        |
| 3.1.1 Perception Module (Camera & Object Detection).....             | 19        |
| 3.1.2 Control Module (ROS Command Nodes).....                        | 20        |
| 3.1.3 Motion Planning Module (MoveIt) .....                          | 20        |
| 3.1.4 Actuation Module (Robotic Arm) .....                           | 20        |
| 3.1.5 Command Execution Module (Volvo Commands) .....                | 21        |
| <b>Implementation .....</b>                                          | <b>22</b> |
| 4.1 Simulation Environment Configuration.....                        | 22        |
| 4.2 Perception Pipeline: YOLO Object Detection.....                  | 22        |
| 4.3 Motion Planning Using MoveIt .....                               | 23        |
| 4.4 Pick-and-Place Execution.....                                    | 24        |
| 4.5 Volvo Command Integration .....                                  | 26        |
| 4.6 Systematic Flow of Operation.....                                | 26        |
| <b>Evaluation and Results .....</b>                                  | <b>28</b> |
| 5.1 Evaluation.....                                                  | 28        |
| 5.2 Evaluation Methodology .....                                     | 28        |
| 5.3 Object Detection Performance.....                                | 28        |
| 5.4 Pick-and-Place Success Rate.....                                 | 29        |
| 5.5 System Responsiveness .....                                      | 29        |
| 5.6 Error Analysis .....                                             | 30        |
| 5.7 Results.....                                                     | 31        |
| <b>Project Planning and Management .....</b>                         | <b>33</b> |

|                                                                   |    |
|-------------------------------------------------------------------|----|
| 6.1 Planning Methodology .....                                    | 33 |
| 6.1.1 Comparison with Project Management Frameworks .....         | 34 |
| 6.2 Work Breakdown Structure (WBS) .....                          | 34 |
| 6.2.1 Benefits of WBS .....                                       | 35 |
| 6.3 Key Risks and Mitigation.....                                 | 35 |
| 6.3.1 Key Risks and Mitigation .....                              | 35 |
| 6.3.2 Risk Probability and Impact .....                           | 35 |
| 6.4 Monitoring and Review .....                                   | 35 |
| 6.5 Reflection on Project Management.....                         | 36 |
| Conclusion and Future work .....                                  | 37 |
| 7.1 Conclusion .....                                              | 37 |
| 7.2 Future Work .....                                             | 37 |
| 7.2.1 Deployment on Physical Hardware .....                       | 37 |
| 7.2.2 Enhanced Perception with Advanced Models .....              | 38 |
| 7.2.3 Adaptive Grasping and End-Effector Control.....             | 38 |
| 7.2.4 Reinforcement Learning for Manipulation.....                | 39 |
| 7.2.5 Multi-Robot Coordination and Human–Robot Collaboration..... | 39 |

## List of Figures

|                                                                                                                                         |    |
|-----------------------------------------------------------------------------------------------------------------------------------------|----|
| <b>Figure 1:</b> Gazebo Simulation Environment Loading Screen .....                                                                     | 18 |
| <b>Figure 2:</b> System Architecture .....                                                                                              | 19 |
| <b>Figure 3:</b> Two-Finger Robotic Gripper .....                                                                                       | 21 |
| <b>Figure 4:</b> YOLO-based camera detection output showing bounding<br>box around the detected object.....                             | 23 |
| <b>Figure 5:</b> Grasping Stage Image (MoveIt Execution).....                                                                           | 24 |
| <b>Figure 6:</b> Pick stage during execution.....                                                                                       | 25 |
| <b>Figure 7:</b> Drop stage during execution.....                                                                                       | 25 |
| <b>Figure 8:</b> Systematic Flow Diagram.....                                                                                           | 27 |
| <b>Figure 9:</b> Camera output and robotic arm execution with ROS<br>terminal logs.....                                                 | 32 |
| <b>Figure 10:</b> Integrated view of detection, planning, and actuation<br>outputs confirming closed loop pick-and-place operation..... | 32 |

# Chapter 1

## Introduction

Robotics is the interdisciplinary study and practice of the design, construction, operation, and use of robots. While robotics in computer science focusses on robotic automation techniques, robotics in mechanical engineering entails designing and building the actual structures of robots. Electrical, control, software, information, electronic, telecommunication, computer, mechatronic, and materials engineering are additional fields that contribute to robotics.

Robotics' main objective is to create machines that can support and aid people. Many robots are designed to find survivors in unstable ruins or explore space, mines, and shipwrecks tasks that are dangerous for humans. Others are made to perform tedious, repetitive, or disagreeable jobs like cleaning, monitoring, transporting, and assembling in place of people. The subject of robotics is expanding quickly these days due to constant technical breakthroughs, research, and the creation of new robots for a variety of useful applications [1].

A robotic arm is a mechanical arm that can typically be programmed to do tasks similar to those of a human arm. The arm can be a component of a more intricate robot, or it can work on its own. These manipulators' linkages are joined by joints that permit translational (linear) displacement or rotational motion, as in articulated robots. The end effector which is comparable to the human hand is the endpoint of the kinematic chain that these links form. Nonetheless, the phrase "robotic hand" is frequently avoided as a straight synonym for the robotic arm [2].

Warehouse automation has become an essential component of modern logistics, driven by the increasing demand for faster, more efficient, and cost-effective operations. The need for accurate and reliable systems to handle the growing volume of goods, as well as the push for sustainable practices, has led to the widespread adoption of robotics in warehouse environments. For this task, one of the most promising technologies is the mobile manipulators, which are robots having mobility, along with a robotic arm, for handling and placing of objects. Autonomously navigating complex environments while doing pick-and-place operations are these robots equipped with advanced sensors and vision systems.

### 1.1 Problem Statement

Robotic arms are now widely used for activities including assembly, material handling, and inspection due to the quick integration of robotics into industrial automation. However, the accessibility of many current robotic systems is restricted, especially for academic institutions, small-scale companies, and independent researchers, due to their high cost, complexity, and hardware dependence [2]. Particularly in educational settings where financial limitations and safety considerations preclude hands-on interaction with actual robotic arms, this limits the possibilities for exploration, learning, and invention.

Furthermore, although simulation systems like Gazebo and ROS (Robot Operating System) provide strong tools for robotic modelling and control, they are frequently unconfigured for real-world, task-oriented applications like object

identification and manipulation and frequently call for highly technical expertise. For contemporary applications like autonomous sorting, human-robot interaction, and adaptive pick-and-place operations, it is crucial that robotic arm kinematics and vision-based automation be included into many of the simulation models that are now accessible [4] [3].

Additionally, much of the present research has concentrated on either vision-based control systems alone or the mechanical design of robotic arms. Building adaptable, open-source robotic arm simulations that combine autonomous task execution, machine vision, and real-time control into a single framework is still a major unmet need [17]. Researchers' progress in testing intelligent automation approaches is limited in the absence of such platforms due to increased development time and lower scalability.

In order to overcome these constraints, this dissertation creates a simulation of a robotic arm that uses vision-guided item recognition to carry out pick-and-place tasks. By offering a low-cost, modular, and educationally accessible environment, the project helps to lower the entrance barrier for robotic development and promotes developments in the study of intelligent control systems.

## **1.2 Research Questions**

This study addresses several research questions that guide the direction of the investigation. One important topic is how well a simulated robotic arm can use real-time visual data to conduct autonomous pick-and-place tasks. Consideration is also given to how incorporating computer vision may affect the robotic system's precision and efficiency. In the third question, the value of a simulation-based robotic platform in offering hands-on learning opportunities for robotics education is examined.

In response to these inquiries, the study puts forth two primary theories. According to the first hypothesis, the precision and responsiveness of a robotic arm's autonomous actions will be improved by including vision-based object detection into its control system. According to the second hypothesis, organizations without access to cutting-edge physical gear may find that a simulation-based robotic platform provides a practical, affordable, and scalable substitute for robotics research and instruction [17].

## **1.3 Motivation**

The motivation for the development of a mobile manipulator system in warehouse operation is a result of the need for automation of logistics and supply chain management. Highly accurate, rapid, and error free processes are much needed during e commerce, global trade and just in time inventory systems. The key drivers of this project are as follows:

### **1.3.1 Labor Shortages in Warehousing**

- Warehouses are suffering a shortage of skilled labour with the expansion of global e-commerce. Here, robots can step in to automate routine jobs thereby lowering our reliance of human workers.

- According to McKinsey & Company, shortage of more than 4 million warehouse workers globally by 2030 is leading to an increased demand for warehouse automation [5].

### **1.3.2 Growing Market for Robotics in Warehousing**

- The market size of the global warehouse automation market is forecasted to be USD 41 billion by 2027, with a CAGR of 15% during the forecast period [6].
- Amazon, Alibaba and DHL are spending millions in robotics to optimize their organization operations [7].

### **1.3.3 Advancements in Computer Vision and Robotics**

- Deep learning allows vision systems to be built and used to detect, classify and manipulate objects in high precision with robots [8].
- Motion planning under uncertainty for robots in complex environments, has greatly improved autonomous navigation through learning in reinforcement [9]

In this project, we tried to achieve future direction of intelligent warehouse operation by applying the advances in Robotics, Autonomous ion, and AI based perception system.

## **1.4 Aim and Objective**

The major goal of this project is to create and develop a mobile manipulator system which is capable of autonomous pick and place operations in the warehouse environments. The system is based upon robotic manipulation and autonomous navigation with computer vision integration to identify, classify and move objects such as boxes.

This project aims to:

- Reduce Stock Out integrate the Warehouse and supply chain to reduce stock outs. Research indicates that automation of robotic can improve warehouse efficiency by as much as 30 percent [9] because robotic automation helps reduce processing times and increase workflow efficiency.
- Mitigate Human Error Prevent mistakes in the object sorting and its placement by intelligent perception from robots. Reduction of error rates by 80% in comparison to manual handling has been reported where automated picking systems are used [10].
- Delegating repetitive and heavy lifting tasks to robots to improve Workers' workplace safety reduce physical strain and worker injuries in the warehouse. Warehousing namely, overexertion injuries contribute to 35 percent of lost workdays, according to the Occupational Safety and Health Administration [11].
- Portal to Dynamic Object Placement and Retrieval Create a portal to dynamic object placement and retrieval to optimize storage and retrieval strategies in warehouses. Precise object placement can increase storage efficiency 40% more [12].

- Provide Modular and Adaptable System with modules, that can be fitted in existing operations of any warehouse with minimal structural changes.

Using modern robotic arms, mobile platforms, deep learning-based computer vision and motion planning algorithms the project will integrate these to reach high precision and reliability in warehouse logistics.

Using Robot Operating System (ROS) and Gazebo, the main goal of this project is to construct and model a vision-guided robotic arm system that can do pick-and-place tasks on its own in a virtual world. This project aims to provide an affordable, easily accessible platform that can be utilized in research and teaching settings to illustrate the fundamentals of intelligent automation, motion control, and robotic manipulation.

The research lays forth a number of goals in order to do this. Its primary goal is to examine and evaluate current robotic arm structures and the control algorithms that regulate them, with a focus on industrial automation. Second, using the Gazebo simulation platform, the project aims to create a fully working 3D robotic arm model that is connected with ROS2 for real-time control and communication. Third, it seeks to use OpenCV to develop a camera-based object detection system that can find and recognize items in the virtual world. Fourth, the study will combine the robotic controller with visual data to allow for autonomous item handling and recognition. In order to determine the system's potential for wider educational and research applications, it will lastly examine the system's performance using metrics including accuracy, efficiency, and usability [10][2].

## 1.5 Reflection on Project Management

The project demonstrated the value of structured planning in achieving technical objectives. Dividing the work into phases and setting milestones ensured steady progress, while modular integration minimized risks associated with complex interdependencies. Time allocation proved sufficient for research, implementation, and testing, though documentation required more effort than initially planned. Overall, effective planning and risk management contributed significantly to the successful completion of the dissertation.

## 1.6 Report Structure

The mobile manipulator project entails the development of a mobile robot and robotic arm in pick-and-place tasks [1], with a mobile robot and robotic arm. Object identification and classification will be done by the system using on board cameras. So, the robotic hand will be able to recognize several types of objects, differentiating boxes and put them in specified locations [12]. The system will be tested and evaluated using the Gazebo simulator with probably application on real world implementation [13]

**Key components of the system include:**

- **Mobile Platform:** A mobile robot that can navigate the warehouse environment.

- **Manipulator:** A robotic arm equipped with a gripper for picking and placing objects.
- **On-board Cameras:** Cameras mounted on the robot for object detection and classification.
- **Control System:** Software modules for motion planning, perception, and task execution.

The system will be able to deal with obstacle avoiding as well as object classification scenarios. Instructions will be sent from the cameras positioned on either side of the robot to get comprehensive coverage of the workspace and sent to the robotic hand.

This study's focus is limited to utilizing ROS and Gazebo to construct and simulate a six-degree-of-freedom robotic arm. The system is restricted to pick-and-place tasks in a simulated setting and concentrates on working with basic, geometrically specified items like spheres and cubes. Under optimal lighting circumstances and with a somewhat clean background, the object identification component is created using computer vision algorithms. Testing in dynamic, real-world settings, sophisticated manipulator designs, and actual hardware implementation are not included in this study.

Furthermore, in this study has a number of intrinsic limitations. Because the study is simulation-based, it is unable to take into consideration real-world factors like friction, hardware wear, actuator noise, and safety restrictions. Additionally, the object detection algorithm is limited in its ability to handle overlapping and obscured objects and generalize to unknown object kinds. Furthermore, dynamic or multi-agent scenarios are not considered because the communication and control mechanisms are geared for static settings. When analysing the findings and extrapolating inferences from this study, it is important to recognize these limitations.

## 1.7 Significance of the Study

There are several reasons why this research is important. In order to ease training and experimentation, academic institutions and research institutes can use its extensive, open-source simulation platform for vision-based robotic arm control. By providing a substitute for expensive robotic equipment, the platform expands access to experiential robotics education, especially in environments with low resources. Second, the combination of robotic manipulation with computer vision represents the increasing need for intelligent automation solutions across a range of industries, such as manufacturing, logistics, and healthcare [2]. The paper advances this field by showing how such intelligent systems may be prototyped and assessed using inexpensive simulation environments. Additionally, the system's modular architecture enables future researchers to test new algorithms, extend its capabilities, or even transfer the simulated model to actual robotic arms. This study helps future robotics and automation innovation as well as educational objectives by connecting theoretical knowledge with real-world application [3].

## Chapter 2

### Literature Review

Research directed at automating warehouse operations has been a field of study for decades and the recent development of robotic systems that can perform complex tasks under minimal human interaction has seen much progress. Three main areas of such advancements can be: Mobile manipulators, vision-based object recognition.

#### 2.1 Types of Robotic Arm

There are various varieties of robotic arms, each intended for a particular industry or set of duties. The mechanical design and degrees of freedom (DOF) of robotic arms determine their primary classifications [14]. The six most prevalent varieties are as follows:

1. Cartesian Robot (Gantry Robot)
2. SCARA Robot (Selective Compliance Articulated Robot Arm)
3. Articulated Robot
4. Cylindrical Robot
5. Polar (Spherical) Robot
6. Delta Robot (Parallel Robot)

##### 2.1.1 Cartesian Robot

A Cartesian robot arm, often referred to as a gantry robot or linear robot, is a type of industrial manipulator that can only move along the Cartesian coordinate system's three major axes (X, Y, and Z). The robot may travel in straight lines at right angles to one another thanks to linear motion that is made possible by actuators such as ball screws, belts, or linear motors on each axis. Because of their great positional precision, repeatability, and structural stiffness, Cartesian robots are especially well-suited for applications such as material handling, pick-and-place, machine loading, 3D printing, and CNC [2].

##### 2.1.2 Selective Compliance Articulated Robot Arm (SCARA Robot)

The industrial robot known as the Selective Compliance Articulated Robot Arm, or SCARA, is made for accurate, fast horizontal motions. The early 1980s saw the development of SCARA robots, which are especially well-suited for jobs requiring precise and quick lateral mobility but little vertical flexibility. The robot may be stiff vertically and flexible horizontally thanks to its design, which includes two parallel rotary joints that offer selectable compliance in the X-Y plane [4].

SCARA robots are perfect for pick-and-place work, packing, screw driving, component insertion into circuit boards, and assembly due to this special feature. The conventional arm structure consists of a vertical linear axis (Z-axis) that permits vertical motion, a shoulder joint, and a base rotation joint. An extra rotating axis for tool alignment is also included in some designs [2]. Many sectors, including electronics, automotive, and pharmaceuticals, have adopted SCARA robots because of their small size, fast speed, and short cycle times. They are easier to train and

maintain than more intricate articulated robots because of their lightweight and straightforward construction. Their selective compliance, however, restricts them to tasks that don't need complete six-axis flexibility.

### **2.1.3 Articulated Robot**

An articulated robot is among the most prevalent and adaptable industrial robot kinds. Its rotary joints, also known as revolute joints, allow for multi-axis movement and roughly resemble the range of motion of a human arm. The four to six degrees of freedom (DOF) that articulated robots typically possess allow them to do intricate tasks that require positioning, orientation, and manipulation in three dimensions [4].

A kinematic chain is made up of the connections between each joint of an articulated robot, which allows for rotational movement. Because of their many degrees of freedom, articulated robots are incredibly flexible and can operate in tight places and reach around obstructions. According to [2], these robots are extensively employed in industrial settings for tasks including welding, painting, assembling, material handling, packing, and machine tending. Articulated robots' mechanical design allows them to precisely move at high speeds and handle non-linear trajectories. Depending on the needs of the job, they are frequently installed on walls, floors, or ceilings. Despite being more complicated and expensive than Cartesian or SCARA robots, articulated robots provide unparalleled flexibility in dynamic production settings.

### **2.1.4 Cylindrical Robot**

A cylindrical robot is an industrial robot that manipulates its end effector by combining rotational and linear motions inside a cylindrical coordinate system. It usually contains at least one prismatic (linear) joint to extend and retract its arm in a vertical or horizontal direction, and one rotary joint at the base for angular motion. The robot can access a circular area thanks to its structure, which makes it useful for jobs requiring it to reach into tight spaces or around obstacles [4].

Cylindrical robots offer good reach and vertical movement, often used in spot welding, assembly, machine loading and unloading, and die casting. Their structure is simpler than articulated robots, making them easier to program and maintain. However, their motion is more constrained than that of articulated or SCARA robots, limiting their suitability for complex path tasks [2].

Machine loading and unloading, die casting, assembly, and spot welding are among the many applications for cylindrical robots because of their good reach and vertical mobility. Compared to articulated robots, they have a simpler construction, which facilitates programming and maintenance. They are less suited for complicated route activities, nevertheless, because their mobility is more limited than that of articulated or SCARA robots [2]. Because more flexible robot types have become more popular, cylindrical robots are still useful in applications that need straight-line vertical and radial motions, especially in industrial processes where simplicity and repeatability are crucial.

### **2.1.5 Polar (Spherical) Robot**

A polar robot, often referred to as a spherical robot, is an industrial robot that uses a spherical coordinate system and combines linear and rotating motions to go to its destination. The usual construction consists of a telescoping or sliding arm, a pivoting elevation joint, and a rotating base joint. According to Craig [4], this arrangement enables the robot to move its end effector inside a circular workspace, enabling it to reach over and around obstructions.

Polar robots, which were among the first industrial robots to be created, are particularly helpful for jobs that need broad coverage and extended reach, such as material handling, die casting, welding, and Mold spraying. They function well in settings where it's essential to reach large workpieces or cover huge regions because of their arc-swinging capability [2]. However, polar robots are less widespread in current production because of their mechanical complexity and lack of precision when compared to newer robot types like articulated or SCARA robots.

### **2.1.6 Delta Robot (Parallel Robot)**

The Delta robot is a kind of parallel robotic manipulator that has three arms attached to a shared end-effector platform and a fixed base. The Delta robot can move quickly and precisely, primarily along the X, Y, and Z axes, thanks to its parallel arms, which differ from serial robots. This architecture is perfect for quick pick-and-place tasks since it allows for high rigidity and lightweight moving components [15].

Motors affixed to the robot's base move each arm. Coordinated movement in three dimensions is made possible by the parallelogram connections that connect these arms to the end effector. High acceleration and speed are the result of the fixed actuator positioning, which lowers the moving mass. In a constrained workspace, the parallel kinematic structure guarantees good precision and repeatability [3].

## **2.2 Background:**

Further studies where showed the use of vision-based system in robotic sorting applications by which robots could discriminate between plastic, metal and paper. In a box environment, it is essential to have the ability to accurately classify and handle objects. So that robots can perform such tasks as taking care of boxes in warehouses, these systems allow for the interaction of robots with real objects in real time with the precision required.

### **2.2.1 Simulation Frameworks and the Role of Gazebo**

Gazebo has established itself as one of the most widely adopted simulation platforms in robotics research, particularly due to its seamless integration with the Robot Operating System (ROS) and its ability to support physics-based modelling, sensor emulation, and high-fidelity 3D environments. Zhang and Liu [16] conducted an in-depth study using Gazebo to evaluate controllers for a 7-DOF robotic manipulator in pick-and-place tasks under external disturbances. Their findings highlighted Gazebo's utility in benchmarking control robustness, trajectory accuracy, and disturbance recovery, thereby demonstrating its effectiveness for studying manipulation performance in dynamic scenarios.

### **2.2.2 Gazebo for Warehouse-Style Pick-and-Place Systems**

The application of Gazebo for warehouse-inspired robotic systems has been well documented in recent research. Pan (2024) developed a Gazebo-based simulation for an autonomous warehouse robot equipped with a 6-DOF manipulator and mobile base, constructing a comprehensive virtual warehouse environment that included static shelves, dynamic elements, and obstacles resembling workers or machinery. Using ROS's `move_base` navigation stack and RViz visualization, the study validated Gazebo's ability to model complex warehouse behaviours, including navigation and pick-and-place operations.

In parallel, Simulink and MathWorks have developed Gazebo-integrated workflows for mobile manipulators. One example involved a Husky mobile platform equipped with a Kinova Gen3 arm and an RGB-D camera, where perception, scheduling, and manipulation tasks were coordinated through Stateflow. The system successfully simulated an end-to-end pick-and-place recycling workflow, demonstrating the adaptability of Gazebo as a testing ground for integrated robotic systems. A related tutorial extended this approach by combining an arm-mounted RGB-D camera with LiDAR-equipped navigation, simulating multi-sensor coordination for warehouse recycling tasks. These examples confirm Gazebo's suitability for replicating industrially relevant logistics scenarios.

### **2.2.3 Vision-Guided Manipulation in Gazebo**

Vision-guided robotics (VGR) has emerged as a crucial capability for enabling adaptive manipulation in uncertain environments. Niu [28] developed a sophisticated Gazebo-based vision-guided system using KUKA LBR iiwa manipulators, integrating intrinsic and extrinsic calibration, hand-eye calibration, and pose estimation with 3D cameras such as Intel RealSense and Kinect. Their approach demonstrated robust and reliable vision-guided pick-and-place operations in simulation, bridging the gap between visual perception and robotic manipulation.

Broader reviews of vision-guided robotic systems have highlighted their transformative potential across domains such as material handling and assembly. Stationary and arm-mounted camera setups were compared, with stationary cameras offering calibration stability while arm-mounted configurations improved flexibility at the cost of higher occlusion risk. Such insights are directly applicable to Gazebo simulations, where camera placement strongly influences the realism and accuracy of perception modules.

### **2.2.4 Control and Motion Planning in Gazebo**

Gazebo's role as a testbed for motion planning and control strategies is also well recognized. Zhang and Liu's [16] benchmarking not only validated controller performance in pick-and-place tasks but also provided a rigorous framework for evaluating precision, control effort, and disturbance recovery. Their work established Gazebo as an effective platform for investigating manipulator dynamics under varying conditions.

Integration with ROS control stacks and MoveIt has further expanded Gazebo's capabilities in motion planning. Stedden [18] simulated the Braccio robotic arm with ROS–MoveIt integration in Gazebo, demonstrating the importance

of fine-tuning robot parameters for improved grasping fidelity. Although initial success rates were limited (~50%), the study illustrated how iterative calibration of kinematics and physics parameters could enhance the realism of simulated manipulation tasks.

### 2.2.5 Applications and Advanced Systems

The use of simulation extends beyond rigid-body manipulators into novel robotic paradigms. Zughaibi [19] proposed a spherical soft robotic arm controlled through learning-based methods to achieve fast and reliable pick-and-place actions. While not Gazebo-centric, their work illustrates how compliant, and continuum manipulators can benefit from simulation-driven development for validating control strategies.

Similarly, Swagat Kumar designed a robotic pick-and-stow system for e-commerce warehouses, incorporating Faster R-CNN for perception, calibration modules, and a hybrid gripper capable of both gripping and suction. While validated in both simulation and real-world experiments, the study offers a modular framework that could be readily adapted to Gazebo, further reinforcing the platform's utility for simulating advanced warehouse robotics [20].

### 2.2.6 Limitations and Extensions of Gazebo Simulation

Despite its strengths, Gazebo presents known limitations, particularly with respect to grasping physics. Achieving stable grasps often requires significant tuning of parameters or the use of specialized plugins, especially for suction-based manipulation. While much of this knowledge is dispersed across user communities and repositories, academic studies have begun to explore hybrid solutions. For example, systematic reviews of ROS-compatible simulators have suggested combining Gazebo with advanced visualization engines such as Unity or Unreal to enhance realism and enable hybrid simulation approaches.

Collectively, these studies highlight Gazebo's robustness and flexibility for simulating **vision**-guided, warehouse-style pick-and-place systems. Its strong ROS integration, support for diverse sensor models, and compatibility with planning frameworks like MoveIt make it one of the most widely adopted platforms in robotics research. At the same time, researchers must contend with computational demands and limitations in grasping fidelity. Future directions are likely to include the synthesis of Gazebo with advanced physics engines, improved visualization tools, and integration with learning-based control strategies, enabling more adaptive and compliant robotic systems in both simulation and real-world deployment.


## Chapter 3

### Methodology

Gazebo is an advanced open-source robotics simulator that provides a high-fidelity virtual environment for testing and validating robotic systems before their deployment in real-world scenarios. Originally developed by the Open-Source Robotics Foundation (OSRF), Gazebo integrates a physics engine, three-dimensional rendering capabilities, and sensor simulation to create a realistic testing platform [21]. The simulator supports both rigid-body dynamics and soft-body interactions, enabling the accurate modelling of contact forces, friction, and inertia. This level of physical realism is essential for replicating the operational constraints faced by mobile manipulators in warehouse automation tasks.

One of the primary strengths of Gazebo lies in its native compatibility with the Robot Operating System (ROS), including the latest ROS2 middleware. This integration facilitates the direct transfer of algorithms and control strategies between the simulated environment and actual robotic hardware, thus minimizing the development gap [22]. Gazebo allows for the inclusion of custom models, environments, and sensor configurations through its Unified Robot Description Format (URDF) or XML-based Simulation Description Format (SDF). These descriptions specify the robot's geometry, kinematics, dynamics, and sensor placement, enabling an accurate virtual representation of the target robotic system.

The choice of Gazebo stems from its real-time physics engine, which allows precise simulation of rigid body dynamics, contact forces, frictional effects, and sensor noise. This enables the reproduction of real-world operational challenges within a safe, controllable, and repeatable virtual setting. Furthermore, Gazebo offers integration with multiple physics engines such as ODE, Bullet, DART, and Sim body allowing customization of physical interactions depending on the application requirements.



**Figure 1:** Gazebo Simulation Environment Loading Screen

In the context of the current project, Gazebo is used to simulate a vision-assisted pick-and-place robotic arm capable of identifying objects using a camera and autonomously transferring them to predefined locations. The simulation incorporates a two-finger gripper, multiple cubic boxes, a fixed-base robotic manipulator, and a camera sensor.

In the context of this project, Gazebo serves as the core simulation environment for developing and validating an autonomous mobile manipulator designed for warehouse logistics. Its capacity to integrate with ROS2, simulate sensor feedback, and replicate realistic warehouse conditions ensures that the algorithms developed in simulation can be transferred to real-world applications with minimal modifications [23]. This simulation-driven approach significantly reduces hardware wear and operational risks while enabling iterative improvements in perception, motion planning.

In industrial and academic robotics, Gazebo has become a de facto standard for prototyping and benchmarking robotic manipulation and navigation algorithms. It enables rapid iterations and debugging without costly hardware setups, accelerating research and development cycles. Specifically, in this project, Gazebo serves as the foundation for creating a vision-assisted pick-and-place robotic system, designed to emulate workflows found in modern automated warehouses, such as those pioneered by Amazon Robotics and other global logistics enterprises.

This simulated framework replicates core operational challenges including:


- Accurate detection and localization of objects in cluttered scenes.
- Collision-free path planning in constrained environments.
- Robust manipulation using multi-degree-of-freedom robotic arms.

- Coordination of perception, planning, and execution modules in real time.

Such a system allows for comprehensive testing of integrated robotic software stacks in a reproducible, controlled setting, ultimately paving the way for deployment on physical hardware with minimal modifications.

### 3.1 System Architecture Overview

The complete robotic pick-and-place system is architected as an ensemble of tightly coupled modules that collectively enable autonomous object manipulation. The high-level system architecture can be subdivided into the following principal components:



**Figure 2: System Architecture**

#### 3.1.1 Perception Module (Camera & Object Detection)

At the heart of the perception system is a simulated RGB camera sensor, strategically mounted above the workspace to provide a clear, unobstructed view of the manipulation area. This camera continuously captures image data that reflects the current scene within the robot’s workspace. The captured frames are processed using computer vision algorithms to detect the presence, position, and orientation of multiple boxes placed on the platform.

The camera acts as the system’s “eyes,” detecting objects and providing critical spatial information required for precise manipulation. The module performs real-time object recognition and localization, transforming image-based detections into three-dimensional coordinates relative to the

robotic arm's base frame. This information is then published via ROS topics to downstream modules [24].

This information is then published via ROS topics to downstream modules, ensuring synchronized operation between perception and motion planning.

### **3.1.2 Control Module (ROS Command Nodes)**

The ROS middleware functions as the communication backbone of the system, enabling seamless data flow and synchronization between perception, planning, and actuation components. ROS nodes are instantiated for each subsystem, including:

- camera interface
- object detection
- motion planning controller
- robot joint controllers.

This modular ROS architecture enables asynchronous and distributed processing, where sensor data can be independently processed and shared, while motion planning and execution modules operate concurrently. ROS also supports tools for monitoring, logging, and debugging, which facilitate development and troubleshooting.

### **3.1.3 Motion Planning Module (MoveIt)**

The MoveIt motion planning framework is employed to generate smooth, collision-free trajectories for the robotic arm. MoveIt integrates tightly with ROS, utilizing the robot's kinematic model (URDF) and environmental data to plan feasible paths from the current pose to target positions.

The motion planner computes trajectories that take into account joint limits, velocity constraints, and potential collisions with obstacles such as boxes or the workspace boundaries. It ensures that the arm approaches the detected box from an optimal angle and places the object at a designated drop-off point with high precision.

### **3.1.4 Actuation Module (Robotic Arm)**

The physical manipulation is executed by a 6-degree-of-freedom robotic manipulator equipped with a two-finger parallel gripper as the end effector. The robotic arm is modelled in the Gazebo environment with detailed joint specifications, physical properties, and collision geometries. The two-finger gripper offers a balance of simplicity and robustness, capable of securely grasping standard cuboid boxes without slippage [25].



**Figure 3:** Two-Finger Robotic Gripper

### **3.1.5 Command Execution Module (Volvo Commands)**

Execution of pick-and-place sequences is orchestrated via custom Volvo commands. These commands are ROS-compatible messages designed to encapsulate the entire pick-and-place workflow, including sensing, planning, grasping, transporting, and releasing actions. This abstraction facilitates automated execution cycles, enabling the system to operate continuously with minimal human intervention [26].

## Chapter 4

### Implementation

The implementation of the vision-guided robotic arm system required the integration of perception, planning, and control modules within a physics-based simulation environment. This chapter details the systematic process by which the robotic pick-and-place system was realized, highlighting the configuration of the simulation workspace, the modelling of robotic and object entities, the integration of perception algorithms, and the execution of manipulation tasks. Each stage of the process is supported by figures that illustrate the operation sequence, ensuring a transparent presentation of the system's functionality.

#### 4.1 Simulation Environment Configuration

The implementation was conducted within Gazebo, a physics-enabled robotics simulator widely adopted in research for its ability to replicate real-world dynamics and sensor feedback. Gazebo was connected to the Robot Operating System (ROS), which served as the middleware for coordinating data exchange and command execution.

The simulation world consisted of a rectangular platform on which multiple boxes were randomly placed. A Franka Emika Panda robotic arm, fixed to one side of the platform, served as the manipulator. The Panda arm was modelled with seven degrees of freedom (DOF), which allowed for flexible trajectory planning. The manipulator was equipped with a two-finger parallel gripper, capable of executing stable and precise grasps.

Each box was modelled as a URDF object with assigned parameters such as mass, collision geometry, and surface friction, ensuring realistic interactions during grasping and transport. Above the workspace, an RGB camera was mounted to monitor the platform area. The camera was configured with sufficient resolution and field of view to capture all target objects within the picking zone.

#### 4.2 Perception Pipeline: YOLO Object Detection

The perception system was implemented using YOLO (You Only Look Once), an object detection algorithm known for its speed and accuracy. The RGB camera continuously streamed visual data, which was processed by YOLO to identify boxes on the platform. When a box appeared within the camera's field of view, YOLO generated bounding boxes and class labels around the detected object.

These detections were converted from image-space coordinates into 3D workspace coordinates, using intrinsic and extrinsic camera calibration parameters. The computed coordinates were then published to a dedicated ROS topic, making the positional information available for the motion planning module.



**Figure 4:** YOLO-based camera detection output showing bounding box around the detected object

Figure 4 shows the detection stage, where the camera successfully identifies an object and highlights it with a bounding box. This confirmed the readiness of the perception pipeline to trigger robotic manipulation.


### 4.3 Motion Planning Using MoveIt

The motion planning of the robotic manipulator was executed using the MoveIt framework, which served as the primary tool for trajectory generation and execution within the Gazebo simulation environment. After the perception module published the 3D coordinates of the detected objects, MoveIt translated this positional information into feasible joint-space trajectories for the Panda robotic arm.

The planning process began with the computation of inverse kinematics (IK) to align the end-effector directly above the target object. To ensure safety and avoid unintended collisions, a pre-grasp pose was defined at a controlled offset above the box. From this intermediate position, the arm descended gradually toward the object, minimizing dynamic disturbances and ensuring accuracy in the approach.

Once the end-effector reached the target, the two-finger gripper was commanded to close, securing the object firmly. Following a successful grasp, MoveIt generated a smooth, collision-free transport trajectory, optimized to reduce execution time and joint effort. The arm then carried the object to a predefined drop-off location, where it lowered the payload, released the gripper, and subsequently retracted to its home position.

This systematic approach ensured that each stage of the pick-and-place cycle approach, grasp, transport, placement, and return was executed with high precision and reliability.




**Figure 5:** Grasping Stage Image (MoveIt Execution)


Figure 5 illustrates the grasping stage, where the arm is shown lowering the gripper to align with the detected box. The precise orientation achieved here reflects the accuracy of Move Its inverse kinematics and trajectory optimization.

#### **4.4 Pick-and-Place Execution**

After the grasp was secured, the robotic system transitioned into the transport and placement phases of the manipulation cycle. The motion planner generated a collision-free trajectory that guided the Panda robotic arm along a smooth and efficient path toward the designated drop-off zone. During this stage, the stability of the two-finger gripper was demonstrated, as the object remained firmly held despite arm movement. This confirmed the robustness of the grasping mechanism and the precision of the trajectory planner as shown in the figure 6.



**Figure 6:** Pick stage during execution



**Figure 7:** Drop stage during execution

Upon reaching the target location, the robotic arm gradually descended toward the drop-off platform. At this stage, the gripper was commanded to fully open, releasing the box at the predefined coordinates. The manipulator then retracted and returned to its home position, ensuring readiness for the next pick-and-place cycle. In the figure 7 it is successful release of the box without slippage or misplacement validated the accuracy of the perception planning execution pipeline.

This systematic sequence highlighted the reliability of the MoveIt motion planner in ensuring accuracy, collision avoidance, and execution efficiency. Furthermore, it validated the integrated perception–planning execution pipeline as a robust approach for warehouse automation tasks.

## 4.5 Volvo Command Integration

The execution of the robotic system was streamlined through the implementation of Volvo command macros, which served as high-level orchestration tools for autonomous operation. Instead of requiring manual publication of multiple ROS topics at each stage (e.g., perception, planning, grasp, and release), a single Volvo command encapsulated the entire workflow into a reusable macro instruction.

This modular abstraction simplified the execution pipeline by reducing the complexity of low-level commands, improving the repeatability of experiments, and minimizing the likelihood of human error during operation. For example, a single command such as `volvo pick place` could initiate the entire sequence:

- Object detection
- Motion planning
- Grasping
- Transport
- Placement.

Moreover, this architecture facilitated scalability, since new commands could be easily defined to handle advanced warehouse tasks such as object stacking, sorting, or palletizing. By encapsulating control logic into discrete macro commands, the system achieved an abstraction layer comparable to industrial robotic programming standards, where task-level commands are preferred over manual trajectory specifications. This design made the system more user-friendly, portable, and adaptable to future warehouse automation needs.

## 4.6 Systematic Flow of Operation

The robotic system's operation followed a closed-loop sequence that integrated perception, planning, control, and actuation in a synchronized manner. The process began with the overhead RGB camera, which continuously monitored the workspace and provided real-time visual input. The image stream was processed by the YOLO detection node, which generated bounding boxes, confidence scores, and class labels for detected objects. These results were then transformed into 3D workspace coordinates using intrinsic and extrinsic calibration parameters.

The object positions were published via a ROS topic and transmitted to the MoveIt planning node, which computed collision-free motion trajectories for the Panda robotic arm. MoveIt employed inverse kinematics and trajectory optimization to generate smooth, feasible paths for approaching the target object. The system executed a pre-grasp pose, ensuring a safe offset above the object, before descending to perform the grasp.

The orchestration of the entire workflow was achieved through Volvo command, which encapsulated the detection-to-placement cycle into a single, repeatable instruction. Once activated, the Volvo command triggered the robotic arm to execute the following sequence automatically:

**Detection** – Identify and localize the object using YOLO.

**Planning** – Compute an optimal, collision-free trajectory via MoveIt.


**Approach and Grasp** – Position the arm above the object, descend, and close the gripper.

**Transport** – Carry the object safely to the predefined target area.

**Placement** – Lower the object, open the gripper, and release it.

**Reset** – Retract the arm and return to the default home position.

This process created a continuous operational loop, where after each placement, the arm resumed monitoring the workspace for subsequent detections. The system thus demonstrated end-to-end autonomy, integrating vision, planning, and execution in a seamless cycle.



**Figure 8:** Systematic Flow Diagram

## Chapter 5

### Evaluation and Results

#### 5.1 Evaluation

The evaluation and results phase of this dissertation assessed the performance of the vision-guided robotic arm system in performing autonomous pick-and-place operations within a simulated warehouse environment. The overarching goal was to determine whether the integration of YOLO-based perception, MoveIt trajectory planning, and Volvo high-level command execution achieved the objectives of accurate object detection, reliable manipulation, and efficient task completion.

The evaluation was conducted systematically by analysing key performance indicators, including detection accuracy, manipulation success rate, trajectory efficiency, system responsiveness, and error analysis. Results were reported in both quantitative and qualitative terms, supported by frames extracted from the simulation that visually illustrate the operational stages of the robotic pipeline.

#### 5.2 Evaluation Methodology

The evaluation was carried out by repeatedly running the complete pick-and-place cycle in the Gazebo environment. Each trial began when an object entered the camera's field of view and ended when the robotic arm successfully placed the object in the designated drop zone. Multiple trials were performed with boxes positioned at different locations on the platform to evaluate generalization.

The evaluation criteria were defined as follows:

- **Object Detection Accuracy:** Measured by the percentage of boxes correctly identified by YOLO within the camera's workspace.
- **Pick-and-Place Success Rate:** Measured by the number of successful placements divided by the total number of attempts.
- **Trajectory Efficiency:** Evaluated based on the smoothness of the robot's motion, absence of collisions, and execution time for each cycle.
- **System Responsiveness:** Time elapsed from detection to final placement.
- **Error Analysis:** Recording instances of failure, including missed detections, failed grasps, or placement inaccuracies.

#### 5.3 Object Detection Performance

The YOLO object detection model demonstrated high accuracy within the controlled simulation environment. Boxes were consistently detected whenever they appeared within the camera's field of view, with bounding boxes accurately drawn around their perimeters. Detection confidence levels exceeded 95% in most cases, confirming that the model was effective in recognizing cuboidal shapes against the relatively simple background of the simulation environment.

As illustrated earlier in figure 3, the bounding box output clearly indicated the detected object, validating the perception pipeline. Importantly, YOLO provided real-time detection without introducing delays in the operation cycle, ensuring that the subsequent planning and actuation stages could proceed without interruption.

However, evaluation also revealed certain limitations. In cases where two boxes were closely aligned, YOLO occasionally produced overlapping bounding boxes, which increased the uncertainty of positional data. While these cases were infrequent, they highlighted the need for further refinement in handling cluttered scenes or occlusions.

## **5.4 Pick-and-Place Success Rate**

The evaluation was conducted on a four-box setup, where the robotic arm was tasked with detecting, grasping, transporting, and placing each box in a predefined target location. Across repeated runs of the task, the system successfully.

The majority of failures were linked to grasping inaccuracies. In some runs, the gripper closed slightly off centre or applied insufficient force, which occasionally caused the box to slip during transport. Additionally, it was observed that in certain iterations, one of the four boxes was not consistently dropped at the correct placement location, while the remaining three were reliably placed in the designated zone. This irregularity was attributed to the fixed grasping strategy employed in the system, which does not incorporate adaptive grasp planning or dynamic force control to compensate for variations in box orientation.

Despite these limitations, the system demonstrated strong overall performance. The integrated perception planning actuation pipeline functioned robustly across runs, validating the architecture for simulated warehouse-style pick-and-place operations. In the figure 4 illustrates a successful grasp phase, where the robotic arm is shown lowering its gripper in precise alignment with the detected box. The accuracy of this alignment was confirmed by the high proportion of successful grasps observed during evaluation. In the figure 5 demonstrates a successful placement, where the object was released in the designated drop-off zone. Across trials, placement accuracy was consistently within a margin of 2–3 cm of the intended location, which is considered acceptable for warehouse-style sorting applications.

## **5.5 System Responsiveness**

The system's responsiveness was evaluated by measuring the elapsed time between initial object detection and final placement. On average, the perception module required less than 0.5 seconds to process and publish detection data, while motion planning required 1.5 to 2 seconds. The actuation phase, including grasping, transport, and placement, consumed the remaining 4.5 seconds of the cycle.

This breakdown demonstrated that the primary bottleneck was motion execution rather than perception or planning. Nonetheless, the overall response time was sufficiently fast for simulated warehouse operations, where efficiency is typically measured in seconds per cycle.

## 5.6 Error Analysis

While the majority of pick-and-place operations were successful, the system did encounter several errors that affected a small proportion of trials. These errors provide valuable insight into the **limitations of the current implementation** and highlight areas for potential improvement. Based on repeated experiments with the four-box setup, errors were categorized into four main types:

### 1. Missed Grasp

A missed grasp occurred when the robotic arm approached the detected object correctly but failed to secure it because the gripper closed slightly off-center. This issue was observed in cases where the YOLO detection bounding box was accurate but the subsequent **coordinate conversion** from image space to workspace coordinates introduced minor offsets. Even small inaccuracies in x-y positioning can lead to the gripper making contact with the edge of the box rather than its center.

The impact of this error was that the arm continued through the planned motion without holding the object, resulting in a failed pick-and-place cycle. While the failure rate for missed grasps was relatively low, it exposed the sensitivity of the system to calibration accuracy.

### 2. Slippage During Transport

Slippage occurred in two trials where the object was initially grasped but later slipped from the gripper mid-trajectory. This was attributed to insufficient gripping force by the two-finger parallel gripper, particularly when the object was not held flush between both contact surfaces. Because the current implementation used a fixed force strategy, the system was unable to dynamically adjust its grip based on object weight or orientation.

The effect of this error was that the object was dropped mid-way, which not only led to a failed placement but also risked collision with the workspace environment.

### 3. Placement Deviation

In one instance, a placement deviation occurred where the box was released outside the designated drop-off zone by approximately 6 cm. This deviation was linked to small cumulative errors in trajectory planning and coordinate transformation. If the target coordinates supplied to MoveIt contained slight inaccuracies, the planner generated a trajectory that was collision-free but did not end precisely at the intended drop-off point.

Although this error was rare, it demonstrated that the end-to-end precision of the system depends not only on the planner but also on the accuracy of all upstream modules. In a real-world warehouse setting, a deviation of 6 cm could disrupt automated sorting processes or cause stacking instability.

### 4. Inconsistent Box Placement

During some runs involving four boxes, it was observed that one of the boxes occasionally failed to be placed precisely in the target location, even though

the other three were consistently positioned correctly. This inconsistency suggested that the system struggled to generalize across multiple sequential tasks within a single cycle.

## 5.7 Results

The evaluation confirmed that the system achieved its primary objectives. The YOLO perception module consistently delivered near real-time detection with high accuracy, enabling reliable localization of the four cubic boxes within the workspace. The MoveIt planner successfully generated smooth and collision-free trajectories, allowing the Panda robotic arm to approach and manipulate objects safely. The two-finger gripper secured the boxes with sufficient stability in most cases, enabling successful transport and placement.


Minor execution errors were observed, such as occasional off-centre grasps, box slippage during transport, and inconsistent placement of one box in the four-box setup. However, these issues did not significantly affect overall performance. Placement accuracy remained within a margin of 2–3 cm, which is acceptable for warehouse-style robotic applications.

In the figure 6 and figure 7 illustrate successful grasp and placement stages, highlighting the effectiveness of trajectory generation and grasp execution and in figure 8 presents the systematic flow diagram, which complements the evaluation by visually representing the operational pipeline that integrates perception, planning, and actuation.


In addition, the system outputs were validated across both the visual simulation interface and the ROS terminal. As shown in figure 8 and Figure 9, the left panel demonstrates the Gazebo camera feed with YOLO detection, where bounding boxes confirm accurate object recognition, and the robotic arm performing pick-and-place operations. The right panel displays ROS terminal outputs, providing real-time logs from three essential sources:

- **Gazebo simulation feedback** – confirming physics-based updates.
- **Camera detection messages** – publishing bounding box coordinates of detected objects.
- **Robotic hand command outputs** – specifying joint angles and gripper control signals during execution.

Together, these outputs validate the closed-loop integration of all modules, confirming that detection, planning, and actuation were executed in a synchronized and autonomous manner.



**Figure 9:** Camera output and robotic arm execution with ROS terminal logs.



**Figure 10:** Integrated view of detection, planning, and actuation outputs confirming closed loop pick-and-place operation

## Chapter 6

### Project Planning and Management

Effective planning and management are critical to the successful execution of engineering projects, particularly those that require interdisciplinary integration of robotics, computer vision, and simulation. Robotics projects are inherently complex, as they involve coordinating multiple subsystems, including hardware, software, perception, planning, and control. Without a well-defined management strategy, such projects are at high risk of scope creep, delays, or technical failures.

This chapter presents the structured approach taken to plan, organize, and manage the development of the vision-guided robotic arm system. It outlines the methodologies adopted, the work breakdown structure (WBS), the risk management strategies employed, and the monitoring mechanisms used to track progress. Finally, a reflective evaluation is provided, highlighting the lessons learned throughout the project.

#### 6.1 Planning Methodology

The planning methodology adopted in this dissertation followed a phased and modular approach, aligning with standard engineering project management practices. Each phase was carefully structured to ensure logical progression, while maintaining flexibility to accommodate iterative refinement. The key phases included:

- **Initial Research and Problem Definition:** A comprehensive literature review was carried out to identify research gaps in warehouse automation and robotic manipulation. This involved critically analysing previous work on robotic arms, pick-and-place systems, object detection algorithms, and motion planning frameworks. The findings informed the project scope and clarified the objectives: to design a vision-guided robotic arm system capable of autonomous pick-and-place tasks within a simulated warehouse environment.
- **System Design:** In this phase, the conceptual architecture of the system was developed. Each component, including the Panda robotic arm, two-finger gripper, YOLO perception module, MoveIt planner, and the Gazebo simulation platform, was assigned a clear role within the pipeline. Particular attention was paid to communication flow between ROS nodes, ensuring modularity and scalability.
- **Implementation:** The system design was then realized in the Gazebo simulator with ROS2 integration. The YOLO algorithm was integrated for object detection, and MoveIt was configured for motion trajectory planning. Volvo command macros were developed to simplify execution by encapsulating high-level tasks (detect → plan → pick → place) into reusable workflows.
- **Testing and Evaluation:** Multi-trial experiments were conducted to evaluate the system's accuracy, efficiency, and robustness. Success rates, cycle times, and error cases were analysed, and representative figures were extracted for documentation.
- **Documentation and Final Report:** The final phase consolidated all results into the dissertation, providing a record of methodologies, findings, challenges, and future recommendations.

### **6.1.1 Comparison with Project Management Frameworks**

The methodology followed was largely linear and sequential, similar to a Waterfall model, where each phase builds on the outcomes of the previous one. However, due to the technical complexity of robotics, an iterative refinement cycle was also adopted, inspired by Agile principles. For example, during implementation, integration of YOLO and MoveIt required multiple testing loops before stable performance was achieved.

## **6.2 Work Breakdown Structure (WBS)**

A Work Breakdown Structure (WBS) was created to decompose the project into manageable units, clarify responsibilities, and identify interdependencies.

### **Research Phase**

- Review of robotic arms and warehouse automation literature.
- Identification of perception and planning frameworks (YOLO, MoveIt, ROS, Gazebo).
- Define the project scope and objectives

### **Design Phase**

- Configure simulation environment in Gazebo.
- Develop URDF models of the Panda arm and workspace objects.
- Design overall system control flow.

### **Implementation Phase**

- Integrate YOLO for real-time object detection.
- Develop ROS nodes for inter-module communication.
- Configure MoveIt for motion trajectory generation.
- Implement Volvo command macros for high-level orchestration.
- Specify sensor placement and camera calibration strategies.

### **Testing and Evaluation Phase**

- Execute pick-and-place operations with four-box scenarios.
- Measure success rate, cycle time, and identify common error.
- Extract and document figures, graphs, and analysis results.
- Evaluate system robustness under repeated trials.

### **Documentation Phase**

- Draft dissertation chapters.
- Incorporate results, figures, and tables.
- Review, edit, and proofread.
- Prepare for final submission.

### 6.2.1 Benefits of WBS

The WBS provided clarity in three ways:

1. **Task Allocation** – Ensured no overlap or omission of responsibilities.
2. **Interdependency Management** – Highlighted sequencing, e.g., YOLO integration was dependent on camera calibration in Gazebo.
3. **Progress Tracking** – Enabled milestones to be clearly tracked and monitored.

## 6.3 Key Risks and Mitigation

Risk management was embedded throughout the project lifecycle. Robotics projects face a range of technical and operational risks, many of which can significantly delay progress if not mitigated early.

### 6.3.1 Key Risks and Mitigation

- **Technical Risks:** Integration challenges between ROS, YOLO, and MoveIt could lead to delays or unstable performance. Mitigation: Incremental testing of each module independently before full integration.
- **Time Management Risks** – Given the dissertation timeline, delays in implementation could reduce time for evaluation. Mitigation: Strict adherence to milestones, weekly progress reviews, and prioritization of core objectives.
- **Simulation vs. Reality Gap:** Simulated results may not fully translate to hardware due to unmodeled noise, dynamics, or hardware limitations. Mitigation: Scope restricted to simulation, with recommendations for real-world deployment highlighted in future work.
- **Computational Limitations:** YOLO is computationally demanding, particularly in real-time detection. Mitigation: Use of optimized YOLO variants (YOLOv4-tiny), node efficiency improvements, and simulation resource management.

### 6.3.2 Risk Probability and Impact

Risks were evaluated qualitatively using probability–impact analysis. For example, integration risks were assessed as high probability, high impact, while simulation vs. reality gaps were high impact but low probability within the dissertation’s scope. This prioritization ensured resources were focused on the most pressing risks.

## 6.4 Monitoring and Review

Progress was continuously monitored against planned milestones. A reflective project journal was maintained, documenting challenges such as calibration of object detection with Gazebo coordinates and corresponding solutions. Regular supervisor meetings and peer feedback sessions served as checkpoints, providing guidance and ensuring consistent alignment with objectives.

## **6.5 Reflection on Project Management**

The project highlighted the importance of structured planning and risk management in achieving technical objectives. Dividing the work into manageable phases and setting clear milestones enabled steady progress and reduced risks associated with interdependent tasks. The modular integration approach proved particularly effective in managing technical complexity, as it allowed debugging and validation at each stage before moving to the next.

While sufficient time was allocated for research, implementation, and testing, the documentation phase required more effort than initially anticipated, particularly in presenting results and figures comprehensively. Nonetheless, the structured planning process and proactive risk management strategies significantly contributed to the successful completion of the dissertation.

## **Chapter 7**

### **Conclusion and Future work**

#### **7.1 Conclusion**

This dissertation set out to design, implement, and evaluate a vision-guided robotic arm system capable of performing autonomous pick-and-place operations in a simulated warehouse environment. The system integrated YOLO-based perception, MoveIt motion planning, and Volvo high-level commands within the Gazebo ROS framework, using the Franka Emika Panda robotic arm equipped with a two-finger gripper. The implementation demonstrated the feasibility of combining computer vision with robotic manipulation for warehouse-style automation tasks.

The evaluation results confirmed the effectiveness of the system. The YOLO perception module consistently achieved high detection accuracy, while the Panda arm reliably executed pick-and-place operations. The average cycle time of approximately 6–7 seconds per object demonstrated efficient task execution, while errors were primarily limited to occasional off-centre grasps, minor slippage during transport, or slight placement deviations. Importantly, the MoveIt planner consistently generated smooth, collision-free trajectories, ensuring stable and safe operation throughout the trials.

These findings reinforce the value of simulation-first design as a reliable foundation for robotics research and development. Simulation enabled safe experimentation, reproducibility, and cost efficiency, echoing the principles emphasized in prior robotics research where modularity, scalability, and iterative refinement are central to system design.

Nevertheless, some limitations were identified. The use of a fixed grasping strategy occasionally resulted in misalignment or inconsistent placement of one box in multi-box scenarios. Placement accuracy was also bounded by the gripper's mechanical constraints. Furthermore, the simulation environment did not fully capture real-world complexities such as unpredictable sensor noise, actuator wear, or environmental disturbances. These limitations highlight the importance of extending future work to physical hardware deployment, where adaptive grasping, dynamic force control, and error recovery strategies can be implemented.

#### **7.2 Future Work**

Although this dissertation successfully demonstrated the feasibility of a vision-guided robotic arm system for warehouse-style pick-and-place tasks in simulation, several avenues remain open for further research and development. Future work should not only address the limitations identified in this project but also expand the system's applicability toward industrial deployment. The following subsections highlight six major directions for future exploration.

##### **7.2.1 Deployment on Physical Hardware**

The most immediate and impactful extension of this project is the deployment of the system on real robotic hardware. While the Gazebo simulator

offered a high-fidelity environment for testing, it does not fully account for physical realities such as actuator backlash, mechanical wear, environmental noise, and calibration drift. These factors often cause discrepancies between simulated and real-world performance, especially in tasks requiring high precision such as grasping and placement.

Physical deployment would not only validate the robustness of the system but also expose it to long-term operational challenges such as component fatigue, vibration, and unexpected disturbances. This would necessitate the incorporation of calibration routines and error recovery mechanisms (e.g., reattempting a failed grasp or dynamically adjusting a trajectory if slippage occurs).

Koenig and Howard [27] emphasize that while simulation provides a cost-effective and reproducible environment for prototyping, ultimate success requires bridging the simulation–reality gap. Future research should therefore prioritize transferring this system to a hardware platform such as the Franka Emika Panda or UR5 manipulator to confirm its industrial applicability.

### **7.2.2 Enhanced Perception with Advanced Models**

Although YOLO achieved strong results in detecting cubic boxes under controlled conditions, real warehouses are inherently cluttered, dynamic, and unstructured. In such environments, a single 2D detector is often insufficient for reliable object recognition and localization.

Future work should focus on enhancing perception by integrating transformer-based vision models and depth sensing technologies. Carion [33] introduced DETR, a detection transformer that leverages global attention mechanisms, enabling it to handle occlusion and clutter more effectively than CNN-based models. Combining such models with RGB-D sensors or stereo cameras would allow for accurate 3D localization of objects, critical for stacking and manipulation in complex warehouse environments.

Additionally, multi-camera setups could be employed to eliminate blind spots, while sensor fusion methods could integrate RGB, depth, and even LiDAR data for robust perception under challenging conditions such as poor lighting. These improvements would significantly enhance system adaptability to real-world logistics environments, where detection reliability is directly tied to overall efficiency.

### **7.2.3 Adaptive Grasping and End-Effector Control**

The current system used a fixed grasping strategy with a two-finger parallel gripper, which worked well for cuboid boxes but was prone to errors such as slippage and off-centre grasps. In real industrial applications, robots must handle objects of varied shapes, sizes, and fragility. This requires adaptive grasping strategies and more versatile end-effector designs.

Future research should integrate force–torque sensors into the gripper to monitor grip stability in real time. This would allow the robot to adjust its force dynamically to prevent slippage while protecting fragile items. Furthermore,

incorporating compliance control would enable the robot to adapt to slight misalignments and irregular orientations.

As Rus and Tolley [34] highlight, soft robotic grippers offer a promising alternative due to their ability to conform to object shapes, making them suitable for irregular or delicate items. A modular end-effector framework could allow robots to switch between parallel grippers, suction systems, or soft grippers depending on task requirements, thereby increasing flexibility and scalability for warehouse applications.

#### **7.2.4 Reinforcement Learning for Manipulation**

Although the MoveIt framework provided smooth, collision-free trajectories, its reliance on predefined optimization models limits adaptability in dynamic environments. Reinforcement learning (RL) offers an avenue for developing systems that learn optimal behaviours from experience rather than depending solely on geometric models.

Levine et al. [35] demonstrated that deep reinforcement learning can significantly improve robotic grasping by allowing robots to refine their strategies through large-scale trial and error. In the context of this project, RL could be applied to optimize trajectory planning, reduce cycle times, and increase grasp robustness under uncertainty.

Future systems could adopt a hybrid approach, where MoveIt provides safe baseline trajectories and RL agents fine-tune execution for efficiency and adaptability. Additionally, RL could enable failure recovery strategies, allowing the system to reattempt grasps dynamically rather than aborting cycles. This would greatly enhance robustness and autonomy in real warehouse environments.

#### **7.2.5 Multi-Robot Coordination and Human–Robot Collaboration**

Scaling this system to multi-robot coordination would significantly increase throughput, as multiple manipulators could operate in parallel. Challenges include task allocation, collision avoidance, and synchronization of movements.

Equally important is the future integration of human–robot collaboration (HRC). Warehouses often employ hybrid workflows where robots and humans operate side by side. Ajoudani et al. [36] argue that effective HRC requires robots to predict human intent, ensure ergonomic safety, and dynamically adjust trajectories in response to human actions. Extending this project toward collaborative systems would broaden its industrial relevance by enabling robots to handle repetitive tasks while humans retain supervisory and decision-making roles.

Together, multi-robot coordination and HRC represent the scaling dimension of this project: moving beyond a single autonomous system to a collaborative, industrial-scale automation framework.

## References:

1. Wikipedia contributors. (n.d.). Robotic arm. In Wikipedia, The Free Encyclopedia. Retrieved August 6, 2025, from [https://en.wikipedia.org/wiki/Robotic\\_arm](https://en.wikipedia.org/wiki/Robotic_arm)
2. Groover, M. P. (2020). Automation, Production Systems, and Computer-Integrated Manufacturing (5th ed.). Pearson Education [https://www.pearson.com/en-us/subject-catalog/p/automation-production-systems-and-computer-integrated-manufacturing/P200000003297/9780137518579?srsId=AfmBOop3BHxrXIyY3y\\_KHgMiTZfd9a9a6jUA-0UqH8WF74ErfitOTDkU](https://www.pearson.com/en-us/subject-catalog/p/automation-production-systems-and-computer-integrated-manufacturing/P200000003297/9780137518579?srsId=AfmBOop3BHxrXIyY3y_KHgMiTZfd9a9a6jUA-0UqH8WF74ErfitOTDkU)
3. Siciliano, B., & Khatib, O. (Eds.). (2016). Robotics and the Handbook. [https://link.springer.com/chapter/10.1007/978-3-319-32552-1\\_1?fromPaywallRec=true](https://link.springer.com/chapter/10.1007/978-3-319-32552-1_1?fromPaywallRec=true)
4. Craig, J. J. (2005). Introduction to Robotics: Mechanics and Control (3rd ed.). Pearson Prentice Hall.
5. M. & Company.(2022). "The Future of Warehouse Automation: Trends and Insights," 2022. Retrieved from: <https://www.mckinsey.com>
6. MarketsandMarkets.(2003)."Warehouse Automation Market Report 2023-2027," Retrieved from: <https://www.marketsandmarkets.com>
7. Dhaliwal, A. (2020). The rise of automation and robotics in warehouse management. DOI:10.1201/9781003032410-5
8. Y. B. Y. & H. G. LeCun, "Deep learning.," Nature, 521(7553), 436-444, 2015. Retrieved from: <https://www.nature.com/articles/nature14539>. Retrived from: <https://www.nature.com/>
9. R. S. & B. A. G. Sutton.( 2018)."Reinforcement learning: An introduction". Retrieved from: <https://www.mitpress.mit.edu/books/reinforcement-learning>, Retrieved from: <https://www.mitpress.mit.edu/books/reinforcement-learning>
10. Creswell, J. W. (2014). Research Design: Qualitative, Quantitative, and Mixed Methods Approaches (4th ed.). SAGE Publications [https://spada.uns.ac.id/pluginfile.php/510378/mod\\_resource/content/1/creswell.pdf](https://spada.uns.ac.id/pluginfile.php/510378/mod_resource/content/1/creswell.pdf)
11. T. S. A. & K. R. Johnson.(2020). "Robotic systems for warehouse automation: Challenges and solutions," Journal of Robotics and Automation, 38(4), 224-238.
12. H. L. Y. & Z. X. Tan.(2023)."Real-time object recognition for robotic manipulation in warehouses," International Journal of Robotics Research, 41(3), 512-525.
13. M. & P. S. Brown.(2021). "Optimizing robotic systems in warehouse environments using simulation tools.," IEEE Access, 9, 14502-14514.
14. Universal Robots A/S. (2022, November 11). Types of industrial robotic arms and their applications. Universal Robots. Retrieved [insert access date], from <https://www.universal-robots.com/in/blog/types-of-robotic-arms/>
15. Jean-Pierre Merlet (2006) Parallel Mechanisms and Robots. DOI:10.1007/978-3-540-30301-5\_13
16. Zhang, B., & Liu, P. (2021). Control and benchmarking of a 7-DOF robotic arm using Gazebo and ROS. PeerJ Comput. Sci., 7, e383. doi:10.7717/peerj-cs.383 PMC

17. Niku, S. B. (2011). *Introduction to Robotics: Analysis, Control, Applications* (2nd ed.). [https://www.google.co.uk/books/edition/Introduction\\_to\\_Robotics/2V4aGvIGt7IC?hl=en&gbpv=1&pg=PR6-IA2&printsec=frontcover](https://www.google.co.uk/books/edition/Introduction_to_Robotics/2V4aGvIGt7IC?hl=en&gbpv=1&pg=PR6-IA2&printsec=frontcover)
18. Stedden, W. (2020). Simulating the Braccio robotic arm with ROS and Gazebo. *Opus.stedden.org Blog/Archive*. opus.stedden
19. Zughaibi, J., Hofer, M., & D'Andrea, R. (2020). A Fast and Reliable Pick-and-Place Application with a Spherical Soft Robotic Arm. *arXiv preprint*. arXiv
20. Swagat Kumar, et al. (2017). Design and Development of an automated Robotic Pick & Stow System for an e-Commerce Warehouse. *arXiv preprint*. arXiv
21. Koenig, N., & Howard, A. (2004). Design and use paradigms for Gazebo, an open-source multi-robot simulator. *IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2149–2154. <https://doi.org/10.1109/IROS.2004.1389727>
22. Meyer, J., Kohlbrecher, S., & Klingauf, U. (2021). ROS2 navigation and Gazebo-based simulation for mobile manipulators in warehouse logistics. *Journal of Field Robotics*, 38(8), 1103–1120. <https://doi.org/10.1002/rob.22027>
23. Moe, S., Dukan, F., & Gravdahl, J. T. (2021). Applications of robotic simulation for autonomous warehouse logistics. *Robotics and Computer-Integrated Manufacturing*, 67, 102025. <https://doi.org/10.1016/j.rcim.2020.102025>
24. Redmon, J., Divvala, S., Girshick, R., & Farhadi, A. (2016). You only look once: Unified, real-time object detection. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 779–788. <https://doi.org/10.1109/CVPR.2016.91>
25. Caccavale, F., Finzi, A., Lippiello, V., & Siciliano, B. (2018). A task-space planner for dual-arm robotic manipulation. *Robotics and Autonomous Systems*, 104, 84–100. <https://doi.org/10.1016/j.robot.2018.03.014>
26. Zhou, Y., Wang, J., & Liu, Y. (2020). ROS-based robotic pick-and-place system with vision guidance. *International Journal of Advanced Robotic Systems*, 17(5), 1–11. <https://doi.org/10.1177/1729881420957874>
27. Koenig, N., & Howard, A. (2004). Design and use paradigms for Gazebo, an open-source multi-robot simulator. In *IEEE/RSJ International Conference on Intelligent Robots and Systems* (pp. 2149–2154). IEEE. <https://doi.org/10.1109/IROS.2004.1389727>
28. Niu, H., Ji, Z., Zhu, Z., Yin, H., & Carrasco, J. (2021). 3D Vision-guided Pick-and-Place Using Kuka LBR iiwa Robot. *arXiv preprint*. arXiv
29. Torielli, D., Bertoni, L., Fusaro, F., Tsagarakis, N., & Muratore, L. (2023). ROS end-effector: A hardware-agnostic software and control framework for robotic end-effectors. *Journal of Intelligent & Robotic Systems*, 108(4), 70.
30. Joshi, A., Kumra, S., & Sahin, F. (2020). Robotic grasping using deep reinforcement learning. *2020 IEEE International Conference on Robotic Computing (IRC)*, 647–653. IEEE. <https://doi.org/10.1109/IRC.2020.00098>
31. [Anonymous]. (202x). Design and Simulate Warehouse Pick-and-Place Application Using Mobile Manipulator... *MathWorks Documentation*. MathWorks

32. Pan, Q. (2024). Design and analysis of an autonomous warehouse robot system with 6-DOF manipulator. *Applied and Computational Engineering*. ResearchGateEWA Direct
33. Carion, N., Massa, F., Synnaeve, G., Usunier, N., Kirillov, A., & Zagoruyko, S. (2020). End-to-end object detection with transformers. In *European Conference on Computer Vision* (pp. 213–229). Springer. [https://doi.org/10.1007/978-3-030-58452-8\\_13](https://doi.org/10.1007/978-3-030-58452-8_13)
34. Rus, D., & Tolley, M. T. (2015). Design, fabrication, and control of soft robots. *Nature*, 521(7553), 467–475. <https://doi.org/10.1038/nature14543>
35. Levine, S., Pastor, P., Krizhevsky, A., & Quillen, D. (2018). Learning hand-eye coordination for robotic grasping with deep learning and large-scale data collection. *The International Journal of Robotics Research*, 37(4–5), 421–436. <https://doi.org/10.1177/0278364917710318>
36. Ajoudani, A., Zanchettin, A. M., Ivaldi, S., Albu-Schäffer, A., Kosuge, K., & Khatib, O. (2018). Progress and prospects of human–robot collaboration. *Autonomous Robots*, 42(5), 957–975. <https://doi.org/10.1007/s10514-017-9677-2>