

CPSC 526 Assignment 3

Port forwarding and logging server

Geordie Tait T02
10013837

To compile

```
gcc -pthread -o proxy a3.c
```

To run

```
./proxy [logOptions] [replaceOptions] srcPort server dstPort
```

where: logOptions and replaceOptions are described below
 srcPort is the port for the server to listen on
 server is the hostname for the destination server
 dstPort is the port to connect to the destination server on

Logging options

None specified	The server does not log any traffic
--raw, -w	All traffic is logged as is Incoming and outgoing are specified
--strip, -s	All traffic is logged, but with non-printable characters replaced with '.' Incoming and outgoing traffic are specified
--hex, -h	All traffic is logged in a format identical to the linux utility "hexdump -C" Incoming and outgoing traffic are specified
--auto N, -aN	All traffic is divided into N-byte segments and displayed separately Backslash, tab, newline, and carriage return are logged in escaped form Bytes in the range 32-127 are displayed in raw format All other bytes are displayed as a hex value with a leading backslash Incoming and outgoing traffic are specified

Replace options

```
--replace [text] [with], -r [text] [with]
```

This option can be used multiple times when running the server. It replaces all occurrences of the string [text] with the string [with] in both incoming and outgoing traffic.

Examples of formatting

(All examples use my backdoor server from assignment 2)

None

```
$ ./proxy 2222 localhost 1111
Port forwarding/logging server 1.0
Listening for connections...
```

```
Accepted a new connection
Connected to destination server
Connection terminated
```

Raw

```
$ ./proxy --raw 2222 localhost 1111
Port forwarding/logging server 1.0
Listening for connections...
```

```
Accepted a new connection
Connected to destination server
<-- Backdoor Server 1.0
Enter password:
```

```
--> password
```

```
<-- Login successful
%
--> ps
```

```
<--
<--  PID TTY          TIME CMD
      13822 pts/17      00:00:00 a.out
      13957 pts/17      00:00:00 ps
      27556 pts/17      00:00:00 bash
```

```
<--
```

```
<-- %
--> logout
```

```
<--
<-- Logging out
Connection terminated
```

Strip

```
$ ./proxy --strip 2222 localhost 1111
Port forwarding/logging server 1.0
Listening for connections...
```

```
Accepted a new connection
Connected to destination server
<-- Backdoor Server 1.0.Enter password:.
--> password.
<-- Login successful.
<-- %
--> ps.
<--
<-- PID TTY          TIME CMD.  13822 pts/17   00:00:00 a.out.
<--
<-- 14050 pts/17   00:00:00 ps.
<-- 27556 pts/17   00:00:00 bash.
<-- .
<-- %
--> logout.
<-- Logging out
Connection terminated
```

Hex

```
$ ./proxy --hex 2222 localhost 1111
Port forwarding/logging server 1.0
Listening for connections...
```

```
Accepted a new connection
Connected to destination server
<-- 00000000 42 61 63 6B 64 6F 6F 72 20 53 65 72 76 65 72 20 |Backdoor Server |
<-- 00000010 31 2E 30 0A 45 6E 74 65 72 20 70 61 73 73 77 6F |1.0.Enter passwo|
<-- 00000020 72 64 3A 0A                                |rd:.|
--> 00000000 70 61 73 73 77 6F 72 64 0A          |password.|
<-- 00000000 4C 6F 67 69 6E 20 73 75 63 63 65 73 73 66 75 6C |Login successful|
<-- 00000010 0A                                |.|
<-- 00000000 25 20                                |% |
--> 00000000 70 73 0A                          |ps.|
<-- 00000000 20 20                                | |
<-- 00000000 20 20 50 49 44 20 54 54 59 20 20 20 20 20 20 20 | PID TTY          |
<-- 00000010 20 20 20 54 49 4D 45 20 43 4D 44 0A 20 20 31 33 | TIME CMD.  13|
<-- 00000020 38 32 32 20 70 74 73 2F 31 37 20 20 20 30 30 3A |822 pts/17   00:|
<-- 00000030 30 30 3A 30 30 20 61 2E 6F 75 74 0A          |00:00 a.out.|
<-- 00000000 20 20                                |.|
<-- 00000000 31 34 31 39 35 20 70 74 73 2F 31 37 20 20 20 30 |14195 pts/17   0|
<-- 00000010 30 3A 30 30 3A 30 30 20 70 73 0A          |0:00:00 ps.|
<-- 00000000 20 20 32 37 35 35 36 20 70 74 73 2F 31 37 20 20 | 27556 pts/17  |
<-- 00000010 20 30 30 3A 30 30 3A 30 30 20 62 61 73 68 0A | 00:00:00 bash.|
<-- 00000000 0A                                |.|
<-- 00000000 25 20                                |% |
--> 00000000 6C 6F 67 6F 75 74 0A          |logout.|
<-- 00000000 20 20                                | |
<-- 00000000 4C 6F 67 67 69 6E 67 20 6F 75 74          |Logging out|
Connection terminated
```

Auto 32

```
$ ./proxy --auto 32 2222 localhost 1111
Port forwarding/logging server 1.0
Listening for connections...
```

```
Accepted a new connection
Connected to destination server
<-- Backdoor Server 1.0\nEnter passwo
<-- rd:\n
--> password\n
<-- Login successful\n
<-- %
--> ps\n
<--
<-- PID TTY TIME CMD\n
<-- 13822 pts/17 00:00:00 a.out\n
<--
<-- 14386 pts/17 00:00:00 ps\n
<-- 27556 pts/17 00:00:00 bash\n
<-- \n
<-- %
--> logout\n
<--
<-- Logging out
Connection terminated
```

Replace

```
$ ./proxy -s -r Backdoor "The Best" -r S $ -r ps pwd 2222 localhost 1111
Port forwarding/logging server 1.0
Listening for connections...
```

```
Accepted a new connection
Connected to destination server
<-- The Best $server 1.0.Enter password:.
--> password.
<-- Login successful.
<-- %
--> pwd. ← Note: user entered "ps"
<--
<-- /home/ugb/taitg/526/a3.
<-- %
--> logout.
<--
<-- Logging out
Connection terminated
```