


- Use exterior space to help in reconstruction
- Output: surface mesh, optionally watertight
- Class shape: general
- Main approaches:
  - Scanner visibility
  - Point set visibility
  - Parity


- Sequential integration of range scans
- Take advantage of acquisition:
  - confidence, space carving

[Curless & Levoy SIG'96]




- Construction of signed distance field

[Curless & Levoy SIG'96]



- Handling missing data: space carving [Curless & Levoy SIG'96]
- Interface between empty and unseen space considered to be the surface



- More robust means of range scan integration [Zach et al. ICCV07]
- Minimize gradient magnitude of signed distance field
- Use  $\ell_1$  norm for data fitting

- More robust means of range scan integration [Zach et al. ICCV07]
- Minimize gradient magnitude of signed distance field
- Use  $\ell_1$  norm for data fitting

$$E = \int_{\Omega} \left\{ |\nabla u| + \lambda \sum_{i \in \mathcal{I}(\vec{x})} w_i(\vec{x}) |u - f_i| \right\} d\vec{x}$$

- More robust means of range scan integration [Zach et al. ICCV07]
- Minimize gradient magnitude of signed distance field
- Use l1 norm for data fitting

$$E = \int_{\Omega} \left\{ |\nabla u| + \lambda \sum_{i \in \mathcal{I}(\vec{x})} w_i(\vec{x}) |u - f_i| \right\} d\vec{x}$$

impose smoothness

- More robust means of range scan integration
- Minimize gradient magnitude of signed distance field
- Use l1 norm for data fitting

[Zach et al. ICCV07]

$$E = \int_{\Omega} \left\{ |\nabla u| + \lambda \sum_{i \in \mathcal{I}(\vec{x})} w_i(\vec{x}) |u - f_i| \right\} d\vec{x}$$

impose smoothness

robustness to outliers


- More robust means of range scan integration
- Minimize gradient magnitude of signed distance field
- Use l1 norm for data fitting

[Zach et al. ICCV07]

$$E = \int_{\Omega} \left\{ |\nabla u| + \lambda \sum_{i \in \mathcal{I}(\vec{x})} w_i(\vec{x}) |u - f_i| \right\} d\vec{x}$$

impose smoothness

robustness to outliers




- Handle merging of scans at different resolutions [Fuhrmann & Goelese SIGA'11]

# Multi-resolution Scan Merging

- Handle merging of scans at different resolutions



[Fuhrmann & Goesele SIGA'11]



# Multi-resolution Scan Merging

- Handle merging of scans at different resolutions




[Fuhrmann & Goesele SIGA'11]




# Multi-resolution Scan Merging

- Handle merging of scans at different resolutions

[Fuhrmann & Goesele SIGA'11]




- Determine visible points from arbitrary views [Katz et al. SIG'07]
- Perform spherical inversion of point set from the given view
- Take convex hull of viewpoint & spherical inversion: points on the convex hull are considered visible



# Point Set Visibility


- Use for on-the-fly reconstruction

[Katz et al. SIG'07]



- Use visibility cones centered at points on the surface


[Shalom et al. SIGA'10]



# Cone Carving

- Use visibility cones centered at points on the surface




[Shalom et al. SIGA'10]



# Cone Carving

- Use visibility cones centered at points on the surface




[Shalom et al. SIGA'10]



# Cone Carving

- Use visibility cones centered at points on the surface




[Shalom et al. SIGA'10]




- Cones used to generate off-surface points for RBF reconstruction

- Use visibility cones centered at points on the surface

[Shalom et al. SIGA'10]






- Cones used to generate off-surface points for RBF reconstruction





- Use visibility cones centered at points on the surface

[Shalom et al. SIGA'10]





- Cones used to generate off-surface points for RBF reconstruction



# Cone Carving

- Robust to missing data in challenging scenarios

[Shalom et al. SIGA'10]





- Use parity to assign confidence to exterior/interior labeling [Mullen et al. SGP'10]
- Robust unsigned distance function

- Use parity to assign confidence to exterior/interior labeling [Mullen et al. SGP'10]
- Robust unsigned distance function




$$d_U(x) = \sqrt{\frac{1}{K} \sum_{p \in N_K(x)} ||x - p||^2}$$

- Use parity to assign confidence to exterior/interior labeling [Mullen et al. SGP'10]
- Robust unsigned distance function




$$d_U(x) = \sqrt{\frac{1}{K} \sum_{p \in N_K(x)} ||x - p||^2}$$

- Use parity to assign confidence to exterior/interior labeling [Mullen et al. SGP'10]
- Robust unsigned distance function



$$d_U(x) = \sqrt{\frac{1}{K} \sum_{p \in N_K(x)} ||x - p||^2}$$



$$E(f(x)) = \int_{\Omega} \left[ |f(x)|_S^2 + W(c(x))(f(x) - \bar{\lambda}(x)d_U(x))^2 \right] dx$$

- Assume smoothness in the shape interior
- Output: skeleton curve, surface mesh, generally assumes watertightness
- Class shape: organic, man-made shapes
- Main approaches:
  - Skeletal curve prior
  - Smoothness on medial axis

- Produce skeletal curve from incomplete data

[Tagliasacchi et al. SIG'09]

- Main assumption: local rotational symmetry

$$\mathbf{v}_i^{t+1} = \underset{\mathbf{v} \in \Re^3, \|\mathbf{v}\|=1}{\operatorname{argmin}} \operatorname{var} \{ \langle \mathbf{v}, \mathbf{n}(p_j) \rangle : p_j \in N_i^{(t)} \}, t \geq 0$$

- Produce skeletal curve from incomplete data

[Tagliasacchi et al. SIG'09]

- Main assumption: local rotational symmetry


$$\mathbf{v}_i^{t+1} = \underset{\mathbf{v} \in \mathbb{R}^3, \|\mathbf{v}\|=1}{\operatorname{argmin}} \operatorname{var} \{ \langle \mathbf{v}, \mathbf{n}(p_j) \rangle \mid p_j \in N_i^{(t)} \}, t \geq 0$$

ensure plane representing rotational symmetry is orthogonal to point normals

- Produce skeletal curve from incomplete data
- Main assumption: local rotational symmetry


$$\mathbf{v}_i^{t+1} = \underset{\mathbf{v} \in \mathbb{R}^3, \|\mathbf{v}\|=1}{\operatorname{argmin}} \operatorname{var} \{ \langle \mathbf{v}, \mathbf{n}(p_j) \rangle \mid p_j \in N_i^{(t)} \}, t \geq 0$$

ensure plane representing rotational symmetry is orthogonal to point normals




- Can also be used to resample surface for other reconstruction methods

[Tagliasacchi et al. SIG'09]




- Deformable model for extracting skeleton curve

[Li et al. SIGA'10]



- Deformable model for extracting skeleton curve

[Li et al. SIGA'10]




- Simultaneously grow, merge, and retract individual “snakelets”
- Geometric optimization: satisfy data fitting, smoothness, fairness

$$E_d := \sum_{i,j}^{n,m} w_i^j \| \mathbf{A}_i^j G_i^j - R_i^j \|^2 \quad E_s := \sum_{(i,j)} \| \mathbf{A}_i - \mathbf{A}_j \|_F^2,$$


- Deformable model for extracting skeleton curve

[Li et al. SIGA'10]




- Deformable model for extracting skeleton curve

[Li et al. SIGA'10]




- Deformable model for extracting skeleton curve

[Li et al. SIGA'10]



- Deformable model for extracting skeleton curve

[Li et al. SIGA'10]



- Surface evolution method combining surface smoothness, visibility constraints, and medial axis smoothness

[Tagliasacchi et al. SGP'11]

- Surface evolution method combining surface smoothness, visibility constraints, and medial axis smoothness


[Tagliasacchi et al. SGP'11]

$$\dot{\phi} + \omega_1 F_{\text{fit}} + \omega_2 F_{\text{smooth}} + \omega_3 F_{\text{vol}} = 0$$

- Surface evolution method combining surface smoothness, visibility constraints, and medial axis smoothness

$$\dot{\phi} + \omega_1 F_{\text{fit}} + \omega_2 F_{\text{smooth}} + \omega_3 F_{\text{vol}} = 0$$


[Tagliasacchi et al. SGP'11]



- Surface evolution method combining surface smoothness, visibility constraints, and medial axis smoothness

$$\dot{\phi} + \omega_1 F_{\text{fit}} + \omega_2 F_{\text{smooth}} + \omega_3 F_{\text{vol}} = 0$$

[Tagliasacchi et al. SGP'11]




Surface Smoothness

$$E_{\text{smooth}} = \int \|\Delta_S^2 S\|^2$$



- Surface evolution method combining surface smoothness, visibility constraints, and medial axis smoothness

$$\dot{\phi} + \omega_1 F_{\text{fit}} + \omega_2 F_{\text{smooth}} + \omega_3 F_{\text{vol}} = 0$$



Surface Smoothness


$$E_{\text{smooth}} = \int \|\Delta_S^2 S\|^2$$



Visibility


$$E_{\text{fit}} = \sum_{i=1}^N \|s_i^t - p_i\|^2$$

[Tagliasacchi et al. SGP'11]





- Surface evolution method combining surface smoothness, visibility constraints, and medial axis smoothness

$$\dot{\phi} + \omega_1 F_{\text{fit}} + \omega_2 F_{\text{smooth}} + \omega_3 F_{\text{vol}} = 0$$



Surface Smoothness


$$E_{\text{smooth}} = \int \|\Delta_S^2 S\|^2$$



Visibility

$$E_{\text{fit}} = \sum_{i=1}^N \|s_i^t - p_i\|^2$$

[Tagliasacchi et al. SGP'11]




Medial Axis Smoothness

$$E_{\text{vol}} = \int \|\Delta_{\mathcal{M}} \mathcal{R}\|^2$$

- Surface evolution over time

[Tagliasacchi et al. SGP'11]




- Shape composed of simple geometric primitives
- Output: surface mesh, set of primitives
- Class shape: CAD models, architectural models
- Main approaches:
  - Surface primitives
  - Volume primitives

- Detection of simple surface primitives [Schnabel et al. CGF'07]
- Planes, spheres, cylinders, torii, etc..



- Detection of simple surface primitives
  - Planes, spheres, cylinders, torii, etc..

[Schnabel et al. CGF'07]





- Detection of simple surface primitives
  - Planes, spheres, cylinders, torii, etc..

[Schnabel et al. CGF'07]





- Detection of simple surface primitives
  - Planes, spheres, cylinders, torii, etc..

[Schnabel et al. CGF'07]






- Detection of simple surface primitives
  - Planes, spheres, cylinders, torii, etc..

[Schnabel et al. CGF'07]









- Detection of simple surface primitives
  - Planes, spheres, cylinders, torii, etc..

[Schnabel et al. CGF'07]



- Detection of simple surface primitives
  - Planes, spheres, cylinders, torii, etc..

[Schnabel et al. CGF'07]



- Extrapolate primitives into the rest of the volume for surface completion

[Schnabel et al. EG'09]

- Extrapolate primitives into the rest of the volume for surface completion

[Schnabel et al. EG'09]

$$\begin{aligned} E(\mathcal{S}) &= E_a(\mathcal{S}) - E_p(\mathcal{S}) + E_c(\mathcal{S}) \\ &= \int_{\mathcal{S}} dA - \int_{\mathcal{S}} \mathbf{H}(\langle n|v \rangle) dA + E_c(\mathcal{S}) \end{aligned}$$

- Extrapolate primitives into the rest of the volume for surface completion

[Schnabel et al. EG'09]

$$\begin{aligned} E(\mathcal{S}) &= E_a(\mathcal{S}) - E_p(\mathcal{S}) + E_c(\mathcal{S}) \\ &= \int_{\mathcal{S}} dA - \int_{\mathcal{S}} \mathbf{H}(\langle n|v \rangle) dA + E_c(\mathcal{S}) \end{aligned}$$

minimal surface area

- Extrapolate primitives into the rest of the volume for surface completion

[Schnabel et al. EG'09]

$$\begin{aligned}
 E(\mathcal{S}) &= E_a(\mathcal{S}) - E_p(\mathcal{S}) + E_c(\mathcal{S}) \\
 &= \int_{\mathcal{S}} dA - \int_{\mathcal{S}} \mathbf{H}(\langle n | v \rangle) dA + E_c(\mathcal{S})
 \end{aligned}$$

minimal surface area

input and primitive normals agree

- Extrapolate primitives into the rest of the volume for surface completion

[Schnabel et al. EG'09]

$$\begin{aligned}
 E(\mathcal{S}) &= E_a(\mathcal{S}) - E_p(\mathcal{S}) + E_c(\mathcal{S}) \\
 &= \int_{\mathcal{S}} dA - \int_{\mathcal{S}} \mathbf{H}(\langle n | v \rangle) dA + E_c(\mathcal{S})
 \end{aligned}$$

minimal surface area

input and primitive normals agree

interior/exterior constraints

# Primitive Completion

- Extrapolate primitives into the rest of the volume for surface completion


[Schnabel et al. EG'09]

$$\begin{aligned} E(\mathcal{S}) &= E_a(\mathcal{S}) - E_p(\mathcal{S}) + E_c(\mathcal{S}) \\ &= \int_{\mathcal{S}} dA - \int_{\mathcal{S}} \mathbf{H}(\langle n | v \rangle) dA + E_c(\mathcal{S}) \end{aligned}$$

minimal surface area

input and primitive normals agree

interior/exterior constraints



# Hybrid Reconstruction


- Use primitives where there exists a good fit, otherwise use surface smoothness, by *structuring* the point set

[Lafarge & Alliez EG'13]

# Hybrid Reconstruction

- Use primitives where there exists a good fit, otherwise use surface smoothness, by structuring the point set



[Lafarge & Alliez EG'13]



# Hybrid Reconstruction


- Use primitives where there exists a good fit, otherwise use surface smoothness, by structuring the point set

[Lafarge & Alliez EG'13]



- Extract 2D CSG models, extrude to volumetric 3D primitives [Xiao et al. ECCV'12]

- Extract 2D CSG models, extrude to volumetric 3D primitives [Xiao et al. ECCV'12]



- Extract 2D CSG models, extrude to volumetric 3D primitives [Xiao et al. ECCV'12]





- Extract 2D CSG models, extrude to volumetric 3D primitives

[Xiao et al. ECCV'12]





- Extract 2D CSG models, extrude to volumetric 3D primitives

[Xiao et al. ECCV'12]



- Extract 2D CSG models, extrude to volumetric 3D primitives


[Xiao et al. ECCV'12]



# Volume Primitives


- Extract 2D CSG models, extrude to volumetric 3D primitives

[Xiao et al. ECCV'12]



- Extract 2D CSG models, extrude to volumetric 3D primitives

[Xiao et al. ECCV'12]



## Volume Primitives

- Extract 2D CSG models, extrude to volumetric 3D primitives

[Xiao et al. ECCV'12]

