

Assignment No-2

Using setter and getter

```
public class food1 {  
    private String name;  
    public void setName (String name) {  
        this.name = name;  
    }  
    public String getName () {  
        return name;  
    }  
}  
package mainpack;
```

```
import com.food1;  
public class main {  
    public static void main (String [] args) {  
        food1 food = new food1 ();  
        food.setName ("Bana Biriyani");
```

```
        System.out.println ("My favorite food is : " + food.getName());  
    }  
}
```

Using only getters

```
Package com;
```

```
public class food2 {
```

```
private String name = "Kacchi Biriyani";
```

```
public String getName() {
```

```
return name;
```

```
}
```

```
}
```

```
Package mainpack;
```

```
import com food2;
```

```
public class main2 {
```

```
public static void main (String[] args) {
```

```
food2 food = new food2();
```

```
system.out.println ("My favorite food is:
```

```
" + food.getName());
```

```
}
```

```
}
```

Using constructor :

Package com ;

public class food3 {

private String name;

public food3 (String name) {

this.name = name;

}

public String getName () {

return name;

}

}

package mainpack ;

import com.food3;

public class main3 {

public static void main (String [] args) {

food3 food = new food3 ("Kacchi Biryani");

System.out.println ("My favorite food is:

" + food.getName());

}

}

using toString

Package com ;

public class food4 {

private String name;

public food4 (String name) {

this.name = name;

}

@Override {

public String toString () {

return "My favourite food : " + name ;

}

}
package main pack ;

import com . food4 ;

public class main4 {

public static void main (String [] args) {

food4 food = new food4 ("Kacchi Biriyani") ;

System.out.println (food) ;

}

}