

## TAMCO COMBINE HARVESTER












sett-aung@itochu.com.mm



aungmyintmyat@itochu.com.mm



aungthura@itochu.com.mm

0 95-9-7725 63220











## **TAMCO COMBINE HARVESTER**



Tamco Trading International Co,Ltd. 95-1-9345 592, 593, 594, 595, 596, 597 Fax.95-1-9345 598
Unit-16, 18, 20, Level-16, HAGL Myanmar Centre Tower-2, No 192, Kaba Aye Pagoda Road, Bahan Township, Yangon, Mynmar

SPECIFICATION

Cutter-bar					
Width	mm	3,000			
Threshing System					
Threshing dimension	mm	Threshing rotor diameter 508			
	mm	Threshing length 1,817			
Rotor speed adjustment		Pulley			
Rice unloading system		Hydraulic motor control			
Track system		Special steel track for tough conditions			
Track link assembly	link	45			
Cleaning System					
Cleaning sieve		Sieve especially designed for South East Asia			
Air blower		Air blower cleaning system and oscillating screen			
Rice storage tank					
Tank capacity	kg	2,500			
Transmission					
Reduction Gear	( Ratio 18 : 1 )	15 HD			
Hydraulic pump (Tandem)	cc/cycle	75			
Hydraulic motor	cc/cycle	89			
Operating speed	km/hr	4			
Maximum speed	km/hr	10			
Engine					
Manufacturer		ISUZU	MITSUBISHI	HINO	
Model		6HK1	6M61	J08C	
Number of cylinders		6 cylinders, 4 cycles water cooled, direct injection			
Displacement (l)		6.494			
Supercharging system		Turbocharger			
Maximum power (hp)		261	225	260	
Max engine speed (rpm)		2,000			
Fuel tank capacity (l)			150		
Dimensions					
Height (when folded)	mm	2,888			
Width	mm	3,480			
Length	mm	6,900			
Weight					
Harvester weight	kg	9,100			
Number of Operator	Person		1		