

TAMCO COMBINE HARVESTER

ALL NEW PRO









MR.SETT AUNG

95-9-5418115

sett-aung@itochu.com.mm

MR.AUNG MYINT MYAT

aungmyintmyat@itochu.com.mm

95-9-255 844 633

MR.AUNG THURA MYINT

aungthura@itochu.com.mm

95-9-7725 63220











TAMCO COMBINE HARVESTER



Tamco Trading International Co,Ltd. 95-1-9345 592, 593, 594, 595, 596, 597 Fax.95-1-9345 598
Unit-16, 18, 20, Level-16, HAGL Myanmar Centre Tower-2, No 192, Kaba Aye Pagoda Road, Bahan Township, Yangon, Mynmar

SPECIFICATION

Cutter-bar		
Width	mm	2,820
Threshing System		
Threshing dimension	mm	Threshing rotor diameter 508
	mm	Threshing length 1,502
Rotor speed adjustment		Pulley
Rice unloading system		Hydraulic motor control
Track system		Special steel track for tough conditions
Track link assembly	link	45
Cleaning System		
Cleaning sieve		Sieve especially designed for South East Asia
Air blower		Air blower cleaning system and oscillating screen
Rice storage tank		
Tank capacity	kg	2,000
Transmission		
Reduction Gear	(Ratio 18 : 1)	15 HD
Hydraulic pump (Tandem)	cc/cycle	75
Hydraulic motor	cc/cycle	89
Operating speed	km/hr	4
Maximum speed	km/hr	10
Engine		
Manufacturer		ISUZU
Model		6BG1
Number of cylinders		6 cylinders, 4 cycles water cooled, direct injection
Displacement (l)		6.494
Supercharging system		Turbocharger
Maximum power (hp)		175
Max engine speed (rpm)		2,100
Fuel tank capacity (l)		150
Dimensions		
Height (when folded)	mm	2,857
Width	mm	3,350
Length	mm	6,700
Weight		
Harvester weight	kg	8,800
Number of Operator	Person	1