1	Brand		EQUIPMAX										
2	Model		FD30T	FD35T	FD30T	FD35T	FD30T	FD35T	FD30T	FD35T	FD30T	FD35T	
3	Power Type		1 0001	1 0001	1 0001	1 0001		esel	1 0001	1 0001	1 0001	1 0001	
4	Rated Load Capacity	Q(kg)	3000	3500	3000	3500	3000	3500	3000	3500	3000	3500	
5	Load Centre	C(mm)	3000	3300	3000	3300	5000		3000	3300	3000	3300	
6	Rated Lift Height	H3(mm)		3000									
7	Free Lift Height	H2(mm)	100										
8	Fork Size (L×W×T)	mm	1070×125*45										
9	Mast Tilt Angle (F/R, α°/β°)	deg	6°/12°										
10	Fork Overhang (Wheel Center to Fork Fac	Ü	X1(mm) 484										
11	Rear Overhang	X2(mm)	595	635	595	635	595	635	595	635	595	635	
12	Ground Clearance (Bottom of Mast)	H7(mm)	393	000	393	033	14		393	033	393	000	
13	Length to Face of Fork (Without Fork)	L1(mm)	2700	2775	2700	2775	2700	2775	2700	2775	2700	2775	
14	Overall Width	B1(mm)	2700	2113	2700	2113	12		2700	2113	2700	2113	
15	Mast Lowered Height	H1(mm)		2070									
16	Mast Extended Height (With Backrest)	H4(mm)	4070										
17	Overhead Guard Height	` '	H5(mm) 2235										
18	Turning Radius (Outside)	Wa(mm)	2425	2500	2425	2500	2425	2500	2425	2500	2425	2500	
19	Min.Aisle width for pallets	Ast(mm)	4180	4255	4180	4255	4180	4255	4180	4255	4180	4255	
	Travel Speed (No Load)	km/h	4100	4255	4100	4200	4100		4100	4255	4100	4255	
20 21	Lifting Speed (Full Load)		410	380	410	380	410	380	410	380	410	380	
22	Lowering Speed (Full Load)	mm/sec mm/sec	410	300	410	300	450					300	
23	Max.Drawbar Pull (Full Load/No Load)	KN	26(21)										
24	Max.Gradeability (Full Load)	%	20(21)										
35	Tyre (Front x 2)	mm	20 28*9-15-12PR										
26	Tyre (Rear x 2)	mm	6.5-10-10PR										
27	Front Tread	B2(mm)	1000										
28	Rear Tread	B3(mm)	980										
29	Wheelbase	Y(mm)		1700									
30	Total Weight	kg	4460							4775			
31	Front Axle Weight Distribution (Full Load)	kg	6714	6997	6714	6997	6714	6997	6714	6997	6714	6997	
32	Rear Axle Weight Distribution (Full Load)	kg	746	777	746	777	746	777	746	777	746	777	
33	Front Axle Weight Distribution (No Load)	kg	1784	1910	1784	1910	1784	1910	1784	1910	1784	1910	
34	Rear Axle Weight Distribution (No Load)	kg	2676	2865	2676	2865	2676	2865	2676	2865	2676	2865	
35	Battery	V/Ah	2070	2000	2070	2000	Dec		2070	2000	2070	2000	
36	Engine Model	V/AII	A498BT1-35		C490BPG -37 (EUIII)		C240NKFC-01 (EUIII)		4TNE98 (EUIII & EPAIII)		Miteubiebi 9	848 (ELIIII)	
37	Engine Manufacturer		XINCHAI		XINCHAI		ISUZU		YANMAR		Mitsubishi S4S (EUIII) Mitsubishi		
	8	lass	36.5/2400		36.8/2650		34.5/3500				35.4/2250		
38	Rated Output / r.p.m.	kw N m	193/1600-1800		156/1800		139/1800		42.1/2300		35.4/2250 177/1700		
39	Rated Torque / r.p.m.	N∙m	193/1000-1000		100/1600		139/1800		187-307/1700		1777	1700	
40	No.of Cylinder		00V10F		00105				00440		0.4*4.00		
41	Bore x Stroke	mm	98X105		90×105		86×102		98×110		94*120		
42	Displacement San acity	CC	3168		26	2670 2369			3318		3331		
43	Fuel Tank Capacity	L		50									
44	Transmission Type				Powershift (Manual)								
45	Transmission Stage (FWD/RVS)				1/1(2/2) 17.5								
46	Operating Pressure (For Attachments)	Мра					17	.5					