

pfnet/**plamo-13b**

like 85

Follow Preferred Networks, Inc. 168

Text Generation Transformers Safetensors English Japanese

plamo custom\_code arxiv:2302.13971 License: apache-2.0

Train Deploy Use this model

Model card Files xet Community 6

Downloads last month

789



Safetensors

Model size 13.1B params Tensor type BF16 Files info

Inference Providers NEW

Text Generation

This model isn't deployed by any Inference Provider.

Ask for provider support

Model tree for pfnet/plamo-13b

Quantizations 3 models

Space using pfnet/plamo-13b 1

Collection including pfnet/plamo-13b

PLaMo Collection

5 items • Updated 28 days ago

PLaMo-13B

Model Description

PLaMo-13B is a LLaMA-based 13B model pre-trained on English and Japanese open datasets, developed by Preferred Networks, Inc. PLaMo-13B is released under Apache v2.0 license.

[PLaMo-13B Release blog \(Japanese\)](#).

## [🔗 Usage](#)

## [🔗 Requirements](#)

- numpy
- sentencepiece
- torch
- transformers

## [🔗 Use a pipeline as a high-level helper](#)

```
import transformers
pipeline = transformers.pipeline("text-generation", model="pfnet/plamo-13b", trust_remote_code=True)
print(pipeline("The future of artificial intelligence technology is ", max_new_tokens=100))
```

## [🔗 Load model directly](#)

```
from transformers import AutoTokenizer, AutoModelForCausalLM
tokenizer = AutoTokenizer.from_pretrained("pfnet/plamo-13b", trust_remote_code=True)
model = AutoModelForCausalLM.from_pretrained("pfnet/plamo-13b", trust_remote_code=True)
text = "これからの人工知能技術は"
input_ids = tokenizer(text, return_tensors="pt").input_ids
generated_tokens = model.generate(
    inputs=input_ids,
    max_new_tokens=32,
    do_sample=True,
    top_k=50,
    top_p=0.95,
    temperature=1.0,
)[0]
```

```
generated_text = tokenizer.decode(generated_tokens)
print(generated_text)
```

## [🔗](#) Model Details

- Model size: 13B
- Trained tokens: 1.5T tokens (English: 1.32T tokens, Japanese: 0.18T tokens)
- Context length: 4096
- Developed by: Preferred Networks, Inc
- Model type: Causal decoder-only
- Language(s): English, Japanese
- License: Apache v2.0

## [🔗](#) Training Dataset

### [🔗](#) English

- C4 - English
- Project Gutenberg
- RedPajama - Arxiv
- RedPajama - CommonCrawl - English
- RedPajama - Github
- RedPajama - StackExchange
- RedPajama - Wikipedia

### [🔗](#) Japanese

- mC4 - Japanese
- Wikipedia - Japanese

## [🔗](#) Tokenizer

PLaMo-13B uses sentencepiece tokenizer which is trained on a subset of the datasets for model pre-training.

## [🔗](#) Bias, Risks, and Limitations

PLaMo-13B is a new technology that carries risks with use. Testing conducted to date has been in English and Japanese, and has not covered, nor could it cover all scenarios. For these reasons, as with all LLMs, PLaMo-13B's potential outputs cannot be predicted in advance, and the model may in some instances produce inaccurate, biased or other objectionable responses to user prompts. Therefore, before deploying any applications of PLaMo-13B, developers should perform safety testing and tuning tailored to their specific applications of the model.

## [🔗](#) How to cite

```
@online{PLaMo2023Introducing,
  author    = {Preferred Networks, Inc},
  title     = {PLaMo-13B},
  year      = {2023},
  url       = {https://huggingface.co/pfnet/plamo-13b},
  urldate   = {2023-09-28}
}
```

## [🔗](#) Citations

```
@article{touvron2023llama,
  title={LLaMA: Open and Efficient Foundation Language Models},
  author={Touvron, Hugo and Lavril, Thibaut and Izacard, Gautier and Martinet, Xav
  journal={arXiv preprint arXiv:2302.13971},
  year={2023}
}
```