# VEGETABLE IMPERVEG POLYURETHANE

IMPERVEG® is a vegetable polyurethane resin (originated from castor oil) and is considered a material has the advantage of being obtained from natural and renewable resource, bi-component 100% solid (solvent free), formulated by cold mixture of a prepolymer (A) and a polyol (B), resulting in polymers with different characteristics and excellent properties, such as:

- ➢ Rheological properties (viscosity, fluidity, thixotropic, behavior change in temperature);
- ➢ Surface tension, wetting (wetting power), and capillary penetration;
- ➢ Maximum and minimum processing time;
- ➢ Hardening and healing;
- ➢ Mostly "Economy."

IMPERVEG® is applied at room temperature, and polymerize by catalyst, forming a monolithic membrane completely waterproof and highly insoluble in water.

**PROPERTIES:**

IMPERVEG® as a waterproofing system meets all the recommendations prescribed in the NBR 9575/2003 - "Waterproofing - Design and Selection", NBR 9574 - "Running waterproofing" and NBR 15487 - "polyurethane waterproofing membrane" system being considered as molded " spot "adheres to the substrate, can be applied to various surfaces such as concrete, mortar, masonry, wood and carbon steel.

Because it is a solid material (solvent free) can be applied in confined environments, because it does not release toxic fumes. Meet the 2914 MS ordinance, which defines waterproofing systems in contact with drinking water, and its use in water treatment systems and drinking water reservation, taking full account of the standards of potability.

IMPERVEG® has excellent resistance to weathering action, resisting water containing corrosive substances such as salts, acids and alkalis, acting in accordance with ASTM C-267 "Chemical Resistance of Mortars and grouts Monolithic Surfacing" whose objective is to evaluate the performance of concrete and mortars when they are subjected to the action of aggressive chemical agents.

**FEATURES:**

• Density: 1.05 g / cm $^3$;
• Consistency: fluid;
• Release of toxic elements in the atmosphere: Exempt;
• Heat resistance: it shows only mass loss after 210° C;
• Pot life after mixing: 10 to 20 minutes;
• Dry to touch: 50 to 180 minutes, depending on ambient temperature;
• Tensile strength: 2.5 Mpa;
• Permissible Deformation: 15% to 25%;
• Elongation at rupture: 8% to 50%;
• Module deformation: 1.8 MPa to 2.2 MPa;
• Hardness (Shore D): 30 to 70.