

STM32CubeMX Project_STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx Project_STM32F103C8Tx GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Categories A-Z

System Core

- DMA
- GPIO
- IWDG
- NVIC
- ✓ RCC
- ✓ SYS
- WWDG

Analog

Timers

- RTC
- TM1
- ✓ TM2
- ✓ TM3
- TM4

Connectivity

- CAN
- ✓ I2C1
- ✓ I2C2
- SP1

Mode

IC1 Mode and Configuration

IC1

Configuration

Reset Configuration

Parameter Settings

Configure the below parameters:

Search (Ctrl+F)

Master Features


- IC1 Speed Mode Standard Mode
- IC1 Clock Speed (Hz) 100000

Slave Features

- ✓ Clock No Stretch Mode Disabled
- Primary Address Length selection 7-bit
- Dual Address Acknowledged Disabled

Pinout view System view

STM32F103C8Tx LQFP48



STM32CubeMX Untitled - STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx Untitled - Pinout & Configuration GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Categories A-Z

System Core

- DMA
- GPIO
- IWDG
- NVIC
- ✓ RCC
- ✓ SYS
- WWDG

Analog

Timers

- RTC
- TM1
- ✓ TM2
- ✓ TM3
- TM4

Connectivity

- CAN
- ✓ I2C1
- ✓ I2C2
- SP1

Mode

TM2 Mode and Configuration

Slave Mode Disable

Trigger Source Disable

Clock Source Disable

Channel1 PWM Generation CH1

Channel2 Disable

Channel3 Disable

Channel4 Disable

Combined Channels Disable

Use ETR as Clearing Source

XOR activation

Configuration

Reset Configuration

Parameter Settings

NVIC Interrupt Table

Enabled	Preemption Priority	Sub Priority
☐	0	0

TIM2 global interrupt

Pinout view System view

STM32F103C8Tx LQFP48

