The Beauty of Sharing Knowledge

Max Mustermann

‘Ilm (Urdu: علم) is the Urdu term for knowledge. In its general usage, ‘ilm may refer to *knowledge* of any specific thing or any form of *learning*. Additionally, it is also used to refer to various categories of sciences, especially when used in its plural form (‘ulum).

March 19, 2024

Thank you for using this template ❤️

Don’t forget to give it a ⭐ on github.com/talal/ilm° if you like it 😄

Contents

1 Layout **4**
1.1 Cover . . . 4
1.1.1 Multiple authors . . . 4
1.1.2 Date format . . . 5
1.1.3 Customizing the cover page . . . 5
1.2 Preface . . . 5
1.3 Table of Contents . . . 5
1.4 Body . . . 6
1.5 Appendices . . . 6
1.6 Indices . . . 6
1.7 Bibliography . . . 6
1.8 Footer . . . 7
1.8.1 Customizing page numbering . . . 7

2 Text **8**
2.1 Language . . . 8
2.2 External links . . . 8
2.3 Blockquotes . . . 9
2.4 Small- and all caps . . . 9
2.5 Tables . . . 10

3 Code **11**
3.1 Font and size . . . 11

Appendix A: Happy Accident **12**

List of Figures **13**

List of Tables **13**

List of Listings **13**

Bibliography **14**

1 Layout

The template uses `A4` as its page size, you can specify a different paper size° using:

```
#show: ilm.with(
  paper-size: "us-letter",
)
```

By default the template is set up to display its content in the following order:

1. Cover page
2. Preface page
3. Table of contents
4. Body (main content)
5. Appendix
6. List of figures (images), tables, and listings (code blocks)
7. Bibliography

1.1 Cover

By default, 'Ilm generates a cover/title page with a title, author(s), date, and an abstract:

```
#show: ilm.with(
  title: [Your Title],
  authors: "Your Name",
  abstract: [Your abstract goes here],
)
```

Only the `title` and `authors` fields are required. `date` and `abstract` are optional.

Date will default to today's date and the font size for the title will be automatically adjusted based on the title's length.

1.1.1 Multiple authors

You can specify multiple authors by providing an array. Authors will be displayed on separate lines on the cover page, with font size automatically adjusted based on the number of authors:

```
#show: ilm.with(
  title: [Your Title],
  authors: ("John Doe", "Jane Smith", "Max Mustermann"),
)
```

The `authors` parameter accepts either a string (single author) or an array of strings (multiple authors).

1.1.2 Date format

By default, the date is shown in the format: `Month Day, Year`. You can change the date format by specifying a different format string:

```
#show: ilm.with(
  date-format: "[month repr:long] [day padding:zero], [year repr:full]",
)
```

See Typst's official documentation° for more info on how date format strings are defined.

1.1.3 Customizing the cover page

The cover page is inserted by using the `cover-page()` function.

If you want to remove the cover page entirely then just remove the `cover-page()` line.

If you want to design a custom cover page then simply replace this line with your own page.

1.2 Preface

You can insert any content between the cover and the table of contents page.

As a reference for you, I have inserted a simple preface page (see below `cover-page()` line):

```
#page[
  #align(center + horizon)[
    Thank you for using this template #emoji.heart \
    Don't forget to give it a #emoji.star on #link("https://github.com/talal/ilm")
[github.com/talal/ilm] if you like it #emoji.face.smile
  ]
]
```

🔥 Tip: you can put your content in a separate file (`preface.typ`) and then insert it like so:

```
#page[#include "preface.typ"]
```

1.3 Table of Contents

By default, 'Ilm displays a table of contents before the body (your main content) using the `outline()` function.

You can disable it by simply removing the `outline()` line.

You can customize the behavior of the outline via its different parameters. For example, you can use a different title:

```
#outline(title: "Custom Title")
```

See Typst's official documentation° for more information.

1.4 Body

By default, the template will insert a pagebreak° before each chapter, i.e. first-level heading.

You can disable this behavior using:

```
#show: ilm.with(
  chapter-pagebreak: false,
)
```

1.5 Appendices

To add appendices, wrap your appendix chapters in `#appendix[...]`:

```
#appendix[
  = First Appendix
  = Second Appendix
]
```

This resets the heading counter, configures headings with alphabetical numbering (`A.1`), and sets the heading supplement to `Appendix`.

🔥 Tip: if your appendix is quite long, you can put it in a separate file (`appendix.typ`) and include it:

```
#appendix[
  #include "appendix.typ"
]
```

1.6 Indices

You can display a list of figures (images), tables, and listings (code blocks) using:

```
#list-of-figures()
#list-of-tables()
#list-of-listings()
```

Each function accepts the same arguments as Typst's `outline()`. For example, you can specify a custom title:

```
#list-of-tables(title: "Custom Title")
```

See Typst's official documentation° for more information.

1.7 Bibliography

If your document contains references and you want to display a bibliography, simply call Typst's `#bibliography()` function at the desired location:

```
#bibliography("refs.bib")
```

See Typst's official documentation° for more information.

1.8 Footer

By default, 'Ilm displays page numbers in the footer with alternating alignment (left on even pages, right on odd pages). If a page does not begin with a chapter, the chapter's name is shown alongside the page number.

Look at the page numbering for the current page. It should show *Layout* (in small caps) next to the page number because the current *Footer* section is part of the *Layout* chapter.

When we say chapter, we mean the first-level or top-level heading which is defined using a single equals sign (`=`).

1.8.1 Customizing page numbering

You can customize the page numbering style in footer or disable it entirely:

Disable page numbering:

```
#show: ilm.with(
  footer: none,
)
```

Change style:

```
// Centered page number only
#show: ilm.with(
  footer: "page-number-center",
)
```

Available style options:

```
// Alternating sides with chapter name (default)
footer: "page-number-alternate-with-chapter"

// Left-aligned with chapter name
footer: "page-number-left-with-chapter"

// Right-aligned with chapter name
footer: "page-number-right-with-chapter"

// Centered page number only (no chapter name)
footer: "page-number-center"

// Left-aligned page number only (no chapter name)
footer: "page-number-left"

// Right-aligned page number only (no chapter name)
footer: "page-number-right"
```

2 Text

2.1 Language

Typst defaults to English for the language of the text. If you are writing in a different language then you need to define your language before the 'Ilm template is loaded, i.e. before the `#show: ilm.with()` like so:

```
#set text(lang: "de")
#show: ilm.with(
  // 'Ilm's options defined here.
)
```

By defining the language before the template is loaded, 'Ilm will set the title for bibliography and table of contents as per your language settings as long as you haven't customized it already.

2.2 External links

'Ilm adds a small maroon circle to external (outgoing) links like so°.

This acts as a hint for the reader so that they know that a specific text is a hyperlink. This is far better than underlining a hyperlink or making it a different color. Don't you agree?

If you want to disable this behavior then you can do so by setting the concerning option to `false`:

```
#show: ilm.with(
  external-link-circle: false,
)
```

2.3 Blockquotes

'Ilm also exports a `blockquote` function which can be used to create blockquotes. The function has one argument: `body` of the type content and can be used like so:

```
#blockquote[
  _A wizard is never late, Frodo Baggins. Nor is he early. He arrives precisely
when he means to._

  --- Gandalf
]
```

The above code will render the following:

> *A wizard is never late, Frodo Baggins. Nor is he early. He arrives precisely when he means to.*
>
> — Gandalf

2.4 Small- and all caps

'Ilm also exports functions for styling text in small caps and uppercase, namely: `smallcaps` and `upper` respectively.

These functions will overwrite the standard `smallcaps`° and `upper`° functions that Typst itself provides. This behavior is intentional as the functions that 'Ilm exports fit in better with the rest of the template's styling.

Here is how Typst's own SMALLCAPS and UPPER look compared to the 'Ilm ones:

SMALLCAPS and UPPER

They both look similar, the only difference being that 'Ilm uses more spacing between individual characters.

If you prefer Typst's default spacing then you can use Typst's standard library directly via the `std.` prefix:

```
#std.smallcaps[your content here]
#std.upper[your content here]
```

2.5 Tables

In order to increase the focus on table content, we minimize the table's borders by using thin gray lines instead of thick black ones. Additionally, we use small caps for the header row (regardless of whether you use `table.header()` or regular rows). Take a look at the table below:

Table 2.1: 'Ilm style

Quantity	Symbol	Unit
length	l	m
mass	m	kg
time	t	s
electric current	I	A
temperature	T	K
amount of substance	n	mol
luminous intensity	I_v	cd

For comparison, this is how the same table would look with Typst's default styling:

Table 2.2: Typst's default styling

Quantity	Symbol	Unit
length	l	m
mass	m	kg
time	t	s
electric current	I	A
temperature	T	K
amount of substance	n	mol
luminous intensity	I_v	cd

If you want to disable small caps for the header row, you can override it with a show rule:

```
#show table.cell.where(y: 0): it => table.cell(inset: 7pt, it.body)
```

If you want to remove all styling and restore Typst's default styling, use:

```
#set table(inset: 0% + 5pt, stroke: 1pt + black)
#show table.cell.where(y: 0): it => table.cell(inset: 0% + 5pt, it.body)
```

3 Code

3.1 Font and size

'Ilm uses the `IBM Plex Mono` [1] font for raw text instead of the default `DejaVu Sans Mono`. If IBM Plex Mono is not available then the template will fall back to DejaVu Sans Mono.

For comparison, here is how `inline code` in DejaVu Sans Mono looks like:

Listing 3.1: Code snippet typeset in DejaVu Sans Mono font

```
fn main() {
    let user = ("Adrian", 38);
    println!("User {} is {} years old", user.0, user.1);

    // tuples within tuples
    let employee = (("Adrian", 38), "die Mobiliar");
    println!("User {} is {} years old and works for {}", employee.0.1,
employee.0.1, employee.1);
}
```

and here is how the same `inline code` looks in IBM Plex Mono:

Listing 3.2: Code snippet typeset in IBM Plex Mono font

```
fn main() {
    let user = ("Adrian", 38);
    println!("User {} is {} years old", user.0, user.1);

    // tuples within tuples
    let employee = (("Adrian", 38), "die Mobiliar");
    println!("User {} is {} years old and works for {}", employee.0.1,
employee.0.1, employee.1);
}
```

In the case that both code snippets look identical then it means that IBM Plex Mono is not installed on your system.

Appendix A: Happy Accident

> *Anything we don't like, we'll turn it into a happy little tree or something, because as you know, we don't make mistakes, we just have happy accidents.*
>
> — Bob Ross, 1990



Figure A.1: A happy little tree

List of Figures

Figure A.1 A happy little tree 12

List of Tables

Table 2.1 ‘Ilm style 10
Table 2.2 Typst’s default styling 10

List of Listings

Listing 3.1 Code snippet typeset in DejaVu Sans Mono font 11
Listing 3.2 Code snippet typeset in IBM Plex Mono font 11

Bibliography

[1] “IBM Plex.” Accessed: Nov. 07, 2026. [Online]. Available: https://en.wikipedia.org/w/index.php?title=IBM_Plex&oldid=1369751897°