EXERCICE 04 · CODE COMPLET

# Annuaire d'équipe

Tous les fichiers utilisés, en entier, dans l'ordre de lecture.

1. **correction** (4 fichiers)

## 1 correction

**Styles fournis (copiés tels quels, pas tapés en live)** : src/index.css (104 lignes)

**Fichiers générés par Vite, non modifiés (non affichés)** : src/main.jsx, index.html, vite.config.js, .gitignore, eslint.config.js, public/vite.svg, package.json

FICHIER **correction/src/App.jsx** — 7 lignes

```jsx
import Home from "./Home.jsx";

function App() {
  return <Home />;
}

export default App;
```

FICHIER **correction/src/components/TeamList.jsx** — 20 lignes

```jsx
import MemberCard from "./MemberCard";

function TeamList({ title, members }) {
  return (
    <section>
      <h1>{title}</h1>
      {members.length === 0 ? (
        <p>No members</p>
      ) : (
        <div className="team-grid">
          {members.map((member) => (
            <MemberCard key={member.id} {...member} />
          ))}
        </div>
      )}
    </section>
  );
}

export default TeamList;
```

FICHIER **correction/src/components/MemberCard.jsx** — 12 lignes

```jsx
function MemberCard({ fullName, role, email, remote, showEmail = true }) {
  return (
    <article className="member-card">
      <h2>{fullName}</h2>
      <p className="role">{role}</p>
      {showEmail && <p>Email : {email ? email : "N/A"}</p>}
      {remote && <span className="badge">Remote</span>}
    </article>
  );
}

export default MemberCard;
```

FICHIER **correction/src/Home.jsx** 14 lignes

```jsx
import TeamList from "./components/TeamList";

const members = [
  { id: 1, fullName: "Alice Martin", role: "Lead Developer", email: "alice@company.com", remote: true },
  { id: 2, fullName: "Karim Benali", role: "Product Owner", email: "karim@company.com", remote: false },
  { id: 3, fullName: "Sara Lopez", role: "UX Designer", remote: true },
  { id: 4, fullName: "Tom Durand", role: "QA Engineer", remote: false },
];

function Home() {
  return <TeamList title="Team Directory" members={members} />;
}

export default Home;
```