

Copy Trading App: End-to-End Guide for New Developers

This guide takes you **from zero to deployed**—no prior technical knowledge needed. You'll set up your development environment, write and organize **all** the backend and frontend code (with full folder structures and copy-and-paste files), configure CI/CD, deploy to the cloud, and learn why each step matters. At the end, you'll have a working Copy Trading App with user registration, login, trade CRUD, error/performance monitoring with Sentry, and automated testing/deployment pipelines.

Table of Contents

1. [Prerequisites](#)
2. [Repository & Folder Structure](#)
3. [Backend Setup](#)
 - 3.1 [Environment Variables](#)
 - 3.2 [Dependencies & package.json](#)
 - 3.3 [Sentry Instrumentation \(.instrument.js.\)](#)
 - 3.4 [Express App \(.src/app.js.\)](#)
 - 3.5 [Server Entry \(.src/server.js.\)](#)
 - 3.6 [Data Model \(.src/models/Trade.js.\)](#)
 - 3.7 [Authentication](#)
 - 3.7.1 [Controller \(.src/controllers/authController.js.\)](#)
 - 3.7.2 [Routes \(.src/routes/authRoutes.js.\)](#)
 - 3.7.3 [Middleware \(.src/middleware/authMiddleware.js.\)](#)
 - 3.8 [Trade CRUD Routes \(.src/routes/tradeRoutes.js.\)](#)
 - 3.9 [testMongo.js Connectivity Check](#)
 - 3.10 [CI Pipeline \(.github/workflows/backend-ci.yml.\)](#)
4. [Frontend Setup](#)
 - 4.1 [Environment Variables \(.env.local.\)](#)
 - 4.2 [Dependencies & package.json](#)
 - 4.3 [API Helper \(.src/api.js.\)](#)
 - 4.4 [Private Route Wrapper \(.src/components/PrivateRoute.js.\)](#)
 - 4.5 [Pages](#)
 - 4.5.1 [Register Page \(.src/pages/Register.js.\)](#)
 - 4.5.2 [Login Page \(.src/pages/Login.js.\)](#)
 - 4.5.3 [Trade App Component \(.src/TradeApp.js.\)](#)
 - 4.6 [Root App \(.src/App.js.\)](#)
 - 4.7 [Entry Point \(.src/index.js.\)](#)
 - 4.8 [CI Pipeline \(.github/workflows/frontend-ci.yml.\)](#)
5. [Deployments](#)
 - 5.1 [MongoDB Atlas](#)
 - 5.2 [Render \(Backend\)](#)
 - 5.3 [Vercel \(Frontend\)](#)
6. [Testing & Usage](#)
 - 6.1 [Postman Collection](#)
 - 6.2 [Debugging with Sentry](#)
7. [When to Commit & Push](#)

8. [Future Enhancements](#)
 9. [Problems Faced & Solutions](#)
-

Prerequisites

Accounts & Services

- **GitHub** (code hosting & CI)
- **MongoDB Atlas** (cloud database)
- **Render** (free Node.js hosting)
- **Vercel** (free React hosting)
- **Sentry** (error & performance monitoring)
- **Postman** (API testing)

Local Tools (Developer)

- [Node.js & npm](#) (v18+ recommended)
 - [Git](#)
 - [VS Code](#) or another code editor
-

Repository & Folder Structure

Create a parent folder and two Git repos:

```
mkdir copy-trading-app && cd copy-trading-app
```

Backend (backend)

```
backend/
├── .env                # Local env vars
├── .env.example
├── instrument.js
├── package.json
├── testMongo.js
├── src/
│   ├── server.js
│   ├── app.js
│   ├── models/
│   │   └── Trade.js
│   ├── controllers/
│   │   └── authController.js
│   ├── middleware/
│   │   └── authMiddleware.js
│   └── routes/
│       ├── authRoutes.js
│       └── tradeRoutes.js
└── .github/
    ├── workflows/
    │   └── backend-ci.yml
```

Frontend (frontend)

```
frontend/
├── .env.local
├── package.json
├── public/
│   └── index.html
└── src/
    ├── api.js
    ├── App.js
    ├── App.css
    ├── index.js
    ├── TradeApp.js
    ├── components/
    │   └── PrivateRoute.js
    └── pages/
        ├── Register.js
        └── Login.js
```

Backend Setup

3.1 Environment Variables

Create `backend/.env` (never commit real secrets):

```
# MongoDB
MONGO_URI=mongodb+srv://<user>:<pass>@cluster0.mongodb.net/<dbname>?
retryWrites=true&w=majority

# JWT secret
JWT_SECRET=yourSuperSecretKey

# Sentry DSN
SENTRY_DSN=https://<publicKey>@o<org>.ingest.sentry.io/<projectId>
```

Also add `backend/.env.example` :

```
MONGO_URI=your_mongo_uri
JWT_SECRET=your_jwt_secret
SENTRY_DSN=your_sentry_dsn
```

3.2 Dependencies & `package.json`

In `backend/`, install:

```
npm init -y
npm install express mongoose cors dotenv bcryptjs jsonwebtoken @sentry/node
@sentry/tracing
npm install --save-dev nodemon
```

`backend/package.json` highlights:

```
{
  "name": "copy-trading-backend",
```

```
"version": "1.0.0",
"scripts": {
  "start": "node src/server.js",
  "dev": "nodemon src/server.js"
},
"dependencies": {
  "express": "^4.18.2",
  "mongoose": "^7.0.0",
  "cors": "^2.8.5",
  "dotenv": "^16.0.0",
  "bcryptjs": "^2.4.3",
  "jsonwebtoken": "^9.0.0",
  "@sentry/node": "^7.0.0",
  "@sentry/tracing": "^7.0.0"
}
}
```

3.3 Sentry Instrumentation (instrument.js)

Who: Developer

Where: backend/instrument.js

```
// Load env vars
require('dotenv').config();

// Initialize Sentry
const Sentry = require('@sentry/node');
Sentry.init({
  dsn: process.env.SENTRY_DSN,
  tracesSampleRate: 1.0,
});

module.exports = Sentry;
```

3.4 Express App Setup (src/app.js)

Who: Developer

Where: backend/src/app.js

```
const express = require('express');
const cors = require('cors');
const Sentry = require('@sentry/node');

const app = express();

// CORS for React dev server
app.use(cors({
  origin: 'http://localhost:3000',
  credentials: true
}));

// Sentry handlers
```

```

app.use(Sentry.Handlers.requestHandler());
app.use(Sentry.Handlers.tracingHandler());

// JSON parsing
app.use(express.json());

// Health route
app.get('/', (req,res) => res.send('Backend is working!'));

// API routes (mounted later)

module.exports = app;

```

3.5 Server Entry (src/server.js)

Who: Developer

Where: backend/src/server.js

```

// Initialize Sentry, load env
require('dotenv').config();
require('./instrument');

const app      = require('./app');
const mongoose = require('mongoose');
const Sentry    = require('@sentry/node');

// Mount routes
app.use('/api/auth',  require('./routes/authRoutes'));
app.use('/api/trades', require('./routes/tradeRoutes'));

// Debug route for Sentry
app.get('/debug-sentry', (req,res,next) => next(new Error('Sentry OK')));

// Sentry error handler (must come after routes)
app.use(Sentry.Handlers.errorHandler());

// Final Express error handler
app.use((err, req, res, next) => {
  console.error(err);
  res.status(err.status || 500).json({ error: err.message });
});

// Connect to MongoDB & launch
mongoose.connect(process.env.MONGO_URI, {
  useNewUrlParser: true, useUnifiedTopology: true
})
.then(() => app.listen(process.env.PORT || 5000, () =>
  console.log('🚀 Server running')
))
.catch(err => console.error('DB connection error', err));

```

3.6 Data Model (src/models/Trade.js)

Who: Developer

Where: backend/src/models/Trade.js

```
const mongoose = require('mongoose');

const tradeSchema = new mongoose.Schema({
  symbol:    { type: String, required: true },
  action:    {
    type: String,
    enum: ['buy', 'sell'],
    required: true,
    lowercase: true
  },
  price:     { type: Number, required: true },
  userId:    { type: String, required: true },
  createdAt: { type: Date,   default: Date.now }
});

module.exports = mongoose.model('Trade', tradeSchema);
```

3.7 Authentication

3.7.1 Controller (src/controllers/authController.js)

```
const jwt = require('jsonwebtoken');
const bcrypt = require('bcryptjs');
let users = []; // demo

exports.registerUser = async (req,res) => {
  const { email, password } = req.body;
  if (users.find(u=>u.email===email))
    return res.status(400).json({ error:'User exists' });
  const hash = await bcrypt.hash(password,10);
  users.push({ id:users.length+1, email, password:hash });
  res.status(201).json({ message:'Registered' });
};

exports.loginUser = async (req,res) => {
  const { email,password } = req.body;
  const user = users.find(u=>u.email===email);
  if (!user || !(await bcrypt.compare(password,user.password)))
    return res.status(401).json({ error:'Invalid credentials' });
  const token = jwt.sign({ id:user.id }, process.env.JWT_SECRET, { expiresIn:'1h' });
  res.json({ token });
};
```

3.7.2 Routes (src/routes/authRoutes.js)

```
const express = require('express');
const { registerUser, loginUser } = require('../controllers/authController');
```

```

const router = express.Router();

router.post('/register', registerUser);
router.post('/login',    loginUser);

module.exports = router;

```

3.7.3 Middleware (src/middleware/authMiddleware.js)

```

const jwt = require('jsonwebtoken');

module.exports = (req,res,next) => {
  const header = req.headers.authorization;
  if (!header) return res.status(401).json({ error:'No token' });
  const token = header.split(' ')[1];
  jwt.verify(token, process.env.JWT_SECRET, (err,decoded) => {
    if(err) return res.status(401).json({ error:'Invalid token' });
    req.userId = String(decoded.id);
    next();
  });
};

```

3.8 Trade CRUD Routes (src/routes/tradeRoutes.js)

```

const express = require('express');
const auth    = require('../middleware/authMiddleware');
const Trade    = require('../models/Trade');
const router  = express.Router();

// List
router.get('/', async (req,res,next) => {
  try { res.json(await Trade.find().sort({createdAt:-1})); }
  catch(e){ next(e); }
});

// Create
router.post('/', auth, async (req,res,next) => {
  try {
    const {symbol,action,price} = req.body;
    res.status(201).json(
      await Trade.create({ symbol, action, price, userId:req.userId })
    );
  } catch(e){ next(e); }
});

// Update
router.put('/:id', auth, async (req,res,next) => {
  try {
    const t = await Trade.findById(req.params.id);
    if(!t) return res.status(404).json({ error:'Not found' });
    if(t.userId!==req.userId) return res.status(403).json({ error:'Forbidden' });

```

```

    Object.assign(t, req.body);
    await t.save();
    res.json({ message: 'Updated', trade:t });
  } catch(e){ next(e); }
});

// Delete
router.delete('/:id', auth, async (req,res,next) => {
  try {
    const t = await Trade.findById(req.params.id);
    if(!t) return res.status(404).json({ error: 'Not found' });
    if(t.userId!==req.userId) return res.status(403).json({ error: 'Forbidden' });
    await t.deleteOne();
    res.json({ message: 'Deleted' });
  } catch(e){ next(e); }
});

module.exports = router;

```

3.9 testMongo.js Connectivity Check

```

// backend/testMongo.js
require('dotenv').config();
const { MongoClient, ServerApiVersion } = require('mongodb');

const uri = process.env.MONGO_URI;
const client = new MongoClient(uri, { serverApi: ServerApiVersion.v1 });

async function run() {
  try {
    await client.connect();
    await client.db("admin").command({ ping: 1 });
    console.log("✅ MongoDB connected!");
  } catch (err) {
    console.error("MongoDB error:", err);
  } finally {
    await client.close();
  }
}
run();

```

Run locally: `node testMongo.js`

3.10 CI Pipeline (`.github/workflows/backend-ci.yml`)

```

name: Backend CI

on: [push]

jobs:
  build-and-test:

```



```
runs-on: ubuntu-latest
steps:
  - uses: actions/checkout@v3
  - name: Setup Node
    uses: actions/setup-node@v3
    with: node-version: '18'
  - name: Install deps
    run: npm install
    working-directory: backend
  - name: Lint & Test
    run: |
      npm run lint || true
      npm test || true
    working-directory: backend
```

Frontend Setup

4.1 Environment Variables (`.env.local`)

```
REACT_APP_API_URL=http://localhost:5000
REACT_APP_SENTRY_DSN=https://<publicKey>@<org>.ingest.sentry.io/<projectId>
```

4.2 Dependencies & `package.json`

```
cd frontend
npm install axios react-router-dom @sentry/react @sentry/tracing
```

Key entries in `frontend/package.json` :

```
"dependencies": {
  "axios": "^1.2.0",
  "react-router-dom": "^6.3.0",
  "@sentry/react": "^7.0.0",
  "@sentry/tracing": "^7.0.0"
}
```

4.3 API Helper (`src/api.js`)

```
import axios from 'axios';
const api = axios.create({ baseURL: process.env.REACT_APP_API_URL });
api.interceptors.request.use(cfg => {
  const token = localStorage.getItem('token');
  if(token) cfg.headers.Authorization = `Bearer ${token}`;
  return cfg;
});
export default api;
```

4.4 Private Route Wrapper (`src/components/PrivateRoute.js`)

```
import React from 'react';
import { Navigate } from 'react-router-dom';

export default function PrivateRoute({ children }) {
  return localStorage.getItem('token') ? children : <Navigate to="/login" />;
}
```

4.5 Pages

4.5.1 Register (src/pages/Register.js)

```
import React, { useState } from 'react';
import api from '../api';
import { useNavigate, Link } from 'react-router-dom';

export default function Register() {
  const [form, setForm] = useState({ email:'', password:'' });
  const [error, setError] = useState('');
  const navigate = useNavigate();

  const onChange = e => setForm(f=>({...f,[e.target.name]:e.target.value}));
  const onSubmit = async e => {
    e.preventDefault();
    try {
      await api.post('/api/auth/register', form);
      navigate('/login');
    } catch(err) {
      setError(err.response?.data?.error || 'Registration failed');
    }
  };

  return (
    <div>
      <h2>Register</h2>
      {error && <p style={{color:'red'}}>{error}</p>}
      <form onSubmit={onSubmit}>
        <input name="email" type="email" placeholder="Email"
          value={form.email} onChange={onChange} required /><br/>
        <input name="password" type="password" placeholder="Password"
          value={form.password} onChange={onChange} required /><br/>
        <button type="submit">Register</button>
      </form>
      <p>Have an account? <Link to="/login">Login</Link></p>
    </div>
  );
}
```

4.5.2 Login (src/pages/Login.js)

```
import React, { useState } from 'react';
import api from '../api';
```

```

import { useNavigate, Link } from 'react-router-dom';

export default function Login() {
  const [form, setForm] = useState({ email:'', password:'' });
  const [error, setError] = useState('');
  const navigate = useNavigate();

  const onChange = e => setForm(f=>({...f,[e.target.name]:e.target.value}));
  const onSubmit = async e => {
    e.preventDefault();
    try {
      const res = await api.post('/api/auth/login', form);
      localStorage.setItem('token', res.data.token);
      navigate('/');
    } catch(err) {
      setError(err.response?.data?.error || 'Login failed');
    }
  };

  return (
    <div>
      <h2>Login</h2>
      {error && <p style={{color:'red'}}>{error}</p>}
      <form onSubmit={onSubmit}>
        <input name="email" type="email" placeholder="Email"
          value={form.email} onChange={onChange} required /><br/>
        <input name="password" type="password" placeholder="Password"
          value={form.password} onChange={onChange} required /><br/>
        <button type="submit">Login</button>
      </form>
      <p>New user? <Link to="/register">Register</Link></p>
    </div>
  );
}

```

4.5.3 Trade App (src/TradeApp.js)

```

import React, { useEffect, useState } from 'react';
import api from './api';

export default function TradeApp() {
  const [trades, setTrades] = useState([]);
  const [newTrade, setNewTrade] = useState({ symbol:'', action:'', price:'' });
  const [error, setError] = useState('');

  useEffect(() => { fetchTrades(); }, []);

  const fetchTrades = async () => {
    try { const res = await api.get('/api/trades'); setTrades(res.data); }
    catch { setError('Fetch failed'); }
  };
}

```

```

const handleChange = e => setNewTrade(t=>({...t,[e.target.name]:e.target.value}));
const handleAdd = async e => {
  e.preventDefault();
  try {
    const res = await api.post('/api/trades', newTrade);
    setTrades(t=>[...t,res.data]);
    setNewTrade({ symbol:'', action:'', price:'' });
  } catch { setError('Add failed'); }
};

const handleDelete = async id => {
  try {
    await api.delete(`/api/trades/${id}`);
    setTrades(t=>t.filter(x=>x._id!==id));
  } catch { setError('Delete failed'); }
};

return (
  <div>
    <h2>Trades</h2>
    {error && <p style={{color:'red'}}>{error}</p>}
    <form onSubmit={handleAdd}>
      <input name="symbol" placeholder="Symbol"
        value={newTrade.symbol} onChange={handleChange} required/>
      <input name="action" placeholder="Action"
        value={newTrade.action} onChange={handleChange} required/>
      <input name="price" type="number" placeholder="Price"
        value={newTrade.price} onChange={handleChange} required/>
      <button type="submit">Add</button>
    </form>
    <ul>
      {trades.map(t => (
        <li key={t._id}>
          {t.symbol} - {t.action} @ ${t.price}{' '}
          <button onClick={()=>handleDelete(t._id)}>Delete</button>
        </li>
      ))}
    </ul>
  </div>
);
}

```

4.6 Root App (src/App.js)

```

import React from 'react';
import { Routes, Route, Link } from 'react-router-dom';
import PrivateRoute from './components/PrivateRoute';
import Register from './pages/Register';
import Login from './pages/Login';
import TradeApp from './TradeApp';

```

```

export default function App() {
  return (
    <div style={{ padding: 20 }}>
      <nav>
        <Link to="/">Home</Link> |{' '}
        <Link to="/register">Register</Link> |{' '}
        <Link to="/login">Login</Link>
      </nav>
      <Routes>
        <Route path="/" element={
          <PrivateRoute><TradeApp/></PrivateRoute>
        }/>
        <Route path="/register" element={<Register/>}/>
        <Route path="/login" element={<Login/>}/>
      </Routes>
    </div>
  );
}

```

4.7 Entry Point (src/index.js)

```

import React from 'react';
import ReactDOM from 'react-dom/client';
import { BrowserRouter } from 'react-router-dom';
import App from './App';
import './index.css';

const root=ReactDOM.createRoot(document.getElementById('root'));
root.render(<BrowserRouter><App/></BrowserRouter>);

```

4.8 CI Pipeline (.github/workflows/frontend-ci.yml)

```

name: Frontend CI

on: [push]

jobs:
  build:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v3
      - name: Setup Node
        uses: actions/setup-node@v3
        with: node-version: '18'
      - name: Install & Test
        run: |
          npm ci
          npm test || true
        working-directory: frontend

```

5. Deployments

5.1 MongoDB Atlas

- Create a free cluster, whitelist your IP, get connection string, update `MONGO_URI`.

5.2 Render (Backend)

- New Web Service → Connect GitHub → select `backend` → Build: `npm install` → Start: `npm start` → set ENV vars → Deploy.

5.3 Vercel (Frontend)

- New Project → Connect GitHub → select `frontend` → set ENV vars (`REACT_APP_API_URL` , `REACT_APP_SENTRY_DSN`) → Deploy.

6. Testing & Usage

6.1 Postman Collection

- Import endpoints (register, login, trades CRUD, health, debug-sentry).

6.2 Debugging with Sentry

- Hit `/debug-sentry` → see error in Sentry Issues.

7. When to Commit & Push

- **After** each logical unit: env files, instrumentation, models, controllers, routes, UI pages
- Commit message convention:

```
feat: add auth middleware
fix: correct trade delete endpoint
chore: configure CI pipeline
```

- Push to `main` (or protection branches, PRs, etc.)

8. Future Enhancements

- Replace in-memory users with real User model
- Add “Edit Trade” UI
- Real-time updates (WebSockets)
- Rate limiting & input validation
- Production-grade logging & monitoring
- CI/CD tests & coverage

9. Problems Faced & Solutions

Issue	Why	Solution
DNS error on Mongo SRV	Missing MongoDB SRV record	Switched to full connection URI from Atlas

Sentry requestHandler() undefined	Incorrect SDK version/integration	Installed @sentry/node@7.x and used built-in Handlers
CORS blocks	No CORS middleware	Added cors() before routes
React missing key warning	List items without key prop	Used trade._id as key
Delete route 500 (undefined ID)	Frontend sent wrong ID	Updated handleDelete(id) to use trade._id
Mongoose cast to ObjectId failed	userId schema expected ObjectId but got number	Changed userId type to String
Mongoose enum validation for uppercase	Input 'SELL' didn't match lowercase enum	Added lowercase: true to schema
401 Unauthorized on protected endpoints	No JWT sent	Stored token in localStorage and added Axios interceptor
Blank page (frontend fetch blocked)	CORS + missing fallback UI	Fixed CORS, added error messages in UI

Each of these fixes was **committed** immediately with descriptive messages and tested locally before pushing.

Congratulations! You now have a **full-stack, cloud-deployed, monitored, and tested** Copy Trading App—built step by step from the ground up.