Object Oriented Programming (CSEG1044)

Unit 01 – Lecture 03: I/O + Command Line + Types + Operators

Tofik Ali

School of Computer Science, UPES Dehradun

February 27, 2026

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Quick Links

Overview Key Topics Demo Summary

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Agenda

1 Overview

2 Key Topics

3 Demo / Example

4 Summary

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Learning Outcomes

- Read input using `Scanner` and print formatted output.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Learning Outcomes

- Read input using `Scanner` and print formatted output.
- Use command line arguments (`args`) for simple programs.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Learning Outcomes

- Read input using `Scanner` and print formatted output.
- Use command line arguments (`args`) for simple programs.
- Apply primitive types, operators, precedence, and casting correctly.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Unit 01: Introduction to OOPs

- Lecture focus: I/O + Command Line + Types + Operators

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Today: Roadmap

- Console I/O (‘Scanner‘, ‘BufferedReader‘) and output formatting

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Today: Roadmap

- Console I/O (‘Scanner‘, ‘BufferedReader‘) and output formatting
- Command line arguments and use-cases

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Today: Roadmap

- Console I/O (‘Scanner‘, ‘BufferedReader‘) and output formatting
- Command line arguments and use-cases
- Data types, variables, operators, precedence, type casting

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Console input: `Scanner` (beginner-friendly)

- Reads **tokens** from `System.in`: `nextInt()`, `nextDouble()`, `next()`.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Console input: `Scanner` (beginner-friendly)

- Reads **tokens** from `System.in`: `nextInt()`, `nextDouble()`, `next()`.
- Reads **lines**: `nextLine()`.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Console input: `Scanner` (beginner-friendly)

- Reads **tokens** from `System.in`: `nextInt()`, `nextDouble()`, `next()`.
- Reads **lines**: `nextLine()`.
- Common pitfall: mixing `nextInt()` then `nextLine()` (newline remains in buffer).

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Console input: `Scanner` (beginner-friendly)

- Reads **tokens** from `System.in`: `nextInt()`, `nextDouble()`, `next()`.
- Reads **lines**: `nextLine()`.
- Common pitfall: mixing `nextInt()` then `nextLine()` (newline remains in buffer).
- Fix: consume leftover newline with one extra `nextLine()`.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Output formatting: `printf`

- `println` is fine for simple output.

Examples

- `%d` integer, `%f` decimal, `%.2f` 2 decimals, `%s` string
- `%n` portable newline

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Output formatting: `printf`

- `println` is fine for simple output.
- `printf` is better for formatted numbers/text.

Examples

- `%d` integer, `%f` decimal, `%.2f` 2 decimals, `%s` string
- `%n` portable newline

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Command line arguments (`args`)

- Run: `java Sum 10 20 30`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Command line arguments (`args`)

- Run: `java Sum 10 20 30`
- Then: `args[0] = "10"`, `args[1] = "20"`, ...

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Command line arguments (`args`)

- Run: `java Sum 10 20 30`
- Then: `args[0] = "10"`, `args[1] = "20"`, ...
- Parse numbers: `Integer.parseInt(args[i])`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Command line arguments (`args`)

- Run: `java Sum 10 20 30`
- Then: `args[0] = "10"`, `args[1] = "20"`, ...
- Parse numbers: `Integer.parseInt(args[i])`
- Pitfall: invalid input throws `NumberFormatException`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Primitive types (quick)

- Integers: `byte`, `short`, `int`, `long`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Primitive types (quick)

- Integers: `byte`, `short`, `int`, `long`
- Floating-point: `float`, `double`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Primitive types (quick)

- Integers: `byte`, `short`, `int`, `long`
- Floating-point: `float`, `double`
- Others: `char` (Unicode), `boolean`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Operator pitfalls (must know)

- Integer division: `5/2 == 2` (use `5/2.0`)

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Operator pitfalls (must know)

- Integer division: `5/2 == 2` (use `5/2.0`)
- Precedence: multiplication before addition (use parentheses when unsure)

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Operator pitfalls (must know)

- Integer division: `5/2 == 2` (use `5/2.0`)
- Precedence: multiplication before addition (use parentheses when unsure)
- Casting: narrowing needs explicit cast (may lose data)

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Operator pitfalls (must know)

- Integer division: `5/2 == 2` (use `5/2.0`)
- Precedence: multiplication before addition (use parentheses when unsure)
- Casting: narrowing needs explicit cast (may lose data)
- Short-circuit: `&&` and `||` help safe null checks

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Example: Args + Scanner + Formatting (1/2)

```java
import java.util.Scanner;

public class InputDemo {
    public static void main(String[] args) {
        int maxMarks = 100;
        if (args.length > 0) maxMarks = Integer.parseInt(
            args[0]);

        Scanner sc = new Scanner(System.in);
        System.out.print("Enter your name: ");
        String name = sc.nextLine();
```

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Example: Args + Scanner + Formatting (2/2)

```
// continued...
        System.out.print("Enter marks (0-" + maxMarks + "): ");
        int marks = sc.nextInt();

        double percent = marks * 100.0 / maxMarks;
        System.out.printf("Hello %s, marks=%d/%d, percent=%.2f%%%n",
                name, marks, maxMarks, percent);
        sc.close();
    }
}
```

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Mini Exercises (2–3 mins)

1. Predict output: `System.out.println(5/2);`

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Mini Exercises (2–3 mins)

1. Predict output: `System.out.println(5/2);`
2. How to get 2.5 from 5 and 2?

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Mini Exercises (2–3 mins)

1. Predict output: `System.out.println(5/2);`
2. How to get 2.5 from 5 and 2?
3. If you run `java Demo A B`, what is `args.length`?

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Key Takeaways

- `Scanner` is easy for input; know the `nextInt()` vs `nextLine()` pitfall.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Key Takeaways

- `Scanner` is easy for input; know the `nextInt()` vs `nextLine()` pitfall.
- `printf` makes output readable (format specifiers).

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Key Takeaways

- `Scanner` is easy for input; know the `nextInt()` vs `nextLine()` pitfall.
- `printf` makes output readable (format specifiers).
- Command line args are strings; parse to numbers when needed.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Key Takeaways

- `Scanner` is easy for input; know the `nextInt()` vs `nextLine()` pitfall.
- `printf` makes output readable (format specifiers).
- Command line args are strings; parse to numbers when needed.
- Watch integer division, precedence, and casting.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Checkpoint Questions

1. Why can `nextLine()` return empty after `nextInt()`?

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Checkpoint Questions

1. Why can `nextLine()` return empty after `nextInt()`?
2. What is the type of `args[i]`?

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Checkpoint Questions

1. Why can `nextLine()` return empty after `nextInt()`?
2. What is the type of `args[i]`?
3. How do you avoid integer division when you want decimals?

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Next Lecture Preview

Next: Control Flow + Arrays + Strings

- Bring one example where you used a loop in C.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).

Next Lecture Preview

Next: Control Flow + Arrays + Strings

- Bring one example where you used a loop in C.
- We will solve simple array + string problems together.

Sources: Schildt, *Java: A Beginner's Guide* (10e), McGraw-Hill (Java fundamentals + OOP basics).; Oracle Java Tutorials: Getting Started + Language Basics + Classes and Objects (accessed February 27, 2026).; Java SE API docs (e.g., `String`, `Scanner`) (accessed February 27, 2026).