

Muhammad Talib Hussain

Roll no: 124

Section: SE-2B

PF Assignment no: 3

Program no:1

```
#include<iostream>
```

```
using namespace std;
```

```
double calculateAverage(int arr[],int size)
```

```
{
```

```
    int sum=0;
```

```
    for (int i=0;i<size;i++)
```

```
    {
```

```
        sum +=arr[i];
    }

    return(double)sum/size;
}

int main(){
    int N;
    cout<<"Enter number of student:";
    cin>>N;
    int scores[N];
    cout<<"enter test scores:";
    for (int i=0;i<N;i++)
    {
        cin>>scores[i];
    }
}
```

```
double average=calculateAverage(scores,N);  
cout<<fixed<<setprecision(2 );  
cout<<"Average Score="<<average<<endl;  
return 0;  
  
}
```

Program no:2

```
using namespace std;  
int calculateLowest(int arr[],int n)  
{  
    int lowest = arr[0];  
    for (int i=1;i<n;i++)
```

```
{  
    if(arr[i] < lowest)  
        lowest = arr[i];  
}  
return lowest;  
}  
  
int calculateHighest(int arr[],int n){  
    int highest = arr[0];  
    for(int i=1;i<n;i++){  
        if(arr[i] > highest)  
            highest = arr[i];  
    }  
    return highest;  
}
```

```
int main()
{
    int n;
    cin>>n;
    int arr[n];
    for (int i=0; i<n; i++)
    {
        cin>>arr[i];
    }

    int lowest = calculateLowest(arr,n);
    int highest = calculateHighest(arr,n);
    cout << "Lowest Score: " << lowest <<endl;
    cout << "Highest Score: " << highest <<endl;
```

```
return 0;
```

```
}
```

Programno:3

```
#include<iostream>
```

```
using namespace std;
```

```
int calculatePower(int base, int exponent){
```

```
    int result = 1
```

```
        for (int i = 1; i <= exponent; i++)
```

```
        {
```

```
            result = result * base;
```

```
        }
```

return result;

}

int main(){

int base, exponent;

cin >> base >> exponent;

int result = calculatePower(base,exponent);

cout << base << " raised to the power " <<exponent
<< "is: " <<result;

return 0;

}

Program no:4

#include<iostream>

using namespace std;

double calculateVoltage(double current, double resistance)



```
{  
    return current * resistance  
}  
  
int main(){  
    double current, resistance;  
    cin >> current >> resistance;  
    double voltage = calculateVoltage(current, resistance);  
    cout << " << Total voltage << " << voltage << " v";  
  
    return 0;  
}
```

Program no:5

```
include<iostream>  
using namespace std;
```

```
bool searcPlayer(char[], int size,char target)
```

```
{
```

```
    for (int i=0; i < size; i++)
```

```
    {
```

```
        if (team[i] ==target)
```

```
        {
```

```
            return true;
```

```
        }
```

```
    }
```

```
    return false;
```

```
}
```

```
int main(){
```

```
    char team[11] = { 'b', 'r','s','f','a','m','h','i','k','n','z'};
```

```
    char target;
```



```
cin >> target;
if(searchPlayer(team, 11, target))
cout << "Player is in the team";
else
cout << "Player not found";
    return 0;
}
```

Program no:6

```
#include<iostream>
using namespace std;
//Function that counts characters until '\'without using strlen()
int countLength(char word[]){
    int count = 0;
    while(word[count]!='\0'){
```

D-ONLY This document is locked for editing by another user.

Save As

```
        count++;  
    }  
    return count;  
}  
  
int main(){  
    char word[100]; //character array for input  
    cout << "Enter a word:";  
    cin >> word; //takes single word, no spaces  
    int length = countLength(word); cout << "Length of the word  
is:" << length;  
    return 0;  
}
```

End of document ■

