

# DHS Visual Improvements — Implementation Roadmap

// client: TalKalisker // date: 2026-04-30 // type: Reference.Roadmap

// deliverable: Reference.Roadmap

# DHS Visual Improvements — Implementation Roadmap

// client: TalKalisker

// 2026-04-30

## 01. /overview

15 visual and UX improvements to the DHS portal shell, organized into 4 delivery phases. Sequenced by impact-to-effort ratio — the first phase alone transforms how every existing and future report feels to open.

All changes live in two files: `_dhs/brand/dashboard_shell.html` (CSS + JS) and `_dhs/scripts/publish.js` (output HTML structure). No source report files need changes. Every improvement applies automatically to all 6 published portals on next rebuild.

|                    |    |     |
|--------------------|----|-----|
| Total improvements | 15 | +15 |
|                    |    |     |

**Files to modify**

2

Stable

**Reports affected**

All (6  
current)

Auto-applies on rebuild

**Estimated total  
effort**

~15 days

4 phases

## 02. /phases

DAY 1-2

### Phase 1 — High-ROI Quick Wins

**Scroll spy on sidebar nav** — IntersectionObserver highlights active section while reading

**Date rendered in report header** — Already in meta; surface it below the client line

**Hero gradient band** — Terracotta-to-transparent sweep behind the report header

**Finding card severity left border** — Color-coded bar by severity, scannable without reading

**Reading progress bar** — Thin terracotta line at top of page, fills as user scrolls

DAY 3-5

## Phase 2 — Card System Upgrades

**Interactive action checkboxes** — Click toggles Done/Pending in localStorage, no backend

**Language switch fade animation** — 150ms opacity transition on incoming language block

**Language indicator pill** — EN / עב pill shows current language next to the toggle button

**Confidential badge** — Styled CONFIDENTIAL label in header for encrypted reports

**Section intro paragraph** — First p per section rendered larger (1.2rem, lighter weight)

DAY 6-9

## Phase 3 — Filtering & Interactivity

**Findings filter bar** — All / Critical / High / Medium / Low above finding card groups

**Action items filter bar** — All / Pending / Blocked / Done above action card groups

**Expandable appendix tables** — Large tables start collapsed with "Show full table" toggle

**Pull quote treatment** — Blockquotes styled with large terracotta quote mark, larger type



DAY 10-15

## Phase 4 — Mobile, Bilingual & Print

**Mobile sidebar drawer** — Hamburger → slide-in panel below 900px instead of stacking

**Swipe language switch** — touchstart / touchend detects swipe, cycles languages on mobile

**Print one-pager mode** — Print-only header with logo + client + date + confidential badge

**Section page-break control** — page-break-before: always on major sections for clean PDF export

## 03. /phase\_1\_detail

*5 changes. Combined effect: every report feels intentional the moment it opens.*



### Scroll Spy — Active Nav Highlighting

dashboard\_shell.html JS

Create one IntersectionObserver targeting all h1[id] elements.

On intersection, find the matching a[href="#id"] in .sidebar-nav and toggle .active. CSS .nav-link.active already has the accent color and right border — the state just never gets set. No layout changes required.



## Date in Report Header

dashboard\_shell.html Handlebars template

{{date}} is already in the meta tag. Add `<div class="report-date">{{date}}</div>` below `.report-client` in the header markup. Style with the same mono font and accent color as the client line. One Handlebars token, one CSS rule.



## Hero Gradient Band

dashboard\_shell.html CSS

Add `::before` pseudo-element to `.report-header`. Absolute position, full width, height ~300px, background: `linear-gradient(135deg, rgba(184,90,68,0.06) 0%, transparent 70%)`. `pointer-events: none`. Zero layout impact — purely visual depth under the title.



## Finding Card Severity Left Border

dashboard\_shell.html CSS

.finding-card already has .sev-critical, .sev-high, .sev-medium, .sev-low classes on the inner .severity badge. Add border-left: 3px solid to .finding-card based on a data attribute, or add a wrapper class. Alternative: target .finding-card:has(.sev-critical) with :has() CSS — no HTML changes needed if browser support is acceptable (Chrome 105+, Safari 15.4+). Transforms scan time for multi-finding sections from "read every card" to "scan the left edge."



## Reading Progress Bar

dashboard\_shell.html CSS + JS

Add <div id="progress-bar"></div> at top of <body>. CSS: position: fixed; top: 0; left: 0; height: 3px; background: var(--accent); width: 0%; z-index: 999; transition: width 0.1s. JS scroll listener: width = (scrollY / (documentHeight - viewportHeight)) \* 100 + '%'. ~8 lines.

# 04. /phase\_2\_detail

*5 changes. Makes the portal feel like a living document, not a static PDF.*



## Interactive Action Card Checkboxes

dashboard\_shell.html JS

Action cards already render a `.action-checkbox` div. Add `data-id` attribute (hash of task text) to each checkbox in `publish.js`. On click: toggle a `done` class, save `localStorage.setItem(id, 'done')`. On `DOMContentLoaded`: read `localStorage` and restore states. Client can tick off items as they execute. State survives page refresh. No server, no backend.



## Language Switch Fade Animation

dashboard\_shell.html CSS + JS

In `setLang()`, instead of `instant display: block/none`, add `.lang-fade-in` class to the incoming block, then remove it after 150ms. CSS: `.lang-fade-in { animation: langFade 150ms ease; }`  
`@keyframes langFade { from { opacity: 0; } to { opacity: 1; } }`. Outgoing block hides immediately; incoming block fades in.



## Language Indicator Pill

dashboard\_shell.html HTML + JS

Add `<span id="lang-indicator">EN</span>` next to the lang toggle button. Style as a small mono pill. In `setLang()`, update `textContent` to `lang.toUpperCase()` or 'עב' for Hebrew. Always shows current language without hovering over the toggle.



## Confidential Badge in Header

dashboard\_shell.html Handlebars

Add `{{#if confidential}}<div class="confidential-badge">// CONFIDENTIAL</div>{{/if}}` to `.report-header`. CSS: mono font, small, accent-red color (`var(--accent-red)`), faint red background pill. Visible context for client that this is an encrypted deliverable.



## Section Intro Paragraph Style

dashboard\_shell.html CSS

`section > p:first-of-type { font-size: 1.15rem; font-weight: 300; color: var(--text-primary); line-height: 1.9; }`. No HTML changes. Applies automatically to every section's opening paragraph across all reports. Creates visual hierarchy between the intro sentence and the body content below it.



## 05. /phase\_3\_detail

*4 changes. Transforms multi-finding audits from walls of cards into filtered, navigable sets.*



### Findings Filter Bar

dashboard\_shell.html JS

After DOMContentLoaded, detect any section containing 3+

.finding-card elements. Inject a filter bar above that section: All · Critical · High · Medium · Low. On click: toggle .hidden on cards whose .severity badge class doesn't match the selected filter. CSS .finding-card.hidden { display: none }. Pure DOM — no changes to publish.js or source files.



### Action Items Filter Bar

dashboard\_shell.html JS

Same pattern as findings filter. Detect sections with 3+ .action-card elements. Filter options: All · Pending · In Progress · Done · Blocked. Match against .action-status text content. Inject filter bar above the group. Single shared utility function handles both filters.



## Expandable Appendix Tables

dashboard\_shell.html JS

On DOMContentLoaded, find all <table> elements with more than 8 rows. Wrap rows 5+ in a <tbody class="table-overflow"> and hide it. Inject a <tfoot> button: "Show all N rows ↓". On click: toggle visibility, update button text. Keeps appendix tables scannable at first glance without losing any data.



## Pull Quote Treatment

dashboard\_shell.html CSS

```
blockquote { position: relative; padding: 1.5rem 1.5rem 1.5rem 3rem; font-size: 1.2rem; font-weight: 300; color: var(--text-primary); border: none; }+
blockquote::before { content: '"'; position: absolute; left: 0; top: -0.5rem; font-size: 4rem; color: var(--accent); opacity: 0.6; font-family: Georgia, serif; line-height: 1; }.Transforms bland blockquotes into visible pull quotes.
```

# 06. /phase\_4\_detail

*4 changes. Mobile-first delivery and print-ready exports.*



## Mobile Sidebar Drawer

dashboard\_shell.html CSS + JS + HTML

Below 900px: replace the stacked sidebar with a hidden drawer. Add

`<button id="nav-toggle">≡</button>` fixed to top-left. CSS:

`.sidebar { transform: translateX(-100%); transition:`

`transform 0.3s; position: fixed; z-index: 100;`

`height: 100vh; } + .sidebar.open { transform:`

`translateX(0) }.` Overlay `<div id="nav-overlay">` closes the

drawer on tap outside. RTL: mirrors to right side.



## Swipe Language Switch

dashboard\_shell.html JS

In `DOMContentLoaded`, on touch devices: track `touchstart` X position

and `touchend` X position on document. If `delta > 60px` and available

languages `> 1`: swipe-left cycles forward, swipe-right cycles backward.

Calls existing `toggleLang()`. ~15 lines. No libraries needed.



## Print One-Pager Header

dashboard\_shell.html CSS

Add a `<div class="print-header">` to the template with logo, client name, report title, date, and confidential badge — all hidden by default (`display: none`). @media print { .print-header { display: block; margin-bottom: 2rem; border-bottom: 2px solid #000; } .sidebar { display: none; } }. PDF output becomes self-contained — no logo, date, or client context currently survives print.



## Section Page-Break Control

dashboard\_shell.html CSS

```
@media print { section { page-break-inside: avoid; }
section + section { page-break-before: auto; } h1 {
page-break-after: avoid; } .finding-card, .action-
card, .timeline-node { page-break-inside: avoid; } }
```

Prevents cards from splitting mid-content across printed pages. Finding cards already have this — extend it to all card types and section boundaries.

## 07. /implementation\_notes

Strategic Decision

High Impact

### **Implement phases in order**

Each phase is designed to be shippable independently. Phase 1 alone justifies a rebuild. Don't wait for Phase 4 to be complete to deploy Phase 1.

Strategic Decision

Medium Impact

### **All JS in dashboard\_shell.html, no external files**

DHS portals are self-contained single HTML files. Keep all enhancements inline.

No additional script tags, no npm packages for runtime. The CryptoJS CDN is the only external dependency and it stays that way.

Strategic Decision

Medium Impact

### **CSS-first, JS only when CSS cannot do it**

Scroll spy, progress bar, filters, drawer: JS required. Everything else (gradient, borders, typography, animations): pure CSS. Keeps the portal lightweight and functional without JavaScript where possible.

Strategic Decision

High Impact

### **Test in both dark and light themes before shipping each phase**

Every color must use CSS variables. No hardcoded hex values in new code. Dark theme is the default and primary — light theme must not be an afterthought. Test the Hebrew RTL layout for Phase 1 and Phase 4 especially.