Schema documentation
for scenario_family.xsd

september 16, 2012

Table of Contents

Resource hierarchy:

Legend: 🔲 *Import,* 🔲 *Include,* 🔲 *Redefine,* 🌀 *Cycle detected*

   scenario_family.xsd

      ↳🔲 uuid_attribute.xsd

Namespace: "http://github.com/talkasab/assayer_process"

Schema(s)

Main schema `scenario_family.xsd`

Namespace	http://github.com/talkasab/assayer_process	
Properties	attribute form default:	unqualified
	element form default:	qualified

Included schema `uuid_attribute.xsd`

Namespace	http://github.com/talkasab/assayer_process	
Properties	attribute form default:	unqualified
	element form default:	qualified

Element(s)

Element `a:scenario_family`

Namespace	http://github.com/talkasab/assayer_process

Diagram	
Properties	content: complex
Model	a:label , a:description{0,1} , a:scenario_reference+
Children	a:description, a:label, a:scenario_reference

Instance	`<a:scenario_family uuid="" xmlns:a="http://github.com/talkasab/assayer_process">`
	`  <a:label>{1,1}</a:label>`
	`  <a:description>{0,1}</a:description>`
	`  <a:scenario_reference filename="" scenario_uuid="" url="">{1,unbounded}</a:scenario_reference>`
	`</a:scenario_family>`

Attributes	QName	Type	Fixed	Default	Use
	uuid	a:uuidPattern			required

Element `a:label`

Namespace	http://github.com/talkasab/assayer_process
Diagram	
Type	xs:string
Properties	content: simple
Used by	Element a:scenario_family

Element `a:description`

Namespace	http://github.com/talkasab/assayer_process
Diagram	
Type	xs:string
Properties	content: simple
Used by	Element a:scenario_family

Element `a:scenario_reference`

Namespace	http://github.com/talkasab/assayer_process
Diagram	
Properties	content: complex

Used by	Element	a:scenario_family				
Attributes	**QName**	**Type**	**Fixed**	**Default**	**Use**	
	filename	xs:string			optional	
	scenario_uuid	a:uuidPattern			required	
	url	xs:anyURI			optional	

Element `a:uuid`

Namespace	http://github.com/talkasab/assayer_process					
Diagram						
Properties	content:	complex				
Attributes	**QName**	**Type**	**Fixed**	**Default**	**Use**	
	uuid	a:uuidPattern			required	

Simple Type(s)

Simple Type `a:uuidPattern`

Namespace	http://github.com/talkasab/assayer_process
Diagram	
Type	restriction of xs:string
Facets	pattern [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}
Used by	Attributes a:at_uuid/@uuid, a:scenario_reference/@scenario_uuid

Attribute Group(s)

Attribute Group `a:at_uuid`

Namespace	http://github.com/talkasab/assayer_process					
Diagram						
Used by	Elements	a:scenario_family, a:uuid				
Attributes	**QName**	**Type**	**Fixed**	**Default**	**Use**	
	uuid	a:uuidPattern			required	

Namespace: ""

Attribute(s)

Attribute `a:scenario_reference` / `@scenario_uuid`

Namespace	No namespace
Type	a:uuidPattern
Properties	use: required
Facets	pattern [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Used by	Element	a:scenario_reference

Attribute `a:scenario_reference / @filename`

Namespace	No namespace	
Type	xs:string	
Properties	content:	simple
Used by	Element	a:scenario_reference

Attribute `a:scenario_reference / @url`

Namespace	No namespace	
Type	xs:anyURI	
Properties	content:	simple
Used by	Element	a:scenario_reference

Attribute `a:at_uuid / @uuid`

Namespace	No namespace	
Type	a:uuidPattern	
Properties	use:	required
Facets	pattern	`[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`
Used by	Attribute Group	a:at_uuid