

# CS1555 Recitation 8

---

**Objective:** To practice Evaluation Modes, Transactions, Procedures, and Functions

---

## PART 1: Constraint Evaluation Modes and Transactions

*DEFERRED : withheld for or until a stated time (COMMIT)*

- a) **Not Deferrable** (default): *every time a database modification statement is executed, the constraints are checked.*
- b) **Deferrable Initially Immediate**: *every time a database modification statement is executed, the constraints are checked IMMEDIATE. BUT, the constraints can be deferred on demand, when needed*
- c) **Deferrable Initially Deferred**: *the constraints are check just BEFORE each transaction commits.*

1. Use the create statement with the deferred statement mentioned below

```
CREATE TABLE notdef (  
    ssn integer,  
    CONSTRAINT pk_ssn_1 PRIMARY KEY(ssn)  
);
```

```
CREATE TABLE defimm (  
    ssn integer,  
    CONSTRAINT pk_ssn_2 PRIMARY KEY(ssn) DEFERRABLE INITIALLY  
IMMEDIATE  
);
```

```
CREATE TABLE defdef (  
    ssn integer,  
    CONSTRAINT pk_ssn_3 PRIMARY KEY(ssn) DEFERRABLE INITIALLY  
DEFERRED  
);
```

2. For each table created above, run the SQL statements and mention if and when you encounter an error.

```
INSERT INTO notdef VALUES (1234);  
INSERT INTO notdef VALUES (1234);
```

3. Now, add `<SET CONSTRAINTS <constraint_name> DEFERRED>` for the constraint set in table defimm; Run the previous insert again. Do you see any difference?

NOTE: remember that we already have value 1234 in the table because of the previous insert statements.

```
BEGIN;  
SET CONSTRAINTS pk_ssn_2 DEFERRED;  
INSERT INTO defimm VALUES (1234);  
COMMIT;
```

4. For each table created above, run the SQL statements and show the table content after the inserts.

- a) set constraints all deferred
- b) insert value 1235
- c) insert value 1235
- d) commit;

Notdef:

```
BEGIN;  
SET CONSTRAINTS ALL DEFERRED;  
INSERT INTO notdef VALUES (1235);  
INSERT INTO notdef VALUES (1235);  
COMMIT;.
```

Defimm:

```
BEGIN;  
SET CONSTRAINTS ALL DEFERRED;  
INSERT INTO defimm VALUES (1235);  
INSERT INTO defimm VALUES (1235);  
COMMIT;
```

Defdef:

```
BEGIN;  
SET CONSTRAINTS ALL DEFERRED;  
INSERT INTO defdef VALUES (1235);  
INSERT INTO defdef VALUES (1235);  
COMMIT;
```

---

## PART 2: Procedures and Functions

Before we start:

- Download the SQL script bank\_db.sql from the course website, in the recitation page.

---

1. Create a stored procedure **transfer\_fund** that, given a from\_account, a to\_account, and an amount, transfer the specified amount from from\_account to to\_account if the balance of the from\_account is sufficient.

2. Call the stored procedure to transfer \$100 from account 124 to 123.

3. Create a function that returns true if a customer can pay their loan or false when their balance is less than their loan.

4. Use the function created using the ssn 123456789.

5. Create a function that returns a trigger upon inserting a tuple into the table customer, it makes sure that the name is in upper cases.

6. Insert the following tuple, and then check the value after insertion: