

---

# Tridiagonal Matrix Algorithm (Thomas Algorithm)

Tamas Kis | [kis@stanford.edu](mailto:kis@stanford.edu) | <https://github.com/tamaskis>

---

## Contents

1	Tridiagonal Matrix Algorithm (Thomas Algorithm)	2
	References	4

---

Copyright © 2021 Tamas Kis

*Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:*

*The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.*

*THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.*



# 1 TRIDIAGONAL MATRIX ALGORITHM (THOMAS ALGORITHM)

A tridiagonal linear system is one of the form

$$\begin{bmatrix} b_1 & c_1 & & & \\ a_1 & b_2 & c_2 & & \\ & a_2 & \ddots & \ddots & \\ & & \ddots & \ddots & c_{n-2} \\ & & & a_{n-2} & b_{n-1} & c_{n-1} \\ & & & & a_{n-1} & b_n \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_{n-1} \\ x_n \end{bmatrix} = \begin{bmatrix} d_1 \\ d_2 \\ \vdots \\ d_{n-1} \\ d_n \end{bmatrix}$$

We can define the  $\mathbf{x}$  and  $\mathbf{d}$  vectors as

$$\mathbf{x} = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_{n-1} \\ x_n \end{bmatrix}, \quad \mathbf{d} = \begin{bmatrix} d_1 \\ d_2 \\ \vdots \\ d_{n-1} \\ d_n \end{bmatrix}$$

and the  $n \times n$  **tridiagonal matrix**<sup>1</sup>,  $\mathbf{A}$ , as

$$\mathbf{A} = \begin{bmatrix} b_1 & c_1 & & & \\ a_1 & b_2 & c_2 & & \\ & a_2 & \ddots & \ddots & \\ & & \ddots & \ddots & c_{n-2} \\ & & & a_{n-2} & b_{n-1} & c_{n-1} \\ & & & & a_{n-1} & b_n \end{bmatrix} \quad (1)$$

Now we can write the tridiagonal linear system as

$$\mathbf{Ax} = \mathbf{d} \quad (2)$$

where  $\mathbf{A} \in \mathbb{R}^{n \times n}$  and  $\mathbf{x}, \mathbf{d} \in \mathbb{R}^n$ .

The **tridiagonal matrix algorithm** (also known as the **Thomas algorithm**) is an algorithm that can efficiently solve the tridiagonal linear system (given by Eq. (2)) for  $\mathbf{x}$ . This algorithm uses three vectors,  $\mathbf{a}$ ,  $\mathbf{b}$ , and  $\mathbf{c}$ , which we define as [1]

$$\mathbf{a} = \begin{bmatrix} a_1 \\ \vdots \\ a_{n-1} \end{bmatrix}, \quad \mathbf{b} = \begin{bmatrix} b_1 \\ \vdots \\ b_n \end{bmatrix}, \quad \mathbf{c} = \begin{bmatrix} c_1 \\ \vdots \\ c_{n-1} \end{bmatrix}$$

<sup>1</sup> In many references, a tridiagonal matrix is defined with the convention

$$\mathbf{A} = \begin{bmatrix} a_1 & b_1 & & & \\ c_1 & a_2 & b_2 & & \\ & c_2 & \ddots & \ddots & \\ & & \ddots & \ddots & b_{n-2} \\ & & & c_{n-2} & a_{n-1} & b_{n-1} \\ & & & & c_{n-1} & a_n \end{bmatrix}$$

When dealing with the tridiagonal matrix algorithm, a convention similar to the one in Eq. (1) is used almost exclusively. However, the convention that most sources have has the  $a_i$ 's ranging from  $a_2$  to  $a_n$ , which is inconvenient from a programming standpoint; therefore, I defined them here as ranging from  $a_1$  to  $a_{n-1}$ . This convention is also reflected in Algorithm 1.

The tridiagonal matrix algorithm is shown below [1–3].

**Algorithm 1:** tridiagonal

Tridiagonal matrix algorithm (Thomas algorithm).

**Given:**  $\mathbf{A}$ ,  $\mathbf{d}$

- $\mathbf{A} \in \mathbb{R}^{n \times n}$
- $\mathbf{d} \in \mathbb{R}^n$
- Corresponds to the tridiagonal linear system  $\mathbf{Ax} = \mathbf{d}$ .

**Procedure:**

1. Determine  $n$  (where  $\mathbf{A} \in \mathbb{R}^{n \times n}$ ).
2. Preallocate vectors of size  $n \times 1$  to store  $\mathbf{b}$  and  $\mathbf{x}$ .
3. Preallocate vectors of size  $(n - 1) \times 1$  to store  $\mathbf{a}$  and  $\mathbf{c}$ .
4. Extract  $\mathbf{a}$  from  $\mathbf{A}$ .

```

for  $i = 2$  to  $n$ 
     $a_{i-1} = A_{i,i-1}$ 
end

```

5. Extract  $\mathbf{b}$  from  $\mathbf{A}$ .

```

for  $i = 1$  to  $n$ 
     $b_i = A_{i,i}$ 
end

```

6. Extract  $\mathbf{c}$  from  $\mathbf{A}$ .

```

for  $i = 2$  to  $n$ 
     $c_{i-1} = A_{i-1,i}$ 
end

```

7. Forward elimination.

```

for  $i = 1$  to  $n$ 
     $w = a_{i-1}/b_{i-1}$ 
     $b_i = b_i - wc_{i-1}$ 
     $d_i = d_i - wd_{i-1}$ 
end

```

8. Backward substitution.

```

for  $i = n - 1$  to  $1$  by  $-1$ 
     $x_i = (d_i - c_i x_{i+1}) / b_i$ 
end

```

**Return:**  $\mathbf{x}$

- $x \in \mathbb{R}^n$ , solution of linear system  $\mathbf{Ax} = \mathbf{d}$

## REFERENCES

- [1] James Hateley. *Linear Systems of Equations and Direct Solvers*. MATH 3620 Course Reader (Vanderbilt University). 2019.
- [2] *Tridiagonal matrix algorithm*. Wikipedia. [https://en.wikipedia.org/wiki/Tridiagonal\\_matrix\\_algorithm](https://en.wikipedia.org/wiki/Tridiagonal_matrix_algorithm) (accessed: January 9, 2021).
- [3] *Tridiagonal matrix algorithm – TDMA (Thomas algorithm)*. CFD Online. [https://www.cfd-online.com/Wiki/Tridiagonal\\_matrix\\_algorithm\\_-\\_TDMA\\_\(Thomas\\_algorithm\)](https://www.cfd-online.com/Wiki/Tridiagonal_matrix_algorithm_-_TDMA_(Thomas_algorithm)) (accessed: January 9, 2021).