



TECHNICAL INFORMATION SHEET

SAFETY DATA SHEET

Product name : **AS 88 degreasing and safety solvent for electrical equipment**

SECTION I : MATERIAL IDENTIFICATION

A straight chain chlorinated hydrocarbon

Manufacturer's name : Allchem Technology Sdn Bhd
No. 5, Jalan BK 1/11
Bandar Kinrara Ind. Park,
47180 Puchong, Selangor
Tel: 03-80762088

SECTION II : HAZARDS IDENTIFICATION



Signal Word Danger

Hazard Statements	H305	May be fatal if swallowed and enter airways
	H315	Causes skin irritation
	H319	Causes serious eye irritation
	H336	May cause drowsiness or dizziness
	H351	Suspected of causing cancer
	H373	May cause damage to liver/ blood through prolonged or repeated exposure
Precautionary Statements	P202	Do not handle until all precautions have been read and understood
	P260	Do not breath mist / vapours /spray
	P262	Do not get in eyes, on skin or on clothing
	P264	Wash skin thoroughly after handling
	P271	Use only outdoor or well ventilated area
	P280	Wear protective gloves / protective clothing/ eye / face protection
	P304 + P340 IF INHALED :	Remove victim to fresh air and keep at rest in a position comfortable for breathing
	P305+P351 IF IN EYES :	Rinse cautiously with water for several minutes.
	+P338	remove contact lenses, if present and easy to do, continue rinsing.

SECTION III : INGREDIENTS

	%	TLV
Hydrocarbons (chlorinated)	> 90%	100-300ppm
Inhibitors	1-2%	nil

SECTION IV : FIRST AID MEASURES

After inhalation – move patient to open ventilated area. If rapid recovery does not occur, obtain medical attention.

After contact with skin – remove contaminated clothing, wash off with soap and plenty of water

After contact with eyes – immediately rinse with plenty of water, for about 15minutes. Get medical attention

After ingestion – do not induce vomiting. Rinse mouth thoroughly. Drink plenty of water. Obtain medical help immediately.

Advice to doctor – treat symptomatically.

SECTION V : FIRE FIGHTING MEASURES

Extinguishing media – none, product is non-flammable. Normal extinguishing media. As appropriate for surrounding fire. Water spray should be used to cool containers.

Unsuitable extinguishing media - non anticipated

Fire Fighting Instructions – Evacuate area. If leak or spill has not ignited, use water spray to dispers the vapours and to protect personnel attempting to stop a leak. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in an enclosed surfaces and to protect personnel.

Special hazards arising from substance or mixture – Explosive mixtures and air can be formed but are difficult to ignite and require high intensity sources of heat, such as welding arcs, sparks and flames or high temperature and pressure; addition of small amounts of flammable substances (such as flammable liquids or gasses) and /or an increase in the oxygen content of the local atmosphere, may strongly enhance these effects. Thermal decomposition and burning will evolve toxic and corrosive vapours. Containers may burst if overheated due to thermal expansion of the contents.

Hazardous Combustion Products : Incomplete combustion products, oxides of carbon, smoke, fume

SECTION VI : ACCIDENTAL RELEASE MEASURE

Personal precautions : avoid contact with skin and eyes. Do not breathe vapour. Ventilate contaminated are thoroughly. Evacuate the area of all non-essential personnel. Shut off leaks, if possible without personal risk.

Personal protection : see Section 8

Environmental precautions : Avoid discharge into drains, water courses or onto the ground.

Methods of cleaning up : Ventilate. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. For waste disposal, see section 13.

SECTION VII : HANDLING AND STORAGE

Handling : Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray / mists. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic / irritating fumes / vapour may be evolved from heated or agitated material. Use only with adequate ventilation. Do not enter storage areas or confined spaces unless adequately ventilated. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electric spark (ignition source). Use proper bonding and / or ground procedures.

Handling temperatures : Ambient

Storage : Keep container tightly closed and in a well-ventilated place. Keep away from direct sunlight and other sources of heat or ignition. Do not smoke in storage areas. Tanks should be fitted with a vapour recovery system.

Storage temperatures : Ambient

SECTION VIII : EXPOSURE CONTROLS AND PERSONAL PROTECTION

Process Conditions : Provide eyewash station. Take precautionary measures against static discharges.

Engineering measures : Provide sufficient ventilation during operations which cause vapour formation.

Respiratory protection : No specific recommendation made, but respiratory protection must be used if the general level exceed exposure limit.

Hand protection : chemical resistant gloves required

Eye protection : wear approved chemicals safety goggles where eye exposure is reasonably probable.

Hygiene measures : Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated.
DO NOT SMOKE IN WORK AREA!

SECTION IX : PHYSICAL DATA

Specific Gravity (28°C) : 1.35 +/- 0.25gm/cc	Boiling point : 75-89°C
Vapour Density (Air=1) : heavier than air	Percent volatile by vol (%) : 100%
Vapour Pressure (30°C): 157	Evaporation rate (nBA=1) : >1
Solubility in water: no	Autoignition Temperature : n/a
Appearance : clear liquid, slight odor	

SECTION X : STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended transport or storage Conditions, will not affect most metals
Stability	:	Stable under normal temperature conditions
Conditions to avoid	:	Heat, open flames, sparks and other ignition sources
Materials to avoid	:	Strong oxidisers
Hazardous decomposition products	:	Material does not decompose at ambient temperature

SECTION XI : TOXICOLOGICAL INFORMATION

Basic for assessment	:	Information given is based on product data and on data on the components and the toxicology of similar products
General information	:	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Eye contact	:	may cause mild, short-lasting discomfort to eyes
Skin contact	:	moderately irritating to skin with prolonged exposure.
Inhalation	:	may be irritating to the respiratory tract. The effects are reversible.
Ingestion	:	minimally toxic

SECTION XII : ECOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on product data and on data on the components and the ecotoxicology of similar products.
Ecotoxicity	:	Material – expected to be toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
Mobility	:	Material Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.
Biodegradation	:	Material – expected to be readily biodegradable
Atmospheric oxidation	:	Material – expected to be degrade rapidly in air
Other Ecological Information : VOC : Yes		

SECTION XIII: DISPOSAL CONSIDERATIONS

Disposal Methods :

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Disposal Recommendations :

Product is suitable for burning in an enclosed controlled burner for value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

Empty containers should be taken for recycling, recovery or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations.

SECTION XIV : TRANSPORT INFORMATION

Proper Shipping name : AS 88



Transport labels :

SECTION XV : REGULATORY INFORMATION

Labelling according to EEC directive :

Risk Phrases :-

- R36 – Irritating to eyes
- R38 – Irritating to skin
- R43 – may cause sensitization to skin on prolonged contact
- R67 – Vapours may cause drowsiness and dizziness

Hazard Statement :-

- H305 May be fatal if swallowed and enter airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness
- H351 Suspected of causing cancer
- H373 May cause damage to liver/ blood through prolonged or repeated exposure

SECTION XVI : OTHER INFORMATION

None

Source of data : SDS of Material Manufacturers

REFERENCES : DATE : 28 March 2021

PREPARED BY : VINCENT WONG

Information herein is given in good faith as authoritative and valid however, no warranty express or implied, can be made.