



Safety Data Sheet

Page 1 of 15

LOCTITE 565 LOW STRENGTH THREAD SEALANT known as
565 PST PIPE SEALANT 50 ML

SDS No. : 153649

V003.5

Revision: 23.11.2020

printing date: 21.03.2023

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 565 LOW STRENGTH THREAD SEALANT known as 565 PST PIPE SEALANT 50 ML

Other means of identification: LOCTITE 565 TB50ML EN/CH/JP/KR

Product code: IDH339604

Recommended use of the chemical and restrictions on use

Intended use: Anaerobic Adhesive

Identification of manufacturer, importer or distributor

Importer: Henkel (Malaysia) Sdn Bhd

Unit 2.01, 2.02, Level 2, MERCU 3, Jalan Bangsar, KL Eco City, 59200 Kuala Lumpur, Malaysia.

Phone :+ 603 22461000 Fax : + 60322461188

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Serious eye damage/eye irritation	Category 2	
Specific target organ toxicity - single exposure	Category 3	respiratory tract irritation
Chronic hazards to the aquatic environment	Category 3	

GHS label elements:

Hazard pictogram:



Signal word:

Warning

Hazard statement:

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients**Substance or Mixture:**

Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Titanium dioxide 13463-67-7	1- 10 %	
α , α -dimethylbenzyl hydroperoxide 80-15-9	1- 10 %	Organic peroxides E H242 Acute toxicity 4; Oral H302 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1B H314 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 2 H411
N,N-Diethyl-p-toluidine 613-48-9	0.1- 1 %	Acute toxicity 3; Oral H301 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 3 H412
Ethane-1,2-diol 107-21-1	0.1- 1 %	Acute toxicity 4; Oral H302 Specific target organ toxicity - repeated exposure 2; Oral H373
Ethene, homopolymer 9002-88-4	0.1- 1 %	
cumene 98-82-8	0.1- 1 %	Flammable liquids 3 H226 Specific target organ toxicity - single exposure 3 H335 Aspiration hazard 1 H304 Chronic hazards to the aquatic environment 2 H411
1,4-Naphthalenedione 130-15-4	< 0.1 %	Acute toxicity 3; Oral H301 Acute toxicity 1; Inhalation H330 Skin corrosion/irritation 2; Dermal H315 Serious eye damage/eye irritation 2 H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410

Section 4. First aid measures

Inhalation:	Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.
Skin contact:	Wash skin with water In case of adverse health effects seek medical advice.
Eye contact:	Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention.
Ingestion:	Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. In case of adverse health effects seek medical advice.
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:	Foam, extinguishing powder, carbon dioxide.
Combustion behaviour:	Non flammable product (flash point is greater than 100°C (CC))
Specific hazards arising from the chemical:	In case of fire, keep containers cool with water spray.
Special protection equipment and precautions for firefighters:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Section 6. Accidental release measures

Personal precautions:	Avoid skin and eye contact. Wear protective equipment. Ensure adequate ventilation. See advice in section 8
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:	Use only in well-ventilated areas. Gloves and safety glasses should be worn Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation. Avoid skin and eye contact. See advice in section 8
Storage:	Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product. Refer to Technical Data Sheet

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

TITANIUM DIOXIDE 13463-67-7	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
TITANIUM DIOXIDE 13463-67-7	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	MY OEL
ETHYLENE GLYCOL, AEROSOL 107-21-1	Value type	Ceiling Limit Value:
	ppm	39.4
	mg/m³	100
	Remarks	MY OEL
ETHYLENE GLYCOL, VAPOR FRACTION 107-21-1	Value type	Time Weighted Average (TWA):
	ppm	25
	Remarks	ACGIH
ETHYLENE GLYCOL, VAPOR FRACTION 107-21-1	Value type	Short Term Exposure Limit (STEL):
	ppm	50
	Remarks	ACGIH
ETHYLENE GLYCOL, AEROSOL ONLY, INHALABLE FRACTION 107-21-1	Value type	Short Term Exposure Limit (STEL):
	mg/m³	10
	Remarks	ACGIH
PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, INHALABLE PARTICLES 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
PARTICULATES NOT OTHERWISE CLASSIFIED (PNOC), INHALABLE PARTICULATE 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	MY OEL The value is for particulate matter containing no asbestos and <1% crystalline silica.
PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, RESPIRABLE PARTICLES 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
PARTICULATES NOT OTHERWISE CLASSIFIED (PNOC), RESPIRABLE PARTICULATE 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	MY OEL The value is for particulate matter containing no asbestos and <1% crystalline silica.
CUMENE 98-82-8	Value type	Time Weighted Average (TWA):
	ppm	50
	Remarks	ACGIH
CUMENE 98-82-8	Value type	Time Weighted Average (TWA):
	ppm	50
	mg/m³	246
	Remarks	MY OEL
CUMENE 98-82-8	Value type	Skin designation:

	Remarks	MY OEL Can be absorbed through the skin.
--	----------------	--

Respiratory protection:	Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)
Hand protection:	Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.
Eye protection:	Wear protective glasses. Protective eye equipment should conform to EN166.
Body protection:	Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.
Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
Hygienic measures:	Take off contaminated clothing and wash before reuse. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

Section 9. Physical and chemical properties

Appearance:	white paste
Odor:	mild
Odor threshold (CA):	No data available.
pH:	Not applicable
Melting point / freezing point:	No data available.
Specific gravity:	1.1
Boiling point:	> 149 °C (> 300.2 °F)
Flash point:	> 93.3 °C (> 199.94 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 27 °C (80.6 °F))	< 6.67 mbar
Vapor density:	No data available.
Density:	1.1 g/cm ³
Solubility:	Slightly soluble
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	< 5 %

(2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible materials:	Strong oxidizing agents.
Chemical stability:	Stable under recommended storage conditions.
Conditions to avoid:	Stable under normal conditions of storage and use.
Hazardous decomposition products:	Oxides of carbon.

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
Inhalative toxicity:	Acute toxicity estimate (ATE) : > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Dermal toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
Symptoms of Overexposure:	Prolonged or repeated contact may cause skin irritation. EYE: Irritation, conjunctivitis. RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Acute oral toxicity:

Titanium dioxide 13463-67-7	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	LD50
	Value	382 mg/kg
	Species	rat
	Method	other guideline:
Ethane-1,2-diol 107-21-1	Value type	Acute toxicity estimate (ATE)
	Value	500 mg/kg
	Species	
	Method	Expert judgement
Ethane-1,2-diol 107-21-1	Value type	LD50
	Value	7,712 mg/kg
	Species	rat
	Method	not specified
Ethene, homopolymer 9002-88-4	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
cumene 98-82-8	Value type	LD50
	Value	2,700 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
1,4-Naphthalenedione 130-15-4	Value type	LD50
	Value	190 mg/kg
	Species	rat
	Method	not specified

Acute inhalative toxicity:

Titanium dioxide 13463-67-7	Value type	LC50
	Value	> 6.82 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
cumene 98-82-8	Value type	LC50
	Value	39 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Titanium dioxide 13463-67-7	Value type	LD50
	Value	>= 10,000 mg/kg
	Species	hamster
	Method	not specified
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	LD50
	Value	530 - 1,060 mg/kg
	Species	rat
	Method	other guideline:
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	Acute toxicity estimate (ATE)
	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
Ethane-1,2-diol 107-21-1	Value type	LD50
	Value	10,600 mg/kg
	Species	rabbit
	Method	not specified
Ethene, homopolymer 9002-88-4	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	not specified
cumene 98-82-8	Value type	LD50
	Value	> 10,000 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

Titanium dioxide 13463-67-7	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	Draize Test
Ethane-1,2-diol 107-21-1	Result	not irritating
	Exposure time	20 h
	Species	rabbit
	Method	BASF Test
cumene 98-82-8	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Titanium dioxide 13463-67-7	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethane-1,2-diol 107-21-1	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	BASF Test
Ethene, homopolymer 9002-88-4	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	FDA Guideline
cumene 98-82-8	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Titanium dioxide 13463-67-7	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Ethane-1,2-diol 107-21-1	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Ethene, homopolymer 9002-88-4	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
cumene 98-82-8	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Result	negative
	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Ethane-1,2-diol 107-21-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethane-1,2-diol 107-21-1	Result	negative
	Type of study / Route of administration	oral: feed
	Metabolic activation / Exposure time	
	Species	rat
	Method	Chromosome Aberration Test
Ethene, homopolymer 9002-88-4	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	Ames Test
cumene 98-82-8	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
cumene 98-82-8	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
cumene 98-82-8	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
cumene 98-82-8	Result	negative
	Type of study / Route of administration	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
cumene 98-82-8	Result	negative
	Type of study / Route of administration	inhalation: gas
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte

		Micronucleus Test)
--	--	--------------------

Repeated dose toxicity:

Titanium dioxide 13463-67-7	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Result	
	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
Ethane-1,2-diol 107-21-1	Result	NOAEL=150 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	16 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
cumene 98-82-8	Result	NOAEL=> 535.8 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	not specified
cumene 98-82-8	Result	NOAEL=125 ppm
	Route of application	inhalation: vapour
	Exposure time / Frequency of treatment	14 w6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Toxicity:

Titanium dioxide 13463-67-7	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	Value type	EC0
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	24 h
	Species	Pseudomonas fluorescens
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	LC50
	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss

	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	EC50
	Value	18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	ErC50
	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
α , α -dimethylbenzyl hydroperoxide 80-15-9	Value type	EC10
	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	not specified
Ethane-1,2-diol 107-21-1	Value type	LC50
	Value	72,860 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
	Value type	NOEC
	Value	15,380 mg/l
	Acute Toxicity Study	Fish
	Exposure time	7 d
	Species	Pimephales promelas
	Method	other guideline:
Ethane-1,2-diol 107-21-1	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethane-1,2-diol 107-21-1	Value type	EC50
	Value	> 6,500 - 13,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethane-1,2-diol 107-21-1	Value type	EC20
	Value	> 1,995 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	activated sludge, domestic
	Method	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Ethene, homopolymer 9002-88-4	Value type	LC50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethene, homopolymer 9002-88-4	Value type	EC0
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	not specified
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
cumene 98-82-8	Value type	LC50
	Value	4.8 mg/l

		Acute Toxicity Study	Fish
		Exposure time	96 h
		Species	Oncorhynchus mykiss
		Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
cumene 98-82-8		Value type	EC50
		Value	4 mg/l
		Acute Toxicity Study	Daphnia
		Exposure time	48 h
cumene 98-82-8		Species	Daphnia magna
		Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
		Value type	EC50
		Value	2.01 mg/l
cumene 98-82-8		Acute Toxicity Study	Algae
		Exposure time	72 h
		Species	Desmodesmus subspicatus
		Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
cumene 98-82-8		Value type	EC10
		Value	1.35 mg/l
		Acute Toxicity Study	Algae
		Exposure time	72 h
cumene 98-82-8		Species	Desmodesmus subspicatus
		Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
		Value type	EC10
		Value	211 mg/l
1,4-Naphthalenedione 130-15-4		Acute Toxicity Study	Bacteria
		Exposure time	24 h
		Species	
		Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
1,4-Naphthalenedione 130-15-4		Value type	EC50
		Value	0.011 mg/l
		Acute Toxicity Study	Algae
		Exposure time	72 h
1,4-Naphthalenedione 130-15-4		Species	Dunaliella bioculata
		Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

α , α -dimethylbenzyl hydroperoxide 80-15-9	Result	
	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Ethane-1,2-diol 107-21-1	Result	readily biodegradable
	Route of application	aerobic
	Degradability	90 - 100 %
	Method	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
Ethene, homopolymer 9002-88-4	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	1 %
	Method	ISO 10708 (BODIS-Test)
cumene 98-82-8	Result	
	Route of application	aerobic
	Degradability	86 %
	Method	ISO 10708 (BODIS-Test)
1,4-Naphthalenedione 130-15-4	Result	not readily biodegradable.
	Route of application	no data
	Degradability	0 - 60 %
	Method	OECD 301 A - F

Bioaccumulative potential / Mobility in soil:

α , α -dimethylbenzyl hydroperoxide 80-15-9	Bioconcentration factor (BCF)	9.1
	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
α , α -dimethylbenzyl hydroperoxide 80-15-9	LogPow	2.16
	Temperature	
	Method	not specified

Ethane-1,2-diol 107-21-1	LogPow	-1.36
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
cumene 98-82-8	Bioconcentration factor (BCF)	35.5
	Exposure time	
	Species	Carassius auratus
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
cumene 98-82-8	LogPow	3.55
	Temperature	23 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	LogPow	1.71
	Temperature	
	Method	not specified

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.
Contribution of this product to waste is very insignificant in comparison to article in which it is used

Packaging

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 [P.U.(A) 310/213]
Industry Code of Practice on Chemicals Classification and Hazard Communication

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
TCSI	yes
CH INV	yes
EINECS	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 [P.U.(A) 310/213] only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).