



VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

Issue date: 25/11/2020 Revision date: 20/04/2022 Supersedes: 21/02/2022 Version: 1.2

SECTION 1: Identification of the hazardous chemical and of the supplier

1.1. Product identifier

Name : VT-210 High Performance Sealant

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Sealants

1.4. Supplier details

Manufacturer

Vital Technical Sdn. Bhd.
No.93, Jalan Industri 3/3
Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603 60942088 - F +603 60992930
sales@vitaltechnical.com

1.5. Emergency phone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to Industry Code of Practice on chemicals classification and hazard communication (2019)

Skin sensitisation, Category 1 H317

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

2.2. Label elements

Labelling according to Industry Code of Practice on chemicals classification and hazard communication (2019)

Hazard pictograms (GHS MY) :



Signal word (GHS MY)

: Warning

Contains

: N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE; BUTAN-2-ONE O,O',O"-
(VINYL)SILYLIDYNE)TRIOXIME; BUTAN-2-ONE O,O',O"-
(METHYLSILYLIDYNE)TRIOXIME

Hazard statements (GHS MY)

: H317 - May cause an allergic skin reaction
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS MY)

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 - Contaminated work clothing should not be allowed out of the workplace
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water/...
P321 - Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards that do not result in classification

No additional information available

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Industry Code of Practice on chemicals classification and hazard communication (2019)
BUTAN-2-ONE O,O',O"- (METHYLSILYLIDYNE)TRIOXIME	CAS-No.: 22984-54-9	1 – 10	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute Not classified
BUTAN-2-ONE O,O',O"- (VINYLSILYLIDYNE)TRIOXIME	CAS-No.: 2224-33-1	0.1 – 1	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute Not classified
N-(3- (TRIMETHOXSILYL)PROPYL)ETHYLENEDIAMINE	CAS-No.: 1760-24-3	0.1 – 1	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335

SECTION 4: First-aid measures

4.1. Description of necessary first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	--

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Physicochemical hazards arising from the chemical

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Special protective equipment and precautions for fire fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment, and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters

No additional information available

Exposure limit values for the other components

No additional information available

8.1.1 Biological monitoring

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures, such as PPE

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls

: Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: Various
Odour	: Characteristic odour
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Non flammable.
Explosive limits	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: ≈ 1.02
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Auto-ignition temperature	: ≈ 450 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
VOC content	: ≈ 43.68 g/l

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport
Chemical stability	: Stable under normal conditions
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use
Conditions to avoid	: None under recommended storage and handling conditions (see section 7)
Incompatible materials	: No data available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE (1760-24-3)	
LD50 oral rat	2295 mg/kg
LD50 dermal	2000 mg/kg
BUTAN-2-ONE O,O',O''-(VINYLILIDYNE)TRIOXIME (2224-33-1)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	≈ 2009 mg/kg
BUTAN-2-ONE O,O',O''-(METHYLSILYLIDYNE)TRIOXIME (22984-54-9)	
LD50 oral rat	≈ 2453 mg/kg
LD50 dermal rat	> 2000 mg/kg
Skin corrosion/irritation	: Not classified pH: No data available
Serious eye damage/irritation	: Not classified
Respiratory sensitization	: Not classified
Skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE (1760-24-3)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
BUTAN-2-ONE O,O',O''-(VINYLILIDYNE)TRIOXIME (2224-33-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
BUTAN-2-ONE O,O',O''-(METHYLSILYLIDYNE)TRIOXIME (22984-54-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
VT-210 High Performance Sealant	
Viscosity, kinematic	Not applicable

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

BUTAN-2-ONE O,O',O''-(VINYLILIDYNE)TRIOXIME (2224-33-1)	
LC50 fish 1	1011 mg/l
EC50 other aquatic organisms 1	201 mg/l
BUTAN-2-ONE O,O',O''-(METHYLSILYLIDYNE)TRIOXIME (22984-54-9)	
LC50 fish 1	972.34 mg/l
EC50 other aquatic organisms 1	231.84 mg/l

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

12.2. Persistence and degradability

VT-210 High Performance Sealant

Persistence and degradability	No additional information available
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential

VT-210 High Performance Sealant

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

12.4. Mobility in soil

VT-210 High Performance Sealant

Mobility in soil	No additional information available
------------------	-------------------------------------

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal information

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transportation information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (UN RTDG)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable

14.3. Transport hazard class(es)

UN RTDG

Transport hazard class(es) (UN RTDG)	: Not applicable
--------------------------------------	------------------

IMDG

Transport hazard class(es) (IMDG)	: Not applicable
-----------------------------------	------------------

IATA

Transport hazard class(es) (IATA)	: Not applicable
-----------------------------------	------------------

14.4. Packing Group, if applicable

Packing group (UN RTDG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

14.6. Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

UN RTDG

No data available

IMDG

No data available

IATA

No data available

14.7. Special precautions for user

Not applicable

14.8. Hazchem or Emergency Action Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental regulations specific for the hazardous chemical in question

Regulation	Component/ Mixture
EHS Notification and Registration Scheme	
Environmental Quality (Chlorofluorocarbons Prohibition) Order 1993	Not applicable
Environmental Quality (Industrial Effluent) Regulations 2009	VT-210 High Performance Sealant
Environmental Quality (Scheduled Wastes) Regulations 2007	VT-210 High Performance Sealant
Control of Industrial Major Accident Hazards Regulations 1996	VT-210 High Performance Sealant
Prohibition of Use of Substance Order 1999	VT-210 High Performance Sealant
Use and Standards of Exposure of Chemical Hazardous to Health Regulations 2000	VT-210 High Performance Sealant
Chemical Weapons Convention Act	VT-210 High Performance Sealant
Corrosive and Explosive Substances and Offensive Weapons Act	VT-210 High Performance Sealant
Dangerous Drugs Act	VT-210 High Performance Sealant
Pesticides Act	VT-210 High Performance Sealant
Petroleum (Safety Measures) Act	VT-210 High Performance Sealant
Poisons Act 1952	VT-210 High Performance Sealant
Poisons (Psychotropic Substances) Regulations 1989	VT-210 High Performance Sealant

15.2. International agreements

No additional information available

SECTION 16: Other information

Version : 1.2
Issue date : 25/11/2020
Revision date : 20/04/2022
Supersedes : 21/02/2022

VT-210 High Performance Sealant

Safety Data Sheet

according to ICOP 2014,2019

Full text of H-statements	
Acute Tox. Not classified (Dermal)	Acute toxicity (dermal) Not classified
Acute Tox. Not classified (Oral)	Acute toxicity (oral) Not classified
Aquatic Acute Not classified	Hazardous to the aquatic environment – Acute Hazard Not classified
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage or eye irritation, Category 1
Eye Irrit. 2	Serious eye damage or eye irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), Malaysia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.