

SAFETY DATA SHEET

PRODUCT NAME: KRYSTAL AEROSOL PAINT

Page 1 of 5
Date of Printed: 29-May-17
SDS/KAP/R1C2/MAY17

SECTION I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME : KRYSTAL AEROSOL PAINT

CHEMICAL NAME/FAMILY NAME : Mixture of Acrylic Based Lacquer and Propellants

CAS No : None assigned

MANUFACTURER : WILRON PRODUCTS SDN. BHD.
No 5, Jalan Pelabur 23/1
40300 Shah Alam
Selangor Darul Ehsan
Malaysia

Telephone : 603 - 5541 0612
Fax : 603 - 5541 0132

SECTION II. INFORMATION ON INGREDIENT

Paint Mixture

<u>Ingredient</u>	<u>CAS no.</u>	<u>% Range</u>	<u>Exposure limit</u>
Toluene	108-88-3	20.0 - 60.0 %	100 ppm TWA
Acetone	67-64-1	20.0- 40.0 %	1000 ppm TWA
Synthetic Resin	-	30.0 - 50.0 %	Not Available

Propellants

Propane	74-98-6	60.0 - 70.0 %	1000 ppm TWA
Butane	106-97-8	30.0 - 40.0 %	800 ppm TWA

SECTION III PHYSICAL DATA

Paint Mixture

Material state : Mixture of Acrylic and Organic Solvents

Physical state : Low Viscosity Liquid

Appearance and odor : Pigmented Lacquer; odorless

Vapor Pressure (mm/Hg) : Not available

Vapor Density (Air=1) : Not available

Evaporation Rate : More than 1

Viscosity : 12.0-14.0 secs (Ford Cup 4/26°C)

Specific Gravity : 0.80-1.00

Solubility in Water : Negligible

Flash Point (°C) : -100.0(+/-1)

WILRON PRODUCTS SDN. BHD. (52720- X)

SAFETY DATA SHEET

PRODUCT NAME: KRYSTAL AEROSOL PAINT

Page 2 of 5
Date of Printed: 29-May-17
SDS/KAP/R1C2/MAY17

Propellants

Material state	: Mixture of Propane and Butane
Physical state	: Liquified gas
Appearance	: Not applicable
Odor Threshold (ppm)	: Not applicable
Vapor Pressure (psi, 20°C)	: 70.0-80.0
Viscosity	: Not applicable
Specific Gravity	: Not applicable
Solubility in water	: Negligible (Butane, Propane)
Flash Point (°C)	: -100.0(+/-1)
In can pressure (psi)	: 50.0-60.0

SECTION IV. FIRE & EXPLOSION DATA

Flammability	: Yes, vapour can cause flash fires & ignite explosively
Upper Flammable Limit	: 10-15%
Lower Flammable Limit	: 1 -2%
Auto Ignition Temperature	: Not Available
Sensitivity to Mechanical Impact No	: Yes
Sensitivity to Static Discharge	: Yes
Explosion or Fire Hazardous	: Vapors can cause flash fires & may ignite explosively.
Hazardous Combustible Products	: Carbon monoxide, carbon dioxide, hydrocarbon of undetermined nature (depending on environmental condition & reactive product present)

SECTION V. REACTIVITY DATA

Stability	: Stable
Incompatibilities	: Incompatible with strong oxidizing agents e.g.: hypochlorite & peroxides
Hazardous Decomposition Products	: None

SECTION VI. FIRE FIGHTING MEASURES

Extinguishing media	: Foam, CO ₂ and dry chemical.
Special Fire Fighting Procedure	: Water or water foam may cause frothing if sprayed directly into container of hot burning liquid. This may be hazardous to fire-fighters. Best for fire-fighters to be equipped with breathing apparatus as protection against irritation or toxic fumes.

SAFETY DATA SHEET

PRODUCT NAME: KRYSTAL AEROSOL PAINT

Page 3 of 5
Date of Printed: 29-May-17
SDS/KAP/R1C2/MAY17

SECTION VII. TOXICOLOGY PROPERTIES

Route of entry	: Skin contact, skin absorption, eye contact, inhalation & ingestion.
Effect of acute exposure - Ingestion	: May cause headache, fatal.
Effect of acute exposure - Skin contact	: Prolonged repeated contact may lead to skin dryness and/or irritation leads to dermatitis
Effect of acute inhalation	: High vapor concentrations are irritating to the eyes and respiratory tract. May caused headaches, drowsiness & dizziness.
Effect of acute eye contact	: Unknown.
Effect of long term chronic	: Unknown.

SECTION XIII. EXPOSURE CONTROL AND PERSONAL PEOTECTION

Personal protective equipment	: Not required.
Gloves	: Latex, if in prolonged contact.
Respirator	: Not required under normal handling condition. If required when high vapor or mist level is present or irritates, use NIOSH approved respirator.
Eye	: Not required.
Footwear	: Not required.
Clothing	: Not required.
Engineering controls	: Local, good to use in well ventilated area or open air to reduce vapor built-up.

SECTION IX. ACCIDENTAL RELEASE MEASURE

Leak & Spill Procedure	: i) Extinguish all heat & ignition source. Do not operate electrical or sparking devices e.g.: heaters, motors etc. Keep off naked flame & no smoking. ii) Stop the leak if it does not endanger you. iii) For small spill take up with sand or absorbent material or clay. For large spill dig up material and use absorbent or call in professional disposal service.
------------------------	--

SECTION X. HANDLING AND STORAGE

Handling procedure and equipment	: Normal, keep away from naked flame
Storage	: Store in normal ambient temperature. Store in dry & cool place away from naked flame and freezing.

SAFETY DATA SHEET

PRODUCT NAME: KRYSTAL AEROSOL PAINT

Page 4 of 5
Date of Printed: 29-May-17
SDS/KAP/R1C2/MAY17

SECTION XI. FIRST AID MEASURES

Ingestion : If individual is conscious, give milk or water to dilute stomach contents. DO NOT induce vomiting. Keep warm, quiet & get immediate medical attention.

Skin Contact : Flush with large amount of water & soap affected area if necessary.

Inhalation : Move patient to well ventilated area with plenty of fresh air. If there is breathing difficulties, give artificial respiration. Get immediate medical attention.

Eye : Flush with large amount of water holding eyelids open. Get medical help immediately. Cured adhesive may not bond well to surface result of abrasion.

SECTION XII. ECOLOGICAL INFORMATION

Prolonged or repeated contact may cause chronic dermatitis, chemical pneumonitis.

Appreciable evaporation to air is expected in the environment.

SECTION XIII. DISPOSABLE CONSIDERATION

The following advice only applies to the product supplied.

Combination with other materials may well indicate another route of disposal.

Empty can should be disposed through a suitably qualified or licensed contractor. Care should be taken in any case to ensure compliance with EC, national and local regulations

This product is not suitable for disposal by either landfill or via municipal sewers, drain, natural streams or rivers.

SECTION XIV. INFORMATION ON TRANSPORTATION

Shipping and Land Transport Information

UN NUMBER : 1950
LPK CLASS : 3
IMDG : 9022

SAFETY DATA SHEET

PRODUCT NAME: KRYSTAL AEROSOL PAINT

Page 5 of 5
Date of Printed: 29-May-17
SDS/KAP/R1C2/MAY17

SECTION XV. REGULATORY INFORMATION

CLASSIFICATION AND LABELLING

Classification/Symbol : Flammable
Classification/Symbol : Harmful
Governing Directive : Occupational and Health (Classification, Packaging and Labeling of Hazardous Chemical) Regulations 1997

Nature of special risk

R 10 Flammable
R48/20 Danger of serious damage to health by prolong exposure through inhalation

Safety advice

S09 Keep container in a well ventilated place
S16 Keep away from sources of ignition - No smoking
S43A In case of fire use sand, earth, chemical powder or foam

SECTION XVI. OTHER INFORMATION

This information given applies only to our specific product and may not be valid for such material used in combination with other products. Such information is to the best of our knowledge and belief, accurate and reliable as of the date completed. No warranty or guarantee is made as to its accuracy or reliability. It is the user's responsibility to evaluate the suitability of the product and we do not accept liability for any loss or damage that may occur from the use of this information.