

RISALAH DATA KESELAMATAN KIMIA

Chemical Safety Data Sheet

1. PENGENALPASTIAN BAHAN KIMIA & SYARIKAT CHEMICAL PRODUCT & COMPANY IDENTIFICATION			
1.1 Butir-butir Pengenalan Introductory Details			
Mukasurat			
Pages		1 to 4	
Tarikh dikeluarkan			
Date of issued		12 January 2010	
Penyemakan			
Revision		0	
1.2 Maklumat Produk Product Details			
Nama Produk / Dagangan			
Product / Trade Name		PP Retarder KS237	
Kegunaan			
Use		Thinner for printing inks, paints and coatings	
1.3 Pengenalpastian Syarikat			
Nama Pembekal		HAI KUANG PACKING INDUSTRIES SDN BHD	
Supplier		51 Jalan Datuk Haji Eusoff, Damai Kompleks, 50400 Kuala Lumpur	
		Tel:+03-40420071 Fax:+03-40423425	
Nombor Telefon & No. Kecemasan			
Telephone Number & Emergency No.		+03-40420071 (Office hours – Mon to Fri: 9.00am to 5.00pm)	
1.4 Titik Hubungan Contact Point			
Gelaran Jawatan		SWWong	
Designation		Manager	
Nombor Telefon		+03-61874177	
Telephone Number			
2. KOMPOSISI / MAKLUMAT BAHAN COMPOSITION / INFORMATION ON INGREDIENT			
Bahan-bahan Merbahaya Hazardous Ingredients	Kadaran Conc-%	Had Pendedahan Exposure Limit	Data Risiko Risk Phrase
Mixtures of aromatic	> 99 50 ppm, TWA (ACGIH)	R10 / 20 / 36 / 37 / 38 / 65	hydrocarbons (C ₁₀ -C ₁₂)
[The composition is proprietary information. In the event of a medical emergency, composition information will be provided to a doctor]			
3. SIFAT-SIFAT FIZIKAL DAN KIMIA PHYSICAL & CHEMICAL PROPERTIES			
Rupa Appearance	Clear, colorless	Takat didih Boiling point °C	Range from 184 - 205
Bau Odour	Mild aromatic	Takat kilat Flash point °C	63 (TCC)
Graviti Tentu Specific Gravity	090 ± 0.05	Had kemudahan bakaran Flammability - %	LEL: 1.8 UEL: 11
Bahan mudah meruap % Volatile content - %	100	Kebolehlarutan Solubility in Water	Insoluble
Keupatan wap Vapor density (Air=1)	> 1		

RDKK...samb.

CSDS...cont.

Identiti Produk

Product Identification: PP Retarder KS237

4. PENGENALPASTIAN BAHAYA HAZARD IDENTIFICATION	
Bahaya yang utama Most Important hazards	Flammable, irritant, harmful
Laluan kemasukkan Likely routes of entry	Dermal absorption, inhalation Penyedutan
Inhalation	May cause irritation to respiratory tract system. High concentration vapor exposure may cause nausea, dizziness, fatigue, headache
Mata	
Eyes	Direct contact may cause irritation, redness, tearing, blurred vision, conjunctivitis
Kulit	
Skin	Prolonged or repeated contact may cause moderate irritation, redness, defatting, itching
Ingesan	
Ingestion	Harmful if swallowed. May cause lung damage if swallowed.
5. LANGKAH-LANGKAH PERTOLONGAN CEMAS FIRST AID MEASURES	
Sedutan Inhalation	Remove to fresh air, avoid exertion. Seek medical attention if necessary
Mata	
Eyes	Flush with plenty of water. Seek medical attention
Kulit	
Skin	Flush with plenty of water. If irritation persists, seek medical attention
Ingesan	
Ingestion	Keep at rest, do not induce vomiting. Seek medical attention Umum
General	In all cases of doubt or when symptom persists, seek medical attention
6. LANGKAH-LANGKAH PEMADAMAN KEBAKARAN FIRE FIGHTING MEASURES	
Media pemadaman Extinguisher Media	Carbon dioxide, alcohol resistant foam, dry chemical for small fires. DO NOT use water Arahan
pencegahan api Fire-fighting instruction	Use fine water spray to cool fire exposed containers and to protect personnel. Shut off 'fuel' to fire. Extinguish fire with foam or dry chemical or allow fire to burn under controlled conditions Use protective equipment for fire-fighters; self-contained breathing apparatus and full protective clothings.
Bahan-bahan utama Special hazards (if any)	Containers may explode in the heat of fire. Irritating or toxic substances maybe emitted during thermal decomposition.

RDKK...samb.

CSDS...cont.

Identiti Produk

Product Identification: PP Retarder KS237

7. LANGKAH-LANGKAH BAGI MENGHADAPI PELEPASAN TIDAK SENGAJA ACCIDENTAL RELEASE MEASURES	
Kebocoran /Tumpahan Leak / Spill	Contact emergency personnel immediately. Eliminate all igniton sources. Contained spillage. Dispose off as per local state regulations.
8. PENGENDALIAN & PENYIMPANAN HANDLING & STORAGE	
Pengendalian & penyimpanan Handling & storage	Handle product in accordance with safe handling practises. Store in cool, dry, well ventilated area and away from excessive heat and sources of ignition. Avoid excessive contact with skin, clothing and eyes. Observe good personal hygiene practices.
9. KAWALAN PENDEDAHAN & PERLINDUNGAN DIRI EXPOSURE CONTROL & PERSONAL PROTECTION	
a.Had pendedahan Exposure limit	50 ppm, TWA (ACGIH)
b.Pengalihudaraan Engineering measures	Local exhaust ventilation and good general extraction. All areas well ventilated.
c.Perlindungan diri Personal protection	Repirator, face mask, safety googles, chemical resistant gloves, overall where necessary (NIOSH approved)
10. KESTABILAN & KEREAKTIFAN STABILITY & REACTIVITY	
Keadaan yang perlu dielak Condition to avoid	Oxidizing agents, reducing agents, acid, alkali
Bahan tak serasi Incompatibility	Reactive materials – oxidizing and reducing agents
Decomposition products	Carbon monoxide, carbon dioxide, toxic gases
Pempolimeran berbahaya Hazardous polymerization	Will not occur
[Product is stable under ambient storage condition]	
11. MAKLUMAT TOKSIKOLOGI TOXICOLOGICAL INFORMATION	
Data toksikologi Toxicology data	Specific data is not determined. Product is low in toxicity.
12. MAKLUMAT EKOLOGI ECOLOGICAL INFORMATION	
Biodegradasi Biodegradation	Not determined and data not available. Do not dispose off into drains, water courses or be deposited where it can affect ground or surface water
13. MAKLUMAT PEMBUANGAN DISPOSAL INFORMATION	
Residual waste / unused product	Incinerate or dispose off in compliance to local regulations
Contaminated packaging	Empty containers to be disposed off in accordance to local regulations

RDKK..samb.

CSDS...cont.

Identiti Produk

Product Identification: PP Retarder KS237

14. MAKLUMAT PENGANGKUTAN INFORMATION			TRANSPORT
Nombor UN UN Number	1268		
Designasi Designation	Flammable liquid		
Klasifikasi TDG TDG Classification	Not available		
Kumpulan Pembungkusan Packing Group	III		
Arahan Penghantaran Khas Special Shipping Instruction	Environmentally Hazardous Liquid		
15. MAKLUMAT PENGAWALAN INFORMATION			REGULATORY
The product is classified and labelled for supply in accordance to the Occupational Safety and Health (Classification, Packaging and Labelling of Hazardous Chemicals) Regulations 1997 as follow:			
Classification	Flammable Harmful		
Risk phrase	10..... Flammable 20/21/22..... Harmful by inhalation, in contact with skin and if swallowed 36/37/38..... Irritating to eyes, respiratory system and skin 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 65 Harmful: may cause lung damage if swallowed.		
Safety phrase	16..... Keep away from sources of ignition-“NO SMOKING” 20/21..... When using do not eat, drink or smoke 23..... Do not inhale vapors 24/25..... Avoid contact with skin and eyes 26..... In case of contact with eyes, rinse immediately with plenty of water and seek advice. 29..... Do not empty into drains 37/39..... Wear suitable gloves and eye/face protection 43A..... In case of fire, use carbon dioxide, alcohol resistant foam or dry chemical. USE WATER.	medical	NEVER
16. MAKLUMAT LAIN INFORMATION			OTHER
This information is applicable to the product as stated only. The information and data contained herein is based on our present state of knowledge. It provides guidance on health, safety and environmental aspects of the product. It does not constitute a guarantee for product characteristics and technical performance. No warranty is expressed or implied as conditions of product application is outside manufacturer's control. The user is responsible to ensure that the product satisfy his/her requirement and can be handled safely			

Approved by: SWW