



"Certificazione UNI-EN 14001 riferita ai siti di Pogliano Milanese e di Laini"

Revision nr.13
Dated 20/09/2007
Printed on 19/10/2007
Page n. 1 / 6

Safety Data Sheet

1. Identification of the substance / preparation and the Company

1.1 Identification of the substance or preparation

Product name **LR 10050 COD 64**
Chemical name and synonym **SOLVENT BASED SILICONE COMPOUND**

1.2 Use of the substance / preparation

Intended use **RELEASE AGENT**

1.3 Company identification

Name **MARBO ITALIA S.p.A.**
Full address **Via T.Tasso 25/27**
District and Country **20010 Pogliano Milanese MI**
ITALIA
Tel. **+39 02 93961.1**
Fax **+39 02 93550048**

e-mail address of the competent person **info@gruppomarbo.com**

Product distribution by **MARBO ITALIA S.p.A.**

1.4 Emergency telephone

2. Hazards Identification

2.1 Substance/Preparation Classification

This preparete is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this preparete requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: **Xn-N**
Phrases R: **38 - 40 - 50/53 - 65 - 67**

2.2 Danger Identification

IRRITATING TO SKIN.
LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.
VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.
Because of its particular formula, this product may catch fire during use following the evaporation of non-flammable volatile components.



"Certificazione UNI-EN 14001 riferita ai siti di Pogliano Milanese e di Lodi"

Revision nr.13
Dated 20/09/2007
Printed on 19/10/2007
Page n. 2 / 6

3. Composition / Information on ingredients

Contains:

Name	Concentration C	Classification
HEPTANE	30,00<= C <45,00	Xn R65 Xi R38 R67 F R11 N R50/53 Note C 4
<i>C.A.S. number</i> 142-82-5 <i>EEC number</i> 205-563-8 <i>INDEX number</i> 601-008-00-2		
DICHLOROMETHANE	50,00<= C <65,00	Xn R40 Carc. Cat. 3
<i>C.A.S. number</i> 75-09-2 <i>EEC number</i> 200-838-9 <i>INDEX number</i> 602-004-00-3		

The complete text of -R- phrases is specified in section 16.

4. First aid measures

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

INHALATION: Remove to open air. If breathing is irregular, seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Closed containers exposed to the heat of a fire may lead to pressure rise and explode. For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures, refer to the other sections of this sheet.

Extinguishing measures: CO₂, foam, chemical powder for flammable liquids. Water may not be effective to extinguish the fire, nevertheless it should be used to cool the containers exposed to flames and prevent fires and explosions. For leakage and spillage that have not caught fire, nebulized water may be used to disperse the flammable vapours and protect the people involved in stopping the leakage.

Equipment: wear equipment complete with helmet and face shield and protection of the neck, selfbreathing apparatus at pressure or demand, insulative jacket and trousers, with bands around the arms, legs and waist.

6. Accidental release measures

Exclude sources of ignition. Cover with inert absorbent material. Collect spillages by means of sparkproof equipment. Use water only to remove residuals, so as not to run the risk of entering the sewer.

Do not let the product dry. Contaminated clothes must be left to soak in water before washing. In order to choose safety measures and protection equipment, please see the other sections of this sheet.

Spillage in waters: remove the liquid from the surface with flameproof pumps or manual pumps or suitable absorbent material. Resort to sinking and/or dispersion of the product with suitable substances in open waters, if permitted by the law.



"Certificazione UNI-EN 14001 riferita ai siti di Pogliano Milanese e di Laini"

Revision nr.13
Dated 20/09/2007
Printed on 19/10/2007
Page n. 3 / 6

7. Handling and storage

Avoid the accumulation of electrostatic charges. Store the containers sealed and in a well ventilated place. Vapours may ignite with explosion, it is therefore necessary to avoid accumulation keeping the windows and doors open, ensuring crossventilation.

Without adequate ventilation, the vapours may accumulate at the bottom and ignite at a distance, if triggered off, with the risk of flashback. Keep far away from sources of heat, sparks and naked flames. Do not smoke, use matches or lighters. Keep the containers earthed while decanting and wear antistatic boots.

Vigorous stirring and flow through the pipings and equipment may cause the formation and accumulation of electrostatic charges due to the low conductivity of the product. In order to avoid the risk of fire outbreak and explosion never use compressed air during movement.

8. Exposure control / personal protection.

8.1 Exposure limit values

Product name	Type	State	TWA/8h		STEL/15min		
			mg/m3	ppm	mg/m3	ppm	
HEPTANE	TLV-ACGIH		1640		2050		Skin
	OEL	EU	2085				Skin
	OEL	IRL		400			Skin
	WEL	UK		500			Skin
DICHLOROMETHANE	TLV-ACGIH		174				Skin
	OEL	IRL		50	300		Skin
	WEL	UK		100	300		Skin

8.2 Exposure controls

Adopt the closed circuit, if possible. If lacking, in order to avoid exposure and prevent its possible effects, even longterm, it is necessary to use adequate individual protective measures, such as: mask, safety goggles, impermeable gloves and overall, resistant to the product.

Ensure that all the operators follow the recommended precautions. Attach a copy to the containers in which the product may be transferred and do not use the product if the working conditions do not correspond to the recommended precautions; avoid contact with the eyes and skin and prolonged breathing of the vapours; store the container sealed when not being used.

Do not eat, drink or smoke while handling the product. Accurately wash the hands with soap and water before meals and take a shower at the end of the work shift. Working clothes should be washed separately and stored in a separate place.

In order to prevent longterm effects, periodic health controls should be carried out even if not established by the Law, including supplementary examinations which are deemed necessary according to the discretion of the occupational physician.

9. Physical and chemical properties

Colour	COLOURLESS
Odour	TYPICAL
Appearance	LIQUID
Solubility	INSOLUBLE IN WATER
Viscosity	N.A.
Vapour density	>1
Evaporation Rate	N.A.
Reactive Properties	N.A.



Certificazione UNI-EN 14001 riferita ai siti di Pogliano Milanese e di Laini

Revision nr.13
Dated 20/09/2007
Printed on 19/10/2007
Page n. 4 / 6

Partition coefficient: n-octanol/water	N.A.		
pH	N.A.		
Boiling point	N.A.		
Flash point	> 61	°C	
Explosive properties	N.A.		
Vapour pressure	N.A.		
Specific gravity	0,970	Kg/l	
VOC (Directive 1999/13/EC) :	95,00 %	- 921,50	g/litre of preparation
VOC (volatile carbon) :	39,90 %	- 387,03	g/litre of preparation

10. Stability and reactivity

The product is stable in normal conditions of use and storage. Due to thermal decomposition or in the event of a fire vapours may be produced potentially dangerous to health.

Dichloromethane decomposes at temperatures > 120 °C forming toxic fumes of phosgene and corrosive fumes of hydrochloric acid. With water and alkalis, it may give off hydrochloric acid and attack aluminium, copper and alloys; it is not flammable and with air it can form explosive mixtures only in case of strong triggers like flames, electric arcs etc...

11. Toxicological information

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Contact with eyes may cause slight irritation. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product must be handled carefully because of its possible carcinogenic effects. Anyway, currently available data do not allow us to comprehensively assess this product.

Dichloromethane - Acute toxicity in man: cognitive disorders only if inhaled at very high doses; at 200-500 ppm, nausea, vomiting, dizziness, paresthesia, asthenia and headache have been observed. Skin contact causes pain which soon disappears without any burns. Superficial lesions of the cornea occur on contact with the eyes.

Chronic toxicity: the substance is considered by the EEC as probably carcinogenic (category 3) and possibly carcinogenic by ACGIH (category 2).

Epidemiologic studies with exposure around 200 ppm (700 mg/cu.m) revealed no effects on health. Dermatitis may result upon repeated contact. The limit of exposure on an 8 hour work day according to ACGIH is 174 mg/cu.m.

12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it may even have negative effects on the aquatic environment.

The paraffinic hydrocarbons present may be considered biodegradable in water and in air. They distribute mostly in the air. The small amount that is distributed in water and is not biodegradable tends to be accumulated by fish.

HEPTANE

LC50 (96h) 375 mg/l Tilapia mossambica

EC50 (48h) 82,5 mg/l Daphnia magna

IC50 (72h) 1,5 mg/l Algae

13. Disposal consideration

Consider the possibility of burning the product in a suitable incenerator.

Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

14. Transport information

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR/RID:	6.1	UN:2810
Packing Group:	III	
Label:	6.1	
Nr. Kemler:	60	
Proper Shipping Name:	Toxic liquid, organic, n.o.s. (DICHLOROMETHANE)	

Carriage by sea (shipping):

IMO class:	6.1	UN:2810
Packing Group:	III	
Label:	6.1	
EMS:	F-A, S-A	
Proper Shipping Name:	Toxic liquid, organic, n.o.s. (DICHLOROMETHANE)	

Transport by air:

IATA:	6.1	UN:2810
Packing Group:	III	
Label:	6.1	
Cargo:		
Packaging instructions:	618	Maximum quantity: 220 L
Pass.:		
Packaging instructions:	611	Maximum quantity: 60 L

15. Regulatory information

Xn



HARMFUL

N



DANGEROUS FOR THE ENVIRONMENT

R38	IRRITATING TO SKIN.
R40	LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.
R50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.
S13	KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDINGSTUFFS.
S25	AVOID CONTACT WITH EYES.
S29	DO NOT EMPTY INTO DRAINS.
S36/37	WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.



"Certificazione UNI-EN 14001 riferita ai siti di Pogliano Milanese e di Laini"

Revision nr.13
Dated 20/09/2007
Printed on 19/10/2007
Page n. 6 / 6

S61 AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.
S62 IF SWALLOWED, DO NOT INDUCE VOMITING; SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.

Contains:

DICHLOROMETHANE

HEPTANE

May easily become flammable during use.

Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.

Workers exposed to this chemical agent must undergo health checks according to regulation 98/24/EC.

16. Other information

Text of -R- phrases quoted in section 3 of the sheet.

R65 HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R38 IRRITATING TO SKIN.
R50/53 VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R67 VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.
R11 HIGHLY FLAMMABLE.
R40 LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments;
2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament;
4. The Merck Index. - 10th Edition;
5. Handling Chemical Safety;
6. Niosh - Registry of Toxic Effects of Chemical Substances;
7. INRS - Fiche Toxicologique (toxicological sheet);
8. Patty - Industrial Hygiene and Toxicology;
9. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review

The following sections were modified:

03/08/09/12