

MATERIAL SAFETY DATA SHEET

Product Name: SPU 6-22	File name: msds-6-22-5
Date of Preparation: 11/01/2022	Issue No: 6 Pages: 4

SECTION 1 : CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name	SPU 6-22	Use : De-ruster
Manufacturer's Name	: UNASCO (M) SDN.BHD.	
Address	: No.1, Jln PJU 1A/18, Tmn Perindustrian Jaya Subang, 46050 Petaling Jaya, Selangor.	Tel No : 03-78473468
Emergency Tel. No.	: 03-78473468	
Contact point	: Technical Manager	Tel. No. : 03-78473468

SECTION 2 : COMPOSITION/INFORMATION OF INGREDIENT

Chemical Name	CAS No.	Proportion	Exposure Limit
Phosphoric acid	7664-38-2	>20%	1 mg/m ³

SECTION 3 : PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Green liquid		
Solubility in water	Complete	Melting Point	N/A °C
Boiling Point	N/A °C	Flash Point	N/A °C
Auto-ignition temperature	N/A °C	Flammable Limit	Non flammable
Specific Gravity	1.320	pH Value	<1 (Neat)

SECTION 4 : HAZARD IDENTIFICATION

Most important hazard :	Cause burns. Risk of serious damage to eyes.
-------------------------	---

SECTION 5 : FIRST AID MEASURE

Ingestion	Do not induce vomiting. Give large quantities of water and seek medical attention immediately.
Eye contact	Immediately flush with running water for at least 15 minutes. Seek medical attention without delay.
Skin contact	Immediately remove contaminated clothing and shoes-laundry before re-use. Wash skin thoroughly with water. Seek medical advice if redness and irritation occurs.

MATERIAL SAFETY DATA SHEET

Product Name: SPU 6-22	File name: msds-6-22-5
Date of Preparation: 11/01/2022	Issue No: 6 Pages: 4

Inhalation	Remove to fresh air. Give artificial respiration if not breathing. Seek medical attention immediately.
------------	--

SECTION 6 : FIRE FIGHTING MEASURE

Extinguishing Media	Select extinguishing media suitable for surrounding fire.
Fire fighting instruction	Wear self-contained breathing apparatus and protective clothing. Cool fire exposed container with water spray.
Special Hazard	Contact with most metals causes formation of flammable and explosive hydrogen gas.

SECTION 7 : ACCIDENTAL RELEASE MEASURE

Leak and / or Spill	Ventilated area of spill. Wear appropriate personal protective equipment. Contain and recover liquid when possible. Neutralize with alkaline material (soda ash, lime), then absorb with an inert material (dry sand, earth), and place in a chemical waste container for disposal. Wash spillage area with plenty of water.
---------------------	---

SECTION 8 : HANDLING AND STORAGE

Handling	When diluting ALWAYS ADD ACID TO WATER, NEVER WATER TO ACID. Avoid contact with eyes and skin. Wash thoroughly after handling.
Storage	Store in a cool, dry, ventilated storage area. Keep out of direct sunlight and away from heat, and incompatible materials.

SECTION 9 : EXPOSURE CONTROL AND PERSONAL PROTECTION

a. Exposure Limit	ACGIH: TLV: phosphoric acid: 1 mg/m ³ (TWA).
b. Ventilation	Use general or local exhaust ventilation to meet exposure limit requirement. Use only with adequate ventilation.
c. Personal protection	
Eye	Use chemical safety goggles and /or face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.
Skin	Use protecting clothing, gloves, boots to prevent body contact with the liquid.
Respiratory protection	Use NIOSH approved respirator in absence of proper ventilation.

SECTION 10: STABILITY AND REACTIVITY

Condition to avoid	Incompatibles.
Incompatibles	Strong base, most metals, cyanides etc.
Decomposition products	Phosphorus oxides may form when heated to decomposition.
Hazardous Polymerization	Will not occur.

MATERIAL SAFETY DATA SHEET

Product Name: SPU 6-22	File name: msds-6-22-5
Date of Preparation: 11/01/2022	Issue No: 6 Pages: 4

SECTION 11 : ECOLOGICAL INFORMATION	
Mobility	Soluble in water.
Bioaccumulation	N/A
Biodegradability	N/A
Aquatic Toxicity	High concentration will injure aquatic life by the effect on pH. Do not discharge directly into river, pond or stream.

SECTION 12 : TOXICOLOGICAL INFORMATION	
Toxicity Data	Phosphoric acid Oral LD ₅₀ (rat) : 1530 mg/kg
Carcinogenicity	N/A
Effects of overexposure	
Route of entry	Effects
Inhalation	Can cause irritation to nose, throat and upper respiratory tract.
Skin contact	Corrosive. May cause redness, pain, and severe skin burns.
Eye contact	Corrosive. May cause redness, pain, blurred vision, eye burns, and permanent eye damage.
Ingestion	Corrosive. May cause sore throat, abdominal pain, nausea, and severe burns of the mouth, throat, and stomach.
Chronic Effects	No information found.
Target Organs	N/A
Medical conditions generally aggravated by exposure	N/A

SECTION 13 : DISPOSAL INFORMATION
Disposal of waste to be in accordance with the Environmental Quality (Scheduled Wastes) Regulation 2005 and other guidelines issued by DOE and /or local authorities.

SECTION 14 : TRANSPORT INFORMATION	
UN/NA Number	UN 3264
T.D.G classification	Class 8
Packing group	III
Special Shipping instruction	N/A

SECTION 15 : REGULATORY INFORMATION	
a. Proposed classification :	Corrosive.

MATERIAL SAFETY DATA SHEET

Product Name: SPU 6-22		File name: msds-6-22-5
Date of Preparation: 11/01/2022	Issue No: 6	Pages: 4

b. Risk phrase :	R34	Cause burns.
	R41	Risk of serious damage to eyes.
c. Safety phrase :	S26	In case of contact with eyes, rinse immediately with large amount of water and seek medical advice.

SECTION 16: OTHERS INFORMATION

The data given here is based on our current knowledge and experience. The purpose of this Safety Data sheet is to describe the product in terms of their health and safety requirements. Since the conditions of use are outside our UNASCO's control, any recommendations or suggestions are made without guarantee and UNASCO disclaims any liability for loss or damage suffered from use of this information. Users are responsible for safe working.