Supplementary material

Subject-independent forearm sEMG electrode reduction with cross-fitted attribution and non-inferiority testing

This supplement distinguishes internally planned primary criteria, historical secondary analyses and new exploratory validation. Full-precision CSV files accompany the tables; these files and the numeric/figure provenance are the quantitative record.

S1 Development chronology and departures

The internally dated statistical plan was written after an earlier pilot and before the complete reduced-count curve according to the project record. The repository has no commits and no external registration confirming that chronology. The primary 0.02 tolerance, participant unit and bootstrap rule were retained. Detailed secondary test families were specified after their underlying results existed. Budget calibration used test outcomes for participants 1 and 7. Count-feature thresholds were historically pooled and subsequently checked for invariance to exclusion. These disclosures qualify prospective or completely untouched-cohort language.

The original Holm count analysis was completed after the primary curve. The new null-centred analysis is an exploratory statistical sensitivity, not a retrospective replacement of the original plan. Fixed layouts, feature redundancy and individual attribution aggregation were added post hoc. The 2026-10-14 revision additionally retained matched predictions, tested primary-protocol geometric12, shared inner resources between SHAP and grouped permutation, completed the window curves, verified Rest17 and tested a fixed-count random forest. Protocols and eight amendments record the exploratory chronology. Each amendment preceded its own additional computation; the full geometric curve and seed diagnostic followed the initial geometry12 and split-layout outcomes, and the selector-activity audit followed the completed penalty results. No penalty, margin or seed was selected to make a gate pass.

The original CNN/integrated-gradients and mRMR ideas were not executed. No result is supplied for those analyses. No fresh independent cohort with the GRABMyo montage was available; an external validation experiment is a proposed next study.

S2 Feature-chain and threshold checks

Raw-record spot re-extraction, cache-to-feature-table correspondence and prediction-label alignment are checked in the feature-chain report. The primary active cache contains 563,472 windows. Participant exclusion reproduced the rounded monopolar threshold in 43 of 43 folds and the DB5 threshold in 10 of 10 folds. This confirms numerical invariance of the stored threshold, not a prospective fold-wise estimation sequence. Amplitude units and quantized DB5 values are kept distinct. Rest and alternate windows are re-extracted from real raw records; no windows cross trial boundaries.

Implemented filter and feature definitions For DB5, all 21089 saved feature rows were reconstructed exactly from the ten raw exercise files. The common filter function clips the requested upper cutoff to $\min(f_{\text{requested}}, 0.45 f_s - 1)$, giving 10–89 Hz at its sampling rate, although the original extraction report printed the requested 95 Hz. The filtering code and saved features are preserved; this correction changes reporting, not model inputs or outcomes. The band-pass design argument is four, giving eight poles before forward–backward application. GRABMyo's requested upper limit is below this clipping cap.

For one channel, let x_t, $t = 1, \ldots, T$, denote the filtered window, $\bar{x}$ its mean and $d_t = x_{t+1} - x_t$. The implemented amplitude features are

$$\text{MAV} = T^{-1} \sum_{t=1}^{T} |x_t|, \qquad \text{RMS} = \sqrt{T^{-1} \sum_{t=1}^{T} x_t^2},$$

$$\text{VAR} = T^{-1} \sum_{t=1}^{T} (x_t - \bar{x})^2, \qquad \text{WL} = \sum_{t=1}^{T-1} |d_t|,$$

$$\text{IEMG} = \sum_{t=1}^{T} |x_t|, \qquad \text{WAMP} = \sum_{t=1}^{T-1} \mathbf{1}\{|d_t| \geq \tau\}.$$

Variance uses divisor T. IEMG and waveform length are sample sums, without division by sampling rate. The count rules are

$$\mathrm{ZC} = \sum_{t=1}^{T-1} \mathbf{1}\{x_t x_{t+1} < 0,\ |d_t| \geq \tau\},$$
$$\mathrm{SSC} = \sum_{t=2}^{T-1} \mathbf{1}\{a_t b_t > 0,\ \max(|a_t|, |b_t|) \geq \tau\},$$

where $a_t = x_t - x_{t-1}$ and $b_t = x_t - x_{t+1}$. The thresholds are 10^{-2} mV for monopolar GRABMyo, 4×10^{-3} mV for derived bipolar signals and seven stored ADC units for DB5; they are not interchangeable amplitude units.

For spectral features, SciPy Welch estimation uses a periodic Hann window, segment length $\min(T, 256)$, default half-segment overlap, constant detrending and one-sided density scaling. Mean frequency is $\sum_\ell f_\ell P_\ell / (\sum_\ell P_\ell + 10^{-12})$. Median frequency is the first frequency bin whose cumulative power reaches half of that guarded total, clamped to the last bin if none reaches it; no frequency interpolation is used. The feature order within every channel is MAV, RMS, VAR, WL, ZC, SSC, IEMG, WAMP, MNF, MDF. This channel-major mapping is retained when selecting electrodes.

MAV and integrated EMG are redundant at a fixed window length. The historical feature-redundancy diagnostic found mean performance change -0.0005 (95% CI -0.0021 to +0.0010), ranking correlation 0.994 and matching top-twelve sets in 34 outer folds. This diagnostic showed a small observed mean change; it does not establish equivalence or remove all correlated-feature effects in TreeSHAP.

S3 Inference and test families

All intervals resample paired participant scores, not individual windows. Their estimand is the conditional mean out-of-fold performance change. Inner and outer models share training participants, so neither 42 attribution vectors nor 43 outer fits are independent fitted-model replicates. The bootstrap does not refit the entire nested procedure.

The original count decision uses the percentile lower bound. Its original Holm tail is retained explicitly as a historical calculation. The new bootstrap constructs null residuals $d_p - \bar{d}$, resamples them, studentizes the resampled mean and compares it with $(\bar{d} + \delta)/(s_d/\sqrt{n})$; the Monte Carlo probability is $(1 + \#\{t_b \geq t_{\mathrm{obs}}\})/(B + 1)$. A family contains all fifteen reduced counts for one condition, margin and penalty. At a tested fixed count, the unadjusted interval remains a separate descriptive criterion. RF tests only twelve against sixteen and estimates no k^*.

Historical secondary families contain eight attribution-versus-random tests, twelve original penalty tests and fifteen deletion tests. The participant-extension comparison family contains sixty tests (four penalties times fifteen counts). Its penalty diagnostic has twelve tests; the new shared-resource comparison has two; the per-gesture analysis has sixteen. Geometric12 is exploratory, with a direct paired method contrast as well as each method's change from full16. Wilcoxon tests concern signed ranks; percentile intervals concern the mean, so their decisions need not coincide. No favorable seed is substituted near a boundary. In DB5, count decisions also depend on the bootstrap construction: at the 0.03 margin, the historical tail-Holm calculation supports twelve, while the null-centred studentized Holm sensitivity supports no reduced count. This small-cohort disagreement is reported rather than used to select a favorable test.

S4 Participant and gesture predictions

Each revision prediction file stores canonical cache row indices, true labels and model predictions. The full16 and SHAP12 reruns reproduce original participant metrics within 10^{-6}. The entire gesture analysis uses matched models under the primary 300-round, 200,000-window protocol. Per-gesture F1 is computed for every participant before inference; confusion matrices are normalized by true gesture within participant before averaging. Thus large window counts do not inflate the inferential sample size.

Gesture numbers follow MotionSequence.txt, whose explicit numeric order is authoritative. In particular, gesture 14 is forearm pronation; visual row order in GestureList.JPG is not used to assign numeric IDs. Participant-loss summaries are descriptive rather than individual non-inferiority tests. Correlation of a full-array score with its own difference is mathematically coupled and is not interpreted causally.

S5 Participant-level attribution and provenance

For each outer participant, the post-hoc extension takes the median and unscaled MAD across the 42 normalized individual attribution vectors. It preserves all fixed penalties and counts. Person vectors share five attributing models and reflect both person heterogeneity and model differences. This is not a new independent bootstrap or a claim that the penalty is novel.

The old extension's saved hash of the curve runner does not match the later runner source. That historical record was preserved. The revision uses a fresh isolated fit for newly required subsets with a current fingerprint; exact old primary subsets can be reused only with an explicit matching source row and unchanged protocol. Current strict verification compares result subsets, score reconstructions, source hashes and reused metrics. The previous hash mismatch is not relabeled a pass.

A further post-hoc diagnostic quantifies whether each fixed penalty changes the unordered physical site set relative to its unpenalized counterpart. It covers every count and participant for both aggregation rules, reports changed-set counts and mean Jaccard similarity, and verifies metric identity for unchanged inputs. It does not treat unchanged layouts as an equivalence experiment or retune a penalty.

S6 Resources, sensitivity and fixed-layout validation

The historical selection methods used a common final lighter model but unequal ranking resources. Historical RBF-SVM uses $C = 1$ and the scikit-learn scale rule for γ; RF uses 200 trees, minimum leaf size two and no depth limit, with seed 20260728. The RF sensitivity retains those parameters. Stored feature values are float32; feature standardization uses the appropriate training-pool mean and population SD plus 10^{-8}, preserving the distinction between full inner-training scaler pools and capped final-model fit samples. The new comparison instead shares each inner model and its validation observations. Electrode-group permutation preserves within-electrode feature blocks and permutes only within each held-out participant. Negative estimated performance drops are retained. Both methods use the median across inner folds after normalization; SHAP and permutation remain different scoring procedures. Runtime means are descriptive for the recorded GPU/CPU environment and include no prospective device latency.

Rest-inclusive and 150/500 ms analyses cover every count and participant and retain the primary 250 ms rankings. Equal training window counts across different lengths are unequal signal durations. The RF experiment holds the XGBoost-selected layout fixed and compares twelve with sixteen using the pre-existing RF parameters; it is not a RF ranking or count-optimization study.

Fixed-layout rankings use the original five-fold median/MAD rule within development data. Historical pooled feature thresholds still apply. Development and test participants are disjoint; their inner and final models use all development windows, not the primary curve's fixed training cap. Count selection already used the full cohort. Odd-development and even-development derive different layouts. Their reverse-direction result cannot be portrayed as validation of the first layout. A post-hoc diagnostic reran the percentile bootstrap with 200 fixed seeds; the reverse layout qualified in 90 reruns. All seed outcomes are retained, and the original seed is unchanged. This diagnoses Monte Carlo sensitivity rather than the probability that the hypothesis is true. DB5 and derived bipolar analyses use their own references; no channels or participants are pooled across datasets or representations.

S7 Additional figures




Figure S1. Complete sensitivity curves for rest inclusion and alternate window lengths. Each mean paired change compares with full16 under that condition. Shading is a 95% participant-bootstrap interval; dashed lines mark the 0.02 tolerance. Rankings are held at their primary 250 ms values.




Figure S2. SHAP12 minus full16 confusion change. Each participant's confusion matrix is normalized within true gesture before averaging. The color scale is in percentage points, with symmetric limits covering the observed changes; machine-readable values retain full precision. Off-diagonal increases identify specific additional confusions without supplying independent window-level inference.




Figure S3. Historical full-array classifier context. Boxes summarize held-out participant Macro-F1. XGBoost uses all outer-training windows, random forest 200,000 and SVM 40,000; unequal budgets and historical calibration limit a direct classifier-capacity comparison. This is separate from the primary count curve's full16 reference.




Figure S4. All participant-versus-fold aggregation comparisons. Each cell is the mean paired Macro-F1 change for one fixed penalty and count. Asterisks, if present, mark Holm-adjusted signed-rank significance across sixty comparisons. Colors use a symmetric difference scale; no penalty is selected from these outcomes.




Figure S5. Full-array session transfer for all held-out participants. Grey lines connect the same participant; colored points are observed scores and black bars are medians. Training on two sessions uses more observations, so the final contrast confounds session diversity and quantity. These are subject-independent full-array comparisons, not reduced-layout or isolated electrode-displacement tests.




Figure S6. Descriptive attribution heterogeneity. (A) Each participant's normalized profile averaged over outer-fold attribution records. (B) Mean MAD per electrode from five pooled inner-fold vectors versus individual participant vectors. These aggregates share fitted models and overlapping training cohorts; neither cells nor vectors are independent statistical replicates. Larger person dispersion does not imply a beneficial performance penalty.




Figure S7. Complete reduced-count comparison under the primary protocol. SHAP and the fixed geometric ordering use the same training sample and common full16 reference. The left panel includes every reduced count; the right enlarges the tolerance region. Shading gives participant-bootstrap intervals and the dashed line is the 0.02 margin. The full geometric curve was added after geometry12 had been examined. Different minimum qualifying counts do not establish a direct between-method mean difference.

S8 Result tables

Table S1. Full-array (16-electrode) leave-one-subject-out performance of three classifiers on GRABMyo (43 participants, 16 active gestures). CI: 95% participant cluster-bootstrap confidence interval. RBF-SVM: support vector machine with a radial basis function kernel. Training windows: windows used to fit each fold's model.

Model	Training windows	Macro-F1	95% CI	SD	Range
XGBoost	all (550,368 per fold)	0.542	0.517–0.567	0.085	0.385–0.702
RBF-SVM	40,000	0.538	0.513–0.562	0.085	0.383–0.718
Random forest	200,000	0.502	0.475–0.528	0.090	0.346–0.670

Paired comparisons (Wilcoxon signed-rank, Holm over 3): Random forest − RBF-SVM = −0.0362 (95% CI −0.0444 to −0.0284), $p_{\text{Holm}} < 0.001$, $r_{rb} = -0.97$; Random forest − XGBoost = −0.0408 (95% CI −0.0475 to −0.0340), $p_{\text{Holm}} < 0.001$, $r_{rb} = -0.98$; RBF-SVM − XGBoost = −0.0045 (95% CI −0.0107 to +0.0015), $p_{\text{Holm}} = 0.154$, $r_{rb} = -0.25$.

Table S2. Electrode-count performance curve and primary non-inferiority decision on GRABMyo (cross-fitted ranking, $\lambda = 0$; 43 participants; every k retrained from scratch on the same 200,000 training windows of each fold). Δ_k: mean paired difference from the $k = 16$ model of the same curve, with 95% participant cluster-bootstrap confidence interval (CI). Non-inferior: lower bound above $-\delta$ with the primary margin $\delta = 0.02$; Holm: the same decision after Holm correction over the 15 subset sizes. The smallest non-inferior subset (k^*) is in bold; the rule below it marks the boundary. Decisions at the sensitivity margins $\delta = 0.01$ and 0.03 are given in the count-inference audit table.

k	Macro-F1 (mean ± SD)	Δ_k	95% CI	Non-inferior	Non-inferior (Holm)
16	0.541 ± 0.084	reference			
15	0.538 ± 0.083	−0.0036	−0.0056 to −0.0017	yes	yes
14	0.535 ± 0.083	−0.0060	−0.0081 to −0.0039	yes	yes
13	0.530 ± 0.083	−0.0109	−0.0133 to −0.0085	yes	yes
12	**0.528 ± 0.084**	**−0.0133**	**−0.0160 to −0.0106**	**yes**	**yes**
11	0.521 ± 0.084	−0.0204	−0.0246 to −0.0162	no	no
10	0.515 ± 0.083	−0.0259	−0.0311 to −0.0205	no	no
9	0.510 ± 0.086	−0.0318	−0.0387 to −0.0246	no	no
8	0.505 ± 0.085	−0.0366	−0.0440 to −0.0289	no	no
7	0.500 ± 0.085	−0.0413	−0.0489 to −0.0333	no	no
6	0.480 ± 0.084	−0.0610	−0.0713 to −0.0507	no	no
5	0.428 ± 0.075	−0.1133	−0.1277 to −0.0993	no	no
4	0.397 ± 0.071	−0.1444	−0.1590 to −0.1306	no	no
3	0.340 ± 0.057	−0.2015	−0.2212 to −0.1822	no	no
2	0.299 ± 0.057	−0.2420	−0.2603 to −0.2230	no	no
1	0.181 ± 0.040	−0.3603	−0.3832 to −0.3369	no	no

Table S3. H2: attribution-ranked subsets versus the mean of random subsets of the same size (GRABMyo, 43 participants; secondary family of 8 tests, Holm-corrected; the detailed test family was specified after the underlying results were available). All subsets were evaluated with one comparison model (XGBoost, 50 boosting rounds, 150,000 training windows per fold), these scores use a different protocol from table S2. Random: participant's mean over 100 random subsets (500 at $k = 12$). Difference: mean paired difference (attribution minus random) with 95% participant cluster-bootstrap confidence interval (CI). Higher/lower: participants for whom the attribution subset scored above/below their random mean. p_{Holm}: Wilcoxon signed-rank, Holm-corrected; r_{rb}: matched-pairs rank-biserial correlation.

k	Ranking	Attribution	Random	Difference	95% CI	Higher/lower	p_{Holm}	r_{rb}
4	Cross-fitted SHAP ($\lambda = 0$)	0.382	0.366	+0.0163	+0.0060 to +0.0267	29/14	0.007	+0.47
	Penalized SHAP ($\lambda = 0.5$)	0.383	0.366	+0.0172	+0.0071 to +0.0274	30/13	0.007	+0.50
6	Cross-fitted SHAP ($\lambda = 0$)	0.453	0.416	+0.0370	+0.0286 to +0.0452	37/6	<0.001	+0.92
	Penalized SHAP ($\lambda = 0.5$)	0.453	0.416	+0.0370	+0.0286 to +0.0452	37/6	<0.001	+0.92
8	Cross-fitted SHAP ($\lambda = 0$)	0.468	0.445	+0.0230	+0.0161 to +0.0298	36/7	<0.001	+0.82
	Penalized SHAP ($\lambda = 0.5$)	0.469	0.445	+0.0243	+0.0176 to +0.0308	37/6	<0.001	+0.86
12	Cross-fitted SHAP ($\lambda = 0$)	0.485	0.478	+0.0074	+0.0046 to +0.0103	35/8	<0.001	+0.71
	Penalized SHAP ($\lambda = 0.5$)	0.485	0.478	+0.0074	+0.0046 to +0.0103	35/8	<0.001	+0.71

Table S4. H3: stability-regularised ranking ($\lambda > 0$) minus magnitude-only ranking ($\lambda = 0$) on the electrode-count performance curve (GRABMyo, 43 participants). Mean paired difference with 95% participant cluster-bootstrap confidence interval (CI). Tied: participants for whom both rankings select the identical subset. p_{Holm}: Wilcoxon signed-rank, Holm over 12 tests. r_{rb} is computed from untied participants only and is undefined (–) when all are tied; with most participants tied it is not informative about magnitude.

λ	k	Mean difference	95% CI	Tied	p_{Holm}	r_{rb}
0.25	4	−0.0002	−0.0005 to +0.0000	41/43	1.000	−1.00
0.25	6	+0.0000	+0.0000 to +0.0000	43/43	1.000	–
0.25	8	+0.0001	+0.0000 to +0.0002	42/43	1.000	+1.00
0.25	12	+0.0000	+0.0000 to +0.0000	43/43	1.000	–
0.5	4	+0.0004	−0.0005 to +0.0018	40/43	1.000	+0.00
0.5	6	+0.0000	+0.0000 to +0.0000	43/43	1.000	–
0.5	8	+0.0008	+0.0000 to +0.0019	40/43	1.000	+1.00
0.5	12	+0.0000	+0.0000 to +0.0000	43/43	1.000	–
1	4	+0.0010	−0.0003 to +0.0027	38/43	1.000	+0.47
1	6	+0.0000	+0.0000 to +0.0000	43/43	1.000	–
1	8	+0.0015	+0.0004 to +0.0028	36/43	0.216	+1.00
1	12	−0.0005	−0.0014 to +0.0000	42/43	1.000	−1.00

Table S5. H4: deletion with retraining (GRABMyo, 43 participants). Retained: electrodes kept after deletion. Remove-Top, Remove-Bottom and Remove-Random delete the highest-ranked, lowest-ranked or randomly chosen electrodes; Remove-Random uses the random subsets of the H2 comparison and exists only where these were sampled. All orders use the same comparison model and training sample. Difference: mean paired difference (first minus second order) with 95% participant cluster-bootstrap confidence interval (CI); negative values follow the expected ordering. p_{Holm}: Wilcoxon signed-rank, Holm over the 15 contrasts; r_{rb}: matched-pairs rank-biserial correlation.

Retained	Contrast	First	Second	Difference	95% CI	p_{Holm}	r_{rb}
2	Top − Bottom	0.263	0.292	−0.0297	−0.0419 to −0.0166	<0.001	−0.67
4	Top − Bottom	0.351	0.382	−0.0314	−0.0447 to −0.0177	<0.001	−0.64
	Top − Random	0.351	0.366	−0.0151	−0.0239 to −0.0061	0.010	−0.51
	Random − Bottom	0.366	0.382	−0.0163	−0.0265 to −0.0061	0.013	−0.47
6	Top − Bottom	0.376	0.454	−0.0775	−0.0921 to −0.0627	<0.001	−0.96
	Top − Random	0.376	0.416	−0.0398	−0.0487 to −0.0307	<0.001	−0.91
	Random − Bottom	0.416	0.454	−0.0377	−0.0459 to −0.0293	<0.001	−0.93
8	Top − Bottom	0.408	0.469	−0.0618	−0.0772 to −0.0461	<0.001	−0.89
	Top − Random	0.408	0.445	−0.0377	−0.0476 to −0.0273	<0.001	−0.86
	Random − Bottom	0.445	0.469	−0.0242	−0.0309 to −0.0172	<0.001	−0.86
10	Top − Bottom	0.445	0.475	−0.0297	−0.0399 to −0.0188	<0.001	−0.73
12	Top − Bottom	0.455	0.485	−0.0302	−0.0385 to −0.0218	<0.001	−0.84
	Top − Random	0.455	0.478	−0.0228	−0.0296 to −0.0158	<0.001	−0.81
	Random − Bottom	0.478	0.485	−0.0074	−0.0101 to −0.0046	<0.001	−0.74
14	Top − Bottom	0.487	0.491	−0.0038	−0.0084 to +0.0009	0.150	−0.25

Table S6. Agreement of electrode rankings on GRABMyo ($\lambda = 0$). Values are mean (SD) over all pairs of rankings in each group. They are descriptive summaries: pairwise observations share rankings and are not independent, so no inferential interval is given.

Rankings compared	Pairs	Spearman ρ	Kendall τ	Jaccard, top 4	Jaccard, top 6	Jaccard, top 8
Individual participants	903	0.927 (0.038)	0.801 (0.066)	0.752 (0.194)	0.905 (0.137)	0.803 (0.132)
Inner folds (disjoint participant groups)	430	0.948 (0.021)	0.840 (0.046)	0.816 (0.200)	0.992 (0.047)	0.838 (0.105)
Outer folds (overlapping training sets*)	903	0.987 (0.008)	0.943 (0.028)	0.888 (0.180)	1.000 (0.000)	0.923 (0.106)

*Outer training sets share about 98% of their participants, so their agreement is descriptive only and is not an estimate of between-participant stability.

Table S7. NinaPro DB5 channel-count performance curve (exploratory replication; cross-fitted ranking, $\lambda = 0$; 10 subjects; reference $k = 16$, mean Macro-F1 0.281; margin $\delta = 0.02$). The lower 95% bound is shown to six decimals because the $k = 12$ decision lies at the margin. Non-inferior: lower bound above $-\delta$, unadjusted and after Holm correction over 15 subset sizes. Bootstrap reruns: number of 200 reruns of the bootstrap with different random seeds in which the unadjusted decision was non-inferior. This is a Monte Carlo decision-stability diagnostic, not a probability that the hypothesis is true.

k	Macro-F1	Δ_k	Lower bound	Non-inf.	Non-inf. (Holm)	Non-inf. in bootstrap reruns
15	0.270	−0.0108	−0.023773	no	no	0/200 (0.0%)
14	0.269	−0.0119	−0.027438	no	no	0/200 (0.0%)
13	0.266	−0.0143	−0.031186	no	no	0/200 (0.0%)
12	0.268	−0.0126	−0.019994	yes	no	191/200 (95.5%)
11	0.260	−0.0211	−0.034121	no	no	0/200 (0.0%)
10	0.265	−0.0160	−0.031368	no	no	0/200 (0.0%)
9	0.260	−0.0202	−0.036943	no	no	0/200 (0.0%)
8	0.252	−0.0288	−0.055369	no	no	0/200 (0.0%)
7	0.232	−0.0486	−0.075346	no	no	0/200 (0.0%)
6	0.231	−0.0498	−0.081816	no	no	0/200 (0.0%)
5	0.200	−0.0803	−0.118422	no	no	0/200 (0.0%)
4	0.180	−0.1006	−0.150266	no	no	0/200 (0.0%)
3	0.162	−0.1185	−0.174145	no	no	0/200 (0.0%)
2	0.138	−0.1430	−0.195307	no	no	0/200 (0.0%)
1	0.105	−0.1754	−0.229548	no	no	0/200 (0.0%)

Table S8. Cross-session evaluation on GRABMyo (exploratory; full array). All conditions are also subject-independent: the test participant is never in training.

Design	Train sessions	Test session	Train windows	Macro-F1
CS1	1	1	183,456	0.492 ± 0.101
CS1	1	2	183,456	0.528 ± 0.088
CS1	1	3	183,456	0.510 ± 0.090
CS2	1+2	3	366,912	0.530 ± 0.095

Paired contrasts (exploratory, uncorrected): CS1: test S2 − test S1: +0.0355 (95% CI +0.0091 to +0.0621), $p = 0.024$; CS1: test S3 − test S1: +0.0172 (95% CI −0.0038 to +0.0391), $p = 0.272$; S3 test: CS2 (train S1+S2) − CS1 (train S1): +0.0210 (95% CI +0.0146 to +0.0274), $p < 0.001$.

Table S9. GRABMyo derived bipolar pairs $F_j - F_{j+8}$ (exploratory; 43 participants; $\lambda = 0$; count-feature threshold 4×10^{-3} mV; margin $\delta = 0.02$). Reference: the $k = 8$ model of the same curve, trained on the curve's 200,000-window sample (mean Macro-F1 0.480). An additional full-array bipolar value (0.478) comes from a separate model trained on all 550,368 training windows of each fold, as for the monopolar analysis. Δ_k: mean paired difference with 95% participant cluster-bootstrap confidence interval (CI). Bootstrap reruns: as in the DB5 table in this Supplementary.

k	Macro-F1	Δ_k	95% CI	Non-inf.	Non-inf. in bootstrap reruns
7	0.464	−0.0158	−0.0203 to −0.0113	no	0/200 (0.0%)
6	0.442	−0.0375	−0.0451 to −0.0303	no	0/200 (0.0%)
5	0.405	−0.0742	−0.0845 to −0.0646	no	0/200 (0.0%)
4	0.356	−0.1240	−0.1392 to −0.1096	no	0/200 (0.0%)
3	0.310	−0.1697	−0.1852 to −0.1546	no	0/200 (0.0%)
2	0.240	−0.2399	−0.2615 to −0.2177	no	0/200 (0.0%)
1	0.174	−0.3052	−0.3298 to −0.2790	no	0/200 (0.0%)

Table S10. Paired participant-level gesture F1: SHAP12 minus full16, with Holm correction across all sixteen active gestures. Numeric IDs follow the dataset MotionSequence.txt, reproduced in the gesture dictionary.

Gesture ID	Full16	SHAP12	$\bar{\Delta}$	95% CI	p_{Holm}
1	0.449	0.437	-0.0119	[-0.0210, -0.0035]	0.086
2	0.308	0.284	-0.0242	[-0.0356, -0.0132]	0.003
3	0.519	0.516	-0.0030	[-0.0117, +0.0054]	1.000
4	0.348	0.341	-0.0069	[-0.0137, -0.0001]	0.121
5	0.490	0.483	-0.0066	[-0.0176, +0.0045]	1.000
6	0.604	0.592	-0.0115	[-0.0222, -0.0008]	0.133
7	0.503	0.504	+0.0009	[-0.0059, +0.0083]	1.000
8	0.499	0.489	-0.0099	[-0.0215, +0.0006]	0.787
9	0.387	0.357	-0.0300	[-0.0436, -0.0167]	0.002
10	0.533	0.514	-0.0192	[-0.0299, -0.0094]	0.005
11	0.940	0.939	-0.0003	[-0.0018, +0.0012]	1.000
12	0.830	0.819	-0.0107	[-0.0202, -0.0014]	0.079
13	0.813	0.804	-0.0093	[-0.0156, -0.0036]	0.085
14	0.487	0.441	-0.0456	[-0.0594, -0.0323]	< 0.001
15	0.543	0.536	-0.0066	[-0.0142, +0.0014]	0.168
16	0.410	0.392	-0.0179	[-0.0322, -0.0034]	0.168

Table S11. Fresh isolated participant-level extension minus original fold aggregation at count 12. Holm adjustment covers all sixty reduced-count comparisons across four penalties; full results are in the paired-comparison CSV.

λ	k	$\bar{\Delta}$	95% CI	p_{Holm}
0.0	12	+0.0000	[+0.0000, +0.0000]	1.000
0.25	12	+0.0000	[+0.0000, +0.0000]	1.000
0.5	12	+0.0000	[+0.0000, +0.0000]	1.000
1.0	12	+0.0005	[+0.0000, +0.0014]	1.000

Table S12. Participant aggregation: penalized minus unpenalized attribution. Holm correction covers all twelve tests; all fixed penalty settings are reported.

λ	k	$\bar{\Delta}$	95% CI	p_{Holm}
0.25	4	+0.0000	[+0.0000, +0.0000]	1.000
0.25	6	+0.0000	[+0.0000, +0.0000]	1.000
0.25	8	+0.0002	[-0.0008, +0.0011]	1.000
0.25	12	+0.0000	[+0.0000, +0.0000]	1.000
0.5	4	+0.0001	[+0.0000, +0.0004]	1.000
0.5	6	+0.0000	[+0.0000, +0.0000]	1.000
0.5	8	+0.0000	[-0.0011, +0.0011]	1.000
0.5	12	+0.0000	[+0.0000, +0.0000]	1.000
1.0	4	+0.0030	[+0.0006, +0.0060]	0.332
1.0	6	+0.0000	[+0.0000, +0.0000]	1.000
1.0	8	+0.0005	[-0.0008, +0.0018]	1.000
1.0	12	+0.0000	[+0.0000, +0.0000]	1.000

Table S13. Post-hoc descriptive selector activity: each fixed positive penalty versus its unpenalized counterpart. Counts concern physical site sets, not rank order. Every row includes all 43 participants; the CSV retains all sixteen counts. No new models or equivalence tests were added.

Aggregation	λ	k	Changed sets	Mean Jaccard
Fold	0.25	4	2/43	0.981
Fold	0.25	6	0/43	1.000
Fold	0.25	8	1/43	0.995
Fold	0.25	12	0/43	1.000
Fold	0.5	4	3/43	0.972
Fold	0.5	6	0/43	1.000
Fold	0.5	8	3/43	0.984
Fold	0.5	12	0/43	1.000
Fold	1.0	4	5/43	0.953
Fold	1.0	6	0/43	1.000
Fold	1.0	8	7/43	0.964
Fold	1.0	12	1/43	0.996
Participant	0.25	4	0/43	1.000
Participant	0.25	6	0/43	1.000
Participant	0.25	8	3/43	0.984
Participant	0.25	12	0/43	1.000
Participant	0.5	4	1/43	0.991
Participant	0.5	6	0/43	1.000
Participant	0.5	8	5/43	0.974
Participant	0.5	12	0/43	1.000
Participant	1.0	4	6/43	0.944
Participant	1.0	6	0/43	1.000
Participant	1.0	8	7/43	0.964
Participant	1.0	12	0/43	1.000

Table S14. Two exploratory split-derived layouts at twelve electrodes, fitted with all development windows. Six-decimal limits preserve the strict boundary decision. Layout estimation excludes test participants, but count selection had already used the full cohort. All penalties produced the same layout within each split.

Development / test	n test	Dropped sites	$\bar{\Delta}$	95% CI	NI
odd / even	21	3, 9, 11, 12	-0.0124	[-0.017901, -0.007658]	yes
even / odd	22	9, 11, 12, 13	-0.0135	[-0.020020, -0.006627]	no

Table S15. Full fixed geometric ordering under the primary 300-round, 200,000-window protocol. Each count uses all 43 participants and the common primary full16 reference. Count 12 and full16 reuse the exact matched metrics; remaining subsets were fitted separately. The count-family null test is exploratory and Holm-adjusted over fifteen reduced counts; geometry12 outcomes were known before this additional curve was planned.

k	Mean F1	$\bar{\Delta}$	95% CI	NI CI	NI null Holm
1	0.191	-0.3506	[-0.3718, -0.3288]	no	no
2	0.289	-0.2523	[-0.2714, -0.2325]	no	no
3	0.367	-0.1746	[-0.1911, -0.1569]	no	no
4	0.407	-0.1341	[-0.1497, -0.1185]	no	no
5	0.432	-0.1095	[-0.1232, -0.0954]	no	no
6	0.450	-0.0917	[-0.1030, -0.0796]	no	no
7	0.484	-0.0574	[-0.0683, -0.0463]	no	no
8	0.502	-0.0395	[-0.0467, -0.0321]	no	no
9	0.505	-0.0367	[-0.0438, -0.0296]	no	no
10	0.514	-0.0274	[-0.0337, -0.0210]	no	no
11	0.518	-0.0229	[-0.0290, -0.0165]	no	no
12	0.522	-0.0193	[-0.0254, -0.0132]	no	no
13	0.525	-0.0159	[-0.0218, -0.0099]	no	no
14	0.527	-0.0143	[-0.0201, -0.0082]	no	no
15	0.537	-0.0040	[-0.0063, -0.0016]	yes	yes

Table S16. Count decisions from the historical percentile rule, original percentile-tail Holm calculation and exploratory null-centred studentized bootstrap. Inference uses participants; each condition and margin is its own count family.

Condition	Margin	Percentile CI	Historical Holm	Null-centred Holm
Derived bipolar	0.01	none	none	none
Derived bipolar	0.02	none	none	none
Derived bipolar	0.03	7	7	7
NinaPro DB5	0.01	none	none	none
NinaPro DB5	0.02	12	none	none
NinaPro DB5	0.03	12	12	none
Geometric	0.01	15	15	15
Geometric	0.02	15	15	15
Geometric	0.03	11	12	12
Participant ($\lambda = 0$)	0.01	14	14	14
Participant ($\lambda = 0$)	0.02	12	12	12
Participant ($\lambda = 0$)	0.03	11	11	11
Participant ($\lambda = 0.25$)	0.01	14	14	14
Participant ($\lambda = 0.25$)	0.02	12	12	12
Participant ($\lambda = 0.25$)	0.03	11	11	11
Participant ($\lambda = 0.5$)	0.01	14	14	14
Participant ($\lambda = 0.5$)	0.02	12	12	12
Participant ($\lambda = 0.5$)	0.03	11	11	11
Participant ($\lambda = 1$)	0.01	14	14	14
Participant ($\lambda = 1$)	0.02	12	12	12
Participant ($\lambda = 1$)	0.03	11	11	11
Primary ($\lambda = 0$)	0.01	14	14	14
Primary ($\lambda = 0$)	0.02	12	12	12
Primary ($\lambda = 0$)	0.03	11	11	11
Rest included	0.01	14	14	14
Rest included	0.02	12	12	12
Rest included	0.03	11	11	11
150 ms	0.01	14	14	14
150 ms	0.02	12	12	12
150 ms	0.03	10	11	11
500 ms	0.01	14	14	14
500 ms	0.02	12	12	12
500 ms	0.03	10	11	11

Table S17. Observed resource-matched selection-stage runtime per outer fold on the recorded workstation. Inner training is shared and counted once. Early folds overlapped CPU RF fits, so timings are observational rather than an isolated benchmark. No online or real-time latency is inferred.

Stage	Mean s	SD s	Min s	Max s
Shared inner training	117.1	3.7	114.7	136.4
TreeSHAP selection	4.0	0.2	3.8	4.3
Grouped permutation	10.6	1.1	9.8	13.3

S9 Machine-readable evidence and reproduction

The revision's tables directory retains full-precision statistical outputs, including every participant, gesture, count, margin and penalty. Figure source-data CSVs and `figure_provenance.csv` map plotted values to inputs. Numeric macros have separate historical and revision provenance files. Experimental protocols, amendments, input manifests, environment snapshots and execution logs identify the executed analyses. The reproducibility README provides execution and strict verification commands. Raw datasets remain at their public repositories rather than being redistributed as new data.