

Ex.No – 06

Roll no: 210701284

**Implementation of Round Robin Task Scheduling in Both Time
Shared and Space Shared CPU**

AIM:

To implement the round robin task scheduling in both time shared and space shared CPU using CloudSim.

PROCEDURE:

1. Create a new project by selecting java console line application template and JDK 18.
2. Open project settings from the file menu of the options window.
3. Navigate to project dependencies and select on add external jars and then click on 'Browse' to open the path where you have unzipped the Cloudsim Jars and click on apply.
4. Create a java file with the cloudsim code to implement the round robin scheduling algorithm.
5. Run the application as a java file to see the output in the console below.

CODE:

```
import org.cloudbus.cloudsim.*; import
org.cloudbus.cloudsim.core.CloudSim;
import java.util.*;
```

```
public class RoundRobinScheduler
{ public static void main(String[] args) {
    try {
```

```
int numUser = 1; // number of cloud users
Calendar calendar = Calendar.getInstance();
boolean traceFlag = false; // mean trace
events
```

```
CloudSim.init(numUser, calendar, traceFlag);
```

```
Datacenter                                datacenter0                =
createDatacenter("Datacenter_0");
```

```
DatacenterBroker broker = createBroker();
int brokerId = broker.getId();
```

```
List<Vm> vmList = new ArrayList<>();
```

```
int vmId = 0;
```

```
int mips =
```

```
1000;
```

```
long size = 10000; // image size
```

```
(MB) int ram = 512; // vm
```

```
memory (MB) long bw = 1000;
```

```
int pesNumber = 1; // number of CPUs
```

```
String vmm = "Xen"; // VMM name
```

```
for (int i = 0; i < 3; i++) {
```

```
vmList.add(new Vm(vmId++, brokerId, mips, pesNumber, ram,
bw, size, vmm, new CloudletSchedulerTimeShared()));
```

```
}
```

```
broker.submitVmList(vmList);
```

```
List<Cloudlet> cloudletList =
```

```

new ArrayList<>(); int

cloudletId = 0; long length =

40000; long fileSize = 300;

long outputSize = 300;

UtilizationModel      utilizationModel      =      new
UtilizationModelFull();

for (int i = 0; i < 6; i++) {
    Cloudlet cloudlet = new Cloudlet(cloudletId++, length,
pesNumber,      fileSize,      outputSize,      utilizationModel,
utilizationModel,      utilizationModel);
cloudlet.setUserId(brokerId); cloudletList.add(cloudlet);
}

broker.submitCloudletList(cloudletList)

;

CloudSim.startSimulation();

List<Cloudlet> newList =

broker.getCloudletReceivedList();

CloudSim.stopSimulation(); printCloudletList(newList);

```

```

    } catch (Exception e)
    { e.printStackTrace()
      ;
    }
  }
}

private static Datacenter createDatacenter(String name)
{ List<Host> hostList = new ArrayList<>();

  int mips = 1000;
  int ram = 2048; // host memory (MB)
  long storage = 1000000; // host
  storage int bw = 10000;

  for (int i = 0; i < 2; i++) {
    List<Pe> peList = new ArrayList<>();
    peList.add(new Pe(0, new PeProvisionerSimple(mips)));

    hostList.add(new Host(i, new RamProvisionerSimple(ram),
    new BwProvisionerSimple(bw), storage, peList, new
VmSchedulerTimeShared(peList)));
  }

  String arch = "x86";
  String os = "Linux"; String
vmm = "Xen"; double
time_zone = 10.0; double
cost = 3.0; double
costPerMem = 0.05; double
costPerStorage = 0.001;
double costPerBw = 0.0;
DatacenterCharacteristics

```

```
characteristics    =    new  
DatacenterCharacteristics(arc  
h,    os,    vmm,    hostList,  
time_zone, cost, costPerMem,  
costPerStorage, costPerBw);
```

```
Datacenter datacenter = null;  
try {  
    datacenter = new Datacenter(name, characteristics, new  
VmAllocationPolicySimple(hostList), new LinkedList<Storage>(),  
0);  
} catch (Exception e)  
    { e.printStackTrace()  
    ;  
    }  
  
return datacenter;  
}
```

```
private    static    DatacenterBroker  
createBroker() { DatacenterBroker broker  
= null; try {  
    broker = new DatacenterBroker("Broker");  
} catch (Exception e)  
    { e.printStackTrace()  
    ; return null;  
    }  
return broker;  
}
```

```
private static void printCloudletList(List<Cloudlet> list)
```

```

    { String indent = "  ";
      System.out.println();
      System.out.println("===== OUTPUT =====");
      System.out.println("Cloudlet ID" + indent + "STATUS" + indent
                          +
                          "Data center ID" + indent + "VM ID" + indent + "Time" +
indent + "Start Time" + indent + "Finish Time");

      for (Cloudlet cloudlet : list) {
        System.out.print(indent + cloudlet.getCloudletId() + indent
                        + indent);

        if (cloudlet.getStatus() == Cloudlet.SUCCESS)
          { System.out.print("SUCCESS");

            System.out.println(indent + indent + indent + indent +
cloudlet.getResourceId() + indent + indent + indent +
cloudlet.getVmId() + indent + indent +
cloudlet.getActualCPUTime() + indent + indent +
cloudlet.getExecStartTime() + indent + indent +
cloudlet.getFinishTime());
          }
        }
      }
    }

```

OUTPUT:

```

.0: Broker: Trying to Create VM #0 in Datacenter_0
.0: Broker: Trying to Create VM #1 in Datacenter_0
.0: Broker: Trying to Create VM #2 in Datacenter_0
VmScheduler.VmCreate] Allocation of VM #2 to Host #0 failed by MIPS
VmScheduler.VmCreate] Allocation of VM #2 to Host #1 failed by MIPS
.1: Broker: VM #0 has been created in Datacenter #2, Host #0
.1: Broker: VM #1 has been created in Datacenter #2, Host #1
.1: Broker: Creation of VM #2 failed in Datacenter #2
.1: Broker: Sending cloudlet 0 to VM #0
.1: Broker: Sending cloudlet 1 to VM #1
.1: Broker: Sending cloudlet 2 to VM #0
.1: Broker: Sending cloudlet 3 to VM #1
.1: Broker: Sending cloudlet 4 to VM #0
.1: Broker: Sending cloudlet 5 to VM #1
20.09800000000001: Broker: Cloudlet 0 received
20.09800000000001: Broker: Cloudlet 2 received
20.09800000000001: Broker: Cloudlet 4 received
20.09800000000001: Broker: Cloudlet 1 received
20.09800000000001: Broker: Cloudlet 3 received
20.09800000000001: Broker: Cloudlet 5 received
20.09800000000001: Broker: All Cloudlets executed. Finishing...
20.09800000000001: Broker: Destroying VM #0
20.09800000000001: Broker: Destroying VM #1
roker is shutting down...
imulation: No more future events
loudInformationService: Notify all CloudSim entities for shutting down.
atacenter_0 is shutting down...
roker is shutting down...
imulation completed.
imulation completed.

```

===== OUTPUT =====

cloudlet ID	STATUS	Data center ID	VM ID	Time	Start Time	Finish Time
0	SUCCESS	2	0	119.99800000000002	0.1	120.09800000000001
2	SUCCESS	2	0	119.99800000000002	0.1	120.09800000000001
4	SUCCESS	2	0	119.99800000000002	0.1	120.09800000000001
1	SUCCESS	2	1	119.99800000000002	0.1	120.09800000000001
3	SUCCESS	2	1	119.99800000000002	0.1	120.09800000000001
5	SUCCESS	2	1	119.99800000000002	0.1	120.09800000000001

RESULT:

Thus, to implement the round robin task scheduling using CloudSim is done successfully.