



ŘEDITELSTVÍ SILNIC A DÁLNIC ČR

NDIC - DDR XML - Winter driving conditions

Release 3.2.5rev0

Národní Dopravní Informační Centrum

2017-08-12

CONTENTS

Identifier and version:

uri
cz-ndic_ddr-winter-v3.2.5

Format
3.2.5

Specification
3.2.5rev0

Updated
2017-08-12

Format type:

Publication
DDR v3.2.5/Common

Extends
none

Publisher and author:

Publisher
NDIC

Author
Jan Vlčinský, Petr Bureš

The document describes a data format of a data distribution interface (DDR) of NDIC, used for winter driving condition information service.

INTRODUCTION

This document shall be used by publisher and / or subscriber. Subscriber shall use it for format suitability evaluation and for possible implementation of received NDIC data import into own information system. Publisher shall use it as a specification of data to be published format and for possible implementation of data export from own information system into NDIC.

Here you can find:

- conceptual description of published information
- information about location referencing methods used
- W3C XML schema of the format and other schemas (RELAX NG)
- data sample(s)

Following topics are out of scope of this document and if present, shall be considered as informative only:

- transfer protocol incl. access point, life cycle etc.
- related data formats
- typical data origin
- typical data use

1.1 General terms

Following terms are used in this document:

format

description of data structure for transferring some kind of information

protocol

description of data transfer process and rules

NDIC

national traffic information centre

DDR

data distribution interface, a proprietary format used by NDIC

(W3C) XML schema

language, which allows definition of rules for a XML document structure.

RELAX NG schema

human readable language, which allows definition of rules for a XML document structure.

XSD

XML document containing XML schema. Sometimes it is synonym for XML schema itself.

uri

uniform resource identifier, text, used as unique identifier. In this document, every format has it's own uri.

CONCEPTS

This section highlights main concepts, used by this format. For complete description refer to schemas with definitions in comments.

In this section are provided some snippets of real XML documents. For more examples, see *Appendix A: Message examples*

2.1 XML Document Sections

The XML Document is built using following elements and sections:

- DOC (document root)
- INF (metadata)
- MJD (container for messages)
- MSG (message)

2.1.1 Document root (*DOC*)

The *DOC* element represents single publication (one instance of information message).

Attribute *id* provides unique identity to given publication as a whole.

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <DOC DataSet="extended" country="CZ" id="{6E6A4889-7F14}" version="3.0">
3   <INF receiver="JB007" sender="JSDI_NDIC" transmission="HTTP">
4     <DAT>
5       <UIRADR structure="4.2" version="522"/>
6     </DAT>
7   </INF>
8 </MJD count="1">
```

2.1.2 Metadata (*INF*)

INF element provides meta-information about whole publication:

- reference to GDF 4.0 map data set publisher and version
- reference to state organization units and areas enumeration UIR-ADR

```
1 <INF receiver="JB007" sender="JSDI_NDIC" transmission="HTTP">
2   <DAT>
3     <UIRADR structure="4.2" version="522"/>
4   </DAT>
```

(continues on next page)

(continued from previous page)

```

5 </INF>
6 <MJD count="1">

```

2.1.3 Message container (*MJD*)

Single traffic messages are put into one parent element *MJD*. It can contain one or more messages.

2.1.4 Traffic Message (*MSG*)

Particular message is represented by a *MSG* element.

The message itself has following sections:

- validity *MTIME*
- textual description of whole event *MTXT*
- weather description *MEVT/WCOND*
- road conditions description *MEVT/MTNCOND*
- location reference *WDEST* (*where*) to enumeration of winter conditions report region
- reference to a region in Czech Republic *MDST*

```

9 <MSG id="40172-124" planned="false" type="WCOND" version="1">
10 <MTIME format="YYYY-MM-DDThh:mm:ssTZD">
11 <TGEN>2010-02-01T02:58:14+01:00</TGEN>
12 <TSTA>2010-02-01T02:57:00+01:00</TSTA>
13 <TSTO>2010-02-01T14:55:00+01:00</TSTO>
14 </MTIME>
15 <MTXT language="CZ">okres Havlíčkův Brod - Teplota od -8 do -7°C; Počasí:
↳ zataženo, sněhové přeháňky, bezvětří, viditelnost bez omezení; ; ; Silnice I.
↳ třídy: vrstva nového sněhu, sjízdné se zvýšenou opatrností; Silnice II. a III.
↳ třídy: vrstva nového sněhu, sjízdné se zvýšenou opatrností; ; ; </MTXT>
16 <MEVT>
17 <WCOND urgency="2">
18 <TEMP from="-8" to="-7" unit="°C"/>
19 <CLD CloudyCode="8" language="CZ">zataženo</CLD>
20 <PREC PrecipitationCode="10" language="CZ">sněhové přeháňky</PREC>
21 <WIND WindCode="2" WindDirectionCode="1" language="CZ">bezvětří</WIND>
22 <VIS VisibilityCode="2" language="CZ">viditelnost bez omezení</VIS>
23 <WTXT language="CZ">Počasí: zataženo, sněhové přeháňky, bezvětří,
↳ viditelnost bez omezení</WTXT>
24 <TTXT language="CZ">Teplota od -8 do -7°C</TTXT>
25 </WCOND>
26 <MTNCOND>
27 <ISTN InterestsSectionCode="3" InterestsSectionName="Silnice I. třídy"
↳ urgency="3">
28 <RCOND RoadConditionCode="3" language="CZ">sjízdné se zvýšenou opatrností
↳ </RCOND>
29 <RSCOND RoadSurfaceConditionCode="11" language="CZ">vrstva nového sněhu</
↳ RSCOND>
30 <TXISTN language="CZ">Silnice I. třídy: vrstva nového sněhu, sjízdné se
↳ zvýšenou opatrností</TXISTN>
31 </ISTN>
32 <ISTN InterestsSectionCode="4" InterestsSectionName="Silnice II. a III.
↳ třídy" urgency="3">

```

(continues on next page)

(continued from previous page)

```

33      <RCOND RoadConditionCode="3" language="CZ">sjízdné se zvýšenou opatrností
↪ </RCOND>
34      <RSCOND RoadSurfaceConditionCode="11" language="CZ">vrstva nového sněhu</
↪ RSCOND>
35      <TXISTN language="CZ">Silnice II. a III. třídy: vrstva nového sněhu,
↪ sjízdné se zvýšenou opatrností</TXISTN>
36      </ISTN>
37      </MTNCOND>
38      </MEVT>
39      <WDEST NewsRegionCode="124" NewsRegionName="okres Havlíčkův Brod" coordsystem=
↪ "S-JTSK">
40      <COORD x="-678806" y="-1095819"/>
41      </WDEST>
42      <MLOC/>
43      <MDST>
44      <DEST CountryName="Česká republika" RegionCode="108" RegionName="Vysočina kraj
↪ " Township=" Havlíčkův Brod " TownshipCode="3601"/>
45      </MDST>
46      </MSG>

```

Message identity and version

Message itself has unique identifier *id* and version. Version shall start from 1 and be incremented by each update.

Validity of the message in time is specified by simple time range from start time to end time, but in fact only start time is relevant.

```

9      <MSG id="40172-124" planned="false" type="WCOND" version="1">
10      <MTIME format="YYYY-MM-DDThh:mm:ssTZD">
11      <TGEN>2010-02-01T02:58:14+01:00</TGEN>
12      <TSTA>2010-02-01T02:57:00+01:00</TSTA>
13      <TSTO>2010-02-01T14:55:00+01:00</TSTO>
14      </MTIME>

```

Weather description

The *MEVT/WCOND* element contains set of meteorological parameters (temperature, precipitation, wind, visibility etc.)

```

17      <WCOND urgency="2">
18      <TEMP from="-8" to="-7" unit="C"/>
19      <CLD CloudyCode="8" language="CZ">zataženo</CLD>
20      <PREC PrecipitationCode="10" language="CZ">sněhové přeháňky</PREC>
21      <WIND WindCode="2" WindDirectionCode="1" language="CZ">bezvětrí</WIND>
22      <VIS VisibilityCode="2" language="CZ">viditelnost bez omezení</VIS>
23      <WTXT language="CZ">Počasí: zataženo, sněhové přeháňky, bezvětrí,
↪ viditelnost bez omezení</WTXT>
24      <TTXT language="CZ">Teplota od -8 do -7°C</TTXT>
25      </WCOND>

```

Driving Conditions description

The *MEVT/MTNCOND* element contains parameters , describing driving conditions.

```

26      <MTNCOND>
27      <ISTN InterestsSectionCode="3" InterestsSectionName="Silnice I. třídy"
↳ urgency="3">
28      <RCOND RoadConditionCode="3" language="CZ">sjízdné se zvýšenou opatrností
↳ </RCOND>
29      <RSCOND RoadSurfaceConditionCode="11" language="CZ">vrstva nového sněhu</
↳ RSCOND>
30      <TXISTN language="CZ">Silnice I. třídy: vrstva nového sněhu, sjízdné se
↳ zvýšenou opatrností</TXISTN>
31      </ISTN>
32      <ISTN InterestsSectionCode="4" InterestsSectionName="Silnice II. a III.
↳ třídy" urgency="3">
33      <RCOND RoadConditionCode="3" language="CZ">sjízdné se zvýšenou opatrností
↳ </RCOND>
34      <RSCOND RoadSurfaceConditionCode="11" language="CZ">vrstva nového sněhu</
↳ RSCOND>
35      <TXISTN language="CZ">Silnice II. a III. třídy: vrstva nového sněhu,
↳ sjízdné se zvýšenou opatrností</TXISTN>
36      </ISTN>
37      </MTNCOND>

```

Location description

DDR (Winter) is using references to areas, from which are information provided.

There are following location referencing methods used:

- Reference to enumeration of report regions (see *Enumeration of report regions*)
- Coordinate of centre of report region
- Reference to region in Czech Republic using enumeration UIR-ADR.

```

39      <WDEST NewsRegionCode="124" NewsRegionName="okres Havlíčkův Brod" coordsystem=
↳ "S-JTSK">
40      <COORD x="-678806" y="-1095819"/>
41      </WDEST>
42      <MLOC/>
43      <MDST>
44      <DEST CountryName="Česká republika" RegionCode="108" RegionName="Vysočina kraj
↳ " TownShip=" Havlíčkův Brod " TownShipCode="3601"/>
45      </MDST>

```

2.2 Enumeration of report regions

Report regions are defined in *WinterConditionsRegionCodes.rnc*, each having a code and in a name.

For complete list see *WinterConditionsRegionCodes.rnc - enumeration of report regions*.

```

1  ## Winter Conditions Area Codes
2  ##
3  ## For reference only. Not used in the real-world application.
4

```

(continues on next page)

(continued from previous page)

```
5 type-region-code =
6
7 ## okres Jeseník
8 "4" |
9
10 ## okres Olomouc
11 "5" |
12
13 ## okres Prostějov
14 "6" |
15
16 ## okres Přerov
17 "7" |
18
19 ## okres Šumperk
20 "8" |
21
22 ## okres Bruntál
23 "9" |
24
25 ## okres Frýdek - Místek
26 "10" |
27
28 ## okres Karviná
```

APPENDIX A: MESSAGE EXAMPLES

3.1 dry-roads.xml

Publication contains exactly one message about clear sky and ideal weather.

```
<?xml version="1.0" encoding="utf-8"?>
<DOC DataSet="extended" country="CZ" id="{B7E48E7C-4C78}" version="1.0">
  <INF receiver="odběratel DI" sender="JSDI_NDIC" transmission="HTTP">
    <DAT>
      <SNET country="CZ" type="SN" version="1.00"/>
      <UIRADR date="2006-04-06" structure="4.2" version="522"/>
    </DAT>
  </INF>
  <MJD count="1">
    <MSG id="eca17d6a-5eea-48e6-b61f-f6060f6ada54" planned="false" type="WCOND"
    ↪version="1">
      <MTIME format="YYYY-MM-DDThh:mm:ssTZD">
        <TGEN>2007-09-26T08:27:19+02:00</TGEN>
        <TSTA>2007-09-26T08:27:19+02:00</TSTA>
        <TSTO>2007-10-26T08:27:19+02:00</TSTO>
      </MTIME>
      <MTXT language="CZ">Plzeň (Kralovicko) - Teplota od 1 do 3°C; Počasí:
      jasno, bez srážek, bezvětří, viditelnost bez omezení; Silnice I.
      třídy: holé suché, sjízdné bez omezení; Silnice II. a III. třídy:
      holé suché, sjízdné bez omezení; Volný text;</MTXT>
      <MEVT>
        <WCOND urgency="1">
          <TEMP from="1" to="3" unit="°C"/>
          <CLD CloudyCode="2" language="CZ">jasno</CLD>
          <PREC PrecipitationCode="2" language="CZ">bez srážek</PREC>
          <WIND WindCode="2" WindDirectionCode="1" language="CZ">bezvětří</WIND>
          <VIS VisibilityCode="2" language="CZ">viditelnost bez
          omezení</VIS>
          <WTXT language="CZ">Počasí: jasno, bez srážek, bezvětří,
          viditelnost bez omezení</WTXT>
          <TTXT language="CZ">Teplota od 1 do 3°C</TTXT>
        </WCOND>
        <MTNCOND>
          <ISTN InterestsSectionCode="2" InterestsSectionName="Silnice I. třídy"
          ↪urgency="1">
            <RCOND RoadConditionCode="2" language="CZ">sjízdné bez
            omezení</RCOND>
            <RSCOND RoadSurfaceConditionCode="2" language="CZ">holé
            suché</RSCOND>
            <TXISTN language="CZ">holé suché, sjízdné bez omezení</TXISTN>
```

(continues on next page)

(continued from previous page)

```

    </ISTN>
    <ISTN InterestsSectionCode="3" InterestsSectionName="Silnice II. a III.
→třídý" urgency="1">
      <RCOND RoadConditionCode="2" language="CZ">sjízdné bez
      omezení</RCOND>
      <RSCOND RoadSurfaceConditionCode="2" language="CZ">holé
      suché</RSCOND>
      <TXISTN language="CZ">holé suché, sjízdné bez omezení</TXISTN>
    </ISTN>
    </MTNCOND>
    <OTXT language="CZ">volný text</OTXT>
  </MEVT>
  <WDEST NewsRegionCode="161" NewsRegionName="Kralovicko" coordsystem="S-JTSK">
    <COORD x="-599220" y="-1163113"/>
  </WDEST>
  <MDST>
    <DEST CountryName="Česká republika" RegionCode="43" RegionName="Plzeňský"
→TownShip="Plzeň-město" TownShipCode="3405"/>
  </MDST>
</MSG>
</MJD>
</DOC>

```

3.2 new-snow-cover.xml

Publication contains exactly one message about snowing and new snow cover on roads.

```

<?xml version="1.0" encoding="utf-8"?>
<DOC DataSet="extended" country="CZ" id="{6E6A4889-7F14}" version="3.0">
  <INF receiver="JB007" sender="JSDI_NDIC" transmission="HTTP">
    <DAT>
      <UIRADR structure="4.2" version="522"/>
    </DAT>
  </INF>
  <MJD count="1">
    <MSG id="40172-124" planned="false" type="WCOND" version="1">
      <MTIME format="YYYY-MM-DDThh:mm:ssTZD">
        <TGEN>2010-02-01T02:58:14+01:00</TGEN>
        <TSTA>2010-02-01T02:57:00+01:00</TSTA>
        <TSTO>2010-02-01T14:55:00+01:00</TSTO>
      </MTIME>
      <MTXT language="CZ">okres Havlíčkův Brod - Teplota od -8 do -7°C; Počasí:
→zataženo, sněhové přeháňky, bezvětří, viditelnost bez omezení; ; ; Silnice I.
→třídý: vrstva nového sněhu, sjízdné se zvýšenou opatrností; Silnice II. a III.
→třídý: vrstva nového sněhu, sjízdné se zvýšenou opatrností; ; ; </MTXT>
      <MEVT>
        <WCOND urgency="2">
          <TEMP from="-8" to="-7" unit="°C"/>
          <CLD CloudyCode="8" language="CZ">zataženo</CLD>
          <PREC PrecipitationCode="10" language="CZ">sněhové přeháňky</PREC>
          <WIND WindCode="2" WindDirectionCode="1" language="CZ">bezvětří</WIND>
          <VIS VisibilityCode="2" language="CZ">viditelnost bez omezení</VIS>
          <WTXT language="CZ">Počasí: zataženo, sněhové přeháňky, bezvětří,
→viditelnost bez omezení</WTXT>
        </WCOND>
      </MEVT>
    </MSG>
  </MJD>
</DOC>

```

(continues on next page)

(continued from previous page)

```

    <TTXT language="CZ">Teplota od -8 do -7°C</TTXT>
  </WCOND>
  <MTNCOND>
    <ISTN InterestsSectionCode="3" InterestsSectionName="Silnice I. třídy"
    ↪urgency="3">
      <RCOND RoadConditionCode="3" language="CZ">sjízdné se zvýšenou opatrností
    ↪</RCOND>
      <RSCOND RoadSurfaceConditionCode="11" language="CZ">vrstva nového sněhu</
    ↪RSCOND>
      <TXISTN language="CZ">Silnice I. třídy: vrstva nového sněhu, sjízdné se
    ↪zvýšenou opatrností</TXISTN>
      </ISTN>
      <ISTN InterestsSectionCode="4" InterestsSectionName="Silnice II. a III.
    ↪třídy" urgency="3">
        <RCOND RoadConditionCode="3" language="CZ">sjízdné se zvýšenou opatrností
    ↪</RCOND>
        <RSCOND RoadSurfaceConditionCode="11" language="CZ">vrstva nového sněhu</
    ↪RSCOND>
        <TXISTN language="CZ">Silnice II. a III. třídy: vrstva nového sněhu,
    ↪sjízdné se zvýšenou opatrností</TXISTN>
        </ISTN>
      </MTNCOND>
    </MEVT>
    <WDEST NewsRegionCode="124" NewsRegionName="okres Havlíčkův Brod" coordsystem=
    ↪"S-JTSK">
      <COORD x="-678806" y="-1095819"/>
    </WDEST>
    <MLOC/>
    <MDST>
      <DEST CountryName="Česká republika" RegionCode="108" RegionName="Vysočina kraj
    ↪" Township=" Havlíčkův Brod " TownshipCode="3601"/>
    </MDST>
  </MSG>
</MJD>
</DOC>

```

APPENDIX B: REPRESENTATIVE XML SCHEMA: RELAX NG

We use RELAX NG Compact syntax to describe the XML document structure and we recommend you to try reading it in this form as it seems to be the most compact and readable schema format we have found.

Anyway, if you insist on using XML Schema 1.0, we include also this sort of schema produced by conversion from RELAX NG.

4.1 RELAX NG Compact Syntax Schema (RNC)

RNC schema describes expected structures of XML documents.

Root element is introduced by *start* =

All other *<SomeName>* = elements define named patterns.

In our schema there are following sections:

- prolog (namespace declaration)
- includes (not used here)
- root element definition (*start* =)
- patterns for elements
- patterns for attributes
- patterns for data types

Comments *##* specify more details about meaning of particular parts.

4.1.1 *WinterConditions.rnc* - root of the schema

```
default namespace = ""

start =

## Root element of the document
element DOC {

    ## Format version
    attribute version { type-formatVersion },

    ## Document GUID string
    ##
    ## The format of the GUID is not specified. Any format
    ## (6-4, 6-4-4-4-6, 8-4-4-4-12, number, ...) is acceptable,
    ## however it has to be unique.
```

(continues on next page)

(continued from previous page)

```

attribute id { text },

## Country code
##
## One document can only contain events from one country
attribute country { type-country },

## Data set type
##
## Always "extended"
attribute DataSet { "extended" },

## Metadata regarding subjects involved
##
## Also contains data set versions
element INF {

    ## ID of the organization supplying the TI
    ##
    ## Example: "JSDI_NDIC"
    attribute sender { text },

    ## ID of the organization for which the TI are provided
    attribute receiver { text },

    ## Transfer protocol
    attribute transmission { "HTTP" | "SMTP" | "FTP" },

    ## Metadata regarding data sets used in the document
    element DAT {

        ## Alert-C Location Table
        # TODO: Missing from the format specification
        # TODO: Not present in all real-world samples
        element LOCT {

            ## Version
            attribute version { type-AlertCLocationTableVersion },

            ## Location Table Number
            attribute number { xsd:positiveInteger },

            ## County Code
            attribute country { xsd:positiveInteger }
        }?,

        ## Street network metadata
        ##
        ## Mandatory if the document makes use of referencing to any street_
↪network
        element SNET {

            ## Street Network Type
            ##
            ## "SN" = streetnet "GN" = GlobalNetwork
            attribute type { type-snet-type },

```

(continues on next page)

(continued from previous page)

```

    ## Version
    attribute version { type-networkVersion },

    ## Country
    attribute country { "CZ" }
  }?,

  ## Metadata regarding UIRADR (Czech Street Addresses Database)
  # TODO: The format specification names this element 'UIADR' (spelling
  ↳mistake likely)
  # TODO: The format specification permits to omit this element if the
  ↳document does not
  # make use of the UIRADR database
  element UIRADR {

    ## Structure version
    attribute structure { text },

    ## Data version
    attribute version { type-nonZeroDecimal },

    ## Date of publication
    attribute date { xsd:date }?
  }
},

## Container for all traffic information (TI) Messages
element MJD {

  ## Number of TI messages in this document
  attribute count { xsd:positiveInteger },

  ## Container for a single TI message
  element-MSG*
}

#####

element-MSG =

## Container for a single TI Message
element MSG {

  ## An unique TI message identifier (GUID)
  ##
  ## The format of the GUID is arbitrary.
  attribute id { text },

  ## TI Message Version
  ##
  ## New = 1; any subsequential update +1
  # TODO: Messages with version = "0" do exist in the real-world samples.
  attribute version { xsd:nonNegativeInteger },

```

(continues on next page)

(continued from previous page)

```

## Type of the TI Message
##
## Always value "WCOND" (WinterConditions)
attribute type { "WCOND" },

## Character of the TI Message
##
## "true" ... Planned
## "false" ... Unplanned
attribute planned { xsd:boolean },

## Date and time attributes of the TI Message
element MTIME {

    ## Date time format
    ##
    ## Fixed to the ISO 8601 date and time format
    attribute format { "YYYY-MM-DDThh:mm:ssTZD" },

    ## Time and date when the TI Message was generated
    element TGEN { xsd:dateTime },

    ## Time and date of the START of the event described in the TI Message
    element TSTA { xsd:dateTime },

    ## Time and date of the END of the event described in the TI Message
    element TSTO { xsd:dateTime }
},

## Textual description of the TI Message
element MTXT {

    ## Language
    attribute language { type-language-cz },

    ## The description itself
    text
},

## Event-related data
element MEVT,

## Winter Conditions-related data
element WDEST,

## Location-related data
(element-MLOC | element-MLOC-empty)?,

## Location-related data (with regard to UIRADR database)
# TODO: The format specification permits to omit this element if the document
↪ does not
# make use of the UIRADR database
element MDST?,

## Diversion-related data

```

(continues on next page)

(continued from previous page)

```

##
## Mandatory only if there is a diversion specified in the document
element-DIVLOC?
}

#####

element-MEVT =

## Main container for Weather Conditions
element MEVT {

    ## Weather-related data
    element WCOND {

        ## Urgency
        attribute urgency {

            ## Normal
            "1" |

            ## Urgent
            "2" |

            ## Extremely Urgent
            "3"
        },

        ## Temperature information
        element TEMP {

            ## Temperature unit
            ##
            ## "°C" - Celsius "F" - Fahrenheit
            attribute unit { "°C" | "F" },

            ## Temperature From
            attribute from { xsd:integer },

            ## Temperature To
            attribute to { xsd:integer }
        },

        ## Cloud Cover
        element CLD {

            ## Cloud Cover Type Code
            attribute CloudyCode {

                ## Unspecified
                "1" |

                ## Clear
                "2" |

                ## Clear to Scattered

```

(continues on next page)

(continued from previous page)

```

    "3" |

    ## Scattered
    "4" |

    ## Scattered to Broken
    "5" |

    ## Broken
    "6" |

    ## Broken to Overcast
    "7" |

    ## Overcast
    "8"
  },

  ## Language
  attribute language { type-language-cz },

  ## Textual description
  text
},

## Precipitation
element PREC {

  ## Precipitation Type Code
  attribute PrecipitationCode {

    ## Unspecified
    "1" |

    ## No Precipitation
    "2" |

    ## Drizzle
    "3" |

    ## Freezing rain
    "4" |

    ## Rain Showers
    "5" |

    ## Rain
    "6" |

    ## Storm
    "7" |

    ## Ice pellets / Hailstones
    "8" |

    ## Rain and snow

```

(continues on next page)

(continued from previous page)

```

        "9" |

        ## Snow showers
        "10" |

        ## Snowfall
        "11" |

        ## Heavy snowfall
        "12" |

        ## Winter storm
        "13" |

        ## Snowfall, zero visibility
        "14"
    },

    ## Language
    attribute language { type-language-cz },

    ## Textual description
    text
},

## Wind
element WIND {

    ## Wind Type Code
    attribute WindCode {

        ## Unspecified
        "1" |

        ## Calm
        "2" |

        ## Strong breeze
        "3" |

        ## Strong gale
        "4" |

        ## Storm
        "5" |

        ## Strong winds, intermediate
        "6"
    },

    ## Wind Direction Code
    # TODO: Verify the meaning of the attribute:
    # direction the wind blows FROM or TO
    attribute WindDirectionCode {

        ## Unspecified

```

(continues on next page)

(continued from previous page)

```

        "1" |

        ## North
        "2" |

        ## North East
        "3" |

        ## North West
        "4" |

        ## East
        "5" |

        ## Soouth East
        "6" |

        ## South
        "7" |

        ## South West
        "8" |

        ## West
        "9" |

        ## Changing
        "10"
    },

    ## Language
    attribute language { type-language-cz },

    ## Textual description
    text
},

## Visibility
element VIS {

    ## Visibility Type Code
    attribute VisibilityCode {

        ## Unspecified
        "1" |

        ## Good
        "2" |

        ## Lowered due to rain
        "3" |

        ## Haze
        "4" |

        ## Cloudy

```

(continues on next page)

(continued from previous page)

```

        "5" |

        ## Intermittent Fog
        "6" |

        ## Fog
        "7" |

        ## Fog, visibility up to 100m
        "8" |

        ## Fog, visibility up to 50m
        "9" |

        ## Fog, visibility up to 30m
        "10" |

        ## Zero visibility
        "11"
    },

    ## Language
    attribute language { type-language-cz },

    ## Textual description
    text
},

## Aggregated textual information about weather conditions
element WTXT {

    ## Language
    attribute language { type-language-cz },

    ## Textual description
    text
},

## Aggregated textual information about temperature conditions
element TTXT {

    ## Language
    attribute language { type-language-cz },

    ## Textual description
    text
}
},

## Encapsulates all Road Conditions in the message
element MTNCOND {

    ## Encapsulates Road Condition for one road
    element ISTN {

        ## Road Class Code

```

(continues on next page)

(continued from previous page)

```

attribute InterestsSectionCode {

    ## Motorway
    "1" |

    ## Semi-motorway
    "2" |

    ## 1st Class Road
    "3" |

    ## 2nd Class Road
    "4" |

    ## Local Communication
    "5"
},

## Road Class Name
##
## "Motorway", "1st Class Road", ...
attribute InterestsSectionName { text },

## Urgency
##
attribute urgency {

    ## Normal
    "1" |

    ## Urgent
    "2" |

    ## Extremely Urgent
    "3"
},

## Road Condition - Passability State
element RCOND {

    ## Passability State Code
    attribute RoadConditionCode {

        ## Unspecified
        "1" |

        ## Easily passable
        "2" |

        ## Passable with caution
        "3" |

        ## One Lane Passable
        "4" |

        ## Two Lanes Passable

```

(continues on next page)

(continued from previous page)

```

        "5" |

        ## Passable With Snow Chains
        "6" |

        ## Impassable - Closed
        "7" |

        ## Impassable - Not maintained during winter
        "8"
    },

    ## Language
    attribute language { type-language-cz },

    ## Textual Description
    text
},

## Road Condition - Surface State
element RSCOND {

    ## Surface State
    attribute RoadSurfaceConditionCode {

        ## Unspecified
        "1" |

        ## Bare and Dry
        "2" |

        ## Bare and Dry, frozen
        "3" |

        ## Bare and Damp
        "4" |

        ## Bare and Wet
        "5" |

        ## Wet, chemically treated
        "6" |

        ## Slushy snow
        "7" |

        ## Slushy snow, chemically treated
        "8" |

        ## Patches of snow, chemically treated
        "9" |

        ## Patches of snow after snowplough
        "10" |

        ## Layer of fresh snow

```

(continues on next page)

(continued from previous page)

```

        "11" |

        ## Snow Packed
        "12" |

        ## Snow Packed, with grit
        "13" |

        ## Ice Covered
        "14" |

        ## Ice Covered, with grit
        "15" |

        ## Ice Covered,
        "16" |

        ## Black Ice
        "17" |

        ## Partly Black Ice
        "18" |

        ## Partly Snow Packed
        "19" |

        ## Snowdrift
        "20" |

        ## Calamity Situation
        "21"
    },

    ## Language
    attribute language { type-language-cz },

    ## Textual decription
    text
},

## Aggregated textual information about road conditions
element TXISTN {

    ## Language
    attribute language { type-language-cz },

    ## Textual description
    text
}
}+
},

## Free text supplied by the TI Message provider
##
## Mandatory on if present in the message
element OTXT {

```

(continues on next page)

(continued from previous page)

```

    ## Message
    text
  }?
}

#####

element-MLOC-empty =

## Location-related data
##
# TODO: According to the format specification the element is NOT mandatory.
# However it is present in the real-world samples, but it is empty.
element MLOC {
  empty
}

#####

element-MLOC =

## Location-related data
element MLOC {

  ## Textual description of the location or suggested diversion
  element-TXPL,

  ## Location specified using Alert-C Location Table
  element TMCL {

    ## Alert-C Primary Location
    ##
    ## The format specification refers to it as "Primarycode"
    attribute primarycode { xsd:positiveInteger },

    ## Alert-C Extent
    ## The format specification refers to it as "Extent"
    attribute extent { xsd:integer { minInclusive="0" maxInclusive="32" } },

    ## Alert-C Direction
    ## The format specification refers to it as "Direction"
    attribute direction { "+" | "-" },

    ## Road ID
    ## The format specification refers to it as "Roadid"
    attribute roadid { xsd:positiveInteger }
  }?,

  ## Location specified by a road network
  element SNTL {

    ## Coordinate system used
    attribute coordsystem { type-coord-system },

    ## Number of road elements affected

```

(continues on next page)

(continued from previous page)

```

    ## The format specification refers to it as "Count"
    attribute count { xsd:positiveInteger },

    ## Coordinates of the beginning of the event in the sense of traffic_
    direction,
    ## in the specified coordinate system. For linear locations it is the_
    tail of
    ## a traffic event, the place of first arrival or the secondary TMC_
    location).

    element COORD {

        ## x-coord
        attribute x { xsd:decimal },

        ## x-coord
        attribute y { xsd:decimal }
    },

    ## Road network elements affected
    element STEL {

        ## ID of the road element
        attribute el_code { xsd:positiveInteger }
    }+
}

#####

element-TXPL =

## Textual description of the location or suggested diversion
element TXPL { text }

#####

element-WDEST =

## Encapsulates information about the Area the message refers to
element WDEST {

    ## Coordinate system used
    attribute coordsystem { type-coord-system },

    ## Area Code
    ##
    ## Refer to the list of Area Codes supplied
    attribute NewsRegionCode { xsd:nonNegativeInteger },

    ## Name of the Area
    attribute NewsRegionName { text },

    ## Coordinates of the beginning of the event in the sense of traffic direction,
    ## in the specified coordinate system. For linear locations it is the tail of
    ## a traffic event, the place of first arrival or the secondary TMC location).

```

(continues on next page)

(continued from previous page)

```

element COORD {

    ## x-coord
    attribute x { xsd:decimal },

    ## x-coord
    attribute y { xsd:decimal }
}
}

#####

element MDST =

## Location-related data (with regard to UIRADR database)
# TODO: Mandatory if the message uses UIRADR database
element MDST {

    ## Container for information related to one administration unit
    ##
    ## Can be repeated if the TI Message affects more administration units
    element DEST {

        ## Country Name
        attribute CountryName { text },

        ## Part of the Town
        ##
        ## Mandatory if it exists
        attribute TownDistrictName { text }?,

        ## Code of the Part of the Town
        ##
        ## Mandatory if it exists
        attribute TownDistrictCode { xsd:integer }?,

        ## District Name
        attribute TownShip { text },

        ## District Code
        attribute TownShipCode { xsd:positiveInteger },

        ## Region Name
        attribute RegionName { text },

        ## Region Code
        attribute RegionCode { xsd:positiveInteger }
    }+

    # Note:
    # Element "ROAD" does not appear in the real-world samples and was removed
    # from the schema.
}

#####

```

(continues on next page)

(continued from previous page)

```

type-nonZeroDecimal = xsd:decimal { minExclusive="0.0" }
type-formatVersion = type-nonZeroDecimal
type-version = xsd:positiveInteger
type-AlertCLocationTableVersion = type-nonZeroDecimal
type-language-cz = "CZ"
type-country = "CZ" | "AT" | "DE" | "SK" | "PL"
type-snet-type = "SN" | "GN"
type-networkVersion = type-nonZeroDecimal
type-coord-system = "S-JTSK" | "WGS-84"

```

4.1.2 *WinterConditionsRegionCodes.rnc* - enumeration of report regions

```

1  ## Winter Conditions Area Codes
2  ##
3  ## For reference only. Not used in the real-world application.
4
5  type-region-code =
6
7  ## okres Jeseník
8  "4" |
9
10 ## okres Olomouc
11 "5" |
12
13 ## okres Prostějov
14 "6" |
15
16 ## okres Přerov
17 "7" |
18
19 ## okres Šumperk
20 "8" |
21
22 ## okres Bruntál
23 "9" |
24
25 ## okres Frýdek - Místek
26 "10" |
27
28 ## okres Karviná
29 "11" |
30
31 ## okres Nový Jičín
32 "12" |
33
34 ## okres Opava

```

(continues on next page)

(continued from previous page)

```

35 "13" |
36
37 ## R43 0-7 km
38 "14" |
39
40 ## město Brno
41 "16" |
42
43 ## okres Blansko
44 "17" |
45
46 ## okres Brno-venkov
47 "19" |
48
49 ## okres Břeclav
50 "20" |
51
52 ## okres Hodonín
53 "21" |
54
55 ## okres Vyškov
56 "22" |
57
58 ## okres Znojmo
59 "23" |
60
61 ## Jeseníky (Olomoucký kraj)
62 "25" |
63
64 ## město Ostrava
65 "26" |
66
67 ## D1 0-45 km
68 "27" |
69
70 ## Pardubicko
71 "31" |
72
73 ## Holicko
74 "32" |
75
76 ## Přeloučsko
77 "33" |
78
79 ## Chrudimsko
80 "34" |
81
82 ## Hlinecko
83 "35" |
84
85 ## Skutečsko
86 "36" |
87
88 ## Železné Hory - Třemošnicko
89 "37" |
90

```

(continues on next page)

(continued from previous page)

```
91 ## Orlicko - Ústecko
92 "38" |
93
94 ## Lanškrounsko
95 "39" |
96
97 ## Vysokomýtsko
98 "40" |
99
100 ## Žamberecko
101 "41" |
102
103 ## Litomyšlsko
104 "42" |
105
106 ## Svitavsko
107 "43" |
108
109 ## Moravskotřebovsko
110 "44" |
111
112 ## Poličsko
113 "45" |
114
115 ## okres Ústí nad Labem
116 "46" |
117
118 ## okres Teplice
119 "47" |
120
121 ## okres Most
122 "48" |
123
124 ## okres Chomutov
125 "49" |
126
127 ## okres Louny
128 "50" |
129
130 ## okres Litoměřice
131 "51" |
132
133 ## okres Děčín
134 "52" |
135
136 ## Krušné Hory (Ústecký kraj)
137 "53" |
138
139 ## okres Jičín
140 "58" |
141
142 ## okres Hradec Králové
143 "59" |
144
145 ## okres Náchod
146 "60" |
```

(continues on next page)

(continued from previous page)

```

147
148 ## okres Trutnov
149 "61" |
150
151 ## okres Rychnov nad Kněžnou
152 "62" |
153
154 ## Krkonoše (Královéhradecký kraj)
155 "63" |
156
157 ## Krkonoše (Liberecký kraj) II. a III. tř.
158 "64" |
159
160 ## Orlické Hory (Královéhradecký kraj)
161 "65" |
162
163 ## Jizerské Hory (Liberecký kraj) II. a III. tř.
164 "66" |
165
166 ## okres České Budějovice
167 "67" |
168
169 ## okres Český Krumlov
170 "68" |
171
172 ## okres Jindřichův Hradec
173 "69" |
174
175 ## okres Písek
176 "70" |
177
178 ## okres Strakonice
179 "71" |
180
181 ## okres Tábor
182 "72" |
183
184 ## okres Prachatice
185 "73" |
186
187 ## Šumava (Jihočeský kraj)
188 "74" |
189
190 ## D1 45-94 km
191 "75" |
192
193 ## D1 94-141,5 km
194 "76" |
195
196 ## D1 141,5-188,5 km
197 "77" |
198
199 ## D1 188,5-219 km
200 "78" |
201
202 ## D2 0-11 km

```

(continues on next page)

(continued from previous page)

```

203 "79" |
204
205 ## D2 11-61 km
206 "80" |
207
208 ## D5 0-28,5 km
209 "81" |
210
211 ## D5 28,5-80 km
212 "82" |
213
214 ## D5 80-131 km
215 "83" |
216
217 ## D8 0-48 km
218 "84" |
219
220 ## D11 0-49 km
221 "85" |
222
223 ## D5 131-151 km
224 "86" |
225
226 ## R35 261,5-298,5 km
227 "87" |
228
229 ## okres Karlovy Vary
230 "88" |
231
232 ## okres Sokolov
233 "90" |
234
235 ## okres Cheb
236 "91" |
237
238 ## okres Benešov
239 "92" |
240
241 ## okres Příbram
242 "93" |
243
244 ## okres Kutná Hora
245 "94" |
246
247 ## okres Kolín
248 "95" |
249
250 ## okres Nymburk
251 "96" |
252
253 ## okres Praha - východ (jih)
254 "97" |
255
256 ## okres Vsetín (II. a III. tř.)
257 "98" |
258

```

(continues on next page)

(continued from previous page)

```

259 ## okres Kroměříž
260 "99" |
261
262 ## okres Zlín (II. a III. tř.)
263 "100" |
264
265 ## okres Uherské Hradiště (II. a III. tř.)
266 "101" |
267
268 ## Hlavní město Praha
269 "102" |
270
271 ## město Plzeň
272 "103" |
273
274 ## Beskydy (Moravskoslezský kraj)
275 "105" |
276
277 ## Jeseníky (Moravskoslezský kraj)
278 "106" |
279
280 ## okres Kladno
281 "107" |
282
283 ## okres Beroun
284 "108" |
285
286 ## okres Praha - západ
287 "109" |
288
289 ## okres Rakovník
290 "110" |
291
292 ## R1 0-3,5 km
293 "114" |
294
295 ## okres Havlíčkův Brod
296 "124" |
297
298 ## okres Jihlava
299 "125" |
300
301 ## okres Pelhřimov
302 "126" |
303
304 ## okres Třebíč
305 "127" |
306
307 ## město Pardubice
308 "128" |
309
310 ## město Hradec Králové
311 "129" |
312
313 ## město Mladá Boleslav
314 "130" |

```

(continues on next page)

(continued from previous page)

```

315
316 ## město Kladno
317 "131" |
318
319 ## město Liberec
320 "132" |
321
322 ## město Ústí nad Labem
323 "133" |
324
325 ## město Zlín
326 "134" |
327
328 ## město Karlovy Vary
329 "135" |
330
331 ## město České Budějovice
332 "136" |
333
334 ## město Havířov
335 "137" |
336
337 ## město Olomouc
338 "138" |
339
340 ## město Jihlava
341 "139" |
342
343 ## město Teplice
344 "140" |
345
346 ## okres Žďár nad Sázavou
347 "141" |
348
349 ## okres Rokycany
350 "142" |
351
352 ## okres Domažlice
353 "144" |
354
355 ## okres Česká Lípa (II. a III. tř.)
356 "149" |
357
358 ## R6 0-32 km
359 "150" |
360
361 ## okres Jablonec n. Nisou (II. a III. tř.)
362 "151" |
363
364 ## okres Liberec (II. a III. tř.)
365 "152" |
366
367 ## R10 3,5-33 km
368 "154" |
369
370 ## okres Semily (II. a III. tř.)

```

(continues on next page)

(continued from previous page)

```

371 "155" |
372
373 ## R10 33-66,5 km
374 "157" |
375
376 ## Šumava (Plzeňský kraj)
377 "158" |
378
379 ## Orlické Hory (Pardubický kraj)
380 "159" |
381
382 ## město Opava
383 "160" |
384
385 ## město Karviná
386 "161" |
387
388 ## R4 0-41 km
389 "175" |
390
391 ## město Most
392 "176" |
393
394 ## okres Česká Lípa (I. tř.)
395 "178" |
396
397 ## okres Liberec (I. tř.)
398 "179" |
399
400 ## okres Semily (I. tř.)
401 "180" |
402
403 ## R10 66,5-73 km
404 "181" |
405
406 ## R35 11-44 km
407 "182" |
408
409 ## okres Jablonec n. Nisou (I. tř.)
410 "183" |
411
412 ## D8 64-80 km
413 "187" |
414
415 ## R7 0-19 km
416 "188" |
417
418 ## R46 34-39,5 km
419 "191" |
420
421 ## R52 0-26,5 km
422 "192" |
423
424 ## R63 0-6 km
425 "194" |
426

```

(continues on next page)

(continued from previous page)

```

427 ## D3 62,1-104,1 km
428 "195" |
429
430 ## R35 219-260 km
431 "196" |
432
433 ## Krkonoše (Liberecký kraj) I. tř.
434 "198" |
435
436 ## Jizerské Hory (Liberecký kraj) I. tř.
437 "199" |
438
439 ## D11 49-86 km
440 "200" |
441
442 ## okres Kladno (I/6, I/7, I/16)
443 "203" |
444
445 ## okres Benešov (I/3, I/18)
446 "204" |
447
448 ## okres Příbram (I/4, I/18, I/19, I/66)
449 "205" |
450
451 ## okres Rakovník (I/6, I/27)
452 "206" |
453
454 ## okres Praha - východ (I/2, I/12)
455 "207" |
456
457 ## okres Kutná Hora (I/2, I/17, I/38)
458 "208" |
459
460 ## okres Kolín (I/2, I/12, I/38)
461 "209" |
462
463 ## okres Nymburk (I/11, I/32, I/38)
464 "210" |
465
466 ## Mladoboleslavsko (I. tř.)
467 "211" |
468
469 ## Mělnicko (I. tř.)
470 "212" |
471
472 ## Mnichovo Hradiště a okolí (I. tř.)
473 "213" |
474
475 ## Kralupsko (I. tř.)
476 "214" |
477
478 ## město Jindřichův Hradec
479 "215" |
480
481 ## D8 80-92 km
482 "216" |

```

(continues on next page)

(continued from previous page)

```
483
484 ## město Holice
485 "218" |
486
487 ## město Nymburk
488 "219" |
489
490 ## město Volary
491 "220" |
492
493 ## město Čelákovice
494 "221" |
495
496 ## město Horní Slavkov
497 "222" |
498
499 ## město Lomnice nad Popelkou
500 "223" |
501
502 ## město Prostějov
503 "224" |
504
505 ## město Vrbno
506 "225" |
507
508 ## město Nový Bor
509 "226" |
510
511 ## město Třinec
512 "227" |
513
514 ## město Humpolec
515 "228" |
516
517 ## město Chomutov
518 "229" |
519
520 ## město Nová Bystřice
521 "230" |
522
523 ## město Strážnice
524 "231" |
525
526 ## město Otrokovice
527 "232" |
528
529 ## město Postoloprty
530 "233" |
531
532 ## město Lanškroun
533 "234" |
534
535 ## město Moravská Třebová
536 "235" |
537
538 ## město Valašské Klobouky
```

(continues on next page)

(continued from previous page)

```

539 "236" |
540
541 ## město Lipník nad Bečvou
542 "237" |
543
544 ## město Holešov
545 "238" |
546
547 ## město Dačice
548 "240" |
549
550 ## město Velké Meziříčí
551 "241" |
552
553 ## město Nové město na Moravě
554 "242" |
555
556 ## město Bruntál
557 "243" |
558
559 ## město Pelhřimov
560 "244" |
561
562 ## město Příbram
563 "245" |
564
565 ## okres Plzeň - sever
566 "246" |
567
568 ## okres Plzeň - jih
569 "247" |
570
571 ## město Mimoň
572 "249" |
573
574 ## město Blatná
575 "250" |
576
577 ## oblast Uherský Brod (I. tř.)
578 "251" |
579
580 ## oblast Uherské Hradiště (I. tř.)
581 "252" |
582
583 ## město Jablonec nad Nisou
584 "253" |
585
586 ## město Svitavy
587 "254" |
588
589 ## město Benátky nad Jizerou
590 "255" |
591
592 ## město Sedlčany
593 "258" |
594

```

(continues on next page)

(continued from previous page)

```

595 ## město Slavonice
596 "259" |
597
598 ## město Frýdlant nad Ostravicí
599 "260" |
600
601 ## město Česká Třebová
602 "261" |
603
604 ## město Litvínov
605 "262" |
606
607 ## město Dvůr Králové nad Labem
608 "263" |
609
610 ## D1 341,5-376,5 km
611 "264" |
612
613 ## město Sušice
614 "265" |
615
616 ## město Cheb
617 "266" |
618
619 ## město Broumov
620 "267" |
621
622 ## město Napajedla
623 "268" |
624
625 ## město Bohumín
626 "269" |
627
628 ## město Havlíčkův Brod
629 "311" |
630
631 ## město Kunovice
632 "314" |
633
634 ## město Příbor
635 "315" |
636
637 ## D1 296-341,5 km
638 "316" |
639
640 ## město Česká Lípa
641 "317" |
642
643 ## R35 Sedlice-Opatovice
644 "319" |
645
646 ## okres Mladá Boleslav
647 "322" |
648
649 ## okres Mělník
650 "323" |

```

(continues on next page)

(continued from previous page)

```

651
652 ## okres Praha - východ (sever)
653 "324" |
654
655 ## R1 0-29 km
656 "326" |
657
658 ## R1 75-82,56 km
659 "327" |
660
661 ## okres Klatovy
662 "328" |
663
664 ## okres Tachov
665 "329" |
666
667 ## R55 15-31,7 km
668 "331" |
669
670 ## R46 0-33 km
671 "332" |
672
673 ## D1 218-272 km
674 "333" |
675
676 ## I/21 a I/64 (Karlovarský kraj)
677 "334" |
678
679 ## R6 a I/6 (Karlovarský kraj)
680 "335" |
681
682 ## I/6, I/13, I/20 a I/25 (Karlovarský kraj)
683 "336" |
684
685 ## I/49, I/55 a I/69 (Zlínský kraj)
686 "337" |
687
688 ## I/35, I/49 a I/57 (Zlínský kraj)
689 "338" |
690
691 ## R56 39,5-42 km
692 "339" |
693
694 ## R56 42-52 km
695 "340" |
696
697 ## R48 0-3 km
698 "341" |
699
700 ## R48 30-31 km
701 "342" |
702
703 ## R48 38-44 km
704 "343" |
705
706 ## R48 46-62 km

```

(continues on next page)

(continued from previous page)

707
708
709
710

"344" |
R48 62-70 km
"345"

CHANGELOG

version 3.2.5.0

- Initial format and documentation

ALTERNATIVE XML SCHEMA: W3C XML SCHEMA 1.0 (XSD)

W3C XML Schema 1.0 is probably the most popular format for describing XML structures today.

XSD schema provided bellow was created by transforming RNC schema and shall reflect all the features from RNC. In (unlikely) case, there are differences, RELAX NG Compact syntax is the one to use.

6.1 *WinterConditions.xsd* - root of the schema

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema elementFormDefault="qualified" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="DOC">
    <xs:annotation>
      <xs:documentation>Root element of the document</
↪xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="INF"/>
        <xs:element ref="MJD"/>
      </xs:sequence>
      <xs:attribute name="version" type="type-formatVersion" use=
↪"required">
        <xs:annotation>
          <xs:documentation>Format version</
↪xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="id" use="required">
        <xs:annotation>
          <xs:documentation>Document GUID string The
↪format of the GUID is
        not specified. Any format (6-4, 6-4-4-4-6, 8-4-4-4-12, number,
        ...) is acceptable, however it has to be
        unique.</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="country" type="type-country" use="required
↪">
        <xs:annotation>
          <xs:documentation>Country code One document
↪can only contain
        events from one country</xs:documentation>
        </xs:annotation>
      </xs:attribute>
```

(continues on next page)

(continued from previous page)

```

        <xs:attribute name="DataSet" use="required">
          <xs:annotation>
            <xs:documentation>Data set type Always
            &quot;extended&quot;</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:token">
              <xs:enumeration value="extended"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:attribute>
      </xs:complexType>
    </xs:element>
    <xs:element name="INF">
      <xs:annotation>
        <xs:documentation>Metadata regarding subjects involved Also
        ↪ contains
        data set versions</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:sequence>
          <xs:element ref="DAT"/>
        </xs:sequence>
        <xs:attribute name="sender" use="required">
          <xs:annotation>
            <xs:documentation>ID of the organization
            ↪ supplying the TI
            Example: &quot;JSDI_NDIC&quot;</xs:documentation>
          </xs:annotation>
        </xs:attribute>
        <xs:attribute name="receiver" use="required">
          <xs:annotation>
            <xs:documentation>ID of the organization for
            ↪ which the TI are
            provided</xs:documentation>
          </xs:annotation>
        </xs:attribute>
        <xs:attribute name="transmission" use="required">
          <xs:annotation>
            <xs:documentation>Transfer protocol</
            ↪ xs:documentation>
          </xs:annotation>
        </xs:simpleType>
        <xs:restriction base="xs:token">
          <xs:enumeration value="HTTP"/>
          <xs:enumeration value="SMTP"/>
          <xs:enumeration value="FTP"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:attribute>
  </xs:complexType>
</xs:element>
<xs:element name="DAT">
  <xs:annotation>
    <xs:documentation>Metadata regarding data sets used in the
    document</xs:documentation>

```

(continues on next page)

(continued from previous page)

```

        </xs:annotation>
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" ref="LOCT"/>
                <xs:element minOccurs="0" ref="SNET"/>
                <xs:element ref="UIRADR"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="LOCT">
        <xs:annotation>
            <xs:documentation>Alert-C Location Table</xs:documentation>
        </xs:annotation>
        <xs:complexType>
            <xs:attribute name="version" type="type-
↪AlertCLocationTableVersion" use="required">
                <xs:annotation>
                    <xs:documentation>Version</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="number" type="xs:positiveInteger" use=
↪"required">
                <xs:annotation>
                    <xs:documentation>Location Table Number</
↪xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="country" type="xs:positiveInteger" use=
↪"required">
                <xs:annotation>
                    <xs:documentation>County Code</
↪xs:documentation>
                </xs:annotation>
            </xs:attribute>
        </xs:complexType>
    </xs:element>
    <xs:element name="SNET">
        <xs:annotation>
            <xs:documentation>Street network metadata Mandatory if the
↪document
            makes use of referencing to any street network</xs:documentation>
        </xs:annotation>
        <xs:complexType>
            <xs:attribute name="type" type="type-snet-type" use="required
↪">
                <xs:annotation>
                    <xs:documentation>Street Network Type &quot;
↪SN&quot;; = streetnet &quot;GN&quot;; =
            GlobalNetwork</xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="version" type="type-networkVersion" use=
↪"required">
                <xs:annotation>
                    <xs:documentation>Version</xs:documentation>
                </xs:annotation>

```

(continues on next page)

(continued from previous page)

```

        </xs:attribute>
        <xs:attribute name="country" use="required">
          <xs:annotation>
            <xs:documentation>Country</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:token">
              <xs:enumeration value="CZ"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:attribute>
      </xs:complexType>
    </xs:element>
    <xs:element name="UIRADR">
      <xs:annotation>
        <xs:documentation>Metadata regarding UIRADR (Czech Street_
↪Addresses
        Database)</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:attribute name="structure" use="required">
          <xs:annotation>
            <xs:documentation>Structure version</
↪xs:documentation>
          </xs:annotation>
        </xs:attribute>
        <xs:attribute name="version" type="type-nonZeroDecimal" use=
↪"required">
          <xs:annotation>
            <xs:documentation>Data version</
↪xs:documentation>
          </xs:annotation>
        </xs:attribute>
        <xs:attribute name="date" type="xs:date">
          <xs:annotation>
            <xs:documentation>Date of publication</
↪xs:documentation>
          </xs:annotation>
        </xs:attribute>
      </xs:complexType>
    </xs:element>
    <xs:element name="MJD">
      <xs:annotation>
        <xs:documentation>Container for all traffic information (TI)
        Messages</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:sequence>
          <xs:element maxOccurs="unbounded" minOccurs="0" ref=
↪"MSG">
            <xs:annotation>
              <xs:documentation>Container for a_
↪single TI
            message</xs:documentation>
          </xs:annotation>
        </xs:element>

```

(continues on next page)

(continued from previous page)

```

        </xs:sequence>
        <xs:attribute name="count" type="xs:positiveInteger" use=
↪ "required">
            <xs:annotation>
                <xs:documentation>Number of TI messages in
↪ this
                document</xs:documentation>
            </xs:annotation>
        </xs:attribute>
    </xs:complexType>
</xs:element>
<xs:element name="MSG">
    <xs:annotation>
        <xs:documentation>Container for a single TI
Message</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="MTIME"/>
            <xs:element ref="MTXT"/>
            <xs:element ref="MEVT">
                <xs:annotation>
                    <xs:documentation>Event-related data</
↪ xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element ref="WDEST">
                <xs:annotation>
                    <xs:documentation>Winter Conditions-
↪ related
                    data</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:choice minOccurs="0">
                <xs:annotation>
                    <xs:documentation>Location-related
↪ data</xs:documentation>
                </xs:annotation>
                <xs:group ref="element-MLOC"/>
                <xs:group ref="element-MLOC-empty"/>
            </xs:choice>
            <xs:element minOccurs="0" ref="MDST">
                <xs:annotation>
                    <xs:documentation>Location-related
↪ data (with regard to UIRADR
                    database)</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element minOccurs="0" ref="DIVLOC">
                <xs:annotation>
                    <xs:documentation>Diversion-related
↪ data Mandatory only if
                    there is a diversion specified in the
                    document</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

(continues on next page)

(continued from previous page)

```

        </xs:sequence>
        <xs:attribute name="id" use="required">
          <xs:annotation>
            <xs:documentation>An unique TI message_
↪ identifier (GUID) The
            format of the GUID is arbitrary.</xs:documentation>
          </xs:annotation>
        </xs:attribute>
        <xs:attribute name="version" type="xs:nonNegativeInteger" use=
↪ "required">
          <xs:annotation>
            <xs:documentation>TI Message Version New = 1;_
↪ any subsequential
            update +1</xs:documentation>
          </xs:annotation>
        </xs:attribute>
        <xs:attribute name="type" use="required">
          <xs:annotation>
            <xs:documentation>Type of the TI Message_
↪ Always value &quot;WCOND&quot;;
            (WinterConditions)</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:token">
              <xs:enumeration value="WCOND"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:attribute>
        <xs:attribute name="planned" type="xs:boolean" use="required">
          <xs:annotation>
            <xs:documentation>Character of the TI Message_
↪ &quot;true&quot;; ... Planned
            &quot;false&quot;; ... Unplanned</xs:documentation>
          </xs:annotation>
        </xs:attribute>
      </xs:complexType>
    </xs:element>
    <xs:element name="MTIME">
      <xs:annotation>
        <xs:documentation>Date and time attributes of the TI
Message</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:sequence>
          <xs:element ref="TGEN"/>
          <xs:element ref="TSTA"/>
          <xs:element ref="TSTO"/>
        </xs:sequence>
        <xs:attribute name="format" use="required">
          <xs:annotation>
            <xs:documentation>Date time format Fixed to_
↪ the ISO 8601 date and
            time format</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:token">

```

(continues on next page)

(continued from previous page)

```

<xs:enumeration value="YYYY-MM-DDThh:mm:ssTZD"/>
    </xs:restriction>
  </xs:simpleType>
</xs:attribute>
</xs:complexType>
</xs:element>
<xs:element name="TGEN" type="xs:dateTime">
  <xs:annotation>
    <xs:documentation>Time and date when the TI Message was
generated</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="TSTA" type="xs:dateTime">
  <xs:annotation>
    <xs:documentation>Time and date of the START of the event.
described
in the TI Message</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="TSTO" type="xs:dateTime">
  <xs:annotation>
    <xs:documentation>Time and date of the END of the event.
described in
the TI Message</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="MTXT">
  <xs:annotation>
    <xs:documentation>Textual description of the TI
Message</xs:documentation>
  </xs:annotation>
  <xs:complexType mixed="true">
    <xs:attribute name="language" type="type-language-cz" use=
required">
      <xs:annotation>
        <xs:documentation>Language</xs:documentation>
      </xs:annotation>
    </xs:attribute>
  </xs:complexType>
</xs:element>
<xs:element name="MEVT">
  <xs:annotation>
    <xs:documentation>Main container for Weather
Conditions</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="WCOND"/>
      <xs:element ref="MTNCOND"/>
      <xs:element minOccurs="0" ref="OTXT"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="WCOND">
  <xs:annotation>

```

(continues on next page)

(continued from previous page)

```

        <xs:documentation>Weather-related data</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="TEMP"/>
            <xs:element ref="CLD"/>
            <xs:element ref="PREC"/>
            <xs:element ref="WIND"/>
            <xs:element ref="VIS"/>
            <xs:element ref="WTXT"/>
            <xs:element ref="TTXT"/>
        </xs:sequence>
        <xs:attribute name="urgency" use="required">
            <xs:annotation>
                <xs:documentation>Urgency</xs:documentation>
            </xs:annotation>
            <xs:simpleType>
                <xs:restriction base="xs:token">
                    <xs:enumeration value="1">
                        <xs:annotation>
                            <xs:documentation>
↪ Normal</xs:documentation>
                        </xs:annotation>
                    </xs:enumeration>
                    <xs:enumeration value="2">
                        <xs:annotation>
                            <xs:documentation>
↪ Urgent</xs:documentation>
                        </xs:annotation>
                    </xs:enumeration>
                    <xs:enumeration value="3">
                        <xs:annotation>
                            <xs:documentation>
↪ Extremely Urgent</xs:documentation>
                        </xs:annotation>
                    </xs:enumeration>
                </xs:restriction>
            </xs:simpleType>
        </xs:attribute>
    </xs:complexType>
</xs:element>
<xs:element name="TEMP">
    <xs:annotation>
        <xs:documentation>Temperature information</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:attribute name="unit" use="required">
            <xs:annotation>
                <xs:documentation>Temperature unit &quot;;°C&
↪ quot; - Celsius &quot;;F&quot;; -
                Fahrenheit</xs:documentation>
            </xs:annotation>
            <xs:simpleType>
                <xs:restriction base="xs:token">
                    <xs:enumeration value="°C"/>
                    <xs:enumeration value="°F"/>

```

(continues on next page)

(continued from previous page)

```

        </xs:restriction>
      </xs:simpleType>
    </xs:attribute>
    <xs:attribute name="from" type="xs:integer" use="required">
      <xs:annotation>
        <xs:documentation>Temperature From</
<xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:attribute name="to" type="xs:integer" use="required">
      <xs:annotation>
        <xs:documentation>Temperature To</
<xs:documentation>
      </xs:annotation>
    </xs:attribute>
  </xs:complexType>
</xs:element>
<xs:element name="CLD">
  <xs:annotation>
    <xs:documentation>Cloud Cover</xs:documentation>
  </xs:annotation>
  <xs:complexType mixed="true">
    <xs:attribute name="CloudyCode" use="required">
      <xs:annotation>
        <xs:documentation>Cloud Cover Type Code</
<xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:restriction base="xs:token">
      <xs:enumeration value="1">
        <xs:annotation>
          <xs:documentation>
<xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="2">
        <xs:annotation>
          <xs:documentation>
<xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="3">
        <xs:annotation>
          <xs:documentation>
<xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="4">
        <xs:annotation>
          <xs:documentation>
<xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="5">
        <xs:annotation>
          <xs:documentation>
<xs:documentation>
        </xs:annotation>
      </xs:enumeration>
    </xs:restriction>
  </xs:complexType>
</xs:element>

```

(continues on next page)

(continued from previous page)

```

↪ Scattered to Broken</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="6">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Broken</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="7">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Broken to Overcast</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="8">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Overcast</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                </xs:restriction>
                                </xs:simpleType>
                                </xs:attribute>
                                <xs:attribute name="language" type="type-language-cz" use=
↪ "required">
                                    <xs:annotation>
                                        <xs:documentation>Language</xs:documentation>
                                    </xs:annotation>
                                </xs:attribute>
                                </xs:complexType>
                            </xs:element>
                            <xs:element name="PREC">
                                <xs:annotation>
                                    <xs:documentation>Precipitation</xs:documentation>
                                </xs:annotation>
                                <xs:complexType mixed="true">
                                    <xs:attribute name="PrecipitationCode" use="required">
                                        <xs:annotation>
                                            <xs:documentation>Precipitation Type Code</
↪ xs:documentation>
                                        </xs:annotation>
                                    <xs:simpleType>
                                        <xs:restriction base="xs:token">
                                            <xs:enumeration value="1">
                                                <xs:annotation>
                                                    <xs:documentation>
↪ Unspecified</xs:documentation>
                                                </xs:annotation>
                                            </xs:enumeration>
                                            <xs:enumeration value="2">
                                                <xs:annotation>
                                                    <xs:documentation>No_
↪ Precipitation</xs:documentation>
                                                </xs:annotation>
                                            </xs:enumeration>

```

(continues on next page)

(continued from previous page)

```

<xs:enumeration value="3">
  <xs:annotation>
    <xs:documentation>
      ↪ Drizzle</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="4">
    <xs:annotation>
      <xs:documentation>
        ↪ Freezing rain</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="5">
      <xs:annotation>
        <xs:documentation>
          ↪ Rain Showers</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="6">
        <xs:annotation>
          <xs:documentation>Rain
            ↪ </xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="7">
        <xs:annotation>
          <xs:documentation>
            ↪ Storm</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="8">
          <xs:annotation>
            <xs:documentation>Ice
              ↪ pellets /
                Hailstones</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="9">
          <xs:annotation>
            <xs:documentation>
              ↪ Rain and snow</xs:documentation>
            </xs:annotation>
          </xs:enumeration>
          <xs:enumeration value="10">
            <xs:annotation>
              <xs:documentation>
                ↪ Snow showers</xs:documentation>
              </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="11">
              <xs:annotation>
                <xs:documentation>
                  ↪ Snowfall</xs:documentation>
                </xs:annotation>
              </xs:enumeration>
              <xs:enumeration value="12">

```

(continues on next page)

(continued from previous page)

```

<xs:annotation>
  <xs:documentation>
↪ Heavy snowfall</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>
↪ Winter storm</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>
↪ Snowfall, zero
    visibility</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:attribute>
<xs:attribute name="language" type="type-language-cz" use=
↪ "required">
  <xs:annotation>
    <xs:documentation>Language</xs:documentation>
  </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>
<xs:element name="WIND">
  <xs:annotation>
    <xs:documentation>Wind</xs:documentation>
  </xs:annotation>
  <xs:complexType mixed="true">
    <xs:attribute name="WindCode" use="required">
      <xs:annotation>
        <xs:documentation>Wind Type Code</
↪ xs:documentation>
      </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:token">
        <xs:enumeration value="1">
          <xs:annotation>
            <xs:documentation>
↪ Unspecified</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="2">
          <xs:annotation>
            <xs:documentation>Calm
↪ </xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="3">
          <xs:annotation>
            <xs:documentation>

```

(continues on next page)

(continued from previous page)

```

↪ Strong breeze</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="4">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Strong gale</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="5">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Storm</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="6">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Strong winds,
    intermediate</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                </xs:restriction>
                                </xs:simpleType>
                                </xs:attribute>
                                <xs:attribute name="WindDirectionCode" use="required">
                                    <xs:annotation>
                                        <xs:documentation>Wind Direction Code</
↪ xs:documentation>
                                </xs:annotation>
                                <xs:simpleType>
                                    <xs:restriction base="xs:token">
                                        <xs:enumeration value="1">
                                            <xs:annotation>
                                                <xs:documentation>
↪ Unspecified</xs:documentation>
                                    </xs:annotation>
                                    </xs:enumeration>
                                    <xs:enumeration value="2">
                                        <xs:annotation>
                                            <xs:documentation>
↪ North</xs:documentation>
                                    </xs:annotation>
                                    </xs:enumeration>
                                    <xs:enumeration value="3">
                                        <xs:annotation>
                                            <xs:documentation>
↪ North East</xs:documentation>
                                    </xs:annotation>
                                    </xs:enumeration>
                                    <xs:enumeration value="4">
                                        <xs:annotation>
                                            <xs:documentation>
↪ North West</xs:documentation>
                                    </xs:annotation>
                                    </xs:enumeration>

```

(continues on next page)

(continued from previous page)

```

<xs:enumeration value="5">
  <xs:annotation>
    <xs:documentation>East
↪</xs:documentation>

    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="6">
    <xs:annotation>
      <xs:documentation>
↪South East</xs:documentation>

    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="7">
    <xs:annotation>
      <xs:documentation>
↪South</xs:documentation>

    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="8">
    <xs:annotation>
      <xs:documentation>
↪South West</xs:documentation>

    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="9">
    <xs:annotation>
      <xs:documentation>West
↪</xs:documentation>

    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="10">
    <xs:annotation>
      <xs:documentation>
↪Changing</xs:documentation>

    </xs:annotation>
  </xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:attribute>
<xs:attribute name="language" type="type-language-cz" use=
↪"required">

    <xs:annotation>
      <xs:documentation>Language</xs:documentation>
    </xs:annotation>
  </xs:attribute>
</xs:complexType>
</xs:element>
<xs:element name="VIS">
  <xs:annotation>
    <xs:documentation>Visibility</xs:documentation>
  </xs:annotation>
  <xs:complexType mixed="true">
    <xs:attribute name="VisibilityCode" use="required">
      <xs:annotation>
        <xs:documentation>Visibility Type Code</
↪xs:documentation>

```

(continues on next page)

(continued from previous page)

```

        </xs:annotation>
        <xs:simpleType>
            <xs:restriction base="xs:token">
                <xs:enumeration value="1">
                    <xs:annotation>
                        <xs:documentation>
<-- Unspecified</xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="2">
                    <xs:annotation>
                        <xs:documentation>Good
<-- </xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="3">
                    <xs:annotation>
                        <xs:documentation>
<-- Lowered due to rain</xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="4">
                    <xs:annotation>
                        <xs:documentation>Haze
<-- </xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="5">
                    <xs:annotation>
                        <xs:documentation>
<-- Cloudy</xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="6">
                    <xs:annotation>
                        <xs:documentation>
<-- Intermitent Fog</xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="7">
                    <xs:annotation>
                        <xs:documentation>Fog
<-- </xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="8">
                    <xs:annotation>
                        <xs:documentation>Fog,
<-- visibility up to
                           100m</xs:documentation>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="9">
                    <xs:annotation>
                        <xs:documentation>Fog,
<-- visibility up to

```

(continues on next page)

(continued from previous page)

```

50m</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="10">
                                    <xs:annotation>
                                        <xs:documentation>Fog,
↪ visibility up to
30m</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                <xs:enumeration value="11">
                                    <xs:annotation>
                                        <xs:documentation>
↪ Zero visibility</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                </xs:restriction>
                                </xs:simpleType>
                                </xs:attribute>
                                <xs:attribute name="language" type="type-language-cz" use=
↪ "required">
                                    <xs:annotation>
                                        <xs:documentation>Language</xs:documentation>
                                    </xs:annotation>
                                </xs:attribute>
                                </xs:complexType>
                            </xs:element>
                            <xs:element name="WTXT">
                                <xs:annotation>
                                    <xs:documentation>Aggregated textual information about weather
conditions</xs:documentation>
                                </xs:annotation>
                                <xs:complexType mixed="true">
                                    <xs:attribute name="language" type="type-language-cz" use=
↪ "required">
                                        <xs:annotation>
                                            <xs:documentation>Language</xs:documentation>
                                        </xs:annotation>
                                    </xs:attribute>
                                </xs:complexType>
                            </xs:element>
                            <xs:element name="TTXT">
                                <xs:annotation>
                                    <xs:documentation>Aggregated textual information about_
↪ temperature
conditions</xs:documentation>
                                </xs:annotation>
                                <xs:complexType mixed="true">
                                    <xs:attribute name="language" type="type-language-cz" use=
↪ "required">
                                        <xs:annotation>
                                            <xs:documentation>Language</xs:documentation>
                                        </xs:annotation>
                                    </xs:attribute>
                                </xs:complexType>
                            </xs:element>

```

(continues on next page)

(continued from previous page)

```

<xs:element name="MTNCOND">
  <xs:annotation>
    <xs:documentation>Encapsulates all Road Conditions in the
message</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" ref="ISTN"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ISTN">
  <xs:annotation>
    <xs:documentation>Encapsulates Road Condition for one
road</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="RCOND"/>
      <xs:element ref="RSCOND"/>
      <xs:element ref="TXISTN"/>
    </xs:sequence>
    <xs:attribute name="InterestsSectionCode" use="required">
      <xs:annotation>
        <xs:documentation>Road Class Code</
↪xs:documentation>
        </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:token">
          <xs:enumeration value="1">
            <xs:annotation>
              <xs:documentation>
↪Motorway</xs:documentation>
            </xs:annotation>
          </xs:enumeration>
          <xs:enumeration value="2">
            <xs:annotation>
              <xs:documentation>
↪Semi-motorway</xs:documentation>
            </xs:annotation>
          </xs:enumeration>
          <xs:enumeration value="3">
            <xs:annotation>
              <xs:documentation>1st_
↪Class Road</xs:documentation>
            </xs:annotation>
          </xs:enumeration>
          <xs:enumeration value="4">
            <xs:annotation>
              <xs:documentation>2nd_
↪Class Road</xs:documentation>
            </xs:annotation>
          </xs:enumeration>
          <xs:enumeration value="5">
            <xs:annotation>
              <xs:documentation>

```

(continues on next page)

(continued from previous page)

```

↪Local Communication</xs:documentation>
                                </xs:annotation>
                                </xs:enumeration>
                                </xs:restriction>
                                </xs:simpleType>
                                </xs:attribute>
                                <xs:attribute name="InterestsSectionName" use="required">
                                    <xs:annotation>
                                        <xs:documentation>Road Class Name &quot;;
↪Motorway&quot;;, &quot;;1st Class Road&quot;;,
...</xs:documentation>
                                </xs:annotation>
                                </xs:attribute>
                                <xs:attribute name="urgency" use="required">
                                    <xs:annotation>
                                        <xs:documentation>Urgency</xs:documentation>
                                    </xs:annotation>
                                    <xs:simpleType>
                                        <xs:restriction base="xs:token">
                                            <xs:enumeration value="1">
                                                <xs:annotation>
                                                    <xs:documentation>
↪Normal</xs:documentation>
                                                </xs:annotation>
                                                </xs:enumeration>
                                            <xs:enumeration value="2">
                                                <xs:annotation>
                                                    <xs:documentation>
↪Urgent</xs:documentation>
                                                </xs:annotation>
                                                </xs:enumeration>
                                            <xs:enumeration value="3">
                                                <xs:annotation>
                                                    <xs:documentation>
↪Extremely Urgent</xs:documentation>
                                                </xs:annotation>
                                                </xs:enumeration>
                                        </xs:restriction>
                                    </xs:simpleType>
                                </xs:attribute>
                            </xs:complexType>
                        </xs:element>
                    <xs:element name="RCOND">
                        <xs:annotation>
                            <xs:documentation>Road Condition - Passability
State</xs:documentation>
                        </xs:annotation>
                        <xs:complexType mixed="true">
                            <xs:attribute name="RoadConditionCode" use="required">
                                <xs:annotation>
                                    <xs:documentation>Passability State Code</
↪xs:documentation>
                                </xs:annotation>
                                <xs:simpleType>
                                    <xs:restriction base="xs:token">
                                        <xs:enumeration value="1">

```

(continues on next page)

(continued from previous page)

```

<xs:annotation>
  <xs:documentation>
↪ Unspecified</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="2">
  <xs:annotation>
    <xs:documentation>
↪ Easily passable</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="3">
  <xs:annotation>
    <xs:documentation>
↪ Passable with caution</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4">
  <xs:annotation>
    <xs:documentation>One↵
↪ Lane Passable</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="5">
  <xs:annotation>
    <xs:documentation>Two↵
↪ Lanes Passable</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="6">
  <xs:annotation>
    <xs:documentation>
↪ Passable With Snow
    Chains</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7">
  <xs:annotation>
    <xs:documentation>
↪ Impassable - Closed</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="8">
  <xs:annotation>
    <xs:documentation>
↪ Impassable - Not maintained during
    winter</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:attribute>
<xs:attribute name="language" type="type-language-cz" use=
↪ "required">
  <xs:annotation>
    <xs:documentation>Language</xs:documentation>

```

(continues on next page)

(continued from previous page)

```

        </xs:annotation>
      </xs:attribute>
    </xs:complexType>
  </xs:element>
  <xs:element name="RSCOND">
    <xs:annotation>
      <xs:documentation>Road Condition - Surface State</
↪ xs:documentation>
    </xs:annotation>
    <xs:complexType mixed="true">
      <xs:attribute name="RoadSurfaceConditionCode" use="required">
        <xs:annotation>
          <xs:documentation>Surface State</
↪ xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="1">
              <xs:annotation>
                <xs:documentation>
↪ Unspecified</xs:documentation>
              </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="2">
              <xs:annotation>
                <xs:documentation>
↪ Bare and Dry</xs:documentation>
              </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="3">
              <xs:annotation>
                <xs:documentation>
↪ Bare and Dry, frozen</xs:documentation>
              </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="4">
              <xs:annotation>
                <xs:documentation>
↪ Bare and Damp</xs:documentation>
              </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="5">
              <xs:annotation>
                <xs:documentation>
↪ Bare and Wet</xs:documentation>
              </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="6">
              <xs:annotation>
                <xs:documentation>Wet,
↪ chemically
              treated</xs:documentation>
            </xs:annotation>
          </xs:enumeration>
          <xs:enumeration value="7">
            <xs:annotation>

```

(continues on next page)

(continued from previous page)

↪ Slushy snow</xs:documentation>	<xs:documentation>
	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="8">
	<xs:annotation>
	<xs:documentation>
↪ Slushy snow, chemically treated</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="9">
	<xs:annotation>
	<xs:documentation>
↪ Patches of snow, chemically treated</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="10">
	<xs:annotation>
	<xs:documentation>
↪ Patches of snow after snowplough</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="11">
	<xs:annotation>
	<xs:documentation>
↪ Layer of fresh snow</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="12">
	<xs:annotation>
	<xs:documentation>
↪ Snow Packed</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="13">
	<xs:annotation>
	<xs:documentation>
↪ Snow Packed, with grit</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="14">
	<xs:annotation>
	<xs:documentation>Ice_
↪ Covered</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="15">
	<xs:annotation>
	<xs:documentation>Ice_
↪ Covered, with grit</xs:documentation>	</xs:annotation>
	</xs:enumeration>
	<xs:enumeration value="16">

(continues on next page)

(continued from previous page)

```

<xs:annotation>
  <xs:documentation>Ice
↪ Covered,</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>
↪ Black Ice</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>
↪ Partly Black Ice</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="19">
  <xs:annotation>
    <xs:documentation>
↪ Partly Snow Packed</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="20">
  <xs:annotation>
    <xs:documentation>
↪ Snowdrift</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="21">
  <xs:annotation>
    <xs:documentation>
↪ Calamity Situation</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:attribute>
<xs:attribute name="language" type="type-language-cz" use=
↪ "required">
  <xs:annotation>
    <xs:documentation>Language</xs:documentation>
  </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>
<xs:element name="TXISTN">
  <xs:annotation>
    <xs:documentation>Aggregated textual information about road
conditions</xs:documentation>
  </xs:annotation>
<xs:complexType mixed="true">
  <xs:attribute name="language" type="type-language-cz" use=
↪ "required">
    <xs:annotation>
      <xs:documentation>Language</xs:documentation>

```

(continues on next page)

(continued from previous page)

```

        </xs:annotation>
    </xs:attribute>
</xs:complexType>
</xs:element>
<xs:element name="OTXT">
    <xs:annotation>
        <xs:documentation>Free text supplied by the TI Message_
provider
Mandatory on if present in the message</xs:documentation>
    </xs:annotation>
    <xs:complexType mixed="true">
        <xs:attribute name="language" type="type-language-cz" use=
"required">
            <xs:annotation>
                <xs:documentation>Language</xs:documentation>
            </xs:annotation>
        </xs:attribute>
    </xs:complexType>
</xs:element>
<xs:group name="element-MLOC-empty">
    <xs:annotation>
        <xs:documentation/>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="MLOC">
            <xs:annotation>
                <xs:documentation>Location-related data</
xs:documentation>
            </xs:annotation>
        <xs:complexType/>
    </xs:element>
</xs:sequence>
</xs:group>
<xs:group name="element-MLOC">
    <xs:annotation>
        <xs:documentation/>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="MLOC">
            <xs:annotation>
                <xs:documentation>Location-related data</
xs:documentation>
            </xs:annotation>
        <xs:complexType>
            <xs:complexContent>
                <xs:extension base="element-TXPL">
                    <xs:sequence>
                        <xs:element minOccurs=
"0" ref="TMCL"/>
                        <xs:element ref="SNTL
"/>
                    </xs:sequence>
                </xs:extension>
            </xs:complexContent>
        </xs:complexType>
    </xs:element>

```

(continues on next page)

(continued from previous page)

```

        </xs:sequence>
    </xs:group>
    <xs:element name="TMCL">
        <xs:annotation>
            <xs:documentation>Location specified using Alert-C Location
Table</xs:documentation>
        </xs:annotation>
        <xs:complexType>
            <xs:attribute name="primarycode" type="xs:positiveInteger"
↪use="required">
                <xs:annotation>
                    <xs:documentation>Alert-C Primary Location↪
↪The format
specification refers to it as <xs:documentation>
                    </xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="extent" use="required">
                <xs:annotation>
                    <xs:documentation>Alert-C Extent The format↪
↪specification refers
to it as <xs:documentation>
                    </xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:integer">
                        <xs:minInclusive value="0"/>
                        <xs:maxInclusive value="32"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:attribute>
            <xs:attribute name="direction" use="required">
                <xs:annotation>
                    <xs:documentation>Alert-C Direction The↪
↪format specification
refers to it as <xs:documentation>
                    </xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:token">
                        <xs:enumeration value="+"/>
                        <xs:enumeration value="-"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:attribute>
            <xs:attribute name="roadid" type="xs:positiveInteger" use=
↪"required">
                <xs:annotation>
                    <xs:documentation>Road ID The format↪
↪specification refers to it
as <xs:documentation>
                    </xs:documentation>
                </xs:annotation>
            </xs:attribute>
        </xs:complexType>
    </xs:element>
    <xs:element name="SNTL">
        <xs:annotation>
            <xs:documentation>Location specified by a road
network</xs:documentation>

```

(continues on next page)

(continued from previous page)

```

        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="COORD">
              <xs:annotation>
                <xs:documentation>Coordinates of the
↳ beginning of the event in
                the specified coordinate system</xs:documentation>
              </xs:annotation>
              <xs:complexType>
                <xs:attribute name="x" type=
↳ "xs:decimal" use="required">
                  <xs:annotation>
                    <xs:documentation>x-
↳ coord</xs:documentation>
                  </xs:annotation>
                </xs:attribute>
                <xs:attribute name="y" type=
↳ "xs:decimal" use="required">
                  <xs:annotation>
                    <xs:documentation>x-
↳ coord</xs:documentation>
                  </xs:annotation>
                </xs:attribute>
              </xs:complexType>
            </xs:element>
            <xs:element maxOccurs="unbounded" ref="STEL"/>
          </xs:sequence>
          <xs:attribute name="coordsystem" type="type-coord-system" use=
↳ "required">
            <xs:annotation>
              <xs:documentation>Coordinate system used</
↳ xs:documentation>
            </xs:annotation>
          </xs:attribute>
          <xs:attribute name="count" type="xs:positiveInteger" use=
↳ "required">
            <xs:annotation>
              <xs:documentation>Number of road elements
↳ affected The format
              specification refers to it as &quot;Count&quot;</xs:documentation>
            </xs:annotation>
          </xs:attribute>
        </xs:complexType>
      </xs:element>
      <xs:element name="STEL">
        <xs:annotation>
          <xs:documentation>Road network elements affected</
↳ xs:documentation>
        </xs:annotation>
      </xs:complexType>
      <xs:attribute name="el_code" type="xs:positiveInteger" use=
↳ "required">
        <xs:annotation>
          <xs:documentation>ID of the road element</
↳ xs:documentation>

```

(continues on next page)

(continued from previous page)

```

        </xs:annotation>
      </xs:attribute>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="element-TXPL">
    <xs:annotation>
      <xs:documentation/>
    </xs:annotation>
    <xs:sequence>
      <xs:element ref="TXPL"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="TXPL" type="xs:string">
    <xs:annotation>
      <xs:documentation>Textual description of the location or
↪ suggested
diversion</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="WDEST">
    <xs:annotation>
      <xs:documentation>Encapsulates information about the Area the
↪ message
refers to</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="COORD">
          <xs:annotation>
            <xs:documentation>Coordinates of the
↪ beginning of the event in the sense
of traffic direction, in the
↪ specified coordinate system. For linear locations
it is the tail of a traffic event,
↪ the place of first arrival or the secondary
TMC location).</xs:documentation>
          </xs:annotation>
          <xs:complexType>
            <xs:attribute name="x" type=
↪ "xs:decimal" use="required">
              <xs:annotation>
                <xs:documentation>x-
↪ coord</xs:documentation>
              </xs:annotation>
            </xs:attribute>
            <xs:attribute name="y" type=
↪ "xs:decimal" use="required">
              <xs:annotation>
                <xs:documentation>x-
↪ coord</xs:documentation>
              </xs:annotation>
            </xs:attribute>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="coordsystem" type="type-coord-system" use=

```

(continues on next page)

(continued from previous page)

```

↪ "required">
                                <xs:annotation>
                                    <xs:documentation>Coordinate system used</
↪ xs:documentation>
                                </xs:annotation>
                                </xs:attribute>
                                <xs:attribute name="NewsRegionCode" type=
↪ "xs:nonNegativeInteger" use="required">
                                    <xs:annotation>
                                        <xs:documentation>Area Code Refer to the list
↪ of Area Codes
                                        supplied</xs:documentation>
                                    </xs:annotation>
                                    </xs:attribute>
                                    <xs:attribute name="NewsRegionName" use="required">
                                        <xs:annotation>
                                            <xs:documentation>Name of the Area</
↪ xs:documentation>
                                        </xs:annotation>
                                        </xs:attribute>
                                    </xs:complexType>
                                </xs:element>
                                <xs:element name="MDST">
                                    <xs:annotation>
                                        <xs:documentation>Location-related data (with regard to UIRADR
database)</xs:documentation>
                                    </xs:annotation>
                                    <xs:complexType>
                                        <xs:sequence>
                                            <xs:element maxOccurs="unbounded" ref="DEST"/>
                                        </xs:sequence>
                                    </xs:complexType>
                                </xs:element>
                                <xs:element name="DEST">
                                    <xs:annotation>
                                        <xs:documentation>Container for information related to one
administration unit Can be repeated if the TI Message affects more
administration units</xs:documentation>
                                    </xs:annotation>
                                    <xs:complexType>
                                        <xs:attribute name="CountryName" use="required">
                                            <xs:annotation>
                                                <xs:documentation>Country Name</
↪ xs:documentation>
                                            </xs:annotation>
                                        </xs:attribute>
                                        <xs:attribute name="TownDistrictName">
                                            <xs:annotation>
                                                <xs:documentation>Part of the Town Mandatory
↪ if it
                                                exists</xs:documentation>
                                            </xs:annotation>
                                            </xs:attribute>
                                            <xs:attribute name="TownDistrictCode" type="xs:integer">
                                                <xs:annotation>
                                                    <xs:documentation>Code of the Part of the

```

(continues on next page)

(continued from previous page)

```

↪Town Mandatory if it
    exists</xs:documentation>
        </xs:annotation>
    </xs:attribute>
    <xs:attribute name="TownShip" use="required">
        <xs:annotation>
            <xs:documentation>District Name</
↪xs:documentation>
                </xs:annotation>
            </xs:attribute>
            <xs:attribute name="TownShipCode" type="xs:positiveInteger"
↪use="required">
                <xs:annotation>
                    <xs:documentation>District Code</
↪xs:documentation>
                        </xs:annotation>
                    </xs:attribute>
                    <xs:attribute name="RegionName" use="required">
                        <xs:annotation>
                            <xs:documentation>Region Name</
↪xs:documentation>
                                </xs:annotation>
                            </xs:attribute>
                            <xs:attribute name="RegionCode" type="xs:positiveInteger" use=
↪"required">
                                <xs:annotation>
                                    <xs:documentation>Region Code</
↪xs:documentation>
                                        </xs:annotation>
                                        </xs:attribute>
                                    </xs:complexType>
                                </xs:element>
                                <xs:element name="DIVLOC">
                                    <xs:annotation>
                                        <xs:documentation>Diversion Mandatory only if a diversion is
specified</xs:documentation>
                                    </xs:annotation>
                                    <xs:complexType>
                                        <xs:sequence>
                                            <xs:element maxOccurs="unbounded" ref="DIVROUTE"/>
                                        </xs:sequence>
                                    </xs:complexType>
                                </xs:element>
                                <xs:element name="DIVROUTE">
                                    <xs:annotation>
                                        <xs:documentation>Textual description of a leg of a
diversion</xs:documentation>
                                    </xs:annotation>
                                    <xs:complexType>
                                        <xs:complexContent>
                                            <xs:extension base="element-TXPL">
                                                <xs:attribute name="description" use="required
↪">
                                                    <xs:annotation>
                                                        <xs:documentation>Description
↪</xs:documentation>

```

(continues on next page)

(continued from previous page)

```

                </xs:annotation>
            </xs:attribute>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
</xs:element>
<xs:simpleType name="type-nonZeroDecimal">
    <xs:restriction base="xs:decimal">
        <xs:minExclusive value="0.0"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="type-formatVersion">
    <xs:restriction base="type-nonZeroDecimal"/>
</xs:simpleType>
<xs:simpleType name="type-version">
    <xs:restriction base="xs:positiveInteger"/>
</xs:simpleType>
<xs:simpleType name="type-AlertCLocationTableVersion">
    <xs:restriction base="type-nonZeroDecimal"/>
</xs:simpleType>
<xs:simpleType name="type-language-cz">
    <xs:restriction base="xs:token">
        <xs:enumeration value="CZ"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="type-country">
    <xs:restriction base="xs:token">
        <xs:enumeration value="CZ"/>
        <xs:enumeration value="AT"/>
        <xs:enumeration value="DE"/>
        <xs:enumeration value="SK"/>
        <xs:enumeration value="PL"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="type-snet-type">
    <xs:restriction base="xs:token">
        <xs:enumeration value="SN"/>
        <xs:enumeration value="GN"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="type-networkVersion">
    <xs:restriction base="type-nonZeroDecimal"/>
</xs:simpleType>
<xs:simpleType name="type-coord-system">
    <xs:restriction base="xs:token">
        <xs:enumeration value="S-JTSK"/>
        <xs:enumeration value="WGS-84"/>
    </xs:restriction>
</xs:simpleType>
</xs:schema>

```