

Description of the data structure profile of Network and Timetable Exchange (NeTEx) standard for the electronic publication of timetables in the Czech National Timetable Information System

1 Overview

The Czech National Information System of Timetables (hereinafter referred to as CIS JR) is an information system containing information on transport connections.

CIS JŘ contains approved timetables of national regular public transportation (including urban bus transportation) and approved timetables of public railway passenger transportation on tram, trolleybus, special or cable railways operated in the Czech Republic. Timetables are submitted to CIS JR in electronic form mostly in JDF format. The JDF-1.11 version contains a description of the JDF format for bus transport and is published as Annex in the guideline for CIS JŘ.

CIS JR contains approved timetables of public railway passenger transportation on nationwide, regional in the Czech Republic. Timetables are submitted to CISJR in electronic form in format version TAF/TAP TSI version 2.1. The data set in the DJŘ_CIS format is a single XML file and contains the timetable of one specific train or its variants in terms of the train operation calendar. The data file is submitted to the CIS JŘ by the Railway Administration, state organisation.

NeTEx CEN/TS 16614 series (<http://www.netex-cen.eu>) is dedicated to the exchange of scheduled data (network, timetable, and fare information). The XML schema is based on the Transmodel V6 (EN 12986) abstract model (<http://www.transmodel-cen.eu>) which contains general concepts and data structures for public transport and can be used to exchange many different types of data between passenger information systems, including descriptive data and SIRI (CEN/TS 15531-4/5 and EN 15531-1/2/3) and supports information exchange of relevance to public transport services for passenger information and AVMS systems.

More information can be found here <https://data4pt-project.eu/knowledge-database/data4pt-wiki/>.

The NeTEx standard consists of the following set of documents:

- ČSN P CEN/TS 16614-1, Network and Timetable Exchange (NeTEx) - Network description
- ČSN P CEN/TS 16614-2, Network and Timetable Exchange (NeTEx) - Timing information
- ČSN P CEN/TS 16614-3, Network and Timetable Exchange (NeTEx) - Fare description
- ČSN P CEN/TS 16614-4, Network and Timetable Exchange (NeTEx) -Passenger Information European Profile EPIP
- ČSN P CEN/TS 16614-5, Network and Timetable Exchange (NeTEx) - Alternative modes exchange format
- ČSN P CEN/TS 16614-6, Network and Timetable Exchange (NeTEx) - European Passenger Information Accessibility Profile – EPIAP

The European Passenger Information Profile (EPIP), which is described in the technical specification ČSN P CEN/TS 16614-4, has been chosen for publishing the current timetables of national regular public transportation, timetables of public passenger rail transport on special railways, tramways, trolleybuses and cableways and timetables of public passenger rail transport on national and regional railways within the CIS JŘ in the NeTEx format.

The EPIP profile has been designed to be as concise as possible and to focus on the data elements needed to fulfil the EC's Priority action A of ITS-Directive and EPIP is a subset of the two parts of NeTEx (CSN P CEN/TS 16614-1 and 16614-2) and represents the agreed minimum concepts and data structures for the exchange of public transport data.

The current content of the CIS JŘ in EPIP NeTEx format is published on the portal <https://portal.cisjr.cz> in the following scope:

1. Current timetables of national regular public transportation, which are published in the framework of the CIS JŘ in the JDF 1.11 data format (and lower versions of this format),
2. Current timetables of public passenger rail transport on special railways, tramways, trolleybuses and cableways, which are published in the framework of the CIS JŘ in the JDF 1.11 data format (and lower versions of this format),
3. timetables of public passenger rail transport on national and regional railways which are published within the framework of CIS JŘ in the XML data format with the content according to the "Description of data timetables transmitted to the National Information System on public passenger transport timetables version 1.09".

The published content is updated three times a week, on Monday, Wednesday, and Friday.

2 NeTEx minimum profile of electronic timetables for JDF form National regular public transport

Timetables contains of national regular public transportation published in CIS JŘ consist of one ZIP archives with data files in the JDF format and ZIP archives with data files in the JDF format of timetables of public railway passenger transportation on tram, trolleybus, special or cable railways.

Each JDF data file is converted into a NeTEx EPIP data file. Timetable data file in the NeTEx EPIP structure are published in ZIP archives:

- `NeTEx_VerejnaLinkovaDoprava.zip` - Public line transport timetables,
- `NeTEx_DrahyMestske.zip` - Public passenger rail transport on special railways, tramways, trolleybuses, and cableways timetables.

The following description provides a commentary on how the timetable items are converted from JDF to the NeTEx EPIP profile.

2.1 List of public transport stops profile

The list of stops is created from the JDF file stop codebook (file *Zastavky*).

- Each record is processed into the elements `SiteFrame/stopPlaces/StopPlace`.

- The name of the stop is processed from the structure: Village name, Village part and Nearest place into the element SiteFrame/stopPlaces/StopPlace/Name.
- The characteristics of the stop are listed in the elements:
 - StopPlace,
 - StopPlace/Facilities/SiteFacilitySet,
 - ServiceFrame/journeyPatterns/ServiceJourneyPattern/points InSequence/StopPointInJourneyPattern.

The following data structures of stop are recorded:

NeTeX EPIP data structure element	Value
SiteFacilitySet/AccessFacilityList	"lowFloorAccess"
SiteFacilitySet/CateringFacilityList	"bistro"
SiteFacilitySet/SanitaryFacilityList	"toilet."
SiteFacilitySet/SanitaryFacilityList	"wheelChairAccessToilet"
SiteFacilitySet/AccessibilityInfoFacilityList	"displaysForVisuallyImpaired"
StopPlace/OtherTransportModes	"rail"
StopPointInJourneyPattern/RequestStop	true, false
StopPointInJourneyPattern/ForBoarding	true, false
StopPointInJourneyPattern/ForAlighting	true, false
StopPlace/BorderCrossing	true, false
SiteFacilitySet/MobilityFacilityList	"suitableForHeavilyDisabled"
StopPlace/OtherTransportModes	"bus"
StopPlace/OtherTransportModes	"subway."
StopPlace/OtherTransportModes	"water"
StopPlace/OtherTransportModes	"air"
SiteFacilitySet/ParkingFacilityList	"parkAndRidePark"

2.2 List of operators profile

The list of operators is created from the JDF file carrier codebook (file Dopravci).

- Each record is processed into the element ResourceFrame/organisations/Operator.

The following operators' characteristics are recorded:

Retrieved from	NeTeX EPIP data structure element
ID	Operator/PublicCode
Business name	Operator/LegalName
Headquarters (address)	Operator/Address/AddressLine1
Telephone information	Operator/ContactDetails/Phone
E-mail	Operator/ContactDetails/Email
www	Operator/ContactDetails/Url

2.3 Line profile

The line data is created from the list of JDF file links (file Linky).

- Each record is processed into the element `ServiceFrame/lines/Line`.

The following line are recorded:

Retrieved from	NeTeX EPIP data structure element
Line number	Line/PublicCode and Line/ShortName
Line name	Line/Name
Carrier ID number	Line/OperatorRef
Type of line	Line/keyList/KeyValue/Key['JdfLineType']/Value
Means of transport	Line/TransportMode
TT during disruption	Line/keyList/KeyValue/Key['JdfDetourTimetable']/Value
TT Validity from	Line/ValidBetween/FromDate
TT Validity until	Line/ValidBetween/ToDate

2.4 Additional information

Additional information on the affiliation of the line version to public transport or integrated transport system from the records in the JDF file (`LinExt` file) are processed into the data structure of the NeTeX EPIP standard.

- Each record is processed into an element `ServiceFrame/lines/Line/keyList/Key['JdfLinExt']/Value = "Transport code; Line designation"`.
- The Line label from the record with the Preference flag set is processed into the element `ServiceFrame/lines/Line/ShortName`, replaces the value from the Lines file.

2.5 Line stops profile

Stop point are created from entries lines in file Zaslinky JDF form, which contains a list of stops for each version of the journey.

- Each record is processed into the element `ServiceFrame/scheduledStopPoints/ScheduledStopPoint`
 - the NeTeX EPIP standard requires the `ScheduledStopPoint/Location` element, however the JDF format does not contain information about geographical location.

- The Tariff zone data is processed in the form of the `ScheduledStopPoint/TariffZones/TariffZoneRef` link to the processed list of `ServiceFrame/TariffZones`.
- Line stops features that restrict passenger service are listed in the elements:
 - `ServiceFrame/journeyPatterns/ServiceJourneyPattern`,
 - `ServiceFrame/journeyPatterns/ServiceJourneyPattern/pointsInSequence/StopPointInJourneyPattern`.
- The designation of stops where passengers are not allowed to board for the purpose of transport to other identically marked stops of the connection (restrictions of the type §, §1, §2 and §3) is processed in the form of lists with reference to the given stop in a sequence of stops.

The following stop point elements are recorded:

NeTex EPIP data structure element	Value
<code>StopPointInJourneyPattern/ForBoarding</code>	true, false
<code>StopPointInJourneyPattern/ForAlighting</code>	true, false
<code>StopPointInJourneyPattern/RequestStop</code>	true, false
<code>ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCode\$']/Value</code>	<code>StopPointInJourneyPattern/@id</code>
<code>ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCodeA']/Value</code>	<code>StopPointInJourneyPattern/@id</code>
<code>ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCodeB']/Value</code>	<code>StopPointInJourneyPattern/@id</code>
<code>ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCodeC']/Value</code>	<code>StopPointInJourneyPattern/@id</code>

2.6 Journey profile

Journey data is created from the JDF file connection list (file Spoje).

- Each record is processed into the element `TimetableFrame/vehicleJourneys/ServiceJourney`
- The connection number is specified in the element `ServiceJourney/Name`.
- Fixed sign codes to indicate the days on which the service operates and data to express the time range of the service on specific dates or in specific intervals of days are processed into the connection operation calendar in the element `ServiceCalendarFrame/ServiceCalendar/operatingPeriods/UicOperatingPeriod` of the NeTex EPIP data structure and the reference to the calendar is specified in the elements `ServiceJourney/dayTypes/DayTypeRef` by means of bindings according to the standard.
- The information about the fully or partially booked or conditionally operated connection is processed into the `ServiceJourney/FlexibleServiceProperties` element and its sub-elements `BookingAccess`, `BookingMethods`, `CancellationPossible` and `BookingNote`.

- The information about connection as a service are listed in the `ServiceJourney/facilities/ServiceFacilitySetelement`. Each record is processed into a `ResourceFrame/organizations/Operator` element.

The following services facility are registered on the connection:

NeTEx EPIP data structure element	Value
<code>ServiceFacilitySet/ServiceReservationFacilityList</code>	"reservationsPossible"
<code>ServiceFacilitySet/ServiceReservationFacilityList</code>	"reservationsCompulsory"
<code>ServiceFacilitySet/MobilityFacilityList</code>	"lowFloor"
<code>ServiceFacilitySet/CateringFacilityList</code>	"snacks"
<code>ServiceFacilitySet/MobilityFacilityList</code>	"unaccompaniedMinorAssistance"
<code>ServiceFacilitySet/LuggageCarriageFacilityList</code>	"baggageStorage"
<code>ServiceFacilitySet/LuggageCarriageFacilityList</code>	"cyclesAllowed"

2.7 Stop point in Journey profile

Stop point in journey are created for each connection from the records of the JDF file `Zasspoje`, where there is one record for each connection and its stop at the line stop - stop at the given stop with the given arrival and/or departure times and without the times with the flags "the connection is passing through the stop" or "the journey pattern is on a different journey".

- Only records with arrival and/or departure times are processed.
- The sequence of stops is processed into an element for each stop point journey. `ServiceFrame/journeyPatterns/ServiceJourneyPattern`.
- The stop time data are processed into elements for each link `TimetableFrame/vehicleJourneys/ServiceJourney/passingTimes/TimeTabledPassingTime`,
 - the JDF format does not contain sufficient data to process the `Timing/Offset` sub-elements.
- The tariff distance (Kilometers) is processed as a reference in the `StopPointInJourneyPattern/OnwardServiceLinkRef` element to the distance between two subsequent stops of the connection processed in the `ServiceFrame/serviceLinks/ServiceLink` element.
- The information about the service of a stop on booking or conditional is processed into the element `StopPointInJourneyPattern/FlexiblePointProperties` and further into the element `ServiceJourney/FlexibleServiceProperties` and its sub-elements `BookingAccess`, `BookingMethods`, `CancellationPossible` and `BookingNote`.
- The characteristics of the stop point of the journey that restrict passenger service are listed in the elements:
 - `ServiceFrame/journeyPatterns/ServiceJourneyPattern`,

- ServiceFrame/journeyPatterns/ServiceJourneyPattern/pointsInSequence/StopPointInJourneyPattern.
- The stop points where passengers are not allowed to board for the purpose of transport to other identically marked stops of the connection (restrictions of the type \$, \$1, \$2 and \$3) is processed in the form of lists with reference to the given stop in a sequence of stops.

The following elements of the stop point are recorded:

NeTex EPIP data structure element	Value
StopPointInJourneyPattern/ForBoarding	true, false
StopPointInJourneyPattern/ForAlighting	true, false
StopPointInJourneyPattern/RequestStop	true, false
ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCode\$']/Value	StopPointInJourneyPattern/@id
ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCodeA']/Value	StopPointInJourneyPattern/@id
ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCodeB']/Value	StopPointInJourneyPattern/@id
ServiceJourneyPattern/keyList/KeyValue/Key['JdfFixedCodeC']/Value	StopPointInJourneyPattern/@id

2.8 Additional text notes on the line

The additional text notes for the journey are created from the JDF files.

- Each record is processed into the element ServiceFrame/lines/Line/noticeAssignments/NoticeAssignment element in the form of a text note in the Notice sub-element.

2.9 Essential data for the journey

Various types of essential data related to the journey are created from the records of JDF file Caskody

- Records with data for expressing the time range of operation of the journey on specific data-determined days or at specific intervals of days are processed into the journey operation calendar in the element. ServiceCalendarFrame/ServiceCalendar/operatingPeriods/UicOperatingPeriod of the NeTex EPIP standard data structure and the reference to the calendar is specified in the ServiceJourney/dayTypes/DayTypeRef element using bindings according to the standard.
- Records with textual information about the booking method or condition linked to a journey fully or partially operated on a booking or conditional basis are processed into the ServiceJourney/FlexibleServiceProperties element and its sub-elements BookingAccess, BookingMethods, CancellationPossible and BookingNote.

- Other records with text information tied to the journey are processed into the `ServiceJourney/noticeAssignments/NoticeAssignment` element in the form of a text note in the Notice sub-element.

2.10 Additional textual notes about connection at the journey stop

The additional text notes in the connection stop are created from the records in the JDF batch continuity file, which contains information about waiting for the connection and the possibility of transferring from/to another line at a specific connection stop.

- Each record is processed in the element `ServiceFrame/journeyPatterns/ServiceJourneyPattern/pointsInSequence/StopPointInJourneyPattern/NoticeAssignments/NoticeAssignment`,
 - the Note entry in the form of a text note in the Notice sub-element,
 - data Type of continuity in sub-element `keyList/KeyValue/Key['JdfFixedCode']/Value = "Continuity type"`.

2.11 Alternative operator connections

The information about the carrier of the connection other than the carrier of the line is created from the records of the Altdop JDF batch file.

- Each record is listed in the `TimetableFrame/vehicleJourneys/ServiceJourney/OperatorRef` element.
- The record with the value 0 in the field Connection number is also included in the element `ServiceFrame/lines/Line/AdditionalOperators/OperatorRef`.

2.12 Supplementary text notes on booking connections

The additional text information about the connection reservation is created from entries in the Mistenky JDF batch file.

- Each record is processed in the `TimetableFrame/vehicleJourneys/ServiceJourney/NoticeAssignments/NoticeAssignment` element as a text note in the Notice sub-element.

3 NeTEx minimum profile of electronic timetables for JDF form public railway passenger transportation on nationwide, regional in the Czech Republic

The original current published timetable within the National Timetable Information System consists of several XML files in the DJŘ_CIS format, which are continuously being added as the timetables change. The DTR_CIS containing the train timetable are individually converted into XML files of the NeTEx EPIP data structure, which are published on an

ongoing basis. The names of the source and destination files include the train identification (variant).

The timetable data file in the NeTEx EPIP standard structure are published grouped in ZIP archives in folders according to the train timetable period,

- trunk Time Tables (TT) in the NeTEx_GVDggg*.zip files, where gggg is the GVD year designation, may be followed by the sequence designation of a partial nationwide Time Table change in the train timetable period,
- interim changes in calendar months in the NeTEx_GVDggg_updates_yyy-MM.zip files, where ggg is the GVD year designation, yyy is the year and MM is the calendar month number.

The following is a commentary on the processing of the timetable content of the DJŘ_CIS format into the data structures of the NeTEx EPIP.

3.1 List of stop points profile

The list of stop place is processed in the `SiteFrame/stopPlaces/StopPlace` elements of the NeTEx EPIP data structure - the following data is used:

- `StopPlace/Name`
- `StopPlace/StopPlaceType = "railStation"`

3.2 List of operators profile

The list of carriers is processed in the `ResourceFrame/organisations/Operator` elements of the NeTEx EPIP data structure - the following data is used:

- `Operator/PublicCode`
- `Operator/LegalName`
- `Operator/OrganisationType = "operator"`
- `Operator/Address/AddressLine1`

3.3 Connection (train) profile

The file in the DJŘ_CIS format contains the timetable of one specific train (connection) or its variants in terms of the train operation calendar. The journey is created in the `TimetableFrame/vehicleJourneys/ServiceJourney` element of the NeTEx EPIP data structure.

The basic data about the connection are given in the `ServiceFrame/lines/Line` element.

NeTEx EPIP data structure element	Fixed value or value from the DJŘ_CIS format element
-----------------------------------	--

Line/Name	CZPTTCISMessage/NetworkSpecificParameter [Name=' CZTrainName'][1]/Value or CZPTTLocation[1]/OperationalTrainNumber
Line/ShortName	CZPTTLocation[1]/OperationalTrainNumber
Line/TransportMode	"rail"
Line/PublicCode	CZPTTLocation[1]/OperationalTrainNumber
Line/OperatorRef/@ref	CZPTTLocation[1]/ResponsibleRU

3.4 Connection operating calendar

The link operation calendar is converted from the CZPTTCISMessage/CZPTTInformation/PlannedCalendar element of the DJŘ_CIS format into the ServiceCalendar/operatingPeriods/UicOperatingPeriod element of the NeTex EPIP standard data structure and the calendar reference is specified in the ServiceJourney/dayTypes/DayTypeRef element by means of bindings according to the standard.

3.5 Notes with connection properties

The notes with the connection properties are processed from the so-called "central notes" of the DJŘ_CIS format and are listed in the

ServiceJourney/facilities/ServiceFacilitySet element of the NeTex EPIP data structure.

The following properties are recorded:

Element of the NeTex EPIP standard structure	Value
ServiceFacilitySet/AccommodationFacilityList	"couchette"
ServiceFacilitySet/AccommodationFacilityList	"sleeper"
ServiceFacilitySet/CateringFacilityList	"bistro"
ServiceFacilitySet/CateringFacilityList	"restaurant"
ServiceFacilitySet/CateringFacilityList	"snacks"
ServiceFacilitySet/FareClasses	"firstClass"
ServiceFacilitySet/FareClasses	"secondClass"
ServiceFacilitySet/GenderLimitation	FemaleOnly
ServiceFacilitySet/LuggageCarriageFacilityList	"baggageStorage"
ServiceFacilitySet/LuggageCarriageFacilityList	"cyclesAllowed"
ServiceFacilitySet/LuggageCarriageFacilityList	"cyclesAllowedWithReservation"
ServiceFacilitySet/LuggageCarriageFacilityList	"noCycles"
ServiceFacilitySet/MobilityFacilityList	"suitableForWheelchairs"
ServiceFacilitySet/NuisanceFacilityList	"familyArea"

ServiceFacilitySet/PassengerCommsFacilityList	"powerSupplySockets".
ServiceFacilitySet/PassengerCommsFacilityList	"publicWifi"
ServiceFacilitySet/PassengerCommsFacilityList	"videoEntertainment"
ServiceFacilitySet/ServiceReservationFacilityList	"reservationsCompulsory"
ServiceFacilitySet/ServiceReservationFacilityList	"reservationsPossible"
ServiceFacilitySet/VehicleAccessFacilityList	"wheelchairLift"

Any calendar limitation on the validity of the note is handled in ServiceFacilitySet/KeyList[Key=' DayTypeRef']/Value, where value is the reference to the corresponding element
ServiceCalendarFrame/ServiceCalendar/dayTypes/DayType/@id.

The possible restriction of the validity of the note to only part of the path of the connection is handled in the ServiceFacilitySet/KeyList.

In the elements KeyList[Key='StartPointInPatternRef']/Value and KeyList[Key='EndPointInPatternRef']/Value contains references to the corresponding start and end points in the path of the connection to which the note relates - specifically to the
ServiceFrame/journeyPatterns/ServiceJourneyPattern/pointsInSequence/StopPointInJourneyPattern/@id element of the NeTeX EPIP data structure.

3.6 Text notes to the connection

The text notes to the connection are processed from the so-called "non-central notes" of the DJŘ_CIS format and are listed in the

ServiceJourney/NoticeAssignments/NoticeAssignment element of the NeTeX EPIP data structure - the text is specified in the Notice/Text/Value sub-element.

Any calendar limitation on the validity of the note is handled in NoticeAssignment/KeyList[Key='DayTypeRef']/Value, where value is the reference to the corresponding element
ServiceCalendarFrame/ServiceCalendar/dayTypes/DayType/@id.

Possible restriction of the note validity to only part of the connection path is handled in the elements NoticeAssignment/StartPointInPatternRef and NoticeAssignment/EndPointInPatternRef.

3.7 Connection specific data

DAG_CIS format specific data in CZPTTCISMessage/NetworkSpecificParameter bound elements to the connection are captured in the ServiceJourney/keyList element of the NeTeX EPIP data structure as a list "key-value", registered key values:

- CZReroute
- CZOriginalCalendarStartDate
- CZOriginalCalendarEndDate
- CZOriginalCalendarBitmaps

3.8 Identifiers

The DAG_CIS format data in the CZPTTCISMessage/Identifiers element bound to the connection are captured in the ServiceJourney/keyList element of the NeTeX EPIP data structure in the form of a key-value list. The keys are created from the names of the sub-elements PlannedTransportIdentifier and

RelatedPlannedTransportIdentifiers, the corresponding values are created from the data in the sub-elements ObjectType, Company, Core, Variant, TimetableYear and StartDate processed into a text field with the data separated by /.

3.9 Path of the connection (train)

Connection stops are created from data in

CZPTTCISMessage/CZPTTInformation/CZPTTLocation elements

SGE_CIS format converted to the NeTeX EPIP data structure.

The sequence of stops of the connection is created from the data in the

CZPTTLocation/Location elements of the DJŘ_CIS format converted into the

ServiceFrame/journeyPatterns/ServiceJourneyPattern data structure of the NeTeX EPIP standard. Each waypoint is a

ServiceJourneyPattern/pointsInSequence/StopPointInJourneyPattern element.

The restriction of passenger handling in the stop of the connection is incorporated into the data structure of the NeTeX EPIP standard based on the data in the

CZPTTLocation/TrainActivity/TrainActivityType elements of the DJŘ_CIS format, the following properties are recorded.

Element of the NeTeX EPIP standard structure	Value
StopPointInJourneyPattern/ForBoarding	true, false
StopPointInJourneyPattern/ForAlighting	true, false
StopPointInJourneyPattern/RequestStop	true, false
StopPointInJourneyPattern/StopUse	NoBoardingOrAlighting

The specific data of the DJŘ_CIS format related to the stopping of a link are captured

in the StopPointInJourneyPattern/noticeAssignments/NoticeAssignment/keyList element in the form of a list "key-value".

Key	The value from the DJŘ_CIS format element
OperatorRef	ResourceFrame/organisations/Operator/@id
TrainType	CZPTTLocation/TrainType

TrafficType	CZPTTLocation/TrafficType
CommercialTrafficType	CZPTTLocation/CommercialTrafficType
OperationalTrainNumber	CZPTTLocation/OperationalTrainNumber
CZPassengerServiceNumber	CZPTTLocation/NetworkSpecificParameter [Name='Key']/Value
CZPublicService	CZPTTLocation/NetworkSpecificParameter [Name='Key']/Value
CZAlternativeTransport	CZPTTLocation/NetworkSpecificParameter [Name='Key']/Value
CZPassengerPublicTransportOrderingCoName	CZPTTLocation/NetworkSpecificParameter [Name='Key']/Value
CZService	CZPTTLocation/NetworkSpecificParameter [Name='Key']/Value
CZInconsistentTime	CZPTTLocation/NetworkSpecificParameter [Name='Key']/Value
TrainActivityType	CZPTTLocation/TrainActivity/TrainActivityType

The time data for stopping the connection are created from the data in the CZPTTLocation/TimingAtLocation/Timing elements of the DJŘ_CIS format converted into the TimetableFrame/vehicleJourneys/ServiceJourney/passingTimes/TimetabledPassingTime elements of the NeTex EPIP data structure - the following data are used.

NeTex EPIP data structure element	The value from the DJŘ_CIS format element
TimetabledPassingTime/ArrivalTime	Timing[@TimingQualifierCode='ALA']/Time
TimetabledPassingTime/ArrivalDayOffset	Timing[@TimingQualifierCode='ALA']/Offset
TimetabledPassingTime/DepartureTime	Timing[@TimingQualifierCode='ALD']/Time
TimetabledPassingTime/DepartureDayOffset	Timing[@TimingQualifierCode='ALD']/Offset