

1 Integration API for NDIC predefined locations

The API exposed on NDIC system providing list of predefined locations to be referenced from some types of NDIC traffic information messages.

Integration Platform will try to download the predefined location when starting the application container and also at scheduled run every 24 hours at predefined schedule.

1.1 Technical specification

Protocol	HTTPS/HTML
Data format	XML
Encoding	UTF-8
Authentication & Authorization	Login form
Invocation Style	HTML Form
URL example (form action)	https://datex.rsd.cz/pages/datex.ashx?REQUEST=GetPredefinedLocations&set=NDIC_WeatherStation

1.2 Methods

1.2.1 Method GetPredefinedLocations

Type	HTML Form/POST	
PATH	https://datex.rsd.cz/pages/datex.ashx	
Query Parameters	REQUEST	GetPredefinedLocations
	set	see table below...

Parameter “set” has to be specified according to the specific case:

Case	“set” parameter value
Locations of all weather stations	NDIC_WeatherStation

1.2.1.1 Request Message

Field Name	Type	Format	Cardinality	Description
Payload	Body	HTML/form	Mandatory	Html input form with hidden parameters login and password

1.2.1.2 Response Message

Each location is identified by attribute id and version of predefinedLocationContainer element:

```
/d2LogicalModel/payloadPublication/predefinedLocationContainer/@id  
/d2LogicalModel/payloadPublication/predefinedLocationContainer/@version
```

Each predefinedLocationContainer element contains startPoint and endPoint elements:

```
//predefinedLocationContainer/location/globalNetworkLinear/startPoint  
//predefinedLocationContainer/location/globalNetworkLinear/endPoint
```

These points are describing location of weather station.

1.2.1.3 Request example

```
<html>  
  <form
```

```
action="https://datex.rsd.cz/pages/datex.ashx?REQUEST=GetPredefinedLocation
s&set=NDIC_WeatherStation" method="post">
    <input type="hidden" name="login" value="xxx" />
    <input type="hidden" name="password" value="xxx" />
    <input type="submit" value="Meteo" />
</form>
</html>
```

1.2.1.4 Response example

```
...
<predefinedLocationContainer xsi:type="PredefinedLocation" id="1bb47395-
73e0-4f72-9eee-e7bfd86537eb" version="1">
...
    <location xsi:type="Linear">
        <globalNetworkLinear>
...
            <startPoint>
                <sjtskPointCoordinates>
                    <sjtskX>-753513</sjtskX>
                    <sjtskY>-1044837</sjtskY>
                </sjtskPointCoordinates>
            </startPoint>
            <endPoint>
                <sjtskPointCoordinates>
                    <sjtskX>-753717</sjtskX>
                    <sjtskY>-1045627</sjtskY>
                </sjtskPointCoordinates>
            </endPoint>
...
        </globalNetworkLinear>
    </location>
...
</predefinedLocationContainer>
```

1.3 Error Handling

1.3.1 Error Handling Approach

When there are errors downloading the predefined locations the integration platform will not retry. The data will be downloaded at the next scheduled update run.

1.4 Auditing and monitoring

Integration Platform is storing all API communication into audit DB. Access to this DB is for administrators of Integration Platform only.

ESB layer will audit the following

- timestamp of delivery to the platform

for the purpose of optimization during PoC phase, the complete or partial message will be audited as well