Hydrometallurgical processing of Li-Ion battery scrap from electric vehicles

Poster · June 2011	
CITATIONIC	READS
0	111
2 authoi	rs, including:
	Bernd Friedrich RWTH Aachen University 701 PUBLICATIONS 2,853 CITATIONS SEE PROFILE
Some of the authors of this publication are also working on these related projects:	
Project	Low-emission synthesis of titanium alloys View project
Project	Electronic Scrap Recycling View project

Hydro-recycling of automotive Li-ion batteries

Motivation and Target:

- Treatment of spent batteries of electric vehicles appropriately
- Development of the recycling process economically
- Recovery of all valuable materials environmental friendly





Thermo-Mechanical Treatment

- Disassembling (steel casing, electric scrap, plastic)
- Deactivation and electrolyte decomposition
- Shredding and separation

Valuable products



Cu, Al Scrap







Leaching Process


- The recovery rate of all metals are higher than 95%
- The leaching efficiency (Productivity, acid consumption)






Solution Purification

- Different valuable metals are tried to recovery separately
- •The loss of valuable must be minimized
- •The purity of products (marketable)













Li₂CO₃ Crystallization

- •The recovery rate of lithium is higher than 50% (at moment)
- The raffinate utilization and waste water treatment

Li

Challenge of Recycling of Li-lon HEV Batteries:

- Adjustment of existing recycling processes to future electrode materials
- Backflow of spent batteries will increase drastically, i.e. current recycling capacities have to be increased



Contacts: Honggang Wang, Matthias Vest IME Process Metallurgy and Metal Recycling, RWTH Aachen Intzestr. 3, 52056 Aachen, Germany HWang/MVest@ime-aachen.de

