

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/321360902>

Recovery of Rare Earth Elements from Small Scale Consumer Scrap Magnets – 1. Hydrometallurgy

Poster · September 2013

DOI: 10.13140/RG.2.2.23197.82400

CITATIONS

0

READS

54

3 authors, including:



Daniel Voßenkaul

VACUUMSCHMELZE GmbH & Co. KG

10 PUBLICATIONS 79 CITATIONS

[SEE PROFILE](#)



Bernd Friedrich

RWTH Aachen University

701 PUBLICATIONS 2,853 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



[Libero View project](#)



[Electronic Scrap Recycling View project](#)

Recovery of Rare Earth Elements from Small Scale Consumer Scrap Magnets – 1. Hydrometallurgy

Motivation:

- Becoming more independent from primary REE supply & producers export quota
- Creating a recycling strategy to recover rare earth elements (REE) contained in NdFeB-based magnets (approx. 30 wt.-%) with less energy and chemical consumptions
- Increase of recycling rates and reduction of contaminants in consumer scraps for a closed raw material cycle and green environment



Magnets of used hard disc drives

Methods to enable the separation of rare earth elements and other impurities (Fe):

Objectives (leaching):

- Extraction of REE from the magnet scrap with high yields


Objectives (precipitation):

- Separation of REE from the other dissolved metals


Objectives (solvent extraction):

- Extracting the remaining REE from filtrate


Metal content of the leachate



Metal content of the precipitate



Metal content in the organic phase



1. Leaching




Strong exothermic reaction

2. Precipitation



Best separation at pH 2

3. Solvent extraction



Fast phase separation

Results:

- | | | |
|------------------------|--|---------------------------------|
| 1. Leaching: | 100 % of iron and REE are leached with H_2SO_4 | ⇒ high metal yield |
| 2. Precipitation: | 0 % of iron and 75 % of REE are precipitated with Na_2CO_3 | ⇒ good separation efficiency |
| 3. Solvent extraction: | 0 % of iron and further 16 % of REE are extracted with HDEHP | ⇒ high extraction yield for REE |

Outlook:

- Investigation of the separation of Dy and Nd/Pr for a direct reuse in the magnet production (adherence to high quality standards)
- Development of a purification step to extract remaining impurities for a direct reuse and to build up an inner water cycle (no residues)
- Testing of slag phase coming from thermal preconcentrating step in developed hydrometallurgical process route

Dipl.- Ing. Daniel Voßenkaul
IME Process Metallurgy and Metal Recycling
RWTH Aachen University
52056 Aachen, Germany
dvossenkaul@ime-aachen.de
www.ime-aachen.de

