

COMMONWEALTH OF AUSTRALIA
Copyright Regulation 1969

WARNING

This material has been copied and communicated to you by or on behalf
of **Curtin University of Technology** pursuant to Part VB of the
Copyright Act 1968 (the Act)

The material in this communication may be subject to copyright under the
Act. Any further copying or communication of this material by you
may be the subject of copyright protection under the Act.

Do not remove this notice

Design and Analysis of Algorithms



Lecture 05

Graphs


Topics

- Graph terminology
- Breadth-first-search
- Depth-first-search
- Connected Components
- Analysis of BFS and DFS Algorithms

What is a graph?



Konigsberg Bridges




The town of Königsberg (now Kaliningrad) lay on the banks and on two islands of the Pregel river. The city was connected by 7 bridges.

The puzzle (as encountered by Leonhard Euler in 1736) :
Whether it was possible to start walking from anywhere in town and return to the starting point by crossing all bridges exactly once.


Graph Terminology

- A Graph consists of a set V of vertices (or nodes) and a set E of edges (or links)
- A graph can be directed or undirected
- Edges in a directed graph are ordered pairs
 - The order between the two vertices is important.
Example: (S, P) is an ordered pair because the edge starts at S and terminates at P
 - The edge is **unidirectional**
- Edges of an undirected graph form unordered pairs, written as $\{S, P\}$
- A multigraph is a graph with possibly several edges between the same pair of vertices
- Graphs that are not multigraphs are called simple graphs

Graph Terminologies (cont.)



G1 :Undirected Graph





G2: Directed Graph

Graph Terminologies (cont.)

- The **degree** $d(v)$ of a vertex v is the number of edges incident to v
 $d(A) = 3, d(D) = 2$
- In directed graphs, **indegree** is the number of **incoming** edges at the vertex and **outdegree** is the number of **outgoing** edges from the vertex.

Node P : indegree = 2, outdegree = 1.

Node Q : indegree = 1, outdegree = 2.



Paths and Cycles

- A **path** from vertex v_1 to v_k is a sequence of vertices v_1, v_2, \dots, v_k that are connected by edges $(v_1, v_2), (v_2, v_3), \dots, (v_{k-1}, v_k)$.

Path from D to E : (D, A, B, E)



Edges in the path: $(D, A), (A, B), (B, E)$

- A path is **simple** if each vertex in it appears only once.

$D A B E$ is a simple path

$A B C D A E$ is not a simple path

- Vertex u is said to be **reachable** from v if there is a path from v to u
- A **circuit** is a path whose first and last vertices are the same;
 $DAEBCEAD, ABEA, DABECD, SPQRS, SPQTRS$ are circuits



Paths and Cycles



- A simple circuit is a **cycle** if except for the first (and last) vertex, no other vertex appears more than once.

ABEA, *DABECD*, *SPQRS*, and *STRS* are cycles.

- A **Hamiltonian cycle** of a graph G is a cycle that contains all the vertices of G

DABECD is a Hamiltonian cycle of G_1

PQRSTP is a Hamiltonian of G_2







Subgraph

- A **subgraph** of a graph $G=(V,E)$ is a graph $H=(U,F)$ such that $U \subseteq V$ and $F \subseteq E$.

$H_1 = \{[U_1: A, E, C, D], [F_1: (A, E), (E, C), (C, D), (D, A)]\}$ is subgraph of G_1


$H_2 = \{[U_2: S, P, T], [F_2: (S, P), (S, T), (T, P)]\}$ is a subgraph of G_2



Graph Connectivity

- A graph is said to be **connected** if there is a path from any vertex to any other vertex in the graph $\rightarrow G_1$ and G_2 are both connected graphs.
- A **forest** is a graph that does not contain a cycle.
- A **tree** is a connected forest.
- A **spanning forest** of an undirected graph G is a subgraph of G that is a forest and contains all the vertices of G .
- If a graph $G(V,E)$ is not connected, then it can be partitioned in a unique way into a set of connected subgraphs called **connected components**.
- A **connected component** of G is a connected subgraph of G such that no other connected subgraph of G contains it.







Forest



- $G(A, B, C, D, E, P, Q, R, S, T)$ is a **forest**
- $G(A, B, C, D, E)$ is a **tree**
- (A, B, C, D, E) and (P, Q, R, S, T) are **connected components**

Spanning Tree

- A **spanning tree** of a graph G is a subgraph of G that is a tree and contains all the vertices of G .




Graph Representations

G1: undirected graph
Adjacency Matrix

	A	B	C	D	E
A	0	1	0	1	1
B	1	0	1	0	1
C	0	1	0	1	1
D	1	0	1	0	0
E	1	1	1	0	0

Adjacency list

A	B	D	E
B	A	C	E
C	B	D	E
D	A	C	\
E	A	B	C



Directed Representation


G2: DirectedGraph

Adjacency matrix

	P	Q	R	S	T
P	0	1	0	0	0
Q	0	0	1	0	0
R	0	0	0	1	0
S	1	0	0	0	1
T	1	0	1	0	0

Adjacency list

P	Q	/
Q	R	/
R	S	/
S	P	T
T	P	R



Depth First Search

DFS_Tree $G(V,E)$

Input: $G = (V,E)$ in adjacency list format

x = value on top of stack S

$L[x]$ refers to the adjacency list of x

Output: The DFS tree T

- | | | | |
|--|-------------|-------------|-------------|
| 1. Mark all vertices <i>new</i> and set $T = \{ \}$ | $\Theta(V)$ | | |
| 2. Mark any one vertex $v = old$ | $\Theta(1)$ | | |
| 3. push (S, v) | $\Theta(1)$ | | |
| 4. while S is nonempty do | $\Theta(1)$ | | |
| 5. while exists a <i>new</i> vertex w in $L[x]$ do | $\Theta(1)$ | } V times | } V times |
| 6. $T = T \cup (x,w)$ | $\Theta(1)$ | | |
| 7. $w = old$ | $\Theta(1)$ | | |
| 8. push w onto S | $\Theta(1)$ | | |
| 9. pop S | $\Theta(1)$ | | |

$$O(V + 1 + V^2) = O(V^2)$$

Depth First Search

DFS_Tree $G(V,E)$

Input: $G = (V,E)$ in adjacency list format.

x = value on top of stack

$L[x]$ refers to the adjacency list of x

Output : The DFS tree T

1. Mark all vertices *new* and set $T = \{ \}$

2. Mark any one vertex $v = old$

3. push (S, v)

4. **while** S is nonempty **do**

5. **while** exists a *new* vertex w in $L[x]$ **do**

6. $T = T \cup (x,w)$

7. $w = old$

8. push w onto S

9. pop S

$\Theta(V)$

$\Theta(1)$

$\Theta(1)$

$\Theta(V)$


$\Theta(1)$

$\Theta(1)$

$\Theta(1)$

$\Theta(1)$


$\Theta(1)$



At most $2 \cdot E$
times over the
whole algorithm

$$O(V + V + E) = O(V + E)$$

DFS - Example



Breadth-first Search


BFS_Tree_G(V, E)

Input: $G = (V, E)$. $L[x]$ refers to the adjacency list of x .

Output: The BFS tree T ;

1. Mark all vertices *new* and set $T = \{ \}$
2. Mark the start vertex $v = \text{old}$
3. insert (Q, v) // Q is a queue
4. **while** Q is nonempty **do**
5. $x = \text{dequeue}(Q)$
6. **for** each vertex w in $L[x]$ marked *new* **do**
7. $T = T \cup \{x, w\}$
8. Mark $w = \text{old}$
9. insert (Q, w)

$\Theta(V)$
 $\Theta(1)$



} V times
At most $2 \cdot E$
times over the
whole algorithm
} $\Theta(1)$

$$O(V + V + E) = O(V + E)$$

BFS - Example




new = {A,B,C,D,E}
old = {}
T = {}




L[A] = {B,D,E}
new = {B,C,D,E}
old = {A}
T = {}



L[B] = {A, C, E}
new = {C}
old = {A,B,D,E}
T = {(A,B),(A,D),(A,E)}




L[D] = {A,C}
new = {}
old = {A,B,D,E,C}
T = {(A,B),(A,D),
(A,E),(B,C)}



L[E] = {A,B,C}
new = {}
old = {A,B,D,E,C}
T = {(A,B),(A,D),
(A,E),(B,C)}




L[C] = {B,D,E}
new = {}
old = {A,B,D,E,C}
T = {(A,B),(A,D),
(A,E),(B,C)}



new = {}
old = {A,B,D,E,C}
T = {(A,B),(A,D),
(A,E),(B,C)}

⁷



Connected Components

- The connected component of a graph $G = (V, E)$ is a maximal set of vertices $U \subseteq V$ such that for every pair of vertices u and v in U , we have both u and v reachable from each other. In the following we give an algorithm for finding the connected components of an undirected graph.


Connected_Components_G(V, E)

Input: $G(V, E)$

Output: Number of Connected Components and G_1, G_2 etc, the connected components

```
1.  $V' = V$ 
2.  $c = 0$ 
3. while  $|V'| \neq 0$  do
4.   choose  $u \in V'$ 
5.    $T =$  all nodes reachable from  $u$  (use the DFS_Tree function)
6.    $V' = V' - T$ 
7.    $c = c + 1$ 
8.    $G_c = T$ 
9.    $T = \emptyset$ 
```

Connected Components



- Suppose the DFS tree starts at A, we traverse from $A \rightarrow B \rightarrow C \rightarrow D$ and do not explore the vertices F, G, and H at all! The DFS_tree algorithm does not work with graphs having two or more connected parts.
- We have to modify the DFS_Tree algorithm to find a DFS forest of the given graph.

DFS Forest

DFSForest _G(V,E)

Input: $G = (V,E)$; S is a stack - initially empty;

x refers to the top of stack; initially mark all vertices *new*;

$L[x]$ refers to the adjacency list of x .

DFS Forest $F = \{ \}$;

Output: DFS tree F ;

1. **for** each vertex $v \in V$ **do** //generate all components
2. **if** v is *new* **then** // generate one component
3. $v = old$
4. push (S,v)
5. **while** S is nonempty **do**
6. **while** there exists a vertex w in $L[x]$ marked *new*
7. $F = F \cup (x,w)$
8. $w = old$
9. push (S,w)
10. pop S

The End