

Copyright Warning

COMMONWEALTH OF AUSTRALIA
Copyright Regulation 1969

WARNING

This material has been copied and communicated to you by or on behalf
of **Curtin University of Technology** pursuant to Part VB of the
Copyright Act 1968 (the Act)

The material in this communication may be subject to copyright under the
Act. Any further copying or communication of this material by you
may be the subject of copyright protection under the Act.

Do not remove this notice

Theoretical Foundations of Computer Science 300

Lecture 5 Push-Down Automata

Outline

- What is a Push Down Automaton (PDA)?
 - Formal definition
 - State diagram
 - Examples
- Context Free Languages (CFG)
- Equivalence of PDA and CFG
 - How to convert a CFG to a PDA
- Non-context free languages
 - Pumping lemma for CFG

Unit Learning Outcomes

- Synthesize FA, PDA, CFG, and TMs with specific properties, and convert from one form to another.

Assessment Criteria

- **Model** a specification expressed in English or Mathematics as a PDA.
- **Explain** the operation of a machine on an input string.
- **Express** an English or Mathematical specification as a CFG.
- **Classify** a problem as belonging to the class of PDA and CFG.

PUSHDOWN AUTOMATON

Concept


Formal Definition

Computation

Pushdown automata


- Like NFA but with a stack added
 - Stack provides additional memory
 - Stack allows recognition of some non-regular languages
- Note that deterministic PDAs exist
 - Unlike with DFAs and NFAs, deterministic PDAs are **NOT** equivalent to non-deterministic PDAs
 - Theoretically these are the next step, but not a useful one
 - For this unit, assume all PDAs can be non-deterministic.

Schematic of a Finite Automaton



- State control represents the states and transition function
- Tape contains the input string
- Arrow represents the input head
 - pointing at the next input symbol to be read
- Addition of a stack component will give us the schematic of a pushdown automaton

Schematic of a pushdown automaton



- PDA can write symbols on the stack and read them back later
 - push: writing a symbol at the top of the stack
 - pop: removing a symbol from the top
 - stack can hold unlimited amount of information

- Example: $L(G) = \{0^n 1^n \mid n \geq 0\}$
 - Finite automata cannot recognise this language
 - PDA can store the 0s it has seen, then pop the 0s one by one as 1s are seen
 - if the stack becomes empty exactly when the input of 1s is finished then accept, otherwise reject the input
- PDA can be non-deterministic
 - unlike finite automata, non-determinism adds power to the PDA

Formal definition of PDA

- A PDA is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$, where
 - Q is the set of states
 - Σ is the input alphabet
 - Γ is the stack alphabet
 - $\delta : Q \times \Sigma_{\varepsilon} \times \Gamma_{\varepsilon} \rightarrow P(Q \times \Gamma_{\varepsilon})$ is the transition function
 - $q_0 \in Q$ is the start state, and
 - $F \subseteq Q$ is the set of accept states
- Note that the problem defines the input alphabet (as usual), but the designer defines the stack alphabet.

Input and Stack Alphabets of PDA

- Definition of PDA is similar to that of FA except for the addition of a stack
- Stack contains symbols from a stack alphabet Γ
- $\Sigma_\epsilon = \Sigma \cup \{\epsilon\}$ and $\Gamma_\epsilon = \Gamma \cup \{\epsilon\}$

Transition Function of PDA

- $\delta : Q \times \Sigma_{\varepsilon} \times \Gamma_{\varepsilon} \rightarrow P(Q \times \Gamma_{\varepsilon})$
- Domain of the transition function is $Q \times \Sigma_{\varepsilon} \times \Gamma_{\varepsilon}$
 - Current state, next input symbol and top symbol of stack
 - Either symbol can be ε causing the machine to move without reading input or top of stack
- Range of the transition function is $P(Q \times \Gamma_{\varepsilon})$
 - The machine may enter some new state or possibly write a symbol on the stack
 - Because of non-determinism, there may several legal moves

How a PDA Computes

- $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ accepts input w
 - if $w = w_1 w_2 \dots w_n$, is a string containing members of Σ_ϵ and
 - a sequence of states $r_0, r_1, \dots, r_m \in Q$ and strings $s_0, s_1, \dots, s_m \in \Gamma^*$ exist
 - that satisfy the following three conditions (on next slide)

How a PDA Computes

- M starts in the start state with an empty stack:
 - $r_0 = q_0$ and $s_0 = \varepsilon$.
- M proceeds according to the state, stack and the next input symbol of the transition function:
 - For $i = 0, \dots, m - 1$, we have $(r_{i+1}, b) \in (r_i, w_{i+1}, a)$, where $s_i = at$ and $s_{i+1} = bt$ for some $a, b \in \Gamma_\varepsilon$ and $t \in \Gamma^*$.
- At the end of the input, M is in an accept state:
 - $r_m \in F$.

EXAMPLE


Example

State Diagram and Transition Table

Further Examples


State diagram for a PDA

- PDA recognises $\{0^n 1^n \mid n \geq 0\}$
- $a, b \rightarrow c$ signifies
 - when reading an a from input, replace b at the top of the stack with a c
 - any of a, b , and c may be ϵ
 - if a is ϵ , the machine may take this transition without reading from input
 - $\$$ indicates empty stack




State diagram for a PDA

- $\epsilon, \epsilon \rightarrow \$$
 - Without reading from input and the stack, makes the stack empty
- $0, \epsilon \rightarrow 0$
 - On reading a 0 from input write a 0 to the top of stack (without changing whatever else was on there)
- $1, 0 \rightarrow \epsilon$
 - When a 1 is read from input and a 0 popped from stack, do not write anything to stack
- $\epsilon, \$ \rightarrow \epsilon$
 - When input and stack are empty, do nothing other than change states



Formal description of a PDA


- $M_1 = (Q, \Sigma, \Gamma, \delta, q_0, F)$
- $Q = \{q_1, q_2, q_3, q_4\}, \Sigma = \{0, 1\}$
- $\Gamma = \{0, \$\}, F = \{q_1, q_4\}$
- δ is given by a state transition table (next page)
- In the formal definition, there is no explicit mechanism to test for an empty stack
 - hence the use of $\$$



State Transition Table


Input: Stack:	0 0 \$ ϵ	1 0 \$ ϵ	ϵ 0 \$ ϵ
q_0			$\{(q_1, \$)\}$
q_1	$\{(q_1, 0)\}$	$\{(q_2, \epsilon)\}$	
q_2		$\{(q_2, \epsilon)\}$	$\{(q_3, \epsilon)\}$
q_3			

Another PDA Example



- PDA to recognize $\{a^i b^j c^k \mid i, j, k \geq 0 \text{ and } i=j \text{ or } i=k\}$
 - First read and push the a 's
 - Not known whether to match b 's or c 's
 - Use nondeterminism to guess whether to match b 's or c 's
 - Nondeterminism essential for recognizing this language

Another PDA



- PDA recognizing the language $\{ww^R | w \in \{0,1\}^*\}$
 - Begin by pushing symbols to stack
 - Non-deterministically guess when the middle of the string is reached and then change to popping symbols
 - Accept if the stack empties at the same time as the end of input; otherwise reject.

- Equivalent in power to Context Free Languages
 - gives two options for proving a language context free
 - some languages are more easily described in terms of generators,
 - others are easier to describe using recognizers

CONTEXT-FREE LANGUAGES

Outline

- Context-free grammars and languages
- Design techniques
- Ambiguity
- Chomsky normal form
 - CNF theorem

GRAMMARS

Aims & Background

Context Free Grammars (CFG)

Language of a Grammar

Formal Definition

Aims

- To extend our concept of a machine
 - Studied DFA/NFA
 - Found associated language (RL)
 - Characterised as Regular Expressions
 - Found some languages not Regular
- Context Free Grammars
 - Used to define Context Free Languages (CFLs)
 - Grammars: Define real languages: Java, C
 - Recognising languages = Checking syntax
 - Used in Yacc (and MANY other places)
 - Grammars come from natural languages

Background to CFG

- CFG more powerful than regular languages
 - Can describe features with a recursive structure
 - Some simple languages such as $\{0^n 1^n \mid n \geq 0\}$ cannot be described by regular expressions
- First used in the study of human languages
 - Noun, verb, preposition and their respective phrases
 - Natural recursion *e.g.*, Noun phrases appearing in verb phrases and *vice versa*

Uses of CFG

- Specification and compilation of programming languages
 - An important application
- Grammar for a programming language
 - Reference to learn the language syntax
 - For design of compilers (constructing a parser from the grammar)

Context-Free Languages

- Collection of languages with context-free grammars
 - Include regular languages and many others
- Study of CFLs
 - Formal definition
 - Properties
 - Pushdown automata to recognize CFLs
- PDAs provide additional insights into the power of CFGs, and *vice versa*

Context Free Grammar Terms

- Consider Grammar G_1 :
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$
- Consists of a collection of **substitution rules**
 - also called production rules
- Abbreviation within a Grammar:
 - $A \rightarrow 0A1$ and $A \rightarrow B$, written as $A \rightarrow 0A1 \mid B$

CFG Terms

- Grammar G_1 :
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$
- Each rule has a symbol and a string separated by an arrow
 - Symbol is called a **variable** represented by capital letters, *e.g.*, A, B
 - String contains variables and other symbols called **terminals**, *e.g.*, $0, 1, \#$

CFG Terms

- Grammar G_1 :
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$
- Terminals are analogous to the input alphabet
 - represented by lowercase letters, numbers or special symbols
- One variable designated as **start variable**
 - usually in LHS of topmost rule, *e.g.*, A


Generating Strings of the Language

- Write down the start variable
 - usually the variable on the LHS of top rule
- Find a variable that is written down and a rule starting with it
- Replace the variable with RHS of the rule
- Repeat variable replacement until no variable remains

Generating Strings Example

- Grammar G_1 :
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$
- G_1 generates the string 000#111
- Derivation: Sequence of substitutions to obtain a string
 - $A \Rightarrow 0A1 \Rightarrow 00A11 \Rightarrow 000A111 \Rightarrow 000B111 \Rightarrow 000\#111$
 - Can also be represented by a parse tree

Parse Tree



Parse tree for 000#111 in grammar G_1

Language of the Grammar

- Consists of all strings that can be generated using a context-free grammar
 - Called context-free language
 - Written as $L(G_1)$ for the language of CFG G_1
 - $L(G_1) = \{0^n \# 1^n \mid n \geq 0\}$
- Abbreviation within a Grammar:
 - $A \rightarrow 0A1$ and $A \rightarrow B$, written as $A \rightarrow 0A1 \mid B$

CFG Example- G_2

- Grammar G_2

- $\langle \text{SENTENCE} \rangle \rightarrow \langle \text{NOUN-PHRASE} \rangle \langle \text{VERB-PHRASE} \rangle$
- $\langle \text{NOUN-PHRASE} \rangle \rightarrow \langle \text{CMPLX-NOUN} \rangle | \langle \text{CMPLX-NOUN} \rangle \langle \text{PREP-PHRASE} \rangle$
- $\langle \text{VERB-PHRASE} \rangle \rightarrow \langle \text{CMPLX-VERB} \rangle | \langle \text{CMPLX-VERB} \rangle \langle \text{PREP-PHRASE} \rangle$
- $\langle \text{PREP-PHRASE} \rangle \rightarrow \langle \text{PREP} \rangle \langle \text{CMPLX-NOUN} \rangle$
- $\langle \text{CMPLX-NOUN} \rangle \rightarrow \langle \text{ARTICLE} \rangle \langle \text{NOUN} \rangle$
- $\langle \text{CMPLX-VERB} \rangle \rightarrow \langle \text{VERB} \rangle | \langle \text{VERB} \rangle \langle \text{NOUN-PHRASE} \rangle$
- $\langle \text{ARTICLE} \rangle \rightarrow a | the$
- $\langle \text{NOUN} \rangle \rightarrow boy | girl | flower$
- $\langle \text{VERB} \rangle \rightarrow touches | likes | sees$
- $\langle \text{PREP} \rangle \rightarrow with$

Derivation Example

- $\langle \text{SENTENCE} \rangle \Rightarrow \langle \text{NOUN-PHRASE} \rangle \langle \text{VERB-PHRASE} \rangle$
 $\Rightarrow \langle \text{CMPLX-NOUN} \rangle \langle \text{VERB-PHRASE} \rangle$
 $\Rightarrow \langle \text{ARTICLE} \rangle \langle \text{NOUN} \rangle \langle \text{VERB-PHRASE} \rangle$
 $\Rightarrow a \langle \text{NOUN} \rangle \langle \text{VERB-PHRASE} \rangle$
 $\Rightarrow a \text{ boy } \langle \text{VERB-PHRASE} \rangle$
 $\Rightarrow a \text{ boy } \langle \text{CMPLX-VERB} \rangle$
 $\Rightarrow a \text{ boy } \langle \text{VERB} \rangle$
 $\Rightarrow a \text{ boy sees}$

Formal definition

- A CFG is a 4-tuple (V, Σ, R, S) , where
 - V is a finite set called the variables,
 - Σ is a finite set, disjoint from V , called the terminals,
 - R is a finite set of rules, with each rule comprising an arrow separating a variable and a string of variables and terminals, and
 - S is the start symbol.

Formal Definition

- If u, v, w are strings of variables and terminals, and $A \rightarrow w$ is a rule of the grammar,
 - we say that uAv yields uwv , written as $uAv \Rightarrow uwv$.
- $u \Rightarrow^* v$
 - if $u=v$, or
 - there is a sequence $u \Rightarrow u_1 \Rightarrow u_2 \Rightarrow \dots \Rightarrow u_k \Rightarrow v$, for $k \geq 0$.
- Language of the grammar is $\{w \in \Sigma^* \mid S \Rightarrow^* w\}$

Example

- Grammar $G_1 = (V, \Sigma, R, S)$, where
- $V = \{A, B\}$,
- $\Sigma = \{0, 1, \#\}$
- $S = A$
- R consists of
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$

Example 2

- Grammar G_2
- $V = \{ \langle \text{SENTENCE} \rangle, \langle \text{NOUN-PHRASE} \rangle, \langle \text{VERB-PHRASE} \rangle, \langle \text{CMPLX-NOUN} \rangle, \langle \text{PREP-PHRASE} \rangle, \langle \text{CMPLX-VERB} \rangle, \langle \text{PREP} \rangle, \langle \text{ARTICLE} \rangle, \langle \text{NOUN} \rangle, \langle \text{VERB} \rangle, \langle \text{PREP} \rangle \}$
- $\Sigma = \{a, b, c, \dots, z, \text{“ ”}\}$
 - “ ” is the blank symbol
- $S = \langle \text{SENTENCE} \rangle$
- R consists of rules given earlier

CONSTRUCTING CFG FOR A LANGUAGE

General Approach

CFG for RL

More Hints

Designing CFGs

- Requires creativity
 - Even trickier to construct than finite automata because we are more used to writing programs for specific tasks than describing languages with grammars
- Some design techniques
 - Many CFGs are union of simpler CFGs
 - If possible, break the CFL into simpler pieces, then construct grammars for each piece
 - Individual grammars can be easily combined
 - Put all the rules together
 - Add a new rule $S \rightarrow S_1 | S_2 | \dots | S_k$, where S_i are the start variables for individual grammars

Example

- To design a grammar for the language
 - $\{0^n 1^n | n \geq 0\} \cup \{1^n 0^n | n \geq 0\}$
- First construct the grammar
 - $S_1 \rightarrow 0S_11 | \epsilon$ for the language $\{0^n 1^n | n \geq 0\}$
- Then the grammar
 - $S_2 \rightarrow 1S_20 | \epsilon$ for the language $\{1^n 0^n | n \geq 0\}$
- Add the rule
 - $S \rightarrow S_1 | S_2$
- To get the grammar
 - $S \rightarrow S_1 | S_2$
 - $S_1 \rightarrow 0S_11 | \epsilon$
 - $S_2 \rightarrow 1S_20 | \epsilon$


- CFGs with strings similar to $\{0^n 1^n | n \geq 0\}$
 - The machine would need to remember the number of 0s to verify that it equals the number of 1s
 - Use a rule of the form $R \rightarrow uRv$ to generate strings where the portion containing the u 's corresponds to the portion containing the v 's
 - See S_1 and S_2 in previous example

- Constructing a CFG for a regular language
 - First construct a DFA for the language
 - Convert the DFA into an equivalent CFG
 - See next slide for the method
 - Verify that the CFG generates the same language that the DFA recognizes

DFA to CFG

- Converting a DFA into an equivalent CFG:
 - Make a variable R_i for each state q_i of the DFA
 - Add the rule $R_i \rightarrow aR_j$ to the CFG if $\delta(q_i, a) = q_j$ is a transition in the DFA
 - Add the rule $R_i \rightarrow \varepsilon$ if q_i is an accept state of the DFA
 - Make R_0 the start variable if q_0 is the start state

Example: Even 1's



The DFA

GRAMMAR

$S \rightarrow \text{Even}$
 $\text{Even} \rightarrow 0 \text{ Even}$
 $\text{Even} \rightarrow 1 \text{ Odd}$
 $\text{Odd} \rightarrow 0 \text{ Odd}$
 $\text{Odd} \rightarrow 1 \text{ Even}$
 $\text{Even} \rightarrow \varepsilon$

Derivation of 011

$S \rightarrow \text{Even}$
 $\rightarrow 0 \text{ Even}$
 $\rightarrow 0 1 \text{ Odd}$
 $\rightarrow 011 \text{ Even}$
 $\rightarrow 011$

More Design Techniques

- CFGs for more complex languages
 - Strings may contain certain structures that appear recursively as part of other or the same structures
 - Any time symbol a appears in the example, a parenthesized exp may appear instead
 - Place the variable symbol generating the structure in the location of the rules corresponding to where the structure may recursively appear
- Example:
 - $G_4 = (V, \Sigma, R, \langle \text{EXPR} \rangle)$
 - V is $\{\langle \text{EXPR} \rangle, \langle \text{TERM} \rangle, \langle \text{FACTOR} \rangle\}$
 - Σ is $\{a, +, \times, (,)\}$
 - The rules are
 - $\langle \text{EXPR} \rangle \rightarrow \langle \text{EXPR} \rangle + \langle \text{TERM} \rangle \mid \langle \text{TERM} \rangle$
 - $\langle \text{TERM} \rangle \rightarrow \langle \text{TERM} \rangle \times \langle \text{FACTOR} \rangle \mid \langle \text{FACTOR} \rangle$
 - $\langle \text{FACTOR} \rangle \rightarrow (\langle \text{EXPR} \rangle) \mid a$

AMBIGUITY

Concept

Example

Formal Definition

Ambiguity

- Sometimes a grammar can generate the same string in several ways
 - Different parse trees and different meanings
 - Undesirable for some applications,
 - *e.g.*, Programming languages because a program should have a unique interpretation
- If a grammar generates the same string in several ways, the string is derived ambiguously
 - Then the grammar is said to be ambiguous

Example

- Grammar G_5 :

- $\langle \text{EXPR} \rangle \rightarrow \langle \text{EXPR} \rangle + \langle \text{EXPR} \rangle \mid \langle \text{EXPR} \rangle \times \langle \text{EXPR} \rangle \mid (\langle \text{EXPR} \rangle) \mid a$

- G_5 generates the string $a + a \times a$ ambiguously

- $\langle \text{EXPR} \rangle \Rightarrow \langle \text{EXPR} \rangle + \langle \text{EXPR} \rangle \Rightarrow a + \langle \text{EXPR} \rangle \Rightarrow a + \langle \text{EXPR} \rangle \times \langle \text{EXPR} \rangle \Rightarrow a + a \times \langle \text{EXPR} \rangle \Rightarrow a + a \times a$

- $\langle \text{EXPR} \rangle \Rightarrow \langle \text{EXPR} \rangle \times \langle \text{EXPR} \rangle \Rightarrow \langle \text{EXPR} \rangle + \langle \text{EXPR} \rangle \times \langle \text{EXPR} \rangle \Rightarrow a + \langle \text{EXPR} \rangle \times \langle \text{EXPR} \rangle \Rightarrow a + a \times \langle \text{EXPR} \rangle \Rightarrow a + a \times a$

Example

- Grammar G_4 :
 - $\langle \text{EXPR} \rangle \rightarrow$
 $\langle \text{EXPR} \rangle + \langle \text{TERM} \rangle \mid$
 $\langle \text{TERM} \rangle$
 - $\langle \text{TERM} \rangle \rightarrow \langle \text{TERM} \rangle \times$
 $\langle \text{FACTOR} \rangle \mid \langle \text{FACTOR} \rangle$
 - $\langle \text{FACTOR} \rangle \rightarrow (\langle \text{EXPR} \rangle) \mid a$
- G_4 generates the same strings as G_5 unambiguously
- $\langle \text{EXPR} \rangle \Rightarrow$
 $\langle \text{EXPR} \rangle + \langle \text{TERM} \rangle \Rightarrow$
 $\langle \text{TERM} \rangle + \langle \text{TERM} \rangle \Rightarrow$
 $\langle \text{FACTOR} \rangle + \langle \text{TERM} \rangle$
 $\Rightarrow a + \langle \text{TERM} \rangle \Rightarrow a +$
 $\langle \text{TERM} \rangle \times \langle \text{FACTOR} \rangle$
 $\Rightarrow a + \langle \text{FACTOR} \rangle \times$
 $\langle \text{FACTOR} \rangle \Rightarrow a + a \times$
 $\langle \text{FACTOR} \rangle \Rightarrow a + a \times a$

Real Languages

- Handling Expressions
 - C favours the G_5 in its definition
 - Yacc has precedence rules to resolve these ambiguities
 - Pascal favoured G_4 in its definition
- Yacc and Ambiguity
 - To resolves ambiguity
 - Uses order of definitions
 - Prefers shift to reduce
 - » (Just note it has ambiguity resolution if you have not met Yacc)

Ambiguous Grammar

- If a string has two different parse trees, the grammar is ambiguous
 - Not two different derivations as derivations may differ only in the order in which variables are replaced
- Leftmost derivation is where at every derivation step, the leftmost remaining variable is replaced
- If a string has two different leftmost derivations, the grammar is ambiguous

Inherently Ambiguous Languages

- Some CFLs can be generated only by ambiguous grammars
- Example:
 - $\{0^i 1^j 2^k \mid i=j \text{ or } j=k\}$ is an inherently ambiguous language

CHOMSKY NORMAL FORM

Purpose

Definition

Theorem: CFG into CNF

Purpose of CNF

- CNF: Chomsky Normal Form
 - Simple Context Free Grammar
 - Yet all CFG can be expressed in its form
 - Used to simplify proofs in decidability
- Note from DFA to CFG
 - Regular languages of form
 - $A \rightarrow aB$
 - $A \rightarrow a$
 - $A \rightarrow \epsilon$

Chomsky Normal Form

- Simplified form for CFGs
 - Useful for giving algorithms dealing with CFGs
- Definition: A CFG is in CNF if every rule is of the form
 - $A \rightarrow BC$
 - $A \rightarrow a$

Where:

- a is any terminal and A , B , and C are variables.
- B and C may not be start variables
- The rule $S \rightarrow \epsilon$ is allowed where S is the start variable

CNF Theorem

- Any CFL is generated by a CFG in Chomsky normal form.
- Converting any CFG into CNF
 - Add a new start symbol
 - Eliminate all rules of the form $A \rightarrow \epsilon$ and $A \rightarrow B$
 - Modify the grammar to generate the same language
 - Convert the remaining rules into the proper form

Proof of CNF Theorem

- 1. Add a new start symbol S_0 and the rule $S_0 \rightarrow S$, where S was the original start symbol
 - Guarantees that the start symbol does not occur on the RHS of a rule.
- Example: CFG G_6
 - $S \rightarrow ASA|aB$
 - $A \rightarrow B \mid S$
 - $B \rightarrow b \mid \epsilon$
- *Add a new start symbol*
 - $S_0 \rightarrow S$
 - $S \rightarrow ASA|aB$
 - $A \rightarrow B \mid S$
 - $B \rightarrow b \mid \epsilon$

Proof of CNF Theorem

- 2. Take care of ε -rules.
 - Remove an ε -rule $A \rightarrow \varepsilon$, where A is not a start variable.
 - For each occurrence of an A on the RHS of a rule, add a new rule with that occurrence deleted.
 - If $R \rightarrow A$ is a rule, then add $R \rightarrow \varepsilon$, unless this rule was previously removed
- *Removing $B \rightarrow \varepsilon$*
 - $S_0 \rightarrow S$
 - $S \rightarrow ASA|aB|a$
 - $A \rightarrow B|S|\varepsilon$
 - $B \rightarrow b$
- *Removing $A \rightarrow \varepsilon$*
 - $S_0 \rightarrow S$
 - $S \rightarrow ASA|aB|a|SA|AS|S$
 - $A \rightarrow B|S$
 - $B \rightarrow b$

Proof of CNF theorem

- 3. Handle all unit rules.
 - Remove a unit rule $A \rightarrow B$
 - For any rule $B \rightarrow u$, add $A \rightarrow u$ unless this rule was previously removed
 - u is a string of variables and terminals
 - *Example: From previous slide*
 - $S_0 \rightarrow S$
 - $S \rightarrow ASA|aB|a|SA|AS|S$
 - $A \rightarrow B \mid S$
 - $B \rightarrow b$
- Remove $S \rightarrow S$
 - $S_0 \rightarrow S$
 - $S \rightarrow ASA|aB|a|SA|AS$
 - $A \rightarrow B \mid S$
 - $B \rightarrow b$
- Remove $S_0 \rightarrow S$
 - $S_0 \rightarrow ASA|aB|a|SA|AS$
 - $S \rightarrow ASA|aB|a|SA|AS$
 - $A \rightarrow B \mid S$
 - $B \rightarrow b$

Proof of CNF theorem

- 3. Handle all unit rules.
 - Remove a unit rule $A \rightarrow B$
 - For any rule $B \rightarrow u$, add $A \rightarrow u$ unless this rule was previously removed
 - u is a string of variables and terminals
 - Example:
 - $S_0 \rightarrow ASA|aB|a|SA|AS$
 - $S \rightarrow ASA|aB|a|SA|AS$
 - $A \rightarrow B|S$
 - $B \rightarrow b$
- Remove $A \rightarrow B$
 - $S_0 \rightarrow ASA|aB|a|SA|AS$
 - $S \rightarrow ASA|aB|a|SA|AS$
 - $A \rightarrow S|b$
 - $B \rightarrow b$
- Remove $A \rightarrow S$
 - $S_0 \rightarrow ASA|aB|a|SA|AS$
 - $S \rightarrow ASA|aB|a|SA|AS$
 - $A \rightarrow b|ASA|aB|a|SA|AS$
 - $B \rightarrow b$

Proof of CNF Theorem

- 4. Convert all remaining rules into proper form of $A \rightarrow BC$
 - Replace rules like $A \rightarrow u_1 u_1 \dots u_k$ with $A \rightarrow u_1 A_1, A_1 \rightarrow u_2 A_2 \dots$
 - Replace any terminal u_i with a new variable U_i and add the rule $U_i \rightarrow u_i$
- *Example: From previous slide*
 - $S_0 \rightarrow ASA|aB|a|SA|AS$
 - $S \rightarrow ASA|aB|a|SA|AS$
 - $A \rightarrow b|ASA|aB|a|SA|AS$
 - $B \rightarrow b$
- *Using a single variable U and rule $U \rightarrow a$*
 - $S_0 \rightarrow AA_1|UB|a|SA|AS$
 - $S \rightarrow AA_1|UB|a|SA|AS$
 - $A \rightarrow b|AA_1|UB|a|SA|AS$
 - $A_1 \rightarrow SA$
 - $U \rightarrow a$
 - $B \rightarrow b$

Another Example

- Convert the following CFG into Chomsky normal form, clearly indicating the different steps in the process:
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$

Example 2

- 1. Add a new start symbol
 - $S_0 \rightarrow A$
 - $A \rightarrow 0A1$
 - $A \rightarrow B$
 - $B \rightarrow \#$
- 2. No ε -rules, so go to next step
- 3. Remove unit rules:
 - Remove $A \rightarrow B$
 - $S_0 \rightarrow A$
 - $A \rightarrow 0A1 \mid \#$
 - $B \rightarrow \#$
 - $B \rightarrow \#$ *no longer required.*
 - Remove $S_0 \rightarrow A$
 - $S_0 \rightarrow 0A1 \mid \#$
 - $A \rightarrow 0A1 \mid \#$

Example 2

- 4. Convert to proper form
 - $S_0 \rightarrow CE \mid \#$
 - $A \rightarrow CE \mid \#$
 - $C \rightarrow 0$
 - $D \rightarrow 1$
 - $E \rightarrow AD$

Equivalence of PDA and CFG

Statement of Theorem

CFG to PDA

PDA to CFG sketched

Equivalence of PDA and CFG

- Theorem:
 - A language is context free iff some PDA recognizes it.
- Proof idea:
 - Given any CFL, there is a CFG for it. Convert the CFG to an equivalent PDA.
 - Given a PDA, make a CFG that generates all strings that the PDA accepts.

CFL to PDA

- A CFL A has a CFG G generating it.
- How to convert G to an equivalent PDA P .
 - P works by accepting its input w , if G generates that input *i.e.*, if there is a derivation for w .
 - Design P to determine whether some series of substitutions using the rules of G can lead from the start variable to w .
 - Difficulty in determining which substitutions to make to generate w .
 - PDA's non-determinism allows it to guess the sequence of correct substitutions

- How the PDA P computes.
 - P begins by writing the start variable on its stack.
 - It goes through a series of intermediate strings, making one substitution after another.
 - Eventually, it may arrive at a string containing only terminal symbols.
 - If this string matches the input string, the input is accepted.

Informal description of P

1. Place the marker symbol \$ and the start variable on the stack.
2. Repeat the following steps forever.
 - a) If the top of the stack is a variable symbol A, non-deterministically select one of the rules for A and substitute A by the RHS of the rule.
 - b) If the top of the stack is a terminal symbol a, read the next symbol from input and compare it to a. If they match, repeat. If they do not match, reject on this branch of the non-determinism.
 - c) If the top of the stack is the \$ symbol, enter accept state. Doing so accepts input if it has all been read.


Construction of PDA

- Use short hand notation for transition function.
 - Allows writing an entire string on the stack in one step.
 - This action can be simulated using additional states.
- The start states of P are $Q = \{q_{\text{start}}, q_{\text{loop}}, q_{\text{accept}}\} \cup E$
 - E is the set of states to implement the shorthand.


Construction of PDA

- Transition functions:
- Initialize stack (Step 1 of informal description)
 - $d(q_{\text{start}}, \varepsilon, \varepsilon) = \{(q_{\text{loop}}, S\$)\}$
- Main loop of step 2:
 - Case (a): variable on top of stack
 - $d(q_{\text{loop}}, \varepsilon, A) = \{(q_{\text{loop}}, w) \mid A \rightarrow w \text{ is a rule in } R\}$
 - Case (b): terminal on top of stack
 - $d(q_{\text{loop}}, a, a) = \{(q_{\text{loop}}, \varepsilon)\}$
 - Case (c): \$ on top of the stack
 - $d(q_{\text{loop}}, \varepsilon, \$) = \{(q_{\text{accept}}, \varepsilon)\}$

State Diagram of P



Example




- Construct a PDA from the following CFG G :
 - $S \rightarrow aTb \mid b$
 - $T \rightarrow Ta \mid \epsilon$
 - Transition function is shown by the diagram

Example

- Convert the following CFG into an equivalent pushdown automaton, using the construction used for proving that every CFG has an equivalent PDA:
 - $S \rightarrow TX$
 - $T \rightarrow aT \mid \epsilon$
 - $X \rightarrow bXc \mid \epsilon$
- Give the state diagram and an informal description of the PDA.

Example



PDA to CFG


- See text
 - Very complex
 - Compiler writing interested only in CFG to PDA
 - Have to check for each pair (p,q) how it interacts with any other pair (rs): $A_{pq} \rightarrow aA_{rs}b$
 - Repeat for each triple: $A_{pq} \rightarrow A_{pr}A_{rq}$
 - Repeat for each p: $A_{pp} \rightarrow \varepsilon$

Non-CFL Languages

Relationship of Languages

Pumping lemma

Relationship of RLs and CFLs



- Every regular language is context-free.

Non-context-free languages

- A technique for proving that some languages are not context free
- Based on a pumping lemma for CFLs


Pumping lemma for CFLs

- If A is a context-free language, there is a pumping length p such that if s is any string in A of at least length p , then s may be divided into five pieces, $s = uvxyz$, satisfying the following conditions:
 - for each $i \geq 0$, $uv^ixy^iz \in A$,
 - $|vy| > 0$, and
 - $|vxy| \leq p$.
- The last condition is sometimes useful in proving certain languages to be not CFLs

Summary

- Pushdown automaton
 - Formal definition
 - State diagram
 - Examples
- Expressiveness
 - More expressive (powerful) than DFAs
- Non-context free languages
 - Pumping lemma for CFG

This is the end...



But you can't run from the test on September 9.