


# **COMP5347: Web Application Development**

## **HTML and Client-Side JavaScript**

**Dr. Basem Suleiman**  
**School of Computer Science**



THE UNIVERSITY OF  
**SYDNEY**



**COMMONWEALTH OF  
Copyright Regulations 1969  
WARNING**

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

**Do not remove this notice.**

# Outline

- **More HTML**
  - **Table**
    - **Elements**
    - **Styling**
  - **Form**
    - **Controls**
- **JavaScript**
  - **Location and Basic Syntax**
    - **Variables, Control Structure, Function, Object, Array**
    - **More about functions, objects, variable scopes, passing function as parameter**
  - **Windows and DOM object**
  - **Event model**

# HTML Table basic mark ups

- Tables can be used to display
  - Many types of content
    - Calendars, financial data, etc
  - Any type of data
    - Images, text, links etc
- A **table** in HTML is created using the `<table>` element
  - A basic table contains rows `<tr>` and cells `<td>`
  - Many table contains headings which is a special row to indicate what each cell is about: `<th>`

# HTML Table Examples

The image displays four browser windows, each showing a different HTML table structure:

- Window 1 (Left):** A pricing table with 4 columns: Feature, Free, Basic, and Premium. It includes rows for Upload Space, Daily Uploads, Total Uploads, Social Sharing, Analytics, and Price per year.
- Window 2 (Top Center):** An 'Artist Inventory' table. The first column, 'Artist', contains a portrait of Jacques-Louis David and is spanned by two rows of artwork details. The other columns are Title, Year, and Home.
- Window 3 (Bottom Center):** A table titled 'Paintings' with columns for Title, Artist, Year, and Genre. It lists five paintings with small thumbnail images and an 'Edit' button for each.
- Window 4 (Bottom Right):** A calendar for October 2014, showing days of the week and dates, with navigation links for previous and next months.

# Basic Table Example

Title	Artist	Year	Width	Height
The Death of Marat	Jacques-Louis David	1793	162cm	128cm
Burial at Ornans	Gustave Courbet	1849	314cm	663cm

```
<table>
  <tr>
    <th>Title</th>
    <th>Artist</th>
    <th>Year</th>
    <th>Width</th>
    <th>Height</th>
  </tr>
  <tr>
    <td>The Death of Marat</td>
    <td>Jacques-Louis David</td>
    <td>1793</td>
    <td>162cm</td>
    <td>128cm</td>
  </tr>
  <tr>
    <td>Burial at Ornans</td>
    <td>Gustave Courbet</td>
    <td>1849</td>
    <td>314cm</td>
    <td>663cm</td>
  </tr>
</table>
```



Title	Artist	Year	Width	Height
The Death of Marat	Jacques-Louis David	1793	162cm	128cm
Burial at Ornans	Gustave Courbet	1849	314cm	663cm

# Spanning Rows and Columns

- Simplest table is of a grid structure, with each row having the same number of cells
- It is possible to merge cells horizontally or vertically, e.g. having some cells covering a few rows or columns

<table>						
<tr>		Title	Artist	Year	Size (width x height)	
		<th>	<th>	<th>	<th colspan=2>	
<tr>		The Death of Marat	Jacques-Louis David	1793	162cm	128cm
		<td>	<td>	<td>	<td>	<td>
<tr>		Burial at Ornans	Gustave Courbet	1849	314cm	663cm
		<td>	<td>	<td>	<td>	<td>

```
<table>
<tr>
  <th>Title</th>
  <th>Artist</th>
  <th>Year</th>
  <th colspan="2">Size (width x height)</th>
</tr>
<tr>
  <td>The Death of Marat</td>
  <td>Jacques-Louis David</td>
  <td>1793</td>
  <td>162cm</td>
  <td>128cm</td>
</tr>
...
</table>
```

Notice that this row now only has four cell elements.

use the **colspan** or **rowspan** attributes

# Row Spaning Example

Artist	Title	Year
Jacques-Louis David	The Death of Marat	1793
	The Intervention of the Sabine Women	1799
	Napoleon Crossing the Alps	1800

Notice that these two rows now only have two cell elements.

```

<table>
<tr>
  <th>Artist</th>
  <th>Title</th>
  <th>Year</th>
</tr>
<tr>
  <td rowspan="3">Jacques-Louis David</td>
  <td>The Death of Marat</td>
  <td>1793</td>
</tr>
<tr>
  <td>The Intervention of the Sabine Women</td>
  <td>1799</td>
</tr>
<tr>
  <td>Napoleon Crossing the Alps</td>
  <td>1800</td>
</tr>
...
</table>

```



# Additional Table Elements

<caption>

<col>

<colgroup>

<thead>

<tfoot>

<tbody>

A title for the table is good for accessibility.

These describe our columns, and can be used to aid in styling.

Table header could potentially also include other <tr> elements.

Yes, the table footer comes *before* the body.

Potentially, with styling the browser can scroll this information, while keeping the header and footer fixed in place.

```
<table>
  <caption>19th Century French Paintings</caption>
  <col class="artistName" />
  <colgroup id="paintingColumns">
    <col />
    <col />
  </colgroup>

  <thead>
    <tr>
      <th>Title</th>
      <th>Artist</th>
      <th>Year</th>
    </tr>
  </thead>

  <tfoot>
    <tr>
      <td colspan="2">Total Number of Paintings</td>
      <td>2</td>
    </tr>
  </tfoot>

  <tbody>
    <tr>
      <td>The Death of Marat</td>
      <td>Jacques-Louis David</td>
      <td>1793</td>
    </tr>
    <tr>
      <td>Burial at Ornans</td>
      <td>Gustave Courbet</td>
      <td>1849</td>
    </tr>
  </tbody>
</table>
```



# Tables – Layout




```
<table>
<tr>
  <td>
    
  </td>
  <td>
    <h2>Castle</h2>
    <p>Lewes, UK</p>
    <p>Photo by: Michele Brooks</p>
    <p>Built in 1069, the castle has a tremendous
      view of the town of Lewes and the
      surrounding countryside.
    </p>
  </td>
</tr>
</table>
```

<h3>Other Images by Michele Brooks</h3>

```
<table>
<tr>
  <td></td>
  <td></td>
</tr>
<tr>
  <td></td>
  <td></td>
</tr>
</table>
</td>
</tr>
</table>
```

# Styling Tables

- Most box model styling can be applied to `<table>`, `<tr>`, `<td>` and other tags




Chapter 4 x  
figure04-07.html

19th Century French Paintings

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Total Number of Paintings		4

```
table {  
    border: solid 1pt black;  
}
```




Chapter 4 x  
figure04-07.html

19th Century French Paintings

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Total Number of Paintings		4

```
table {  
    border: solid 1pt black;  
}  
td {  
    border: solid 1pt black;  
}
```




Chapter 4 x  
figure04-07.html

19th Century French Paintings

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Total Number of Paintings		4

```
table {  
    border: solid 1pt black;  
    border-collapse: collapse;  
}  
td {  
    border: solid 1pt black;  
}
```

# Styling Tables




Chapter 5 x

figure05-08.html

19th Century French Paintings

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Total Number of Paintings		4

```
table {  
    border: solid 1pt black;  
    border-collapse: collapse;  
}  
td {  
    border: solid 1pt black;  
    padding: 10pt;  
}
```




19th Century French Paintings

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Total Number of Paintings		4

```
table {  
    border: solid 1pt black;  
    border-spacing: 10pt;  
}  
td {  
    border: solid 1pt black;  
}
```

# Styling Tables



Chapter 5


figure05-09.html

**19TH CENTURY FRENCH PAINTINGS**

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Mademoiselle Caroline Riviere	Jean-Auguste-Dominique Ingres	1806

```
caption {
    font-weight: bold;
    padding: 0.25em 0 0.25em 0;
    text-align: left;
    text-transform: uppercase;
    border-top: 1px solid #DCA806;
}
table {
    font-size: 0.8em;
    font-family: Arial, sans-serif;
    border-collapse: collapse;
    border-top: 4px solid #DCA806;
    border-bottom: 1px solid white;
    text-align: left;
}
```

# Styling Tables



Chapter 5


figure05-09.html

19TH CENTURY FRENCH PAINTINGS

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Mademoiselle Caroline Riviere	Jean-Auguste-Dominique Ingres	1806

```
thead tr {  
    background-color: #CACACA;  
}  
th {  
    padding: 0.75em;  
}
```

# Styling Tables



Chapter 5

figure05-09.html

**19TH CENTURY FRENCH PAINTINGS**

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Ornans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Mademoiselle Caroline Riviere	Jean-Auguste-Dominique Ingres	1806

```
tbody tr {  
    background-color: #F1F1F1;  
    border-bottom: 1px solid white;  
    color: #6E6E6E;  
}  
tbody td {  
    padding: 0.75em;  
}
```

# Nifty Table Styling Tricks: hover effect and zebra-stripes



Chapter4 x


figure04-09.html

19TH CENTURY FRENCH PAINTINGS

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Omsans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Mademoiselle Caroline Riviere	Jean-Auguste-Dominique Ingres	1806

Pseudo class

```
tbody tr:hover {  
    background-color: #9e9e9e;  
    color: black;  
}
```



Chapter4 x

figure04-09.html

19TH CENTURY FRENCH PAINTINGS

Title	Artist	Year
The Death of Marat	Jacques-Louis David	1793
Burial at Omsans	Gustave Courbet	1849
The Sleepers	Gustave Courbet	1860
Liberty Leading the People	Eugene Delacroix	1830
Mademoiselle Caroline Riviere	Jean-Auguste-Dominique Ingres	1806

```
tbody tr:nth-child(odd) {  
    background-color: white;  
}
```



# Outline


- **More HTML**
  - Table
    - Elements
    - Styling
  - **Form**
    - **Controls**
- **JavaScript**
  - Location and Basic Syntax
    - Variables, Control Structure, Function, Object, Array
  - Windows and DOM object
  - Event model

# HTML Forms

- Forms provide a way for users to interact with a web server
- Forms contain elements similar to desktop GUI
  - Plain text or password input
  - Selection
  - Radio and check boxes
  - Buttons


# Form Structures

- Form is main element to allow users enter information and get passed to the server application



```
<form method="get" action="process.php">
  <fieldset>
    <legend>Details</legend>
    <p>
      <label>Title: </label>
      <input type="text" name="title" />
    </p>
    <p>
      <label>Country: </label>
      <select name="where">
        <option>Choose a country</option>
        <option>Canada</option>
        <option>Finland</option>
        <option>United States</option>
      </select>
    </p>
    <input type="submit" />
  </fieldset>
</form>
```

# How Forms Work?



# Form-Related HTML Elements

Type	Description
<code>&lt;button&gt;</code>	Defines a clickable button.
<code>&lt;datalist&gt;</code>	An HTML5 element form defines lists to be used with other form elements.
<code>&lt;fieldset&gt;</code>	Groups related elements in a form together.
<code>&lt;form&gt;</code>	Defines the form container.
<code>&lt;input&gt;</code>	Defines an input field. HTML5 defines over 20 different types of input.
<code>&lt;label&gt;</code>	Defines a label for a form input element.
<code>&lt;legend&gt;</code>	Defines the label for a fieldset group.
<code>&lt;option&gt;</code>	Defines an option in a multi-item list.
<code>&lt;optgroup&gt;</code>	Defines a group of related options in a multi-item list.
<code>&lt;select&gt;</code>	Defines a multi-item list.
<code>&lt;textarea&gt;</code>	Defines a multiline text entry box.

# Text Input Controls

Type	Description
<b>text</b>	Creates a single line text entry box. <code>&lt;input type="text" name="title" /&gt;</code>
<b>textarea</b>	Creates a multiline text entry box. <code>&lt;textarea rows="3" ... /&gt;</code>
<b>password</b>	Creates a single line text entry box for a password <code>&lt;input type="password" ... /&gt;</code>
<b>search</b>	Creates a single-line text entry box suitable for a search string. This is an HTML5 element. <code>&lt;input type="search" ... /&gt;</code>
<b>email</b>	Creates a single-line text entry box suitable for entering an email address. This is an HTML5 element. <code>&lt;input type="email" ... /&gt;</code>
<b>tel</b>	Creates a single-line text entry box suitable for entering a telephone. This is an HTML5 element. <code>&lt;input type="tel" ... /&gt;</code>
<b>url</b>	Creates a single-line text entry box suitable for entering a URL. This is an HTML5 element. <code>&lt;input type="url" ... /&gt;</code>

# Text Input Controls

## Key motivations of new form controls in HTML5

- Usability
- Styling
- Client-side validation

# Text Input Controls – Examples

```
<input type="search" placeholder="enter search text" ... />
```

Search:

Search:

```
<input type="email" ... />
```

Email:

*In Opera*

Please enter a valid email address

Email:

*In Chrome*

Please enter an email address.

```
<input type="url" ... />
```

url:

Please enter a URL.


```
<input type="tel" ... />
```

Tel:



# Select Lists

## Datalist element



# Select Lists

Select:

Select: 

Second

First

Second

Third

Cities: 

London

North America

Calgary

Los Angeles

Europe

London

Paris

Prague

```
<select name="choices">
  <option>First</option>
  <option selected>Second</option>
  <option>Third</option>
</select>
```

```
<select ... >
  <optgroup label="North America">
    <option>Calgary</option>
    <option>Los Angeles</option>
  </optgroup>
  <optgroup label="Europe">
    <option>London</option>
    <option>Paris</option>
    <option>Prague</option>
  </optgroup>
</select>
```

# HTML Forms – Query Strings

How the browser sends the data to the server

- Through HTTP requests
- The browser packages user's data into a query string
- Query string: a series of name=value pairs separated by &
  - HTML form element's name attribute
  - User input data

# Radio Buttons and Checkboxes

Continent:

- ☐ North America
- ☒ South America
- ☐ Asia

```
<input type="radio" name="where" value="1">North America<br/>  
<input type="radio" name="where" value="2" checked>South America<br/>  
<input type="radio" name="where" value="3">Asia
```

I accept the software license ☒ `<label>I accept the software license</label>  
<input type="checkbox" name="accept" >`

Where would you like to visit?

- ☒ Canada
- ☐ France
- ☒ Germany

```
<label>Where would you like to visit? </label><br/>  
<input type="checkbox" name="visit" value="canada">Canada<br/>  
<input type="checkbox" name="visit" value="france">France<br/>  
<input type="checkbox" name="visit" value="germany">Germany
```

# Button Controls


Type	Description
<code>&lt;input type="submit"&gt;</code>	Creates a button that submits the form data to the server.
<code>&lt;input type="reset"&gt;</code>	Creates a button that clears any of the user's already entered form data.
<code>&lt;input type="button"&gt;</code>	Creates a custom button. This button may require Javascript for it to actually perform any action.
<code>&lt;input type="image"&gt;</code>	Creates a custom submit button that uses an image for its display.
<code>&lt;button&gt;</code>	<p>Creates a custom button. The <code>&lt;button&gt;</code> element differs from <code>&lt;input type="button"&gt;</code> in that you can completely customize what appears in the button; using it, you can, for instance, include both images and text, or skip server-side processing entirely by using hyperlinks.</p> <p>You can turn the button into a submit button by using the <code>type="submit"</code> attribute.</p>

# Button Controls – Example


```
<input type="submit" />
```




```
<input type="reset" />
```



```
<input type="button" value="Click Me" />
```



```
<input type="image" src="appointment.png" />
```



```
<button>  
  <a href="email.html">  
      
    Email  
  </a>  
</button>
```

```
<button type="submit" >  
    
  Edit  
</button>
```

# Form Control Elements – Number and Ranges

Rate this photo:

```
<label>Rate this photo: <br/>  
<input type="number" min="1" max="5" name="rate" />
```

Grumpy ————— Ecstatic

```
Grumpy  
<input type="range" min="0" max="10" step="1" name="happiness" />  
Ecstatic
```


Rate this photo:

Grumpy ————— Ecstatic


Controls as they appear in browser  
that doesn't support these input types

# Form Control Elements – Color

Background Color:



```
<label>Background Color: <br/>
<input type="color" name="back" />
```



Background Color:

Control as it appears in browser that  
doesn't support this input type



# Form Control Elements – Date and Time

Date:

Mon	Tue	Wed	Thu	Fri	Sat	Sun
25	26	27	28	1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	31
1	2	3	4	5	6	7

Today

```
<label>Date: <br/>  
<input type="date" ... />
```

Time:

```
<input type="time" ... />
```

DateTime:

```
<input type="datetime" ... />
```

DateTime Local:

```
<input type="datetime-local" ... />
```

# Form Control Elements – File Upload

Upload a travel photo  
 No file chosen



Upload a travel photo  
 IMG\_0020.JPG

```
<form method="post" enctype="multipart/form-data" ... >
...
<label>Upload a travel photo</label>
<input type="file" name="photo" />
...
</form>
```

# Outline

## – More HTML

### – Table

- Elements
- Styling

### – Form

- Controls

## – JavaScript

### – Location and Basic Syntax

- Variables, Control Structure, Function, Object, Array

### – Windows and DOM object

### – Event model

# JavaScript

- JavaScript is an object-based, dynamically typed scripting language
  - client-side scripting language for HTML and CSS
  - Also a server-side implementation
  - *“the most popular programming language in the world”* - W3C school
- As a client-side scripting language
  - It runs inside the browser
  - Able to interact with many browser managed resources: DOM, Browser's object (BOM) such as windows, screen, history, cookies and more
  - It can be written as inline (discouraged!), embedded or as external file

## Brief History

- Created in 10 days in May 1995 by Brendan Erich, then working at Netscape and now of Mozilla
- Became a much more important part of web development in the mid 2000s with **AJAX**
  - Microsoft 1999, get adopted by other browsers
  - Made very popular by Google
  - Received a lot more professional programming attention
- JavaScript frameworks: jQuery, Prototype, AngularJS, etc.
- Server-side JavaScript also gaining popularity

# JavaScript Code – Location

## Inline

```
<a href="JavaScript:OpenWindow();">more info</a>  
<input type="button" onClick="alert('Are you sure?');" />
```

## Embedded

```
<script type="text/javascript">  
    /* A JavaScript Comment */  
    alert("Hello World!");  
</script>
```

## External

```
<head>  
    <script type="text/javascript" src="greeting.js"></script>  
</head>
```

# JavaScript Variables

- Declaring a variable
  - *var name;*
- Does not require specifying data types
- Can contain a value of any data type
- JavaScript automatically converts between values of different types (in many cases)
- Variable has various scopes

**var x;**      ← a variable **x** is defined

**var y = 0;** ← **y** is defined and initialized to 0

**y = 4;**      ← **y** is assigned the value of 4

# Conditionals

```
var hourOfDay;    // var to hold hour of day, set it later...
var greeting;    // var to hold the greeting message.
if (hourOfDay > 4 && hourOfDay < 12){
    // if statement with condition
    greeting = "Good Morning";
}
else if (hourOfDay >= 12 && hourOfDay < 20){
    // optional else if
    greeting = "Good Afternoon";
}
else{ // optional else branch
    greeting = "Good Evening";
}
```

```
/* x conditional assignment */
x = (y==4) ? "y is 4" : "y is not 4";
```

<u>Condition</u>	<u>Value</u> if true	<u>Value</u> if false
------------------	-------------------------	--------------------------

```
/* equivalent to */
if (y==4) {
    x = "y is 4";
}
else {
    x = "y is not 4";
}
```



# Conditionals

```
switch (artType) {  
    case "PT":  
        output = "Painting";  
        break;  
    case "SC":  
        output = "Sculpture";  
        break;  
    default:  
        output = "Other";  
}
```

# Loops

initialization      condition      post-loop operation

```
for (var i = 0; i < 10; i++) {  
    // do something with i  
    // ...  
}
```

```
var i=0; // initialise the Loop Control Variable  
while(i < 10){ //test the loop control variable  
    i++; //increment the loop control variable  
}
```

# Variable types

- Primitive types: represent simple forms of data
  - Boolean, string and number
  - Null, undefined
- Complex types
  - Object (reference types)
  - Array
  - Function

# Primitive Types vs. Reference Types

What is the difference between primitive types and reference types? Use the following examples to explain it to your classmate.

```
var abc = 27;
```

```
var def = "hello";
```

```
var foo = [45, 35, 25]
```

```
var xyz = def;
```

```
var bar = foo;
```

```
bar[0] = 200;
```

# Primitive Types vs. Reference Types

```
var abc = 27;  
var def = "hello";
```

variables with primitive types

```
var foo = [45, 35, 25];
```

variable with reference type  
(i.e., array object)


```
var xyz = def;  
var bar = foo;
```

these new variables differ in important ways  
(see below)

```
bar[0] = 200;
```

changes value of the first element of array

## Memory representation



# JavaScript – Objects

- JavaScript is different to classic OOP, which is class-based
  - It has a clear concept of **Object** similar to object in other OOP
  - The concept of **Class** is the source of confusion
- We usually start by introducing *Object*
  - An object is a collection of related data and/or functionality
  - The “data” part is referred to as “property”
  - The “functionality” part is referred to as “method”
  - In JavaScript, almost “everything” is an object
    - Most data types
    - Functions
  - The easiest way of creating an object is to use Object Literal

# Object Creation using Literal

```
var objName = {  
    name1: value1,  
    name2: value2,  
    // ...  
    nameN: valueN  
};
```

- Access using either of:
  - `objName.name1`
  - `objName["name1"]`

# Object Creation using Literal

```
var person = {  
    firstName:"John",  
    lastName:"Doe",  
    age:50,  
    eyeColor:"blue"  
};
```

```
var person = {  
    firstName:"John",  
    lastName:"Doe",  
    age:50,  
    eyeColor:"blue",  
    fullName : function() {  
        return this.firstName + " " + this.lastName;  
    }  
};
```



# JavaScripts – Arrays

- Arrays are used to store multiple values in a single variable
- Object literal notation
  - `var greetings = ["Good Morning", "Good Afternoon"];`
- `Array()` constructor
  - `Var greetings = new Array("Good Morning", "Good Afternoon");`
- Array element is accessible with index, starting from 0, `greetings[0] = "Good Morning"`
- Useful methods `length()`, `push()`, `reverse()`, `sort()`,

# JavaScript Functions

- **Functions** are the building blocks for modular code in JavaScript
  - They are defined by using the reserved word **function** and then the function name and (optional) parameters

## Example:

```
function subtotal(price,quantity) {  
    return price * quantity;  
}
```

- Call/invoke function:

```
var result = subtotal(10,2);
```

# Functions – Function Expression

A function can be defined using an *anonymous function expression*

```
var calculateSubtotal = function (price,quantity) {  
    return price * quantity;  
};
```

// invokes the function

```
var result = calculateSubtotal (10,2);
```


# JavaScript – Nested Functions

```
function calculateTotal (price,quantity) {  
    var subtotal = price * quantity;  
    return subtotal + calculateTax(subtotal);  
    // this function is nested  
    function calculateTax(subtotal) {  
        var taxRate = 0.05;  
        var tax = subtotal * taxRate;  
        return tax;  
    }  
}
```

# Functions – Hoisting


Listing 1

```
function calculateTotal(price,quantity) {  
    var subtotal = price * quantity;  
    return subtotal + calculateTax(subtotal);  
}  
  
function calculateTax(subtotal) {  
    var taxRate = 0.05;  
    var tax = subtotal * taxRate;  
    return tax;  
}
```



Listing 2

```
function calculateTotal(price,quantity) {  
    var subtotal = price * quantity;  
    return subtotal + calculateTax(subtotal);  
}  
  
var calculateTax = function (subtotal) {  
    var taxRate = 0.05;  
    var tax = subtotal * taxRate;  
    return tax;  
};
```



# Functions – Hoisting

Function declaration is **hoisted** to the beginning of its scope

```
function calculateTotal(price,quantity) {  
  var subtotal = price * quantity;  
  return subtotal + calculateTax(subtotal);  
  
  function calculateTax(subtotal) {  
    var taxRate = 0.05;  
    var tax = subtotal * taxRate;  
    return tax;  
  }  
}
```

Variable declaration is hoisted to the beginning of its scope

**BUT**  
Variable assignment is **not** hoisted

```
function calculateTotal(price,quantity) {  
  var subtotal = price * quantity;  
  return subtotal + calculateTax(subtotal);  
  
  var calculateTax = function (subtotal) {  
    var taxRate = 0.05;  
    var tax = subtotal * taxRate;  
    return tax;  
  };  
}
```

**THUS**

The value of the calculateTax variable here is **undefined**

# JavaScript – Callback Functions

```
var calculateTotal = function (price, quantity, tax) {  
    var subtotal = price * quantity;  
    return subtotal + tax(subtotal);  
};
```

2

The local parameter variable `tax` is a reference to the `calcTax()` function

```
var calcTax = function (subtotal) {  
    var taxRate = 0.05;  
    var tax = subtotal * taxRate;  
    return tax;  
};
```


1

Passing the `calcTax()` function object as a parameter

```
var temp = calculateTotal(50, 2, calcTax);
```

We can say that `calcTax` variable here is a **callback function**


# JavaScript – Callback Anonymous Function





# JavaScript – Variable Scope

Each function is like a box with a one-way window



# Variable Scope

- Each variable in a program has a scope
- The scope of a variable is the portion of the program in which the variable can be used
- JavaScript has function scope
  - The scope changes inside functions
- A variable declared outside a function has global scope
  - In the HTML context, all scripts and functions on a webpage can access it.
- Variables declared inside a function has local scope
  - They can only be accessed within in the function

# Functions and Variable Scope – Exercise

```
1  var c = 0 ;
2  outer();
3
4  function outer() {
5      function inner() {
6          console.log(a);
7          var b = 23;
8          c = 37;
9      }
10     var a = 5;
11     inner();
12     console.log(c);
13     console.log(b);
14 }
```

- What will be logged in the console for the variable **a**?
- What will be logged in the console for the variable **b**?
- What will be logged in the console for the variable **c**?

# Variable Scope - Examples

global variable `c` is defined  
global function `outer()` is called

Anything declared inside this block is global and accessible everywhere in this block

```
1 var c = 0;  
2 outer();
```

Anything declared inside this block is accessible everywhere within this block

```
function outer() {
```

Anything declared inside this block is accessible only in this block

```
function inner() {
```

```
5 console.log(a);
```

✓ allowed

outputs 5

```
6 var b = 23;
```

```
7 c = 37;
```

✓ allowed

```
}
```

local (outer) variable `a` is accessed  
local (inner) variable `b` is defined  
global variable `c` is changed

local (outer) variable `a` is defined  
local function `inner()` is called  
global variable `c` is accessed  
undefined variable `b` is accessed

```
3 var a = 5;
```

```
4 inner();
```

```
8 console.log(c);
```

✓ allowed

outputs 37

```
9 console.log(b);
```

✗ not allowed

generates error or  
outputs undefined

# JavaScript Output


- **alert()** displays content within a pop-up box
  - `alert("Hello world");`
- **console.log()** displays content in the Browser's JavaScript console
- **document.write()** outputs the content (as mark-up) directly to the HTML document

```
var name = "COMP5347";  
document.write("<h1>Title</h1>");  
// this uses the concatenate operator (+)  
document.write("Hello " + name + " and welcome");
```

# JavaScript Output

Web page  
content

JavaScript  
console



Output from  
`console.log()`  
expressions

Using console interactively to query  
value of JavaScript variables

# Outline

- **More HTML**
  - **Table**
    - Elements
    - Styling
  - **Form**
    - Controls
- **JavaScript**
  - **Location and Basic Syntax**
    - Variables, Control Structure, Function, Object, Array
    - More about functions, objects, variable scopes, passing function as parameter
  - **Windows and DOM object**
  - **Event model**

# JavaScript Objects

- JavaScript contains some build-in objects for common processing
  - String, Date, Math and so on
- Client-side JavaScript is able to access browser object
  - window, history, location, etc.
- Client-side JavaScript is able to access HTML elements as a set of objects (DOM)
  - document, various element and other objects

<https://www.w3schools.com/jsref/default.asp>



# DOM standards

- Most commonly implemented specification: DOM level 2
- Several subcategories
  - Core
    - Interface for manipulating hierarchically organized node sets
  - HTML
    - Support for specific HTML elements
  - Style
    - Dealing with element style and style sheets
  - Events
    - Dealing with how event handlers are attached or removed from DOM nodes


# DOM Basics

- The DOM presents documents as a hierarchy of Node objects
  - Node is the most abstract concept
  - Different types of nodes
    - Document: the root of the tree
    - Element: HTML or XML element
    - Attr: attribute of an element (not considered as part of a DOM tree)
    - Comment: HTML comment
    - Text: the textual content of an Element or Attr
    - ...
  - A node may have a child node
    - Element may have other element or text as child node
- DOM allows developers to access all the elements of a web page
- Using JavaScript, programmers can create, modify and remove elements in the page dynamically

# DOM nodes and Trees


- The nodes in a document make up the page's DOM tree
- Nodes have *child-parent* relationships
- A node may have *multiple children*, but only *one parent*
- Nodes with the same parent node are referred to as *siblings*
- The document node has no parent and is called the root node

# The DOM



# DOM Nodes

```
<p>Photo of Conservatory Pond in  
  <a href="http://www.centralpark.com/">Central Park</a>  
</p>
```



# Essential Node Properties

Property	Description
<b>attributes</b>	Collection of node attributes
<b>childNodes</b>	A NodeList of child nodes for this node
<b>firstChild</b>	First child node of this node
<b>lastChild</b>	Last child of this node
<b>nextSibling</b>	Next sibling node for this node
<b>nodeName</b>	Name of the node
<b>nodeType</b>	Type of the node
<b>nodeValue</b>	Value of the node
<b>parentNode</b>	Parent node for this node
<b>previousSibling</b>	Previous sibling node for this node

# Document Object

Method	Description
<b>createAttribute()</b>	Creates an attribute node
<b>createElement()</b>	Creates an element node
<b>createTextNode()</b>	Create a text node
<b>getElementById(id)</b>	Returns the element node whose id attribute matches the passed id parameter
<b>getElementsByTagName(name)</b>	Returns a nodeList of elements whose tag name matches the passed name parameter

[https://www.w3schools.com/js/js\\_html\\_dom\\_document.asp](https://www.w3schools.com/js/js_html_dom_document.asp)

# Accessing Nodes – Selection Methods

```
var abc = document.getElementById("latestComment");
```

```
<body>
  <h1>Reviews</h1>
  <div id="latestComment">
    <p>By Ricardo on <time>September 15, 2012</time></p>
    <p>Easy on the HDR buddy.</p>
  </div>
  <hr/>
  <div>
    <p>By Susan on <time>October 1, 2012</time></p>
    <p>I love Central Park.</p>
  </div>
  <hr/>
</body>
```

```
var list = document.getElementsByTagName("div");
```



# Modifying the DOM

- 1 Create a new text node

"this is dynamic"

```
var text = document.createTextNode("this is dynamic");
```

- 2 Create a new empty <p> element

<p></p>

```
var p = document.createElement("p");
```

- 3 Add the text node to new <p> element

<p> "this is dynamic" </p>

```
p.appendChild(text);
```

- 4 Add the <p> element to the <div>

```
var first = document.getElementById("first");  
first.appendChild(p);
```

# Modifying the DOM

- 4 Add the <p> element to the <div>

```
var first = document.getElementById("first");  
first.appendChild(p);
```

```
<div id="first">  
  <h1>DOM Example</h1>  
  <p>Existing element</p>  
  <p>this is dynamic</p>  
</div>
```

```
<div>  
  <h1> "DOM Example" </h1>  
  <p> "Existing element" </p>  
  <p> "this is dynamic" </p>  
</div>
```

# Modifying Element's Style

```
var commentTag = document.getElementById("specificTag");  
commentTag.style.backgroundColor = "#FFFF00";  
commentTag.style.borderWidth="3px";
```

```
var commentTag = document.getElementById("specificTag");  
commentTag.className = "someClassName";
```

# Outline

- **More HTML**
  - **Table**
    - Elements
    - Styling
  - **Form**
    - Controls
- **JavaScript**
  - **Location and Basic Syntax**
    - Variables, Control Structure, Function, Object, Array
    - More about functions, objects, variable scopes, passing function as parameter
  - **Windows and DOM object**
  - **Event model**

# Events

- HTML events are “things” that happen to HTML elements
- When JavaScript is used in HTML pages, it can “react” on these events
- An HTML event can be something the browser or a user does:
  - An HTML web page has finished loading
  - An HTML input field was changed
  - An HTML button was clicked
- Event handler
  - A function describes what we want to do when an event happens

# Registering Event Handler – Listener Approach

```
function displayTheDate() {  
    var d = new Date();  
    alert ("You clicked this on " + d.toString());  
}  
var element = document.getElementById('example1');  
element.onclick = displayTheDate;  
  
// or using the other approach  
element.addEventListener('click',displayTheDate);
```

```
var element = document.getElementById('example1');  
element.onclick = function() {  
    var d = new Date();  
    alert ("You clicked this on " + d.toString());  
};
```

# Common HTML Events

- Mouse Events
  - onclick, onmousedown, onmouseenter,...
- Keyboard Events
  - onkeydown, onkeyup, ...
- Form events
  - onfocus, onblur, onsubmit, ...
- Frame/Object events
  - onload, onscroll, ...
- Not all browsers implements all events

# The onload event

- Both frame and object can fire onload event
  - **Frame** refers to the browser frame that contains the current web page
  - Onload event fires when “something” is loaded
    - A whole page or a single element

```
window.onload= function(){  
    //all JavaScript initialization here.  
}
```



# The event Object and this

- Event object stores contextual information about the event
  - This can be passed to the event handler
  - The object has a number of properties and methods
- In an event-handling function, *this* refers to the target DOM node on which the event occurred

```
document.getElementById("loginForm").onsubmit = function(e){
    var fieldValue=document.getElementById("username").value;
    if(fieldValue==null || fieldValue== ""){
        // the field was empty. Stop form submission
        e.preventDefault();
        // Now tell the user something went wrong
        alert("you must enter a username");
    }
}
```

# References

- Randy Connolly, Ricardo Hoar, Fundamentals of Web Development, Global Edition, Pearson
- W3Schools, HTML Tutorial  
[<https://www.w3schools.com/html/default.asp>]
- W3Schools, JavaScript tutorial  
[<https://www.w3schools.com/js/default.asp>]

**W3 Tutorial: HTML and  
JavaScript**

**W4 Lecture: JavaScript and  
Browser Rendering Process**

**Assignment 1 - released (in  
W2)**

