VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE

Department of Artificial Intelligence and Machine Learning

FEW-SHOT TEMPORAL ANOMALY GENERATION AND DETECTION IN BRAIN CONNECTIVITY SUBGRAPHS FOR AUTISM DISORDER

Branch: AIML-B

GRN: 4

Day: Tuesday

Date: 13/10/2026

Project Guide

Dr. Premanand Ghadekar

Group Members

Sr. No.	Roll No.	Name	PRN	Email ID
1	58	Hanil Shah	12414322	hanil.shah24@vit.edu
2	59	Harsh Patel	12413448	patel.harsh24@vit.edu
3	62	Tanaya Hartalekar	12410318	tanaya.hartalekar24@vit.edu
4	73	Shravani Dixit	12415111	shravani.dixit24@vit.edu

INTRODUCTION

The Problem

- Autism (ASD) is linked to differences in brain connectivity seen in resting-state fMRI.
- Brain networks change over time, so one static network per scan can miss short-lived changes.
- Labelled ASD scans are few, so we learn what is normal from control scans and flag what deviates.
- We also create synthetic anomalies to see if they help when only a few ASD scans exist.

Project Framing

Can unusual changes in small brain subgraphs be found by learning only normal dynamics, and can synthetic anomalies help with few ASD examples?

Dataset used

871

ABIDE I scans (403 ASD, 468 control)

20

scanning sites

360

brain regions per scan

Scope note: this is a research prototype for anomaly generation and detection, not a clinical diagnostic tool. No claim of ASD diagnosis is made.

OBJECTIVES

1 **Build time-resolved brain graphs**

Convert 871 ABIDE I scans (360 regions) into sliding-window brain graphs.

✓ COMPLETED

2 **Track brain-region subgraphs**

Follow 20 selected regions and their neighbours across time windows.

✓ COMPLETED

3 **Learn normal brain dynamics**

Train a GIN + GRU on control scans only to predict the next window.

✓ COMPLETED

4 **Detect anomalies**

Score prediction errors and set thresholds from validation controls.

✓ COMPLETED

5 **Generate synthetic anomalies**

Gradient-guided edge edits on control subgraphs (7,200 records, 0 rule violations).

✓ COMPLETED

6 **Evaluate few-shot and severity**

Test 1, 5, 10 ASD scans (accuracy, F1, AUROC); severity and demo app.

✓ COMPLETED

LITERATURE SURVEY

VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE

Theme	Key Paper	Key Insight	Relevance to Project
ABIDE dataset	A. Di Martino et al. (2014)	Openly shares rs-fMRI + phenotypic data for 539 ASD / 573 control subjects across 17 sites; reports baseline hypoconnectivity in ASD.	Grounds the ABIDE I dataset (871 subjects, 20 sites) used throughout.
GNN expressive power	Keyulu Xu et al. (2018)	Proves common GNN variants are weaker than the Weisfeiler-Lehman test; introduces GIN, which matches it.	Justifies the weighted GIN encoder used to embed each subgraph.
Dynamic functional connectivity	R. Matthew Hutchison et al. (2013)	Defines and surveys sliding-window estimation of time-varying connectivity and its methodological pitfalls.	Grounds the 30-TR / stride-10 sliding-window graph construction.
Graph anomaly detection	Xiaoxiao Ma et al. (2021)	Taxonomizes deep graph-anomaly-detection methods by anomaly type and technique; flags scarce labels as an open challenge.	Frames the prediction-error, threshold-calibrated anomaly score.
Gradient-based graph perturbation	Kaidi Xu et al. (2019)	Formulates graph structure attacks as constrained optimization solved with projected gradient descent (PGD).	Grounds the PGD-style iterative edge-weight perturbation.

Existing Work → Our Focus




Our focus: existing work provides graph representations, temporal modeling, classification, and anomaly detection; this project additionally investigates structure-aware, gradient-guided anomaly generation for a few-shot brain-subgraph setting. Full 20-paper analysis: *GRAPH_ANOMALY_Literature_Review.xlsx*

PROPOSED METHODOLOGY

VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE

DATA PREPARATION AND PATIENT SPLIT

ABIDE I, 871 patient scans



control patient ASD patient

SLIDING-WINDOW BRAIN GRAPH BUILDING

30-TR windows, stride 10; Pearson correlation; signed graph, top 20% edges

BRAIN-REGION SUBGRAPH TRACKING

20 selected brain regions (ROIs), 1-hop neighbourhood; node set fixed at the first window

GIN ENCODING AND GRU NEXT-WINDOW PREDICTION

2-layer weighted GIN, mean pool, 128-D embedding; GRU (hidden 128), MSE + variance loss, controls only

TEMPORAL SUBGRAPH ANOMALY SCORING FOR ASD DETECTION

patient score = max over regions and transitions

CONTROL-BASED DETECTION THRESHOLD CALIBRATION

95th percentile of validation-control scores (transition and patient level)

SYNTHETIC SUBGRAPH ANOMALY GENERATION


Gradient-guided PGD edge-weight edits, 5 steps, up to 15% of edge pairs, 3 severities


FEW-SHOT ASD ADAPTATION

1 / 5 / 10 ASD patient scans + 30 generated anomalies; logistic regression on 20-D region scores

ANOMALY DETECTION AND SEVERITY OUTPUT

Flag if score exceeds threshold; ADOS-2 severity band






synthetic anomaly (bold = edited)

MAJOR CONTRIBUTIONS

VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE

1 Two-level anomaly detection

Subgraph-step scores localise where and when; a patient-level threshold, calibrated on the patient score itself, decides who is flagged. A step-level cut-off alone flagged all 131 test patients.




2 Guided sub-structure anomaly generation

Only existing connection weights are edited, choosing the connections the model is most sensitive to. 45.8% are detected vs 4.8% for random edits.




3 Control-only temporal subgraph model

Fixed-membership subgraphs are followed over time and a GIN + GRU predicts the next window from control scans only: no labelled anomalies are needed.




tracked subgraph



4 Leakage-safe pipeline and demo application

Patient-level splits, thresholds from validation controls only, and a web app that turns a raw time series into a flag and a severity band.



Demo web app

Upload a raw ROI time series → detector flag, score and severity band.

Runs locally; research prototype.

RESULTS: OVERALL COMPARISON


VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE


Approach	Accuracy	Precision	Recall	F1 score	AUROC
Baseline detector (no few-shot data)	53.4%	0.500	0.033	0.062	0.453
Few-shot data only (normal detection)	**52.1% ± 1.8**	0.354 ± 0.20	0.115 ± 0.05	0.155 ± 0.06	**0.508 ± 0.04**
Random anomaly generation + detection	51.0% ± 2.1	**0.466 ± 0.03**	**0.373 ± 0.07**	**0.411 ± 0.05**	0.507 ± 0.04
Sub-structure anomaly generation + detection	49.5% ± 2.6	0.445 ± 0.04	0.353 ± 0.05	0.393 ± 0.04	0.495 ± 0.04


- **How to read:** average over 1, 5 and 10 ASD scans (each from five random draws), tested on 131 held-out patients; green marks the best value in each column.
- Adding generated anomalies raises recall and F1 over few-shot data alone.
- Accuracy and AUROC stay close to chance (about 50%) for every approach.

RESULTS: 10-SHOT COMPARISON

VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE







9.6×

Sub-structure edits are detected 9.6× more often than random edits (45.8% vs 4.8%).

0.31 → 0.43

10-shot F1 rises from 0.31 with few-shot data alone to 0.43 (random) and 0.40 (sub-structure).


≈ 0.50

AUROC stays near chance for all three approaches: the gain comes from flagging more patients.

RESULTS: DETECTING GENERATED ANOMALIES

VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE

Approach	Accuracy	Precision	Recall	F1 score	AUROC
Random anomaly generation + detection	50.0%	0.500	0.049	0.090	0.491
Sub-structure anomaly generation + detection	**70.2%**	**0.902**	**0.454**	**0.604**	**0.906**



0.91 AUROC for guided edits, against 0.49 for random edits


90% of transitions flagged after guided edits are truly edited


70% accuracy for guided edits, against 50% (chance) for random edits

Setup: 70 held-out test controls × 20 regions = 1,400 edited transitions per method (equal edit budget); threshold 7.43 from validation controls. This measures how detectable the generated anomalies are (the same model guides and scores the edits); it is not ASD diagnosis.


RESULTS: SYNTHETIC ANOMALIES

VISHWAKARMA INSTITUTE OF TECHNOLOGY, PUNE





real control subgraph



after guided edit (edited edges bold)

Guided edits: score 0.62 → 4.83 on this example; 45.8% of guided high-severity steps are detected vs 4.8% for random edits.

DISCUSSION

WHAT WORKED

- Stable training with no representation collapse (embedding std 1.03–1.16).
- Generator works as designed: 7,200 records, 0 rule violations, severity-monotonic.
- Sub-structure edits detected 45.8% of the time vs 4.8% for random edits (9.6×).
- Leakage-safe protocol: patient-level split, thresholds from validation controls only.
- Complete pipeline plus a demo application and 20 sample scans.

CHALLENGES

- Detector is at chance on ABIDE I: AUROC 0.453, accuracy 53.4%.
- A single step-level threshold flagged all 131 test patients; fixed with a patient-level threshold.
- Few-shot F1 gains come from flagging more patients; AUROC stays about 0.50.
- Severity estimate is below a majority guess (43.3% vs 55.0%).
- Only 20 of 360 regions, one training run, no site-level test.

INTERPRETATION

- A diagnosis label is a weak sign of unusual connectivity dynamics; ASD is highly varied.
- Site effects and short, noisy windows may hide a real signal.
- Detectability of generated anomalies is self-referential: the same model guides and scores the edits.
- Guided and random generation behave alike in the few-shot test.
- Research prototype: no clinical claim.

CONCLUSION

- Built and tested an end-to-end pipeline: time-resolved brain graphs, brain-region subgraph tracking, temporal anomaly scoring, synthetic anomaly generation, few-shot adaptation and a severity output.
- All six objectives were completed, including a working demo web application.
- The anomaly generator works as designed: 0 rule violations, and 45.8% of sub-structure edits are detected against 4.8% for random edits.
- On ABIDE I the detector is at chance (AUROC 0.453, accuracy 53.4%); few-shot F1 gains come from a higher flag rate (AUROC about 0.50).
- Severity estimation is below a majority guess (43.3% vs 55.0%).
- Research prototype only: no clinical claim, and all results are reported as found.