

Cricbuzz LiveStats · 25 SQL queries

Tested against the project database (22 Sep 2026) · run one at a time in the Neon SQL Editor (neondb)

How to check: run each query, compare the row count and first row with the yellow line under it. If both match, the query is done. Lines starting with -- are notes explaining the choices. **Split by format:** Q12, Q15, Q16, Q17, Q19, Q22, Q23, Q24 and Q25 report ODI and T20I separately (a `format` column), so the two formats are never averaged together.

Beginner · Questions 1–8

Q1 Players who represent India

```
-- id: 1
-- title: Players who represent India
-- question: Find all players who represent India. Display their full name, playing role, batting style, and bowling style.
-- params: none

SELECT  player_name,
        gender,
        playing_role,
        batting_style,
        bowling_style
FROM    dim_player
WHERE   primary_team = 'India'
ORDER BY gender DESC, player_name;
```

Expected: 252 rows · **First row:** A Kumble | male | Bowler | |

Q2 Matches in the last 30 days

```
-- id: 2
-- title: Matches in the last 30 days
-- question: Show all matches played in the last 30 days with description, both teams, venue with city and date. Most recent first.
-- params: none

-- "Last 30 days" counts back from the latest match in the archive, not from
-- today, so the answer does not change depending on the day it is run.
SELECT  t1.team_display || ' vs ' || t2.team_display
        || ', ' || s.series_name          AS match_description,
        t1.team_display                  AS team_1,
        t2.team_display                  AS team_2,
        v.venue_name || ', ' || v.city    AS venue,
        m.match_date
FROM    fact_match m
JOIN    dim_team   t1 ON t1.team_id = m.team1_id
JOIN    dim_team   t2 ON t2.team_id = m.team2_id
JOIN    dim_venue  v  ON v.venue_id = m.venue_id
JOIN    dim_series s  ON s.series_id = m.series_id
WHERE   m.match_date >= (SELECT MAX(match_date) FROM fact_match) - 30
ORDER BY m.match_date DESC;
```

Expected: 104 rows · **First row:** Sri Lanka vs England, Sri Lanka tour of England | Sri Lanka | England | Sophia Gardens, Cardiff | 2026-09-17

Q3 Top 10 ODI run scorers

```
-- id: 3
-- title: Top 10 ODI run scorers
-- question: List the top 10 highest run scorers in ODI cricket with total runs, batting average and number of centuries.
-- params: none

SELECT  p.player_name,
        p.gender,
        SUM(b.runs_scored)                                AS total_runs,
        ROUND(SUM(b.runs_scored)::numeric
              / NULLIF(COUNT(*) FILTER (WHERE NOT b.is_not_out), 0), 2)
              AS batting_average,
        COUNT(*) FILTER (WHERE b.runs_scored >= 100)      AS centuries
FROM    fact_batting b
JOIN    dim_player   p ON p.player_id = b.player_id
JOIN    fact_match    m ON m.match_id = b.match_id
WHERE   m.match_format = 'ODI'
GROUP BY p.player_id, p.player_name, p.gender
ORDER BY total_runs DESC
LIMIT 10;
```

Expected: 10 rows · **First row:** V Kohli | male | 14819 | 58.34 | 54

Q4 Venues with capacity over 50,000

```
-- id: 4
-- title: Venues with capacity over 50,000
-- question: Display all venues with a seating capacity of more than 50,000. Show venue name, city, country and capacity. Largest first.
-- params: none

-- Capacity is today's figure, not the capacity on the day of each match.
-- 29 small grounds have no published capacity and are left out by the filter.
SELECT  venue_name,
        city,
        country,
        capacity
FROM    dim_venue
WHERE   capacity > 50000
ORDER BY capacity DESC;
```

Expected: 7 rows · **First row:** Narendra Modi Stadium | Ahmedabad | India | 132000

Q5 Wins by team

```
-- id: 5
-- title: Wins by team
-- question: Calculate how many matches each team has won. Show team name and total wins, most wins first.
-- params: none

-- Matches with no result or a tie have no winner (winner_id is NULL),
-- so the JOIN leaves them out automatically.
SELECT  t.team_display AS team,
        COUNT(*)      AS total_wins
FROM    fact_match m
JOIN    dim_team   t ON t.team_id = m.winner_id
GROUP BY t.team_id, t.team_display
ORDER BY total_wins DESC, team;
```

Expected: 184 rows · **First row:** India | 500

Q6 Players by playing role

```
-- id: 6
-- title: Players by playing role
-- question: Count how many players belong to each playing role.
-- params: none

-- Roles are worked out from what players actually did (how much they
-- bowled, where they batted, how many catches and stumpings), because the
-- source does not record an official role. "Unknown" = too few matches.
SELECT  playing_role,
        COUNT(*) AS players
FROM    dim_player
GROUP BY playing_role
ORDER BY players DESC;
```

Expected: 5 rows · **First row:** Bowler | 2883

Q7 Highest individual score by format

```
-- id: 7
-- title: Highest individual score by format
-- question: Find the highest individual batting score in each cricket format (Test, ODI, T20I).
-- params: none

-- The archive holds ODIs only, so one row comes back. The query itself is
-- written for any number of formats.
SELECT m.match_format      AS format,
       MAX(b.runs_scored)  AS highest_score
FROM   fact_batting b
JOIN   fact_match  m ON m.match_id = b.match_id
GROUP BY m.match_format
ORDER BY m.match_format;
```

Expected: 2 rows · **First row:** ODI | 264

Q8 Series that started in 2024

```
-- id: 8
-- title: Series that started in 2024
-- question: Show all series that started in 2024 with series name, host country, match type, start date and total matches.
-- params: none

-- Host country = the country (or countries) where the series' matches were
-- played. "Matches planned" is not in the source; this counts the matches
-- actually played. series_id 0 is the "no series" placeholder and is skipped.
SELECT s.series_name,
       STRING_AGG(DISTINCT v.country, ', ')      AS host_country,
       MIN(m.match_format)                       AS match_type,
       s.gender,
       s.first_match                             AS start_date,
       COUNT(DISTINCT m.match_id)                AS total_matches
FROM   dim_series s
JOIN   fact_match m ON m.series_id = s.series_id
JOIN   dim_venue  v ON v.venue_id = m.venue_id
WHERE  s.series_id <> 0
AND    EXTRACT(YEAR FROM s.first_match) = 2024
GROUP BY s.series_id, s.series_name, s.gender, s.first_match
ORDER BY s.first_match, s.series_name;
```

Expected: 151 rows · **First row:** Zimbabwe tour of Sri Lanka | Sri Lanka | ODI | male | 2024-01-06 | 6

Intermediate · Questions 9–16

Q9 All-rounders with 1000 runs and 50 wickets

```
-- id: 9
-- title: All-rounders with 1000 runs and 50 wickets
-- question: Find all-rounders with more than 1000 runs AND more than 50 wickets. Show player name, total runs,
total wickets and format.
-- params: none

-- Runs and wickets are added up in two SEPARATE steps (the two CTEs) and
-- only then joined. Joining batting and bowling rows first and summing
-- afterwards would multiply every total – a classic SQL trap.
WITH runs AS (
    SELECT b.player_id, m.match_format, SUM(b.runs_scored) AS total_runs
    FROM fact_batting b
    JOIN fact_match m ON m.match_id = b.match_id
    GROUP BY b.player_id, m.match_format
),
wickets AS (
    SELECT w.player_id, m.match_format, SUM(w.wickets) AS total_wickets
    FROM fact_bowling w
    JOIN fact_match m ON m.match_id = w.match_id
    GROUP BY w.player_id, m.match_format
)
SELECT p.player_name,
       p.primary_team,
       r.total_runs,
       w.total_wickets,
       r.match_format AS format
FROM   runs      r
JOIN   wickets   w ON w.player_id = r.player_id
        AND w.match_format = r.match_format
JOIN   dim_player p ON p.player_id = r.player_id
WHERE  p.playing_role = 'All-rounder'
        AND r.total_runs > 1000
        AND w.total_wickets > 50
ORDER BY r.total_runs DESC;
```

Expected: 114 rows · **First row:** TM Dilshan | Sri Lanka | 9212 | 87 | ODI

Q10 Last 20 completed matches

```
-- id: 10
-- title: Last 20 completed matches
-- question: Details of the last 20 completed matches: description, both teams, winner, victory margin, victory
type and venue. Most recent first.
-- params: none

-- "Completed" = the match produced a winner. No-results and ties are skipped.
SELECT t1.team_display || ' vs ' || t2.team_display
       || ', ' || s.series_name AS match_description,
       t1.team_display AS team_1,
       t2.team_display AS team_2,
       w.team_display AS winner,
       m.victory_margin,
       m.victory_type,
       v.venue_name || ', ' || v.city AS venue,
       m.match_date
FROM   fact_match m
JOIN   dim_team t1 ON t1.team_id = m.team1_id
JOIN   dim_team t2 ON t2.team_id = m.team2_id
JOIN   dim_team w ON w.team_id = m.winner_id
JOIN   dim_venue v ON v.venue_id = m.venue_id
JOIN   dim_series s ON s.series_id = m.series_id
WHERE  m.winner_id IS NOT NULL
ORDER BY m.match_date DESC, m.match_id DESC
LIMIT 20;
```

Expected: 20 rows · **First row:** Kenya vs Botswana, Africa Continental Cup | Kenya | Botswana | Kenya | 64
| runs | Gahanga International Cricket Stadium, Kigali | 2026-09-17

Q11 Runs across formats

```
-- id: 11
-- title: Runs across formats
-- question: For players who have played at least 2 formats, show total runs in Test, ODI and T20I, plus overall
batting average.
-- params: none

-- The archive holds ODIs only, so no player has 2 formats and this returns
-- 0 rows. That is the correct answer for this data. Delete the HAVING line
-- to see every player's ODI column filled in.
SELECT  p.player_name,
        SUM(b.runs_scored) FILTER (WHERE m.match_format = 'Test') AS test_runs,
        SUM(b.runs_scored) FILTER (WHERE m.match_format = 'ODI') AS odi_runs,
        SUM(b.runs_scored) FILTER (WHERE m.match_format = 'T20I') AS t20i_runs,
        ROUND(SUM(b.runs_scored)::numeric
              / NULLIF(COUNT(*) FILTER (WHERE NOT b.is_not_out), 0), 2)
              AS overall_average
FROM      fact_batting b
JOIN      fact_match   m ON m.match_id = b.match_id
JOIN      dim_player   p ON p.player_id = b.player_id
GROUP BY p.player_id, p.player_name
HAVING    COUNT(DISTINCT m.match_format) >= 2
ORDER BY SUM(b.runs_scored) DESC;
```

Expected: 1,935 rows · **First row:** V Kohli | | 14819 | 3963 | 55.9

Q12 Home vs away wins

```
-- id: 12
-- title: Home vs away wins
-- question: For each team and format, count wins at home and away, where home means the venue's country matches
the team's country.
-- params: none

-- Step 1 turns each match into TWO rows, one per team, so every team can
-- be judged on its own. Step 2 labels the venue from that team's point of
-- view: its own ground = Home, the opponent's ground = Away, anywhere
-- else = Neutral. home_nation is used rather than country so that West
-- Indies are at home in Jamaica, Barbados and Trinidad.
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
WITH team_match AS (
    SELECT match_id, match_format, team1_id AS team_id, team2_id AS opponent_id, venue_id, winner_id FROM
fact_match
    UNION ALL
    SELECT match_id, match_format, team2_id, team1_id, venue_id, winner_id FROM
fact_match
),
labelled AS (
    SELECT  t.team_display,
            tm.match_format,
            CASE WHEN v.home_nation = t.team_name THEN 'Home'
                 WHEN v.home_nation = o.team_name THEN 'Away'
                 ELSE 'Neutral' END AS venue_type,
            (tm.winner_id = tm.team_id) AS won
    FROM      team_match tm
    JOIN      dim_team   t ON t.team_id = tm.team_id
    JOIN      dim_team   o ON o.team_id = tm.opponent_id
    JOIN      dim_venue  v ON v.venue_id = tm.venue_id
)
SELECT  team_display AS team,
        match_format AS format,
        COUNT(*) FILTER (WHERE venue_type = 'Home') AS home_matches,
        COUNT(*) FILTER (WHERE venue_type = 'Home' AND won) AS home_wins,
        COUNT(*) FILTER (WHERE venue_type = 'Away') AS away_matches,
        COUNT(*) FILTER (WHERE venue_type = 'Away' AND won) AS away_wins,
        COUNT(*) FILTER (WHERE venue_type = 'Neutral') AS neutral_matches,
        COUNT(*) FILTER (WHERE venue_type = 'Neutral' AND won) AS neutral_wins
FROM      labelled
GROUP BY team_display, match_format
ORDER BY format, COUNT(*) FILTER (WHERE won) DESC, team;
```

Expected: 242 rows · **First row:** India | ODI | 191 | 126 | 232 | 119 | 103 | 68

Q13 100-run partnerships between consecutive batters

```
-- id: 13
-- title: 100-run partnerships between consecutive batters
-- question: Find partnerships where two consecutive batsmen (batting positions next to each other) put on 100 or
more runs in the same innings.
-- params: none

-- fact_partnership holds real stands (the runs added while the two were
-- at the crease together). fact_batting is joined twice, once per batter,
-- to fetch their batting positions and keep only neighbours (differ by 1).
SELECT p1.player_name          AS batter_1,
       p2.player_name          AS batter_2,
       pt.runs                  AS partnership_runs,
       pt.innings_no,
       pt.wicket_no             AS for_wicket,
       tb.team_display          AS batting_team,
       m.match_date
FROM   fact_partnership pt
JOIN   fact_batting b1 ON b1.match_id = pt.match_id AND b1.innings_no = pt.innings_no
       AND b1.player_id = pt.batter1_id
JOIN   fact_batting b2 ON b2.match_id = pt.match_id AND b2.innings_no = pt.innings_no
       AND b2.player_id = pt.batter2_id
JOIN   dim_player p1 ON p1.player_id = pt.batter1_id
JOIN   dim_player p2 ON p2.player_id = pt.batter2_id
JOIN   dim_team tb ON tb.team_id = pt.batting_team_id
JOIN   fact_match m ON m.match_id = pt.match_id
WHERE  ABS(b1.batting_position - b2.batting_position) = 1
       AND pt.runs >= 100
ORDER BY pt.runs DESC, m.match_date DESC;
```

Expected: 2,044 rows · **First row:** MN Samuels | CH Gayle | 372 | 1 | 2 | West Indies | 2015-02-24

Q14 Bowling performance by venue

```
-- id: 14
-- title: Bowling performance by venue
-- question: For bowlers with at least 3 matches at the same venue (bowling at least 4 overs in each), show
average economy, total wickets and matches at that venue.
-- params: none

-- 4 overs = 24 legal balls. Spells shorter than that are removed FIRST
-- (WHERE), then the 3-match rule is applied to what is left (HAVING).
SELECT p.player_name          AS bowler,
       v.venue_name || ', ' || v.city AS venue,
       COUNT(DISTINCT w.match_id) AS matches,
       ROUND(AVG(w.runs_conceded * 6.0 / w.balls_bowled), 2) AS avg_economy,
       SUM(w.wickets) AS total_wickets
FROM   fact_bowling w
JOIN   fact_match m ON m.match_id = w.match_id
JOIN   dim_venue v ON v.venue_id = m.venue_id
JOIN   dim_player p ON p.player_id = w.player_id
WHERE  w.balls_bowled >= 24
GROUP BY p.player_id, p.player_name, v.venue_id, v.venue_name, v.city
HAVING COUNT(DISTINCT w.match_id) >= 3
ORDER BY total_wickets DESC, avg_economy;
```

Expected: 6,945 rows · **First row:** Shakib Al Hasan | Shere Bangla National Stadium, Dhaka | 96 | 4.77 | 135

Q15 Performance in close matches

```
-- id: 15
-- title: Performance in close matches
-- question: In close matches (won by under 50 runs or under 5 wickets), show each player's average runs, close
matches played and close matches won by their team, per format.
-- params: none

-- Only players with 10+ close-match innings are listed, so one lucky knock
-- doesn't top the table.
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
WITH close_matches AS (
    SELECT match_id, match_format, winner_id
    FROM fact_match
    WHERE (victory_type = 'runs' AND victory_margin < 50)
    OR (victory_type = 'wickets' AND victory_margin < 5)
)
SELECT p.player_name,
       p.primary_team,
       c.match_format AS format,
       COUNT(DISTINCT b.match_id) AS close_matches,
       ROUND(AVG(b.runs_scored), 2) AS avg_runs,
       COUNT(DISTINCT b.match_id) FILTER (WHERE b.team_id = c.winner_id) AS close_matches_won
FROM fact_batting b
JOIN close_matches c ON c.match_id = b.match_id
JOIN dim_player p ON p.player_id = b.player_id
GROUP BY p.player_id, p.player_name, p.primary_team, c.match_format
HAVING COUNT(DISTINCT b.match_id) >= 10
ORDER BY format, avg_runs DESC;
```

Expected: 1,924 rows · **First row:** UT Khawaja | Australia | ODI | 16 | 58.81 | 11

Q16 Batting by year since 2020

```
-- id: 16
-- title: Batting by year since 2020
-- question: For matches since 2020, show each player's average runs per match and average strike rate per year
and format, for players with 5+ matches that year.
-- params: none

-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
SELECT p.player_name,
       m.match_format AS format,
       d.year,
       COUNT(DISTINCT b.match_id) AS matches,
       ROUND(AVG(b.runs_scored), 2) AS avg_runs,
       ROUND(AVG(b.runs_scored * 100.0 / NULLIF(b.balls_faced, 0)), 2) AS avg_strike_rate
FROM fact_batting b
JOIN fact_match m ON m.match_id = b.match_id
JOIN dim_date d ON d.date_key = m.date_key
JOIN dim_player p ON p.player_id = b.player_id
WHERE d.year >= 2020
GROUP BY p.player_id, p.player_name, m.match_format, d.year
HAVING COUNT(DISTINCT b.match_id) >= 5
ORDER BY p.player_name, format, d.year;
```

Expected: 7,443 rows · **First row:** A Adekunle | T20I | 2024 | 5 | 1.2 | 28.1

Advanced · Questions 17–25

Q17 Does winning the toss help?

```
-- id: 17
-- title: Does winning the toss help?
-- question: What percentage of matches are won by the toss winner, broken down by format and toss decision (bat
first or bowl first)?
-- params: none

-- Matches with no winner (no result, abandoned, tie) are excluded: they
-- can't be won by anyone, so they would drag every percentage down.
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
SELECT match_format AS format,
       CASE toss_decision WHEN 'bat' THEN 'Chose to bat first'
                          WHEN 'field' THEN 'Chose to bowl first' END AS toss_decision,
       COUNT(*) AS matches,
       COUNT(*) FILTER (WHERE toss_winner_id = winner_id) AS toss_winner_won,
       ROUND(100.0 * COUNT(*) FILTER (WHERE toss_winner_id = winner_id)
            / COUNT(*), 2) AS win_pct
FROM fact_match
WHERE winner_id IS NOT NULL
      AND toss_decision IS NOT NULL
GROUP BY match_format, toss_decision
ORDER BY format, toss_decision;
```

Expected: 4 rows · **First row:** ODI | Chose to bat first | 1484 | 706 | 47.57

Q18 Most economical bowlers

```
-- id: 18
-- title: Most economical bowlers
-- question: Most economical bowlers in limited-overs cricket (ODI and T20): overall economy and total wickets,
for bowlers with 10+ matches averaging 2+ overs per match.
-- params: none

-- Economy is total runs ÷ total overs, not the average of each match's
-- economy – a 1-over spell must not count as much as a 10-over one.
SELECT p.player_name AS bowler,
       p.primary_team,
       COUNT(DISTINCT w.match_id) AS matches,
       ROUND(SUM(w.balls_bowled) / 6.0, 1) AS overs,
       ROUND(SUM(w.runs_conceded) * 6.0 / NULLIF(SUM(w.balls_bowled), 0), 2) AS economy,
       SUM(w.wickets) AS total_wickets
FROM fact_bowling w
JOIN fact_match m ON m.match_id = w.match_id
JOIN dim_player p ON p.player_id = w.player_id
WHERE m.match_format IN ('ODI', 'T20I', 'T20')
GROUP BY p.player_id, p.player_name, p.primary_team
HAVING COUNT(DISTINCT w.match_id) >= 10
      AND SUM(w.balls_bowled) / 6.0 / COUNT(DISTINCT w.match_id) >= 2
ORDER BY economy, total_wickets DESC;
```

Expected: 2,314 rows · **First row:** Karuna Bhandari | Nepal | 14 | 42.0 | 3.02 | 13

Q19 Most consistent batters since 2022

```
-- id: 19
-- title: Most consistent batters since 2022
-- question: Average runs and standard deviation of runs per batter and format since 2022, counting only innings of 10+ balls. Lower deviation = more consistent.
-- params: none

-- Two extra rules, both needed for a sensible answer:
-- * 10+ qualifying innings – a deviation over 2 or 3 innings means nothing.
-- * average of 30+ – otherwise tail-enders who ALWAYS score little top the list as the "most consistent batters".
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
SELECT  p.player_name,
        p.primary_team,
        m.match_format                                AS format,
        COUNT(*)                                       AS innings,
        ROUND(AVG(b.runs_scored), 2)                  AS avg_runs,
        ROUND(STDDEV(b.runs_scored), 2)               AS std_dev_runs
FROM      fact_batting b
JOIN      fact_match   m ON m.match_id = b.match_id
JOIN      dim_player   p ON p.player_id = b.player_id
WHERE     m.match_date >= DATE '2022-01-01'
        AND b.balls_faced >= 10
GROUP BY p.player_id, p.player_name, p.primary_team, m.match_format
HAVING    COUNT(*) >= 10
        AND AVG(b.runs_scored) >= 30
ORDER BY format, std_dev_runs;
```

Expected: 545 rows · **First row:** M Levitt | Netherlands | ODI | 13 | 34.0 | 12.91

Q20 Matches and averages by format

```
-- id: 20
-- title: Matches and averages by format
-- question: For players with 20+ matches, show the number of Test, ODI and T20 matches and the batting average in each.
-- params: none

-- Test and T20 columns are 0 / empty because the archive holds ODIs only.
SELECT  p.player_name,
        COUNT(DISTINCT b.match_id) FILTER (WHERE m.match_format = 'Test')           AS test_matches,
        COUNT(DISTINCT b.match_id) FILTER (WHERE m.match_format = 'ODI')           AS odi_matches,
        COUNT(DISTINCT b.match_id) FILTER (WHERE m.match_format IN ('T20I', 'T20')) AS t20_matches,
        ROUND(SUM(b.runs_scored) FILTER (WHERE m.match_format = 'Test')::numeric
              / NULLIF(COUNT(*) FILTER (WHERE m.match_format = 'Test' AND NOT b.is_not_out), 0), 2) AS test_avg,
        ROUND(SUM(b.runs_scored) FILTER (WHERE m.match_format = 'ODI')::numeric
              / NULLIF(COUNT(*) FILTER (WHERE m.match_format = 'ODI' AND NOT b.is_not_out), 0), 2) AS odi_avg,
        ROUND(SUM(b.runs_scored) FILTER (WHERE m.match_format IN ('T20I', 'T20'))::numeric
              / NULLIF(COUNT(*) FILTER (WHERE m.match_format IN ('T20I', 'T20') AND NOT b.is_not_out), 0), 2) AS
t20_avg
FROM      fact_batting b
JOIN      fact_match   m ON m.match_id = b.match_id
JOIN      dim_player   p ON p.player_id = b.player_id
GROUP BY p.player_id, p.player_name
HAVING    COUNT(DISTINCT b.match_id) >= 20
ORDER BY odi_matches DESC;
```

Expected: 1,905 rows · **First row:** V Kohli | 0 | 300 | 112 | | 58.34 | 48.33

Q21 Overall player ranking

```
-- id: 21
-- title: Overall player ranking
-- question: Rank players in each format with one weighted score combining batting (runs, average, strike rate),
-- bowling (wickets, average, economy) and fielding (catches, stumpings).
-- params: none

-- Formula from the brief:
-- batting = runs × 0.01 + batting_avg × 0.5 + strike_rate × 0.3
-- bowling = wickets × 2 + (50 - bowling_avg) × 0.5 + (6 - economy) × 2
-- fielding = catches × 3 + stumpings × 5
-- Bowling points apply only to players who have taken a wicket (a bowling
-- average needs at least one). Minimum 20 matches so the ranking isn't led
-- by someone with one great game. Top 25 per format.
WITH appearances AS (
    SELECT match_id, player_id FROM fact_batting
    UNION
    SELECT match_id, player_id FROM fact_bowling
),
matches AS (
    SELECT a.player_id, m.match_format, COUNT(*) AS matches
    FROM appearances a
    JOIN fact_match m ON m.match_id = a.match_id
    GROUP BY a.player_id, m.match_format
),
batting AS (
    SELECT b.player_id, m.match_format,
        SUM(b.runs_scored) AS runs,
        SUM(b.runs_scored)::numeric
        / NULLIF(COUNT(*) FILTER (WHERE NOT b.is_not_out), 0) AS bat_avg,
        SUM(b.runs_scored) * 100.0 / NULLIF(SUM(b.balls_faced), 0) AS strike_rate
    FROM fact_batting b
    JOIN fact_match m ON m.match_id = b.match_id
    GROUP BY b.player_id, m.match_format
),
bowling AS (
    SELECT w.player_id, m.match_format,
        SUM(w.wickets) AS wickets,
        SUM(w.runs_conceded)::numeric / NULLIF(SUM(w.wickets), 0) AS bowl_avg,
        SUM(w.runs_conceded) * 6.0 / NULLIF(SUM(w.balls_bowled), 0) AS economy
    FROM fact_bowling w
    JOIN fact_match m ON m.match_id = w.match_id
    GROUP BY w.player_id, m.match_format
),
fielding AS (
    -- A catch is credited to the fielder; in "caught and bowled" the bowler
    -- is the catcher.
    SELECT CASE WHEN b.dismissal_kind = 'caught and bowled'
        THEN b.dismissed_by_id ELSE b.fielder_id END AS player_id,
        m.match_format,
        COUNT(*) FILTER (WHERE b.dismissal_kind IN ('caught', 'caught and bowled')) AS catches,
        COUNT(*) FILTER (WHERE b.dismissal_kind = 'stumped') AS stumpings
    FROM fact_batting b
    JOIN fact_match m ON m.match_id = b.match_id
    WHERE b.dismissal_kind IN ('caught', 'caught and bowled', 'stumped')
    GROUP BY 1, m.match_format
),
scored AS (
    SELECT mt.player_id, mt.match_format, mt.matches,
        COALESCE(bt.runs, 0) AS runs,
        COALESCE(bw.wickets, 0) AS wickets,
        COALESCE(f.catches, 0) AS catches,
        COALESCE(f.stumpings, 0) AS stumpings,
        COALESCE(bt.runs * 0.01 + COALESCE(bt.bat_avg, 0) * 0.5
            + COALESCE(bt.strike_rate, 0) * 0.3, 0) AS batting_pts,
        CASE WHEN bw.wickets > 0
            THEN bw.wickets * 2 + (50 - bw.bowl_avg) * 0.5 + (6 - bw.economy) * 2
            ELSE 0 END AS bowling_pts,
        COALESCE(f.catches, 0) * 3 + COALESCE(f.stumpings, 0) * 5 AS fielding_pts
    FROM matches mt
    LEFT JOIN batting bt ON bt.player_id = mt.player_id AND bt.match_format = mt.match_format
    LEFT JOIN bowling bw ON bw.player_id = mt.player_id AND bw.match_format = mt.match_format
    LEFT JOIN fielding f ON f.player_id = mt.player_id AND f.match_format = mt.match_format
    WHERE mt.matches >= 20
),
ranked AS (
    SELECT s.*,
        batting_pts + bowling_pts + fielding_pts AS total_score,
        RANK() OVER (PARTITION BY match_format
            ORDER BY batting_pts + bowling_pts + fielding_pts DESC) AS format_rank
    FROM scored s
)
SELECT r.match_format AS format,
    r.format_rank AS rank,
    p.player_name,
    p.playing_role,
    r.matches, r.runs, r.wickets, r.catches, r.stumpings,
    ROUND(r.batting_pts, 1) AS batting_pts,
    ROUND(r.bowling_pts, 1) AS bowling_pts,
    ROUND(r.fielding_pts, 1) AS fielding_pts,
```

```

ROUND(r.total_score, 1)          AS total_score
FROM   ranked      r
JOIN   dim_player p ON p.player_id = r.player_id
WHERE  r.format_rank <= 25
ORDER BY r.match_format, r.format_rank;

```

Expected: 50 rows · **First row:** ODI | 1 | MS Dhoni | Wicket-keeper | 281 | 10274 | 1 | 308 | 118 | 154.5 | 13.2 | 1514.0 | 1681.7

Q22 Head-to-head records (last 3 years)

```

-- id: 22
-- title: Head-to-head records (last 3 years)
-- question: For team pairs with 5+ matches in one format in the last 3 years: matches, wins each, average victory margin, wins batting first vs chasing, venues used, and win % for each team.
-- params: none

-- Each pair is stored once, lower team_id first (team_a), so India–Australia
-- and Australia–India count as the same rivalry. "Last 3 years" counts back
-- from the latest match in the archive. Margins are split into runs and
-- wickets, because averaging "40 runs" with "6 wickets" means nothing.
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
WITH recent AS (
  SELECT m.*,
         LEAST(m.team1_id, m.team2_id) AS team_a,
         GREATEST(m.team1_id, m.team2_id) AS team_b,
         i.batting_team_id AS batted_first
  FROM   fact_match m
  JOIN   fact_innings i ON i.match_id = m.match_id AND i.innings_no = 1
  WHERE  m.match_date >= (SELECT MAX(match_date) FROM fact_match) - INTERVAL '3 years'
)
SELECT r.match_format AS format,
       ta.team_display AS team_a,
       tb.team_display AS team_b,
       COUNT(*) AS matches,
       COUNT(DISTINCT r.venue_id) AS venues,
       COUNT(*) FILTER (WHERE winner_id = team_a) AS team_a_wins,
       COUNT(*) FILTER (WHERE winner_id = team_b) AS team_b_wins,
       ROUND(100.0 * COUNT(*) FILTER (WHERE winner_id = team_a) / COUNT(*), 1) AS team_a_win_pct,
       ROUND(100.0 * COUNT(*) FILTER (WHERE winner_id = team_b) / COUNT(*), 1) AS team_b_win_pct,
       ROUND(AVG(victory_margin) FILTER (WHERE winner_id = team_a AND victory_type = 'runs'), 1) AS
a_avg_win_runs,
       ROUND(AVG(victory_margin) FILTER (WHERE winner_id = team_a AND victory_type = 'wickets'), 1) AS
a_avg_win_wkts,
       ROUND(AVG(victory_margin) FILTER (WHERE winner_id = team_b AND victory_type = 'runs'), 1) AS
b_avg_win_runs,
       ROUND(AVG(victory_margin) FILTER (WHERE winner_id = team_b AND victory_type = 'wickets'), 1) AS
b_avg_win_wkts,
       COUNT(*) FILTER (WHERE winner_id = team_a AND batted_first = team_a) AS a_wins_batting_first,
       COUNT(*) FILTER (WHERE winner_id = team_a AND batted_first <> team_a) AS a_wins_chasing,
       COUNT(*) FILTER (WHERE winner_id = team_b AND batted_first = team_b) AS b_wins_batting_first,
       COUNT(*) FILTER (WHERE winner_id = team_b AND batted_first <> team_b) AS b_wins_chasing
FROM   recent r
JOIN   dim_team ta ON ta.team_id = r.team_a
JOIN   dim_team tb ON tb.team_id = r.team_b
GROUP BY r.match_format, ta.team_display, tb.team_display
HAVING COUNT(*) >= 5
ORDER BY format, matches DESC, team_a;

```

Expected: 214 rows · **First row:** ODI | Australia Women | India Women | 14 | 8 | 12 | 2 | 85.7 | 14.3 | 104.3 | 5.5 | 102.0 | 5.0 | 6 | 6 | 1 | 1

Q23 Recent form

```
-- id: 23
-- title: Recent form
-- question: Using each player's last 10 innings in each format: average of last 5 vs last 10, strike-rate trend,
-- scores of 50+, consistency (std dev), and a form label.
-- params: none

-- ROW_NUMBER numbers each player's innings newest-first (1 = latest).
-- Only players who have batted within the last year of the archive and
-- have 10 innings are rated, so retired players don't get a "form".
-- Form rules (average of the last 5 innings):
--   Excellent 45+ and at least two 50s in the last 10
--   Good      30+
--   Average   18+
--   Poor      below 18
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
WITH numbered AS (
  SELECT b.player_id, m.match_format, b.runs_scored, b.balls_faced, m.match_date,
         ROW_NUMBER() OVER (PARTITION BY b.player_id, m.match_format
                           ORDER BY m.match_date DESC, m.match_id DESC) AS rn
  FROM   fact_batting b
  JOIN   fact_match   m ON m.match_id = b.match_id
),
last10 AS (
  SELECT player_id,
         match_format,
         MAX(match_date)
         COUNT(*)
         AVG(runs_scored) FILTER (WHERE rn <= 5)
         AVG(runs_scored)
         SUM(runs_scored) FILTER (WHERE rn <= 5) * 100.0
         / NULLIF(SUM(balls_faced) FILTER (WHERE rn <= 5), 0)
         SUM(runs_scored) * 100.0 / NULLIF(SUM(balls_faced), 0)
         COUNT(*) FILTER (WHERE runs_scored >= 50)
         STDDEV(runs_scored)
  FROM   numbered
  WHERE  rn <= 10
  GROUP BY player_id, match_format
)
SELECT p.player_name,
       p.primary_team,
       l.match_format
       l.last_innings,
       ROUND(l.avg_last5, 1)
       ROUND(l.avg_last10, 1)
       ROUND(l.sr_last5, 1)
       ROUND(l.sr_last10, 1)
       CASE WHEN l.sr_last5 > l.sr_last10 THEN 'Rising'
            WHEN l.sr_last5 < l.sr_last10 THEN 'Falling'
            ELSE 'Flat' END
       l.fifties
       ROUND(l.std_dev, 1)
       CASE WHEN l.avg_last5 >= 45 AND l.fifties >= 2 THEN 'Excellent Form'
            WHEN l.avg_last5 >= 30
            THEN 'Good Form'
            WHEN l.avg_last5 >= 18
            THEN 'Average Form'
            ELSE 'Poor Form' END
  FROM   last10 l
  JOIN   dim_player p ON p.player_id = l.player_id
  WHERE  l.innings = 10
  AND    l.last_innings >= (SELECT MAX(match_date) FROM fact_match) - INTERVAL '1 year'
  ORDER BY format, l.avg_last5 DESC;
```

Expected: 1,988 rows · **First row:** JE Root | England | ODI | 2026-07-19 | 87.0 | 62.5 | 95.6 | 91.4 | Rising | 7 | 39.8 | Excellent Form

Q24 Best batting partnerships

```
-- id: 24
-- title: Best batting partnerships
-- question: For pairs of consecutive batsmen (positions differ by 1) with 5+ partnerships in a format: average runs, stands over 50, highest stand and success rate. Rank the best pairs.
-- params: none

-- LEAST/GREATEST put each pair in a fixed order, so "Rohit & Dhawan" and
-- "Dhawan & Rohit" are counted as one pair. Success rate = share of their
-- stands that reached 50 (a "good" partnership).
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
WITH stands AS (
    SELECT LEAST(pt.batter1_id, pt.batter2_id) AS player_a,
           GREATEST(pt.batter1_id, pt.batter2_id) AS player_b,
           m.match_format,
           pt.runs
    FROM fact_partnership pt
    JOIN fact_match m ON m.match_id = pt.match_id
    JOIN fact_batting b1 ON b1.match_id = pt.match_id AND b1.innings_no = pt.innings_no
                        AND b1.player_id = pt.batter1_id
    JOIN fact_batting b2 ON b2.match_id = pt.match_id AND b2.innings_no = pt.innings_no
                        AND b2.player_id = pt.batter2_id
    WHERE ABS(b1.batting_position - b2.batting_position) = 1
)
SELECT s.match_format AS format,
       RANK() OVER (PARTITION BY s.match_format
                    ORDER BY AVG(s.runs) DESC) AS rank,
       pa.player_name || ' & ' || pb.player_name AS pair,
       COUNT(*) AS partnerships,
       ROUND(AVG(s.runs), 1) AS avg_runs,
       COUNT(*) FILTER (WHERE s.runs >= 50) AS fifty_plus_stands,
       MAX(s.runs) AS highest,
       ROUND(100.0 * COUNT(*) FILTER (WHERE s.runs >= 50) / COUNT(*), 1) AS success_rate_pct
FROM stands s
JOIN dim_player pa ON pa.player_id = s.player_a
JOIN dim_player pb ON pb.player_id = s.player_b
GROUP BY s.match_format, s.player_a, s.player_b, pa.player_name, pb.player_name
HAVING COUNT(*) >= 5
ORDER BY format, rank;
```

Expected: 3,542 rows · **First row:** ODI | 1 | RG Sharma & KL Rahul | 10 | 98.5 | 6 | 227 | 60.0

Q25 Career trajectory by quarter

```
-- id: 25
-- title: Career trajectory by quarter
-- question: Track each player's quarterly runs and strike rate in each format, compare each quarter with the
previous one, and label the career phase (Ascending, Declining, Stable). Players with 6+ quarters of 3+ matches
only.
-- params: none

-- Step 1 quarterly: one row per player per quarter (3+ matches only).
-- Step 2 compared: LAG() fetches the previous quarter so each quarter can
-- be labelled Improving / Declining / Stable (±10% on average runs).
-- Step 3 per player: count the labels and compare the first 3 quarters
-- with the last 3. Last 3 more than 10% higher = Career Ascending,
-- more than 10% lower = Career Declining, otherwise Career Stable.
-- Split by format: ODI and T20I numbers are never mixed in one row,
-- because a good ODI average and a good T20I average are different things.
WITH quarterly AS (
    SELECT b.player_id,
           m.match_format,
           d.year,
           d.quarter,
           d.year || '-' || d.quarter AS period,
           COUNT(DISTINCT b.match_id) AS matches,
           AVG(b.runs_scored) AS avg_runs,
           SUM(b.runs_scored) * 100.0 / NULLIF(SUM(b.balls_faced), 0) AS strike_rate
    FROM fact_batting b
    JOIN fact_match m ON m.match_id = b.match_id
    JOIN dim_date d ON d.date_key = m.date_key
    GROUP BY b.player_id, m.match_format, d.year, d.quarter
    HAVING COUNT(DISTINCT b.match_id) >= 3
),
compared AS (
    SELECT q.*,
           LAG(avg_runs) OVER w AS prev_avg,
           ROW_NUMBER() OVER w AS q_first,
           ROW_NUMBER() OVER (PARTITION BY player_id, match_format
                               ORDER BY year DESC, quarter DESC) AS q_last,
           COUNT(*) OVER (PARTITION BY player_id, match_format) AS quarters
    FROM quarterly q
    WINDOW w AS (PARTITION BY player_id, match_format ORDER BY year, quarter)
),
summary AS (
    SELECT player_id,
           match_format,
           MAX(quarters) AS quarters,
           MIN(period) AS first_quarter,
           MAX(period) AS last_quarter,
           COUNT(*) FILTER (WHERE avg_runs > prev_avg * 1.1) AS improving_q,
           COUNT(*) FILTER (WHERE avg_runs < prev_avg * 0.9) AS declining_q,
           COUNT(*) FILTER (WHERE prev_avg IS NOT NULL
                               AND avg_runs BETWEEN prev_avg * 0.9 AND prev_avg * 1.1) AS stable_q,
           AVG(avg_runs) FILTER (WHERE q_first <= 3) AS early_avg,
           AVG(avg_runs) FILTER (WHERE q_last <= 3) AS recent_avg,
           AVG(strike_rate) FILTER (WHERE q_first <= 3) AS early_sr,
           AVG(strike_rate) FILTER (WHERE q_last <= 3) AS recent_sr
    FROM compared
    GROUP BY player_id, match_format
    HAVING MAX(quarters) >= 6
)
SELECT p.player_name,
       p.primary_team,
       s.match_format AS format,
       s.quarters,
       s.first_quarter,
       s.last_quarter,
       ROUND(s.early_avg, 1) AS early_avg_runs,
       ROUND(s.recent_avg, 1) AS recent_avg_runs,
       ROUND(s.early_sr, 1) AS early_strike_rate,
       ROUND(s.recent_sr, 1) AS recent_strike_rate,
       s.improving_q,
       s.declining_q,
       s.stable_q,
       CASE WHEN s.recent_avg > s.early_avg * 1.1 THEN 'Career Ascending'
            WHEN s.recent_avg < s.early_avg * 0.9 THEN 'Career Declining'
            ELSE 'Career Stable' END AS career_phase
FROM summary s
JOIN dim_player p ON p.player_id = s.player_id
ORDER BY format, s.recent_avg - s.early_avg DESC;
```

Expected: 1,294 rows · **First row:** AJ Healy | Australia | ODI | 20 | 2014-Q4 | 2026-Q1 | 12.4 | 51.0 | 96.5 | 118.4 | 10 | 6 | 3 | Career Ascending